




**Flat Power-DIP4-pin type
with high capacity
up to 2A load current**

PhotoMOS®

**PD 1 Form A
(AQY27O)**



FEATURES

1. **Flat-Packaged type**
(W) 8.8 × (D) 9.3 × (H) 3.9 mm
(W) .346 × (D) .366 × (H) .154 inch
2. **High capacity of continuous load current 2A (AQY272)**
3. **High sensitivity and low on-resistance**
Max. 2A load can be controlled with 5mA input current. The on-resistance is low at Typ. 0.11Ω (AQY272).

TYPICAL APPLICATIONS

- Measuring and Testing equipment
- IC Testers and Board Testers
- High speed inspection machines

RoHS compliant

TYPES

Type	Output rating*		Package	Part No.			Packing quantity		
	Load voltage	Load current		Through hole terminal	Surface-mount terminal				
					Tube packing style		Tape and reel packing style		
AC/DC dual use	60V	2.0A	Power-DIP4-pin	AQY272	AQY272A	AQY272AX	AQY272AZ	1 tube contains: 50 pcs. 1 batch contains: 1,000 pcs.	
	100V	1.3A		AQY275	AQY275A	AQY275AX	AQY275AZ		
	200V	0.65A		AQY277	AQY277A	AQY277AX	AQY277AZ		
	400V	0.35A		AQY274	AQY274A	AQY274AX	AQY274AZ		

* Indicate the peak AC and DC values.

Note: The surface mount terminal indicator "A" and the packing style indicator "X" or "Z" are not marked on the device.

RATING

1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)


Item		Symbol	AQY272(A)	AQY275(A)	AQY277(A)	AQY274(A)	Remarks
Input	LED forward current	I _F		50 mA			
	LED reverse voltage	V _R		5 V			
	Peak forward current	I _{FP}		1 A			f = 100 Hz, Duty factor = 0.1%
	Power dissipation	P _{in}		75 mW			
Output	Load voltage (peak AC)	V _L	60 V	100 V	200 V	400 V	
	Continuous load current	I _L	2.0 A	1.3 A	0.65 A	0.35 A	Peak AC, DC
	Peak load current	I _{peak}	6.0 A	4.0 A	2.0 A	1.0 A	100ms (1 shot), V _L = DC
	Power dissipation	P _{out}		700 mW			
Total power dissipation		P _T		750 mW			
I/O isolation voltage		V _{iso}		2,500 Vrms			
Ambient temperature	Operating	T _{opr}	-40 to +85°C -40 to +185°F			(Non-icing at low temperatures)	
	Storage	T _{stg}	-40 to +100°C -40 to +212°F				

PD 1 Form A (AQY27○)

2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item		Symbol	AQY272(A)	AQY275(A)	AQY277(A)	AQY274(A)	Condition	
Input	LED operate current	Typical Maximum	I _{Fon}	1.0 mA		I _L = 100 mA V _L = 10 V		
				3.0 mA				
	LED turn off current	Minimum Typical	I _{Foff}	0.4 mA		I _L = 100 mA V _L = 10 V		
				0.9 mA				
Output	LED dropout voltage	Typical Maximum	V _F	1.25 V (1.16 V at I _F = 10 mA)			I _F = 50 mA	
				1.5 V				
	On resistance	Typical Maximum	R _{on}	0.11 Ω	0.23 Ω	0.7 Ω	2.1 Ω	
				0.18 Ω	0.34 Ω	1.1 Ω	3.2 Ω	
Transfer characteristics	Off state leakage current	Maximum	I _{Leak}	10 μA			I _F = 0 mA, V _L = Max.	
	Turn on time*	Typical Maximum	T _{on}	2.46 ms	2.40 ms	1.12 ms	1.65 ms	
				5.0 ms			I _F = 10 mA, I _L = 100 mA V _L = 10 V	
		Typical Maximum		5.64 ms	5.65 ms	2.57 ms	3.88 ms	
				10.0 ms			I _F = 5 mA, I _L = 100 mA V _L = 10 V	
	Turn off time*	Typical Maximum	T _{off}	0.22 ms	0.21 ms	0.10 ms	0.08 ms	
				3.0 ms			I _F = 5 mA or 10 mA, I _L = 100 mA V _L = 10 V	
	I/O capacitance	Typical Maximum	C _{iso}	0.8 pF			f = 1 MHz V _B = 0 V	
				1.5 pF				
	Initial I/O isolation resistance	Minimum	R _{iso}	1,000 MΩ			500 V DC	
	Max. operating frequency	Maximum	—	0.5 cps			I _F = 10 mA, Duty factor = 50% I _L = Max., V _L = Max.	

*Turn on/Turn off time



3. Recommended operating conditions (Ambient temperature: 25°C 77°F)

Please use under recommended operating conditions to obtain expected characteristics.

Item		Symbol	Min.	Max.	Unit
AQY272(A)	LED current	I _F	5	30	mA
	Load voltage (Peak AC)	V _L	—	48	V
AQY275(A)	Continuous load current	I _L	—	2.0	A
	Load voltage (Peak AC)	V _L	—	80	V
AQY277(A)	Continuous load current	I _L	—	1.3	A
	Load voltage (Peak AC)	V _L	—	160	V
AQY274(A)	Continuous load current	I _L	—	0.65	A
	Load voltage (Peak AC)	V _L	—	320	V
	Continuous load current	I _L	—	0.35	A


■ These products are not designed for automotive use.

If you are considering to use these products for automotive applications, please contact your local Panasonic Corporation technical representative.

REFERENCE DATA


1. Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40 to +85°C
-40 to +185°F




3. Turn on time vs. ambient temperature characteristics

LED current: 10 mA; Load voltage: 10 V (DC); Continuous load current: 100 mA (DC)




6. LED turn off current vs. ambient temperature characteristics

Load voltage: 10 V (DC); Continuous load current: 100 mA (DC)




9.-(1) Off state leakage current vs. load voltage characteristics

Ambient temperature: 25°C 77°F




2.- (1) On resistance vs. ambient temperature characteristics

LED current: 10 mA; Continuous load current: 2.0 A (DC) (AQY272), 1.3 A (DC) (AQY275)




4. Turn off time vs. ambient temperature characteristics

LED current: 10 mA; Load voltage: 10 V (DC); Continuous load current: 100 mA (DC)




7. LED dropout voltage vs. ambient temperature characteristics

Sample: all types; LED current: 5 to 50 mA




9.- (2) Off state leakage current vs. load voltage characteristics

Ambient temperature: 25°C 77°F




2.- (2) On resistance vs. ambient temperature characteristics

LED current: 10 mA; Continuous load current: 0.65 A (DC) (AQY277), 0.35 A (DC) (AQY274)




5. LED operate vs. ambient temperature characteristics

Load voltage: 10 V (DC); Continuous load current: 100 mA (DC)




8. Current vs. voltage characteristics of output at MOS portion

Ambient temperature: 25°C 77°F



10. Turn on time vs. LED forward current characteristics


Load voltage: 10 V (DC); Continuous load current: 100 mA (DC); Ambient temperature: 25°C 77°F



PD 1 Form A (AQY27○)

11. Turn off time vs. LED forward current characteristics

Load voltage: 10 V (DC); Continuous load current: 100 mA (DC); Ambient temperature: 25°C 77°F




12.-(1) Turn on time vs. load voltage characteristics

LED current: 10 mA; Load voltage: 10 V (DC); Ambient temperature: 25°C 77°F


12.-(2) Turn on time vs. load voltage characteristics

LED current: 10 mA; Continuous load current: 100 mA; Ambient temperature: 25°C 77°F




12.-(2) Turn on time vs. load voltage characteristics

LED current: 10 mA; Continuous load current: 100 mA; Ambient temperature: 25°C 77°F



13.-(1) Turn on time vs. load current characteristics

LED current: 10 mA; Load voltage: 10 V (DC); Ambient temperature: 25°C 77°F




13.-(2) Turn on time vs. load current characteristics

LED current: 10 mA; Load voltage: 10 V (DC); Ambient temperature: 25°C 77°F


14.-(1) Turn off time vs. load voltage characteristics

LED current: 10 mA; Continuous load current: 100 mA; Ambient temperature: 25°C 77°F



14.-(2) Turn off time vs. load voltage characteristics

LED current: 10 mA; Continuous load current: 100 mA; Ambient temperature: 25°C 77°F




15.-1) Turn off time vs. load current characteristics

LED current: 10 mA; Load voltage 10 V (DC); Ambient temperature: 25°C 77°F

15.-2) Turn off time vs. load current characteristics

LED current: 10 mA; Load voltage 10 V (DC); Ambient temperature: 25°C 77°F




15.-2) Turn off time vs. load current characteristics

LED current: 10 mA; Load voltage 10 V (DC); Ambient temperature: 25°C 77°F

15.-2) Turn off time vs. load current characteristics


LED current: 10 mA; Load voltage 10 V (DC); Ambient temperature: 25°C 77°F



Sample: All types; LED current: 10 mA; Ambient temperature: 25°C 77°F

V_L: Load voltage, V_L (Max.): Max. rated load voltage

I_L: Load current, I_L (Max.): Max. rated continuous load current



"PhotoMOS®", "PhotoMOS" and "PHOTOMOS" are registered trademarks of Panasonic Corporation.

*Recognized in Japan, the United States, all member states of European Union and other countries.

Please contact

Panasonic Corporation

Electromechanical Control Business Division

■ 1006, Oaza Kadoma, Kadomashi, Osaka 571-8506, Japan
industrial.panasonic.com/ac/e/

Panasonic®

©Panasonic Corporation 2017

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panasonic:

[AQY272A](#) [AQY275A](#) [AQY277A](#) [AQY272](#) [AQY274](#) [AQY212FG2SX](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.