



**Is Now Part of**



**ON Semiconductor®**

**To learn more about ON Semiconductor, please visit our website at**  
**[www.onsemi.com](http://www.onsemi.com)**

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at [www.onsemi.com](http://www.onsemi.com). Please email any questions regarding the system integration to [Fairchild\\_questions@onsemi.com](mailto:Fairchild_questions@onsemi.com).

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.



January 2016

## 1N5221B - 1N5263B Zener Diodes

Tolerance = 5%



DO-35 Glass case  
COLOR BAND DENOTES CATHODE

### Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only. Values are at  $T_A = 25^\circ\text{C}$  unless otherwise noted.

| Symbol    | Parameter                                       | Value       | Unit                 |
|-----------|-------------------------------------------------|-------------|----------------------|
| $P_D$     | Power Dissipation                               | 500         | mW                   |
|           | Derate above $50^\circ\text{C}$                 | 4.0         | mW/ $^\circ\text{C}$ |
| $T_{STG}$ | Storage Temperature Range                       | -65 to +200 | $^\circ\text{C}$     |
| $T_J$     | Operating Junction Temperature Range            | -65 to +200 | $^\circ\text{C}$     |
|           | Lead Temperature (1/16 inch from case for 10 s) | +230        | $^\circ\text{C}$     |

#### Note:

1. These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.  
Non-recurrent square wave Pulse Width = 8.3 ms,  $T_A = 50^\circ\text{C}$

## Electrical Characteristics

Values are at  $T_A = 25^\circ\text{C}$  unless otherwise noted .

| Device  | $V_Z$ (V) @ $I_Z$ <sup>(2)</sup> |      |       | $Z_Z$ ( $\Omega$ ) @ $I_Z$ (mA) |     | $Z_{ZK}$ ( $\Omega$ ) @ $I_{ZK}$ (mA) |      | $I_R$ ( $\mu\text{A}$ ) @ $V_R$ (V) |     | $T_C$<br>(%/°C) |
|---------|----------------------------------|------|-------|---------------------------------|-----|---------------------------------------|------|-------------------------------------|-----|-----------------|
|         | Min.                             | Typ. | Max.  |                                 |     |                                       |      |                                     |     |                 |
| 1N5221B | 2.28                             | 2.4  | 2.52  | 30                              | 20  | 1,200                                 | 0.25 | 100                                 | 1.0 | -0.085          |
| 1N5222B | 2.375                            | 2.5  | 2.625 | 30                              | 20  | 1,250                                 | 0.25 | 100                                 | 1.0 | -0.085          |
| 1N5223B | 2.565                            | 2.7  | 2.835 | 30                              | 20  | 1,300                                 | 0.25 | 75                                  | 1.0 | -0.080          |
| 1N5224B | 2.66                             | 2.8  | 2.94  | 30                              | 20  | 1,400                                 | 0.25 | 75                                  | 1.0 | -0.080          |
| 1N5225B | 2.85                             | 3    | 3.15  | 29                              | 20  | 1,600                                 | 0.25 | 50                                  | 1.0 | -0.075          |
| 1N5226B | 3.135                            | 3.3  | 3.465 | 28                              | 20  | 1,600                                 | 0.25 | 25                                  | 1.0 | -0.07           |
| 1N5227B | 3.42                             | 3.6  | 3.78  | 24                              | 20  | 1,700                                 | 0.25 | 15                                  | 1.0 | -0.065          |
| 1N5228B | 3.705                            | 3.9  | 4.095 | 23                              | 20  | 1,900                                 | 0.25 | 10                                  | 1.0 | -0.06           |
| 1N5229B | 4.085                            | 4.3  | 4.515 | 22                              | 20  | 2,000                                 | 0.25 | 5.0                                 | 1.0 | +/-0.055        |
| 1N5230B | 4.465                            | 4.7  | 4.935 | 19                              | 20  | 1,900                                 | 0.25 | 5.0                                 | 2.0 | +/-0.03         |
| 1N5231B | 4.845                            | 5.1  | 5.355 | 17                              | 20  | 1,600                                 | 0.25 | 5.0                                 | 2.0 | +/-0.03         |
| 1N5232B | 5.32                             | 5.6  | 5.88  | 11                              | 20  | 1,600                                 | 0.25 | 5.0                                 | 3.0 | 0.038           |
| 1N5233B | 5.7                              | 6    | 6.3   | 7.0                             | 20  | 1,600                                 | 0.25 | 5.0                                 | 3.5 | 0.038           |
| 1N5234B | 5.89                             | 6.2  | 6.51  | 7.0                             | 20  | 1,000                                 | 0.25 | 5.0                                 | 4.0 | 0.045           |
| 1N5235B | 6.46                             | 6.8  | 7.14  | 5.0                             | 20  | 750                                   | 0.25 | 3.0                                 | 5.0 | 0.05            |
| 1N5236B | 7.125                            | 7.5  | 7.875 | 6.0                             | 20  | 500                                   | 0.25 | 3.0                                 | 6.0 | 0.058           |
| 1N5237B | 7.79                             | 8.2  | 8.61  | 8.0                             | 20  | 500                                   | 0.25 | 3.0                                 | 6.5 | 0.062           |
| 1N5238B | 8.265                            | 8.7  | 9.135 | 8.0                             | 20  | 600                                   | 0.25 | 3.0                                 | 6.5 | 0.065           |
| 1N5239B | 8.645                            | 9.1  | 9.555 | 10                              | 20  | 600                                   | 0.25 | 3.0                                 | 7.0 | 0.068           |
| 1N5240B | 9.5                              | 10   | 10.5  | 17                              | 20  | 600                                   | 0.25 | 3.0                                 | 8.0 | 0.075           |
| 1N5241B | 10.45                            | 11   | 11.55 | 22                              | 20  | 600                                   | 0.25 | 2.0                                 | 8.4 | 0.076           |
| 1N5242B | 11.4                             | 12   | 12.6  | 30                              | 20  | 600                                   | 0.25 | 1.0                                 | 9.1 | 0.077           |
| 1N5243B | 12.35                            | 13   | 13.65 | 13                              | 9.5 | 600                                   | 0.25 | 0.5                                 | 9.9 | 0.079           |
| 1N5244B | 13.3                             | 14   | 14.7  | 15                              | 9.0 | 600                                   | 0.25 | 0.1                                 | 10  | 0.080           |
| 1N5245B | 14.25                            | 15   | 15.75 | 16                              | 8.5 | 600                                   | 0.25 | 0.1                                 | 11  | 0.082           |
| 1N5246B | 15.2                             | 16   | 16.8  | 17                              | 7.8 | 600                                   | 0.25 | 0.1                                 | 12  | 0.083           |
| 1N5247B | 16.15                            | 17   | 17.85 | 19                              | 7.4 | 600                                   | 0.25 | 0.1                                 | 13  | 0.084           |
| 1N5248B | 17.1                             | 18   | 18.9  | 21                              | 7.0 | 600                                   | 0.25 | 0.1                                 | 14  | 0.085           |
| 1N5249B | 18.05                            | 19   | 19.95 | 23                              | 6.6 | 600                                   | 0.25 | 0.1                                 | 14  | 0.085           |
| 1N5250B | 19                               | 20   | 21    | 25                              | 6.2 | 600                                   | 0.25 | 0.1                                 | 15  | 0.086           |
| 1N5251B | 20.9                             | 22   | 23.1  | 29                              | 5.6 | 600                                   | 0.25 | 0.1                                 | 17  | 0.087           |
| 1N5252B | 22.8                             | 24   | 25.2  | 33                              | 5.2 | 600                                   | 0.25 | 0.1                                 | 18  | 0.088           |
| 1N5253B | 23.75                            | 25   | 26.25 | 35                              | 5.0 | 600                                   | 0.25 | 0.1                                 | 19  | 0.088           |
| 1N5254B | 25.65                            | 27   | 28.35 | 41                              | 4.6 | 600                                   | 0.25 | 0.1                                 | 21  | 0.089           |
| 1N5255B | 26.6                             | 28   | 29.4  | 44                              | 4.5 | 600                                   | 0.25 | 0.1                                 | 21  | 0.090           |
| 1N5256B | 28.5                             | 30   | 31.5  | 49                              | 4.2 | 600                                   | 0.25 | 0.1                                 | 23  | 0.09            |
| 1N5257B | 31.35                            | 33   | 34.65 | 58                              | 3.8 | 700                                   | 0.25 | 0.1                                 | 25  | 0.092           |
| 1N5258B | 34.2                             | 36   | 37.8  | 70                              | 3.4 | 700                                   | 0.25 | 0.1                                 | 27  | 0.093           |
| 1N5259B | 37.05                            | 39   | 40.95 | 80                              | 3.2 | 800                                   | 0.25 | 0.1                                 | 30  | 0.094           |
| 1N5260B | 40.85                            | 43   | 45.15 | 93                              | 3.0 | 900                                   | 0.25 | 0.1                                 | 33  | 0.095           |
| 1N5261B | 44.65                            | 47   | 49.35 | 105                             | 2.7 | 1000                                  | 0.25 | 0.1                                 | 36  | 0.095           |
| 1N5262B | 48.45                            | 51   | 53.55 | 125                             | 2.5 | 1100                                  | 0.25 | 0.1                                 | 39  | 0.096           |
| 1N5263B | 53.2                             | 56   | 58.8  | 150                             | 2.2 | 1300                                  | 0.25 | 0.1                                 | 43  | 0.096           |

$V_F$  Forward Voltage = 1.2V Max. @  $I_F = 200\text{mA}$

### Note:

#### 2. Zener Voltage ( $V_Z$ )

The zener voltage is measured with the device junction in the thermal equilibrium at the lead temperature ( $T_L$ ) at  $30^\circ\text{C} \pm 1^\circ\text{C}$  and 3/8" lead length.

## Top Mark Information

| Device  | Line 1 | Line 2 | Line 3 |
|---------|--------|--------|--------|
| 1N5221B | LOGO   | 22     | 1B     |
| 1N5222B | LOGO   | 22     | 2B     |
| 1N5223B | LOGO   | 22     | 3B     |
| 1N5224B | LOGO   | 22     | 4B     |
| 1N5225B | LOGO   | 22     | 5B     |
| 1N5226B | LOGO   | 22     | 6B     |
| 1N5227B | LOGO   | 22     | 7B     |
| 1N5228B | LOGO   | 22     | 8B     |
| 1N5229B | LOGO   | 22     | 9B     |
| 1N5230B | LOGO   | 23     | 0B     |
| 1N5231B | LOGO   | 23     | 1B     |
| 1N5232B | LOGO   | 23     | 2B     |
| 1N5233B | LOGO   | 23     | 3B     |
| 1N5234B | LOGO   | 23     | 4B     |
| 1N5235B | LOGO   | 23     | 5B     |
| 1N5236B | LOGO   | 23     | 6B     |
| 1N5237B | LOGO   | 23     | 7B     |
| 1N5238B | LOGO   | 23     | 8B     |
| 1N5239B | LOGO   | 23     | 9B     |
| 1N5240B | LOGO   | 24     | 0B     |
| 1N5241B | LOGO   | 24     | 1B     |
| 1N5242B | LOGO   | 24     | 2B     |
| 1N5243B | LOGO   | 24     | 3B     |
| 1N5244B | LOGO   | 24     | 4B     |
| 1N5245B | LOGO   | 24     | 5B     |
| 1N5246B | LOGO   | 24     | 6B     |
| 1N5247B | LOGO   | 24     | 7B     |
| 1N5248B | LOGO   | 24     | 8B     |
| 1N5249B | LOGO   | 24     | 9B     |
| 1N5250B | LOGO   | 25     | 0B     |
| 1N5251B | LOGO   | 25     | 1B     |
| 1N5252B | LOGO   | 25     | 2B     |
| 1N5253B | LOGO   | 25     | 3B     |
| 1N5254B | LOGO   | 25     | 4B     |
| 1N5255B | LOGO   | 25     | 5B     |
| 1N5256B | LOGO   | 25     | 6B     |
| 1N5257B | LOGO   | 25     | 7B     |
| 1N5258B | LOGO   | 25     | 8B     |
| 1N5259B | LOGO   | 25     | 9B     |
| 1N5260B | LOGO   | 26     | 0B     |
| 1N5261B | LOGO   | 26     | 1B     |
| 1N5262B | LOGO   | 26     | 2B     |
| 1N5263B | LOGO   | 26     | 3B     |


**Top Mark Information** (Continued)**General Requirements:**

- 1.0 Cathode Band
- 2.0 First Line: F - Fairchild Logo
- 3.0 Second Line: Device name - For 1Nxx series: 4<sup>th</sup> to 5<sup>th</sup> characters of the device name.  
For BZxx series: 5<sup>th</sup> to 6<sup>th</sup> characters of the device name.
- 4.0 Third Line: Device name - For 1Nxx series: 6<sup>th</sup> to 7<sup>th</sup> characters of the device name.  
For BZXyy series: Voltage rating
- 5.0 Devices shall be marked as required in the device specification (PID or FSC Test Spec).
- 6.0 Maximum no. of marking lines: 3
- 7.0 Maximum no. of digits per line: 2
- 8.0 FSC logo must be 20 % taller than the alphanumeric marking and should occupy the 2 characters of the specified line.
- 9.0 Marking Font: Arial (Except FSC Logo)
- 10.0 First character of each marking line must be aligned vertically.
- 11.0 All device markings must be based on Fairchild device specification.



NOTES: UNLESS OTHERWISE SPECIFIED

- A) PACKAGE STANDARD REFERENCE:  
JEDEC DO-204, VARIATION AH.
- B) HERMETICALLY SEALED GLASS PACKAGE.
- C) PACKAGE WEIGHT IS 0.137 GRAM.
- D) ALL DIMENSIONS ARE IN MILLIMETERS.
- E) DRAWING FILE NAME: DO35AREV03



ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[1N5244BTR](#) [1N5244B\\_T50R](#) [1N5244B\\_S00Z](#) [1N5244B\\_T50A](#) [1N5244B\\_T26A](#) [1N5244B](#) [1N5244B\\_Q](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.