

# 74HC2G125; 74HCT2G125

Dual buffer/line driver; 3-state

Rev. 04 — 4 July 2008

Product data sheet

## 1. General description

The 74HC2G125; 74HCT2G125 is a high-speed, Si-gate CMOS device.

The 74HC2G125; 74HCT2G125 provides two non-inverting buffer/line drivers with 3-state output. The 3-state output is controlled by the output enable input (pin  $\overline{\text{nOE}}$ ). A HIGH level at pin  $\overline{\text{nOE}}$  causes the output to assume a high-impedance OFF-state.

The bus driver output currents are equal compared to the 74HC125 and 74HCT125.

## 2. Features

- Wide supply voltage range from 2.0 V to 6.0 V
- Symmetrical output impedance
- High noise immunity
- Low power consumption
- Balanced propagation delays
- ESD protection:
  - ◆ HBM JESD22-A114E exceeds 2000 V
  - ◆ MM JESD22-A115-A exceeds 200 V
- Multiple package options
- Specified from  $-40\text{ }^{\circ}\text{C}$  to  $+85\text{ }^{\circ}\text{C}$  and  $-40\text{ }^{\circ}\text{C}$  to  $+125\text{ }^{\circ}\text{C}$

## 3. Ordering information

Table 1. Ordering information


| Type number                 | Package                                                         |        |                                                                                                                         |          |
|-----------------------------|-----------------------------------------------------------------|--------|-------------------------------------------------------------------------------------------------------------------------|----------|
|                             | Temperature range                                               | Name   | Description                                                                                                             | Version  |
| 74HC2G125DP<br>74HCT2G125DP | $-40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ | TSSOP8 | plastic thin shrink small outline package; 8 leads; body width 3 mm; lead length 0.5 mm                                 | SOT505-2 |
| 74HC2G125DC<br>74HCT2G125DC | $-40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ | VSSOP8 | plastic very thin shrink small outline package; 8 leads; body width 2.3 mm                                              | SOT765-1 |
| 74HC2G125GD<br>74HCT2G125GD | $-40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ | XSON8U | plastic extremely thin small outline package; no leads; 8 terminals; UTLP based; body $3 \times 2 \times 0.5\text{ mm}$ | SOT996-2 |

4. Marking

Table 2. Marking


| Type number  | Marking code |
|--------------|--------------|
| 74HC2G125DP  | H25          |
| 74HCT2G125DP | T25          |
| 74HC2G125DC  | H25          |
| 74HCT2G125DC | T25          |
| 74HC2G125GD  | H25          |
| 74HCT2G125GD | T25          |

5. Functional diagram



6. Pinning information

6.1 Pinning



## 6.2 Pin description

Table 3. Pin description

| Symbol                                              | Pin  | Description                      |
|-----------------------------------------------------|------|----------------------------------|
| 1 $\overline{\text{OE}}$ , 2 $\overline{\text{OE}}$ | 1, 7 | output enable input (active LOW) |
| 1A, 2A                                              | 2, 5 | data input                       |
| GND                                                 | 4    | ground (0 V)                     |
| 1Y, 2Y                                              | 6, 3 | data output                      |
| V <sub>CC</sub>                                     | 8    | supply voltage                   |

## 7. Functional description

Table 4. Function table<sup>[1]</sup>

| Control                  | Input | Output |
|--------------------------|-------|--------|
| n $\overline{\text{OE}}$ | nA    | nY     |
| L                        | L     | L      |
| L                        | H     | H      |
| H                        | X     | Z      |

[1] H = HIGH voltage level; L = LOW voltage level; X = don't care; Z = high-impedance OFF-state.

## 8. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

| Symbol           | Parameter               | Conditions                                                          | Min              | Max  | Unit |
|------------------|-------------------------|---------------------------------------------------------------------|------------------|------|------|
| V <sub>CC</sub>  | supply voltage          |                                                                     | -0.5             | +7.0 | V    |
| I <sub>IK</sub>  | input clamping current  | V <sub>I</sub> < -0.5 V or V <sub>I</sub> > V <sub>CC</sub> + 0.5 V | <sup>[1]</sup> - | ±20  | mA   |
| I <sub>OK</sub>  | output clamping current | V <sub>O</sub> < -0.5 V or V <sub>O</sub> > V <sub>CC</sub> + 0.5 V | <sup>[1]</sup> - | ±20  | mA   |
| I <sub>O</sub>   | output current          | V <sub>O</sub> = -0.5 V to (V <sub>CC</sub> + 0.5 V)                | <sup>[1]</sup> - | 35   | mA   |
| I <sub>CC</sub>  | supply current          |                                                                     | -                | 70   | mA   |
| I <sub>GND</sub> | ground current          |                                                                     | -70              | -    | mA   |
| T <sub>stg</sub> | storage temperature     |                                                                     | -65              | +150 | °C   |
| P <sub>tot</sub> | total power dissipation | T <sub>amb</sub> = -40 °C to +125 °C                                | <sup>[2]</sup> - | 300  | mW   |

[1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

[2] For TSSOP8 package: above 55 °C the value of P<sub>tot</sub> derates linearly with 2.5 mW/K.  
 For VSSOP8 package: above 110 °C the value of P<sub>tot</sub> derates linearly with 8 mW/K.  
 For XSON8U package: above 45 °C the value of P<sub>tot</sub> derates linearly with 2.4 mW/K.

## 9. Recommended operating conditions

**Table 6. Recommended operating conditions**

Voltages are referenced to GND (ground = 0 V).

| Symbol              | Parameter                           | Conditions              | 74HC2G125 |      |                 | 74HCT2G125 |      |                 | Unit |
|---------------------|-------------------------------------|-------------------------|-----------|------|-----------------|------------|------|-----------------|------|
|                     |                                     |                         | Min       | Typ  | Max             | Min        | Typ  | Max             |      |
| V <sub>CC</sub>     | supply voltage                      |                         | 2.0       | 5.0  | 6.0             | 4.5        | 5.0  | 5.5             | V    |
| V <sub>I</sub>      | input voltage                       |                         | 0         | -    | V <sub>CC</sub> | 0          | -    | V <sub>CC</sub> | V    |
| V <sub>O</sub>      | output voltage                      |                         | 0         | -    | V <sub>CC</sub> | 0          | -    | V <sub>CC</sub> | V    |
| T <sub>amb</sub>    | ambient temperature                 |                         | -40       | +25  | +125            | -40        | +25  | +125            | °C   |
| $\Delta t/\Delta V$ | input transition rise and fall rate | V <sub>CC</sub> = 2.0 V | -         | -    | 625             | -          | -    | -               | ns/V |
|                     |                                     | V <sub>CC</sub> = 4.5 V | -         | 1.67 | 139             | -          | 1.67 | 139             | ns/V |
|                     |                                     | V <sub>CC</sub> = 6.0 V | -         | -    | 83              | -          | -    | -               | ns/V |

## 10. Static characteristics

**Table 7. Static characteristics**

Voltages are referenced to GND (ground = 0 V). All typical values are measured at T<sub>amb</sub> = 25 °C.

| Symbol          | Parameter                 | Conditions                                                                                                                | T <sub>amb</sub> = −40 °C to +85 °C |      |      | T <sub>amb</sub> = −40 °C to +125 °C |      | Unit |
|-----------------|---------------------------|---------------------------------------------------------------------------------------------------------------------------|-------------------------------------|------|------|--------------------------------------|------|------|
|                 |                           |                                                                                                                           | Min                                 | Typ  | Max  | Min                                  | Max  |      |
| 74HC2G125       |                           |                                                                                                                           |                                     |      |      |                                      |      |      |
| V <sub>IH</sub> | HIGH-level input voltage  | V <sub>CC</sub> = 2.0 V                                                                                                   | 1.5                                 | 1.2  | -    | 1.5                                  | -    | V    |
|                 |                           | V <sub>CC</sub> = 4.5 V                                                                                                   | 3.15                                | 2.4  | -    | 3.15                                 | -    | V    |
|                 |                           | V <sub>CC</sub> = 6.0 V                                                                                                   | 4.2                                 | 3.2  | -    | 4.2                                  | -    | V    |
| V <sub>IL</sub> | LOW-level input voltage   | V <sub>CC</sub> = 2.0 V                                                                                                   | -                                   | 0.8  | 0.5  | -                                    | 0.5  | V    |
|                 |                           | V <sub>CC</sub> = 4.5 V                                                                                                   | -                                   | 2.1  | 1.35 | -                                    | 1.35 | V    |
|                 |                           | V <sub>CC</sub> = 6.0 V                                                                                                   | -                                   | 2.8  | 1.8  | -                                    | 1.8  | V    |
| V <sub>OH</sub> | HIGH-level output voltage | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                                                       |                                     |      |      |                                      |      |      |
|                 |                           | I <sub>O</sub> = −20 μA; V <sub>CC</sub> = 2.0 V                                                                          | 1.9                                 | 2.0  | -    | 1.9                                  | -    | V    |
|                 |                           | I <sub>O</sub> = −20 μA; V <sub>CC</sub> = 4.5 V                                                                          | 4.4                                 | 4.5  | -    | 4.4                                  | -    | V    |
|                 |                           | I <sub>O</sub> = −20 μA; V <sub>CC</sub> = 6.0 V                                                                          | 5.9                                 | 6.0  | -    | 5.9                                  | -    | V    |
|                 |                           | I <sub>O</sub> = −6.0 mA; V <sub>CC</sub> = 4.5 V                                                                         | 3.84                                | 4.32 | -    | 3.7                                  | -    | V    |
|                 |                           | I <sub>O</sub> = −7.8 mA; V <sub>CC</sub> = 6.0 V                                                                         | 5.34                                | 5.81 | -    | 5.2                                  | -    | V    |
| V <sub>OL</sub> | LOW-level output voltage  | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                                                       |                                     |      |      |                                      |      |      |
|                 |                           | I <sub>O</sub> = 20 μA; V <sub>CC</sub> = 2.0 V                                                                           | -                                   | 0    | 0.1  | -                                    | 0.1  | V    |
|                 |                           | I <sub>O</sub> = 20 μA; V <sub>CC</sub> = 4.5 V                                                                           | -                                   | 0    | 0.1  | -                                    | 0.1  | V    |
|                 |                           | I <sub>O</sub> = 20 μA; V <sub>CC</sub> = 6.0 V                                                                           | -                                   | 0    | 0.1  | -                                    | 0.1  | V    |
|                 |                           | I <sub>O</sub> = 6.0 mA; V <sub>CC</sub> = 4.5 V                                                                          | -                                   | 0.15 | 0.33 | -                                    | 0.4  | V    |
|                 |                           | I <sub>O</sub> = 7.8 mA; V <sub>CC</sub> = 6.0 V                                                                          | -                                   | 0.16 | 0.33 | -                                    | 0.4  | V    |
| I <sub>I</sub>  | input leakage current     | V <sub>I</sub> = V <sub>CC</sub> or GND; V <sub>CC</sub> = 6.0 V                                                          | -                                   | -    | ±1.0 | -                                    | ±1.0 | μA   |
| I <sub>OZ</sub> | OFF-state output current  | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ;<br>V <sub>O</sub> = V <sub>CC</sub> or GND; V <sub>CC</sub> = 6.0 V | -                                   | -    | ±5.0 | -                                    | ±10  | μA   |

**Table 7.** Static characteristics ...continued

Voltages are referenced to GND (ground = 0 V). All typical values are measured at  $T_{amb} = 25\text{ }^{\circ}\text{C}$ .

| Symbol            | Parameter                 | Conditions                                                                                                  | $T_{amb} = -40\text{ }^{\circ}\text{C to } +85\text{ }^{\circ}\text{C}$ |      |           | $T_{amb} = -40\text{ }^{\circ}\text{C to } +125\text{ }^{\circ}\text{C}$ |           | Unit          |
|-------------------|---------------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|------|-----------|--------------------------------------------------------------------------|-----------|---------------|
|                   |                           |                                                                                                             | Min                                                                     | Typ  | Max       | Min                                                                      | Max       |               |
| $I_{CC}$          | supply current            | $V_I = V_{CC}$ or GND; $I_O = 0\text{ A}$ ;<br>$V_{CC} = 6.0\text{ V}$                                      | -                                                                       | -    | 10        | -                                                                        | 20        | $\mu\text{A}$ |
| $C_I$             | input capacitance         |                                                                                                             | -                                                                       | 1.0  | -         | -                                                                        | -         | pF            |
| $C_O$             | output capacitance        |                                                                                                             | -                                                                       | 1.5  | -         | -                                                                        | -         | pF            |
| <b>74HCT2G125</b> |                           |                                                                                                             |                                                                         |      |           |                                                                          |           |               |
| $V_{IH}$          | HIGH-level input voltage  | $V_{CC} = 4.5\text{ V to } 5.5\text{ V}$                                                                    | 2.0                                                                     | 1.6  | -         | 2.0                                                                      | -         | V             |
| $V_{IL}$          | LOW-level input voltage   | $V_{CC} = 4.5\text{ V to } 5.5\text{ V}$                                                                    | -                                                                       | 1.2  | 0.8       | -                                                                        | 0.8       | V             |
| $V_{OH}$          | HIGH-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ ; $V_{CC} = 4.5\text{ V}$<br>$I_O = -20\text{ }\mu\text{A}$                      | 4.4                                                                     | 4.5  | -         | 4.4                                                                      | -         | V             |
|                   |                           | $I_O = -6.0\text{ mA}$                                                                                      | 3.84                                                                    | 4.32 | -         | 3.7                                                                      | -         | V             |
|                   |                           |                                                                                                             |                                                                         |      |           |                                                                          |           |               |
| $V_{OL}$          | LOW-level output voltage  | $V_I = V_{IH}$ or $V_{IL}$ ; $V_{CC} = 4.5\text{ V}$<br>$I_O = 20\text{ }\mu\text{A}$                       | -                                                                       | 0    | 0.1       | -                                                                        | 0.1       | V             |
|                   |                           | $I_O = 6.0\text{ mA}$                                                                                       | -                                                                       | 0.16 | 0.33      | -                                                                        | 0.4       | V             |
|                   |                           |                                                                                                             |                                                                         |      |           |                                                                          |           |               |
| $I_I$             | input leakage current     | $V_I = V_{CC}$ or GND; $V_{CC} = 5.5\text{ V}$                                                              | -                                                                       | -    | $\pm 1.0$ | -                                                                        | $\pm 1.0$ | $\mu\text{A}$ |
| $I_{OZ}$          | OFF-state output current  | $V_I = V_{IH}$ or $V_{IL}$ ; $V_O = V_{CC}$ or GND; $V_{CC} = 5.5\text{ V}$                                 | -                                                                       | -    | $\pm 5.0$ | -                                                                        | $\pm 10$  |               |
| $I_{CC}$          | supply current            | $V_I = V_{CC}$ or GND; $I_O = 0\text{ A}$ ;<br>$V_{CC} = 5.5\text{ V}$                                      | -                                                                       | -    | 10        | -                                                                        | 20        | $\mu\text{A}$ |
| $\Delta I_{CC}$   | additional supply current | per input; $V_{CC} = 4.5\text{ V to } 5.5\text{ V}$ ;<br>$V_I = V_{CC} - 2.1\text{ V}$ ; $I_O = 0\text{ A}$ | -                                                                       | -    | 375       | -                                                                        | 410       | $\mu\text{A}$ |
| $C_I$             | input capacitance         |                                                                                                             | -                                                                       | 1.0  | -         | -                                                                        | -         | pF            |
| $C_O$             | output capacitance        |                                                                                                             | -                                                                       | 1.5  | -         | -                                                                        | -         | pF            |

## 11. Dynamic characteristics

**Table 8.** Dynamic characteristics

Voltages are referenced to GND (ground = 0 V);  $C_L = 50\text{ pF}$  unless otherwise specified; for test circuit see [Figure 8](#).

| Symbol          | Parameter         | Conditions                                      | T <sub>amb</sub> = −40 °C to +85 °C |                    |     | T <sub>amb</sub> = −40 °C to +125 °C |     | Unit |
|-----------------|-------------------|-------------------------------------------------|-------------------------------------|--------------------|-----|--------------------------------------|-----|------|
|                 |                   |                                                 | Min                                 | Typ <sup>[1]</sup> | Max | Min                                  | Max |      |
| 74HC2G125       |                   |                                                 |                                     |                    |     |                                      |     |      |
| t <sub>pd</sub> | propagation delay | nA to nY; see <a href="#">Figure 6</a>          |                                     |                    |     |                                      |     |      |
|                 |                   | V <sub>CC</sub> = 2.0 V                         | -                                   | 35                 | 115 | -                                    | 135 | ns   |
|                 |                   | V <sub>CC</sub> = 4.5 V                         | -                                   | 11                 | 23  | -                                    | 27  | ns   |
|                 |                   | V <sub>CC</sub> = 5.0 V; C <sub>L</sub> = 15 pF | -                                   | 10                 | -   | -                                    | -   | ns   |
|                 |                   | V <sub>CC</sub> = 6.0 V                         | -                                   | 8                  | 20  | -                                    | 23  | ns   |

**Table 8. Dynamic characteristics ...continued**

Voltages are referenced to GND (ground = 0 V);  $C_L = 50$  pF unless otherwise specified; for test circuit see [Figure 8](#).

| Symbol           | Parameter                     | Conditions                                                                  | T <sub>amb</sub> = −40 °C to +85 °C |                    |     | T <sub>amb</sub> = −40 °C to +125 °C |     | Unit |
|------------------|-------------------------------|-----------------------------------------------------------------------------|-------------------------------------|--------------------|-----|--------------------------------------|-----|------|
|                  |                               |                                                                             | Min                                 | Typ <sup>[1]</sup> | Max | Min                                  | Max |      |
| t <sub>en</sub>  | enable time                   | n $\overline{\text{OE}}$ to nY; see <a href="#">Figure 7</a> <sup>[2]</sup> |                                     |                    |     |                                      |     |      |
|                  |                               | V <sub>CC</sub> = 2.0 V                                                     | -                                   | 40                 | 115 | -                                    | 135 | ns   |
|                  |                               | V <sub>CC</sub> = 4.5 V                                                     | -                                   | 11                 | 23  | -                                    | 27  | ns   |
|                  |                               | V <sub>CC</sub> = 6.0 V                                                     | -                                   | 8                  | 20  | -                                    | 23  | ns   |
| t <sub>dis</sub> | disable time                  | n $\overline{\text{OE}}$ to nY; see <a href="#">Figure 7</a> <sup>[2]</sup> |                                     |                    |     |                                      |     |      |
|                  |                               | V <sub>CC</sub> = 2.0 V                                                     | -                                   | 24                 | 125 | -                                    | 150 | ns   |
|                  |                               | V <sub>CC</sub> = 4.5 V                                                     | -                                   | 12                 | 25  | -                                    | 30  | ns   |
|                  |                               | V <sub>CC</sub> = 6.0 V                                                     | -                                   | 10                 | 21  | -                                    | 26  | ns   |
| t <sub>t</sub>   | transition time               | see <a href="#">Figure 6</a> <sup>[2]</sup>                                 |                                     |                    |     |                                      |     |      |
|                  |                               | V <sub>CC</sub> = 2.0 V                                                     | -                                   | 18                 | 75  | -                                    | 90  | ns   |
|                  |                               | V <sub>CC</sub> = 4.5 V                                                     | -                                   | 6                  | 15  | -                                    | 18  | ns   |
|                  |                               | V <sub>CC</sub> = 6.0 V                                                     | -                                   | 5                  | 13  | -                                    | 15  | ns   |
| C <sub>PD</sub>  | power dissipation capacitance | per buffer; V <sub>I</sub> = GND to V <sub>CC</sub> <sup>[3]</sup>          |                                     |                    |     |                                      |     |      |
|                  |                               | output enabled                                                              | -                                   | 11                 | -   | -                                    | -   | pF   |
|                  |                               | output disabled                                                             | -                                   | 1                  | -   | -                                    | -   | pF   |

**74HCT2G125**

|                  |                               |                                                                                           |                     |    |    |    |    |    |    |
|------------------|-------------------------------|-------------------------------------------------------------------------------------------|---------------------|----|----|----|----|----|----|
| t <sub>pd</sub>  | propagation delay             | nA to nY; see <a href="#">Figure 6</a>                                                    | <a href="#">[2]</a> |    |    |    |    |    |    |
|                  |                               | V <sub>CC</sub> = 4.5 V                                                                   | -                   | 15 | 31 | -  | 38 | ns |    |
|                  |                               | V <sub>CC</sub> = 5.0 V; C <sub>L</sub> = 15 pF                                           | -                   | 12 | -  | -  | -  | ns |    |
| t <sub>en</sub>  | enable time                   | n $\overline{\text{OE}}$ to nY; see <a href="#">Figure 7</a> ;<br>V <sub>CC</sub> = 4.5 V | <a href="#">[2]</a> | -  | 15 | 35 | -  | 42 | ns |
| t <sub>dis</sub> | disable time                  | n $\overline{\text{OE}}$ to nY; see <a href="#">Figure 7</a> ;<br>V <sub>CC</sub> = 4.5 V | <a href="#">[2]</a> | -  | 15 | 31 | -  | 38 | ns |
| t <sub>t</sub>   | transition time               | see <a href="#">Figure 6</a> ; V <sub>CC</sub> = 4.5 V                                    | <a href="#">[2]</a> | -  | 6  | 15 | -  | 18 | ns |
| C <sub>PD</sub>  | power dissipation capacitance | per buffer;<br>V <sub>I</sub> = GND to V <sub>CC</sub> – 1.5 V                            | <a href="#">[3]</a> |    |    |    |    |    |    |
|                  |                               | output enabled                                                                            | -                   | 11 | -  | -  | -  | pF |    |
|                  |                               | output disabled                                                                           | -                   | 1  | -  | -  | -  | pF |    |

[1] All typical values are measured at  $T_{amb} = 25\text{ }^{\circ}\text{C}$ .

[2]  $t_{pd}$  is the same as  $t_{PLH}$  and  $t_{PHL}$ .  
 $t_{en}$  is the same as  $t_{PZL}$  and  $t_{PZH}$ .  
 $t_{dis}$  is the same as  $t_{PLZ}$  and  $t_{PHZ}$ .  
 $t_t$  is the same as  $t_{THL}$  and  $t_{TLH}$ .

[3]  $C_{PD}$  is used to determine the dynamic power dissipation ( $P_D$  in  $\mu\text{W}$ ).

$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$  where:

$f_i$  = input frequency in MHz;

$f_o$  = output frequency in MHz;

$C_L$  = output load capacitance in pF;

$V_{CC}$  = supply voltage in V;

$N$  = number of inputs switching;

$\Sigma(C_L \times V_{CC}^2 \times f_o)$  = sum of outputs.

12. Waveforms






Table 9. Measurement points

| Type       | Input       | Output      |                         |                         |
|------------|-------------|-------------|-------------------------|-------------------------|
|            | $V_M$       | $V_M$       | $V_X$                   | $V_Y$                   |
| 74HC2G125  | $0.5V_{CC}$ | $0.5V_{CC}$ | $V_{OL} + 0.3\text{ V}$ | $V_{OH} - 0.3\text{ V}$ |
| 74HCT2G125 | 1.3 V       | 1.3 V       | $V_{OL} + 0.3\text{ V}$ | $V_{OH} - 0.3\text{ V}$ |



Test data is given in [Table 10](#).

Definitions test circuit:

$R_T$  = Termination resistance should be equal to output impedance  $Z_o$  of the pulse generator.

$C_L$  = Load capacitance including jig and probe capacitance.

$R_L$  = Load resistance.

$S1$  = Test selection switch.

**Fig 8. Load circuitry for measuring switching times**

**Table 10. Test data**

| Type       | Input    |             | Load         |              | S1 position        |                    |                    |
|------------|----------|-------------|--------------|--------------|--------------------|--------------------|--------------------|
|            | $V_I$    | $t_r, t_f$  | $C_L$        | $R_L$        | $t_{PHL}, t_{PLH}$ | $t_{PZH}, t_{PHZ}$ | $t_{PZL}, t_{PLZ}$ |
| 74HC2G125  | $V_{CC}$ | $\leq 6$ ns | 15 pF, 50 pF | 1 k $\Omega$ | open               | GND                | $V_{CC}$           |
| 74HCT2G125 | 3 V      | $\leq 6$ ns | 15 pF, 50 pF | 1 k $\Omega$ | open               | GND                | $V_{CC}$           |

13. Package outline

TSSOP8: plastic thin shrink small outline package; 8 leads; body width 3 mm; lead length 0.5 mm    SOT505-2




Fig 9. Package outline SOT505-2 (TSSOP8)

VSSOP8: plastic very thin shrink small outline package; 8 leads; body width 2.3 mm

SOT765-1




Fig 10. Package outline SOT765-1 (VSSOP8)

XSON8U: plastic extremely thin small outline package; no leads;  
8 terminals; UTLP based; body 3 x 2 x 0.5 mm

SOT996-2




Fig 11. Package outline SOT996-2 (XSON8U)

## 14. Abbreviations

Table 11. Abbreviations

| Acronym | Description                             |
|---------|-----------------------------------------|
| CMOS    | Complementary Metal Oxide Semiconductor |
| DUT     | Device Under Test                       |
| ESD     | ElectroStatic Discharge                 |
| HBM     | Human Body Model                        |
| MM      | Machine Model                           |

## 15. Revision history

Table 12. Revision history

| Document ID     | Release date                                                                                                                                                                                                                                                                                                                                                                                                                         | Data sheet status     | Change notice | Supersedes      |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|---------------|-----------------|
| 74HC_HCT2G125_4 | 20080704                                                                                                                                                                                                                                                                                                                                                                                                                             | Product data sheet    | -             | 74HC_HCT2G125_3 |
| Modifications:  | <ul style="list-style-type: none"><li>• The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors.</li><li>• Legal texts have been adapted to the new company name where appropriate.</li><li>• <a href="#">Section 8</a>: derating factor for TSSOP8, VSSOP8 and XSON8U package added</li><li>• Added type numbers 74HC2G125GD and 74HCT2G125GD (XSON8U package)</li></ul> |                       |               |                 |
| 74HC_HCT2G125_3 | 20060102                                                                                                                                                                                                                                                                                                                                                                                                                             | Product data sheet    | -             | 74HC_HCT2G125_2 |
| 74HC_HCT2G125_2 | 20030303                                                                                                                                                                                                                                                                                                                                                                                                                             | Product specification | -             | 74HC_HCT2G125_1 |
| 74HC_HCT2G125_1 | 20030131                                                                                                                                                                                                                                                                                                                                                                                                                             | Product specification | -             | -               |

## 16. Legal information

### 16.1 Data sheet status

| Document status <sup>[1][2]</sup> | Product status <sup>[3]</sup> | Definition                                                                            |
|-----------------------------------|-------------------------------|---------------------------------------------------------------------------------------|
| Objective [short] data sheet      | Development                   | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet    | Qualification                 | This document contains data from the preliminary specification.                       |
| Product [short] data sheet        | Production                    | This document contains the product specification.                                     |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

### 16.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

### 16.3 Disclaimers

**General** — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

**Right to make changes** — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or

malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Terms and conditions of sale** — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

### 16.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 17. Contact information

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

## 18. Contents

|           |                                               |           |
|-----------|-----------------------------------------------|-----------|
| <b>1</b>  | <b>General description</b> .....              | <b>1</b>  |
| <b>2</b>  | <b>Features</b> .....                         | <b>1</b>  |
| <b>3</b>  | <b>Ordering information</b> .....             | <b>1</b>  |
| <b>4</b>  | <b>Marking</b> .....                          | <b>2</b>  |
| <b>5</b>  | <b>Functional diagram</b> .....               | <b>2</b>  |
| <b>6</b>  | <b>Pinning information</b> .....              | <b>2</b>  |
| 6.1       | Pinning .....                                 | 2         |
| 6.2       | Pin description .....                         | 3         |
| <b>7</b>  | <b>Functional description</b> .....           | <b>3</b>  |
| <b>8</b>  | <b>Limiting values</b> .....                  | <b>3</b>  |
| <b>9</b>  | <b>Recommended operating conditions</b> ..... | <b>4</b>  |
| <b>10</b> | <b>Static characteristics</b> .....           | <b>4</b>  |
| <b>11</b> | <b>Dynamic characteristics</b> .....          | <b>5</b>  |
| <b>12</b> | <b>Waveforms</b> .....                        | <b>7</b>  |
| <b>13</b> | <b>Package outline</b> .....                  | <b>9</b>  |
| <b>14</b> | <b>Abbreviations</b> .....                    | <b>12</b> |
| <b>15</b> | <b>Revision history</b> .....                 | <b>12</b> |
| <b>16</b> | <b>Legal information</b> .....                | <b>13</b> |
| 16.1      | Data sheet status .....                       | 13        |
| 16.2      | Definitions .....                             | 13        |
| 16.3      | Disclaimers .....                             | 13        |
| 16.4      | Trademarks .....                              | 13        |
| <b>17</b> | <b>Contact information</b> .....              | <b>13</b> |
| <b>18</b> | <b>Contents</b> .....                         | <b>14</b> |

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

founded by

**PHILIPS**

© NXP B.V. 2008.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

Date of release: 4 July 2008

Document identifier: 74HC\_HCT2G125\_4



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.