

## Aluminum Capacitors + 85 °C, Miniature, Axial Lead



Fig.1 Component outlines

### FEATURES

- Low leakage current
- Long shelf life
- Ideal for application in TV sets, auto radios, radio-phone combinations, electronic testing equipment



| QUICK REFERENCE DATA                    |                                      |
|---|--------------------------------------|
| DESCRIPTION                             | VALUE                                |
| Nominal case size<br>Ø D x L in mm      | 6.350 x 12.700<br>to 34.925 x 92.075 |
| Operating temperature                   |                                      |
| 6 WVDC to 100 WVDC                      | - 40 °C to + 85 °C                   |
| 101 WVDC to 475 WVDC                    | - 20 °C to + 85 °C                   |
| 500 WVDC and higher                     | 20 °C to + 65 °C                     |
| Rated Capacitance range, C <sub>R</sub> | 1 µF to 15 000 µF                    |

### ORDERING EXAMPLE (1)

Order by Distribution part no. Example: TVA1318.7

**Note** (1) For lead (Pb)-free/RoHS compliant products add the suffix “-E3” to the part no. Example: TVA1318.7-E3

| DIMENSIONS in inches [millimeters] |                |                |           |                |                 |
|------------------------------------|----------------|----------------|-----------|----------------|-----------------|
| CASE CODE                          | D              | L              | CASE CODE | D              | L               |
| BA                                 | 0.250 [6.350]  | 0.500 [12.700] | FJ        | 0.625 [15.875] | 1.625 [41.275]  |
| BB                                 | 0.250 [6.350]  | 0.687 [17.450] | FK        | 0.485 [12.319] | 1.750 [44.450]  |
| CB                                 | 0.312 [7.925]  | 0.687 [17.450] | GE        | 0.750 [19.050] | 1.125 [28.575]  |
| CC                                 | 0.312 [7.925]  | 0.812 [20.625] | GG        | 0.750 [19.050] | 1.375 [34.925]  |
| DC                                 | 0.375 [9.525]  | 0.812 [20.625] | GH        | 0.625 [15.875] | 1.500 [38.100]  |
| DD                                 | 0.375 [9.525]  | 0.937 [23.800] | GL        | 0.750 [19.050] | 2.125 [53.975]  |
| DF                                 | 0.375 [9.525]  | 1.250 [31.750] | GK        | 0.625 [15.875] | 1.750 [44.450]  |
| DH                                 | 0.375 [9.525]  | 1.500 [38.100] | GJ        | 0.750 [19.050] | 1.625 [41.275]  |
| EE                                 | 0.500 [12.700] | 1.125 [28.575] | HG        | 0.875 [22.225] | 1.375 [34.925]  |
| EF                                 | 0.438 [11.125] | 1.250 [31.750] | HJ        | 0.875 [22.225] | 1.625 [41.275]  |
| EG                                 | 0.500 [12.700] | 1.375 [34.925] | HK        | 0.875 [22.225] | 1.875 [47.625]  |
| EH                                 | 0.438 [11.125] | 1.500 [38.100] | HL        | 0.875 [22.225] | 2.125 [53.975]  |
| EJ                                 | 0.500 [12.700] | 1.625 [41.275] | JB        | 1.0 [25.4]     | 3.375 [85.725]  |
| FG                                 | 0.625 [15.875] | 1.375 [34.925] | JJ        | 1.0 [25.4]     | 1.625 [41.275]  |
| FH                                 | 0.485 [12.319] | 1.500 [38.100] | JK        | 1.0 [25.4]     | 1.875 [47.625]  |
| JL                                 | 1.0 [25.4]     | 2.125 [53.975] | KP        | 1.125 [28.575] | 2.625 [66.675]  |
| JN                                 | 1.0 [25.4]     | 2.375 [60.325] | KS        | 1.125 [28.575] | 3.125 [79.375]  |
| JP                                 | 1.0 [25.4]     | 2.625 [66.675] | LP        | 1.250 [31.750] | 2.625 [66.675]  |
| JR                                 | 1.0 [25.4]     | 2.875 [73.025] | LS        | 1.250 [31.750] | 3.125 [79.375]  |
| JS                                 | 1.0 [25.4]     | 3.125 [79.375] | LT        | 1.250 [31.750] | 3.625 [92.075]  |
| JU                                 | 1.0 [25.4]     | 3.625 [92.075] | MD        | 1.375 [34.925] | 4.125 [104.775] |
| JW                                 | 1.0 [25.4]     | 3.875 [98.425] | MN        | 1.375 [34.925] | 2.375 [60.325]  |
| KL                                 | 1.125 [28.575] | 2.125 [53.975] | MS        | 1.375 [34.925] | 3.125 [79.375]  |
| KN                                 | 1.125 [28.575] | 2.375 [60.325] | MT        | 1.375 [34.925] | 3.625 [92.075]  |

**ELECTRICAL DATA AND ORDERING INFORMATION**

| CAPACITANCE<br>( $\mu$ F)       | WVDC | CASE<br>CODE | PART NUMBER <sup>(1)</sup> |
|---------------------------------|------|--------------|----------------------------|
| <b>SINGLE UNITS (POLARIZED)</b> |      |              |                            |
| 200.0                           | 6    | CB           | TVA1101.7                  |
| 5000.0                          | 10   | GK           | TVA1129.5                  |
| 25.0                            | 16   | BA           | TVA1148                    |
| 50.0                            | 16   | BB           | TVA1150                    |
| 100.0                           | 16   | CB           | TVA1160                    |
| 200.0                           | 16   | CC           | TVA1160.6                  |
| 250.0                           | 16   | DC           | TVA1161                    |
| 500.0                           | 16   | DD           | TVA1162                    |
| 600.0                           | 16   | DF           | TVA1162.2                  |
| 800.0                           | 16   | DF           | TVA1162.3                  |
| 1000.0                          | 16   | DH           | TVA1163                    |
| 1200.0                          | 16   | EH           | TVA1164                    |
| 1500.0                          | 16   | EH           | TVA1175.2                  |
| 2000.0                          | 16   | FK           | TVA1170                    |
| 3000.0                          | 16   | GH           | TVA1175                    |
| 5000.0                          | 16   | JL           | TVA1175.5                  |
| 10 000.0                        | 16   | LP           | TVA1175.8                  |
| 10.0                            | 25   | BA           | TVA1204                    |
| 25.0                            | 25   | BA           | TVA1205                    |
| 50.0                            | 25   | BB           | TVA1206                    |
| 75.0                            | 25   | CB           | TVA1206.1                  |
| 100.0                           | 25   | CC           | TVA1207                    |
| 150.0                           | 25   | DC           | TVA1207.5                  |
| 200.0                           | 25   | DC           | TVA1207.7                  |
| 250.0                           | 25   | DD           | TVA1208                    |
| 500.0                           | 25   | EF           | TVA1209                    |
| 1000.0                          | 25   | FH           | TVA1211                    |
| 1500.0                          | 25   | GH           | TVA1212                    |
| 2000.0                          | 25   | GK           | TVA1213                    |
| 2500.0                          | 25   | JK           | TVA1213.5                  |
| 5000.0                          | 25   | KP           | TVA1214.5                  |
| 500.0                           | 35   | EH           | TVA1227                    |
| 5500.0                          | 35   | JB           | TVA1229                    |
| 1.0                             | 50   | BA           | TVA1300                    |
| 2.0                             | 50   | BA           | TVA1301                    |
| 5.0                             | 50   | BA           | TVA1303                    |
| 5.0                             | 50   | BA           | TVA1303.1                  |
| 10.0                            | 50   | BA           | TVA1304                    |
| 15.0                            | 50   | BB           | TVA1305                    |
| 20.0                            | 50   | BB           | TVA1305.5                  |
| 25.0                            | 50   | BB           | TVA1306                    |
| 40.0                            | 50   | CC           | TVA1306.5                  |
| 50.0                            | 50   | CC           | TVA1308                    |
| 75.0                            | 50   | DC           | TVA1309.4                  |
| 100.0                           | 50   | DC           | TVA1310                    |
| 150.0                           | 50   | DD           | TVA1311                    |
| 200.0                           | 50   | DF           | TVA1311.5                  |
| 250.0                           | 50   | DH           | TVA1312                    |
| 300.0                           | 50   | EF           | TVA1312.1                  |
| 400.0                           | 50   | FH           | TVA1313                    |
| 500.0                           | 50   | FH           | TVA1315                    |
| 600.0                           | 50   | GH           | TVA1315.2                  |
| 1000.0                          | 50   | GK           | TVA1316                    |
| 1500.0                          | 50   | HL           | TVA1318                    |
| 2000.0                          | 50   | KL           | TVA1318.2                  |
| 2500.0                          | 50   | KP           | TVA1318.3                  |
| 3000.0                          | 50   | LP           | TVA1318.4                  |
| 5000.0                          | 50   | MS           | TVA1318.7                  |
| 1.0                             | 63   | BA           | TVA1319.10                 |
| 10.0                            | 100  | CB           | TVA1337                    |

**Note**<sup>(1)</sup> For other capacitance and voltage ratings, please see Types 500D and 53D.



| <b>ELECTRICAL DATA AND ORDERING INFORMATION</b> |             |                      |                        |
|---|-------------|----------------------|------------------------|
| <b>CAPACITANCE<br/>(<math>\mu</math>F)</b>      | <b>WVDC</b> | <b>CASE<br/>CODE</b> | <b>PART NUMBER (1)</b> |
| <b>SINGLE UNITS (POLARIZED)</b>                 |             |                      |                        |
| 50.0  | 100         | DF                   | TVA1343                |
| 100.0   | 100         | EH                   | TVA1346                |
| 250.0   | 100         | GK                   | TVA1349                |
| 500.0   | 100         | KL                   | TVA1376                |
| 1.0   | 150         | BA                   | TVA1400                |
| 2.0   | 150         | BB                   | TVA1400.1              |
| 4.0   | 150         | CC                   | TVA1402                |
| 5.0   | 150         | CC                   | TVA1403                |
| 8.0   | 150         | DC                   | TVA1405                |
| 10.0  | 150         | DC                   | TVA1406                |
| 16.0  | 150         | DD                   | TVA1409                |
| 20.0  | 150         | DF                   | TVA1410                |
| 25.0  | 150         | DF                   | TVA1411                |
| 30.0  | 150         | EF                   | TVA1412                |
| 40.0  | 150         | EH                   | TVA1413                |
| 50.0  | 150         | EH                   | TVA1414                |
| 80.0  | 150         | GK                   | TVA1418                |
| 100.0   | 150         | GK                   | TVA1420                |
| 150.0   | 150         | HL                   | TVA1422                |
| 200.0   | 150         | JL                   | TVA1423                |
| 300.0   | 150         | KP                   | TVA1425                |
| 3.0   | 200         | CC                   | TVA1436                |
| 5.0   | 200         | DC                   | TVA1438                |
| 10.0  | 200         | DD                   | TVA1441                |
| 20.0  | 200         | EF                   | TVA1442.1              |
| 100.0   | 200         | HL                   | TVA1445                |
| 4.0   | 250         | DC                   | TVA1501                |
| 10.0  | 250         | DF                   | TVA1504                |
| 12.0  | 250         | EF                   | TVA1505                |
| 20.0  | 250         | EH                   | TVA1508                |
| 30.0  | 250         | GH                   | TVA1510                |
| 40.0  | 250         | GK                   | TVA1511                |
| 50.0  | 250         | HG                   | TVA1512                |
| 60.0  | 250         | HJ                   | TVA1513                |
| 100.0   | 250         | JK                   | TVA1522                |
| 1.0   | 300         | CB                   | TVA1540                |
| 3.0   | 350         | DD                   | TVA1600.1              |
| 4.0   | 350         | DF                   | TVA1601                |
| 5.0   | 350         | DF                   | TVA1602.5              |
| 8.0   | 350         | EH                   | TVA1603                |
| 10.0  | 350         | EH                   | TVA1604                |
| 15.0  | 350         | FK                   | TVA1607                |
| 20.0  | 350         | GK                   | TVA1608                |
| 60.0  | 350         | HL                   | TVA1613                |
| 100.0   | 350         | JP                   | TVA1620                |
| 1.0   | 450         | DC                   | TVA1700                |
| 2.0   | 450         | DF                   | TVA1701                |
| 4.0   | 450         | EH                   | TVA1702                |
| 5.0   | 450         | EH                   | TVA1703                |
| 8.0   | 450         | FK                   | TVA1704                |
| 10.0  | 450         | GK                   | TVA1705                |
| 12.0  | 450         | GK                   | TVA1706                |
| 20.0  | 450         | HJ                   | TVA1709                |
| 30.0  | 450         | HK                   | TVA1711                |
| 40.0  | 450         | HL                   | TVA1712                |
| 50.0  | 450         | KL                   | TVA1713                |
| 100.0   | 450         | LS                   | TVA1718                |
| 60.0  | 450         | KL                   | TVA1714                |
| 80.0  | 450         | JP                   | TVA1716                |
| 20.0  | 500         | HL                   | TVA1906                |
| 16.0  | 475         | HJ                   | TVA1803.1              |
| 40.0  | 500         | JN                   | TVA1908                |
| 10.0  | 600         | JR                   | TVA1963                |
| 20.0  | 600         | JW                   | TVA1966                |
| 30.0  | 500         | JJ                   | TVA1907                |

**Note**

(1) For other capacitance and voltage ratings, please see Types 500D and 53D.



Aluminum Capacitors  
+ 85 °C, Miniature, Axial Lead

| <b>ELECTRICAL DATA AND ORDERING INFORMATION</b> |             |                      |                                   |
|---|-------------|----------------------|-----------------------------------|
| <b>CAPACITANCE<br/>(<math>\mu</math>F)</b>      | <b>WVDC</b> | <b>CASE<br/>CODE</b> | <b>PART NUMBER <sup>(1)</sup></b> |
| <b>NON-POLARIZED</b>                            |             |                      |                                   |
| 50.0  | 10          | CB                   | TVAN1117                          |
| 10.0  | 25          | BB                   | TVAN1204.1                        |
| 16.0  | 25          | BB                   | TVAN1204.3                        |
| 25.0  | 25          | CB                   | TVAN1205.1                        |
| 50.0  | 25          | CC                   | TVAN1206.1                        |
| 100.0   | 25          | DD                   | TVAN1207.1                        |
| 20.0  | 30          | CB                   | TVAN1220                          |
| 2.0   | 50          | BA                   | TVAN1301.1                        |
| 3.0   | 50          | BA                   | TVAN1302.1                        |
| 5.0   | 50          | BB                   | TVAN1303.1                        |
| 8.0   | 50          | BB                   | TVAN1303.4                        |
| 10.0  | 50          | CB                   | TVAN1304.1                        |
| 25.0  | 50          | DC                   | TVAN1306.1                        |
| 50.0  | 50          | DD                   | TVAN1308.1                        |
| 100.0   | 50          | DH                   | TVAN1310.1                        |
| 10.0  | 100         | EJ                   | TVAN1333                          |
| 20.0  | 100         | FJ                   | TVAN1335                          |
| 60.0  | 200         | JP                   | TVAN1440                          |
| 1.0   | 300         | EG                   | TVAN1560                          |
| 5.0   | 350         | GJ                   | TVAN1602                          |
| 20.0  | 400         | JL                   | TVAN1652                          |

**Note**

<sup>(1)</sup> For other capacitance and voltage ratings, please see Types 500D and 53D.



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.