

## Network cable - NBC-MS/10,0-94B/R4RC SCO - 1407429

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid  
(<http://download.phoenixcontact.com>)



Network cable, Ethernet CAT5 (0.1 Gbps), Ethernet CAT5e (0.1 Gbps), 8-position, PUR, water blue RAL 5021, shielded, Plug Straight M12 SPEEDCON / IP67, Coding: A, on Plug Straight RJ45 Push Pull / IP67, Cable length: 10 m



### Key commercial data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 pc     |
| Custom tariff number | 85444210 |
| Country of origin    | Poland   |

### Technical data

#### Dimensions

|                 |      |
|-----------------|------|
| Length of cable | 10 m |
|-----------------|------|

#### Ambient conditions

|                      |                       |
|----------------------|-----------------------|
| Degree of protection | IP65 (M12 connector)  |
|                      | IP67 (M12 connector)  |
|                      | IP67 (RJ45 connector) |

#### General data

|                       |                                          |
|-----------------------|------------------------------------------|
| Rated current at 40°C | 1 A                                      |
| Rated voltage         | 30 V                                     |
| Number of positions   | 8                                        |
| Signal type/category  | Ethernet CAT5 (IEC 11801:2002), 0.1 Gbps |
|                       | Ethernet CAT5e (TIA 568B:2001), 0.1 Gbps |
| Standards/regulations | M12 connector IEC 61076-2-101            |

#### Characteristics head 1

|                                          |                                   |
|------------------------------------------|-----------------------------------|
| Head type                                | Plug Straight M12 SPEEDCON / IP67 |
| No. of positions (pin connector pattern) | 8                                 |

# Network cable - NBC-MS/10,0-94B/R4RC SCO - 1407429

## Technical data

### Characteristics head 1

|                                 |                                                    |
|---------------------------------|----------------------------------------------------|
| Coding                          | A (Standard)                                       |
| Color                           | black                                              |
| Material (component)            | CuZn (Contact)                                     |
|                                 | Ni/Au (Contact surface)                            |
|                                 | TPU GF (Contact carriers)                          |
|                                 | TPU, hardly inflammable, self-extinguishing (Grip) |
|                                 | Zinc die-cast, nickel-plated (Screw connection)    |
| Contact resistance              | $\leq 5 \text{ m}\Omega$                           |
| Insulation resistance           | $\geq 100 \text{ M}\Omega$                         |
| Insertion/withdrawal cycles     | $\geq 100$                                         |
| Torque                          | 0.4 Nm                                             |
| Ambient temperature (operation) | -25 °C ... 90 °C                                   |

### Characteristics head 2

|                                          |                                        |
|------------------------------------------|----------------------------------------|
| Head type                                | Plug Straight RJ45 Push Pull / IP67    |
| No. of positions (pin connector pattern) | 8 (8)                                  |
| Color                                    | silver                                 |
| Material (component)                     | CuSn (Contact)                         |
|                                          | Ni/Au (Contact surface)                |
|                                          | PC (Contact carriers)                  |
|                                          | Zinc die-cast, nickel-plated (Housing) |
| Insertion/withdrawal cycles              | $\geq 750$                             |
| Ambient temperature (operation)          | -40 °C ... 70 °C                       |

### Cable

|                                    |                                                                            |
|------------------------------------|----------------------------------------------------------------------------|
| Cable type                         | Ethernet, flexible, CAT5e                                                  |
| Cable type (abbreviation)          | 94B                                                                        |
| UL AWM style                       | 20963 (80°C/30 V)                                                          |
| Signal type/category               | Ethernet CAT5 (IEC 11801:2002), 0.1 Gbps                                   |
|                                    | Ethernet CAT5e (TIA 568B:2001), 0.1 Gbps                                   |
| Cable structure                    | 4x2xAWG26/7; SF/UTP                                                        |
| Conductor cross section            | 4x 2x 0.14 mm <sup>2</sup>                                                 |
| AWG signal line                    | 26                                                                         |
| Conductor structure signal line    | 7x 0.16 mm                                                                 |
| Core diameter including insulation | 0.98 mm                                                                    |
| Thickness, insulation              | 0.25 mm                                                                    |
| Wire colors                        | white/blue-blue, white/orange-orange, white/green-green, white/brown-brown |
| Twisted pairs                      | 2 cores to the pair                                                        |

# Network cable - NBC-MS/10,0-94B/R4RC SCO - 1407429

## Technical data

### Cable

|                                               |                                                    |
|-----------------------------------------------|----------------------------------------------------|
| Overall twist                                 | 4 pairs                                            |
| Shielding                                     | Aluminum-coated foil, tinned copper braided shield |
| Optical shield covering                       | 70 %                                               |
| External sheath, color                        | water blue RAL 5021                                |
| Outer sheath thickness                        | 1 mm                                               |
| External cable diameter D                     | 6.4 mm ±0.2 mm                                     |
| Smallest bending radius, fixed installation   | 25.6 mm                                            |
| Smallest bending radius, movable installation | 51.2 mm                                            |
| Tensile strength short-term/long-term         | ≤ 100 N                                            |
| Cable weight                                  | 47 kg/km                                           |
| Outer sheath, material                        | PUR                                                |
| Material conductor insulation                 | PE                                                 |
| Conductor material                            | Bare Cu litz wires                                 |
| Insulation resistance                         | ≥ 500 MΩ*km                                        |
| Loop resistance                               | ≤ 290 Ω (per kilometer)                            |
| Working capacitance                           | 48 nF (At 1 kHz)                                   |
| Wave impedance                                | 100 Ω ±5 Ω (at 100 MHz)                            |
| Signal runtime                                | 5.3 ns/m                                           |
| Coupling resistance                           | ≤ 100.00 mΩ/m (At 10 MHz)                          |
| Nominal voltage, cable                        | ≤ 100 V                                            |
|                                               | 300 V (Outer cable sheath)                         |
| Test voltage Core/Core                        | 700 V (50 Hz, 1 min.)                              |
| Test voltage Core/Shield                      | 700 V (50 Hz, 1 min.)                              |
| Flame resistance                              | IEC 60332-1-2                                      |
| Halogen-free                                  | According to IEC 60754-1                           |
| Resistance to oil                             | in accordance with DIN EN 60811-2-1                |
| Ambient temperature (operation)               | -40 °C ... 80 °C (cable, fixed installation)       |
|                                               | -20 °C ... 80 °C (cable, flexible installation)    |
| Ambient temperature (installation)            | -20 °C ... 80 °C                                   |
| Ambient temperature (storage/transport)       | -20 °C ... 80 °C                                   |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060306 |
| eCl@ss 4.1 | 27060306 |
| eCl@ss 5.0 | 27061801 |

## Network cable - NBC-MS/10,0-94B/R4RC SCO - 1407429

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27061801 |
| eCl@ss 6.0 | 27061801 |
| eCl@ss 7.0 | 27061801 |
| eCl@ss 8.0 | 27061801 |

#### ETIM


|          |          |
|----------|----------|
| ETIM 3.0 | EC001855 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC001855 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |

### Drawings

Schematic diagram




Connector pin assignment plug RJ45

Cable cross section




Ethernet, flexible, CAT5e [94B]

Schematic diagram



Pin assignment M12 plug, 8-pos., A-coded, view plug side


Dimensioned drawing



Plug, M12 x 1, straight, shielded


## Network cable - NBC-MS/10,0-94B/R4RC SCO - 1407429

Dimensioned drawing



RJ45 Push-Pull connector, IP67

Circuit diagram



Contact assignment of the M12 and RJ45 plug



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.