

Type WMC Polyester Film/Foil Capacitors

Axial Lead, Miniature Size for Automatic Insertion



Type WMC axial-lead polyester film/foil capacitors are ideal for automatic insertion in printed circuit boards. It is an ultraminiature version of Type WMF and the sections of these non-inductive capacitors are constructed with extended foil, polyester film, with tinned copper-clad steel leads.

Highlights

- Miniature Size
- Available on tape and reel
- Film/foil construction, non-inductive design
- High dV/dt ratings
- Good for high pulse applications

Specifications



Complies with the EU Directive 2002/95/EC requirement restricting the use of Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent chromium (Cr(VI)), PolyBrominated Biphenyls (PBB) and PolyBrominated Diphenyl Ethers (PBDE).

| | |
|-------------------------------|--|
| Capacitance Range: | .001 μ F to .47 μ F |
| Voltage Range: | 80 to 400 Vdc |
| Capacitance Tolerance: | \pm 10% standard, \pm 5% optional |
| Temperature Range: | -55 to +125 $^{\circ}$ C <small>(Full-rated voltage at 85 $^{\circ}$C--Derate linearly to 50%-rated voltage at 125 $^{\circ}$C)</small> |
| Dielectric Strength: | 250% of rated voltage for 1 minute |
| Dissipation Factor: | .75% Max. (25 $^{\circ}$ C, 1 kHz) |
| Insulation Resistance: | 30,000 M Ω x μ F, 100,000 M Ω Min. |
| Life Test: | 250 hours at 85 $^{\circ}$ C at 125% rated voltage |

Outline Drawing



Lead Diameters:

No. 24 AWG to .282" (6.35mm) diameter
No. 22 AWG .283" (6.38mm) diameter and up

NOTE: Other capacitance values, sizes and performance specifications are available. Contact us.

Pulse Ratings

| Pulse Capability | | | | | |
|--|-------------|-----------|-----------|-------|-------|
| Rated Voltage | Body Length | | | | |
| | $\leq .437$ | .531-.593 | .656-.718 | 0.906 | 1.218 |
| dV/dt — volts per microsecond, maximum | | | | | |
| 80 | 5000 | 2100 | 1500 | 900 | 690 |
| 200 | 10800 | 5000 | 3000 | 1700 | 1260 |
| 400 | 30700 | 14500 | 9600 | 3600 | 2600 |

Ratings

| Cap (μ F) | Catalog Part Number | D Inches (mm) | L Inches (mm) | d Inches (mm) |
|----------------|---------------------|---------------|---------------|---------------|
| 80 Vdc | | | | |
| 0.0010 | WMC08D1K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0012 | WMC08D12K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0015 | WMC08D15K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0018 | WMC08D18K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0022 | WMC08D22K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0027 | WMC08D27K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |

| Cap (μ F) | Catalog Part Number | D Inches (mm) | L Inches (mm) | d Inches (mm) |
|----------------|---------------------|---------------|---------------|---------------|
| 80 Vdc | | | | |
| 0.0033 | WMC08D33K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0039 | WMC08D39K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0047 | WMC08D47K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0056 | WMC08D56K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0068 | WMC08D68K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0082 | WMC08D82K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |

Type WMC Polyester Film/Foil Capacitors

| Cap (μ F) | Catalog Part Number | D Inches (mm) | L Inches (mm) | d Inches (mm) |
|--------------------|------------------------|------------------|------------------|------------------|
| 80 Vdc | | | | |
| 0.010 | WMC08S1K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.012 | WMC08S12K-F | .185 (4.7) | .468 (11.9) | .020 (.5) |
| 0.015 | WMC08S15K-F | .185 (4.7) | .468 (11.9) | .020 (.5) |
| 0.018 | WMC08S18K-F | .185 (4.7) | .531 (13.5) | .020 (.5) |
| 0.022 | WMC08S22K-F | .185 (4.7) | .531 (13.5) | .020 (.5) |
| 0.027 | WMC08S27K-F | .229 (5.8) | .468 (11.9) | .020 (.5) |
| 0.033 | WMC08S33K-F | .229 (5.8) | .468 (11.9) | .020 (.5) |
| 0.039 | WMC08S39K-F | .229 (5.8) | .593 (15.1) | .020 (.5) |
| 0.047 | WMC08S47K-F | .229 (5.8) | .593 (15.1) | .020 (.5) |
| 0.056 | WMC08S56K-F | .250 (6.3) | .593 (15.1) | .020 (.5) |
| 0.068 | WMC08S68K-F | .250 (6.3) | .593 (15.1) | .020 (.5) |
| 0.082 | WMC08S82K-F | .343 (8.7) | .531 (13.5) | .024 (.6) |
| 0.10 | WMC08P1K-F | .343 (8.7) | .531 (13.5) | .024 (.6) |
| 0.12 | WMC08P12K-F | .343 (8.7) | .656 (16.7) | .024 (.6) |
| 0.15 | WMC08P15K-F | .343 (8.7) | .656 (16.7) | .024 (.6) |
| 0.18 | WMC08P18K-F | .382 (9.7) | .656 (16.7) | .024 (.6) |
| 0.22 | WMC08P22K-F | .382 (9.7) | .656 (16.7) | .024 (.6) |
| 0.27 | WMC08P27K-F | .382 (9.7) | .905 (23.0) | .024 (.6) |
| 0.33 | WMC08P33K-F | .382 (9.7) | .905 (23.0) | .024 (.6) |
| 0.39 | WMC08P39K-F | .382 (9.7) | 1.218 (30.9) | .024 (.6) |
| 0.47 | WMC08P47K-F | .382 (9.7) | 1.218 (30.9) | .024 (.6) |
| 200/250 Vdc | | | | |
| 0.0010 | WMC2D1K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0012 | WMC2D12K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0015 | WMC2D15K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0018 | WMC2D18K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0022 | WMC2D22K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0027 | WMC2D27K-F | .185 (4.7) | .406 (10.3) | .020 (.5) |
| 0.0033 | WMC2D33K-F | .185 (4.7) | .468 (11.9) | .020 (.5) |
| 0.0039 | WMC2D39K-F | .185 (4.7) | .468 (11.9) | .020 (.5) |
| 0.0047 | WMC2D47K-F | .185 (4.7) | .468 (11.9) | .020 (.5) |
| 0.0056 | WMC2D56K-F | .185 (4.7) | .468 (11.9) | .020 (.5) |
| 0.0068 | WMC2D68K-F | .185 (4.7) | .468 (11.9) | .020 (.5) |
| 0.0082 | WMC2D82K-F | .185 (4.7) | .531 (13.5) | .020 (.5) |
| 0.010 | WMC2S1K-F | .185 (4.7) | .531 (13.5) | .020 (.5) |
| 0.012 | WMC2S12K-F | .229 (5.8) | .468 (11.9) | .020 (.5) |
| 0.015 | WMC2S15K-F | .229 (5.8) | .468 (11.9) | .020 (.5) |
| 0.018 | WMC2S18K-F | .229 (5.8) | .656 (16.7) | .020 (.5) |

| Cap (μ F) | Catalog Part Number | D Inches (mm) | L Inches (mm) | d Inches (mm) |
|--------------------|------------------------|------------------|------------------|------------------|
| 200/250 Vdc | | | | |
| 0.022 | WMC2S22K-F | .229 (5.8) | .656 (16.7) | .020 (.5) |
| 0.027 | WMC2S27K-F | .250 (6.3) | .656 (16.7) | .020 (.5) |
| 0.033 | WMC2S33K-F | .250 (6.3) | .656 (16.7) | .020 (.5) |
| 0.039 | WMC2S39K-F | .343 (8.7) | .531 (13.5) | .024 (.6) |
| 0.047 | WMC2S47K-F | .343 (8.7) | .531 (13.5) | .024 (.6) |
| 0.056 | WMC2S56K-F | .343 (8.7) | .656 (16.7) | .024 (.6) |
| 0.068 | WMC2S68K-F | .343 (8.7) | .656 (16.7) | .024 (.6) |
| 0.082 | WMC2S82K-F | .382 (9.7) | .656 (16.7) | .024 (.6) |
| 0.10 | WMC2P1K-F | .382 (9.7) | .656 (16.7) | .024 (.6) |
| 0.12 | WMC2P12K-F | .382 (9.7) | .906 (23.0) | .024 (.6) |
| 0.15 | WMC2P15K-F | .382 (9.7) | .906 (23.0) | .024 (.6) |
| 0.18 | WMC2P18K-F | .382 (9.7) | 1.218 (30.9) | .024 (.6) |
| 0.22 | WMC2P22K-F | .382 (9.7) | 1.218 (30.9) | .024 (.6) |
| 400 Vdc | | | | |
| 0.0010 | WMC4D1K-F | .185 (4.7) | .468 (11.9) | .020 (.5) |
| 0.0012 | WMC4D12K-F | .185 (4.7) | .468 (11.9) | .020 (.5) |
| 0.0015 | WMC4D15K-F | .185 (4.7) | .468 (11.9) | .020 (.5) |
| 0.0018 | WMC4D18K-F | .185 (4.7) | .531 (13.5) | .020 (.5) |
| 0.0022 | WMC4D22K-F | .185 (4.7) | .531 (13.5) | .020 (.5) |
| 0.0027 | WMC4D27K-F | .229 (5.8) | .531 (13.5) | .020 (.5) |
| 0.0033 | WMC4D33K-F | .229 (5.8) | .531 (13.5) | .020 (.5) |
| 0.0039 | WMC4D39K-F | .229 (5.8) | .531 (13.5) | .020 (.5) |
| 0.0047 | WMC4D47K-F | .229 (5.8) | .531 (13.5) | .020 (.5) |
| 0.0056 | WMC4D56K-F | .250 (6.3) | .656 (16.7) | .020 (.5) |
| 0.0068 | WMC4D68K-F | .250 (6.3) | .656 (16.7) | .020 (.5) |
| 0.0082 | WMC4D82K-F | .250 (6.3) | .656 (16.7) | .020 (.5) |
| 0.010 | WMC4S1K-F | .250 (6.3) | .656 (16.7) | .020 (.5) |
| 0.012 | WMC4S12K-F | .343 (8.7) | .593 (15.1) | .024 (.6) |
| 0.015 | WMC4S15K-F | .343 (8.7) | .593 (15.1) | .024 (.6) |
| 0.018 | WMC4S18K-F | .343 (8.7) | .718 (18.2) | .024 (.6) |
| 0.022 | WMC4S22K-F | .343 (8.7) | .718 (18.2) | .024 (.6) |
| 0.027 | WMC4S27K-F | .382 (9.7) | .718 (18.2) | .024 (.6) |
| 0.033 | WMC4S33K-F | .382 (9.7) | .718 (18.2) | .024 (.6) |
| 0.039 | WMC4S39K-F | .382 (9.7) | .906 (23.0) | .024 (.6) |
| 0.047 | WMC4S47K-F | .382 (9.7) | .906 (23.0) | .024 (.6) |
| 0.056 | WMC4S56K-F | .382 (9.7) | 1.218 (30.9) | .024 (.6) |
| 0.068 | WMC4S68K-F | .382 (9.7) | 1.218 (30.9) | .024 (.6) |

Type WMC Polyester Film/Foil Capacitors

Notice and Disclaimer: All product drawings, descriptions, specifications, statements, information and data (collectively, the "Information") in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements ("Cornell Dubilier") has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.