



AT-4000-A Advanced Wire Tracer Series

Advanced in Wire Tracing Technology

Quickly trace energized and non-energized wires effortlessly with the Amprobe AT-4000-A Wire Tracer Series. Out-performing other wire tracers in its class, these advanced tracers combine features and functions to make locating wires more accurate and your job more efficient.

- AT-4001-A Advanced Wire Tracer with Soft Case
- AT-4003-A Advanced Wire Tracer
- AT-4004-A Advanced Wire Tracer with Clamp-On Attachment
- AT-4005-A Advanced Wire Tracer with Clamp-On Attachment, Battery Booster & Charger



R-4000



T-4000-A



AT-4005-A

- Determines presence of energized or non-energized wires hidden behind walls, flooring or conduit
- Pinpoints wires, breakers, neutrals, shorts, broken wires and ground lines
- Operates safely and easily without interrupting power or interfering with sensitive electronic equipment
- Get accurate readings without rotating the unit – receiver is not position sensitive
- Clamp-on attachment injects signal for non-contact operation (AT-4004-A and AT-4005-A only)
- Optional Battery Booster accessory strengthens signal for open tracing (AT-4005-A only)

AT-4000-A SPECIFICATIONS

Specifications	AT-4001-A	AT-4003-A	AT-4004-A	AT-4005-A
Transmitter operating voltage	9 - 300 V ac			
Operating frequency	32.786kHz			
Receiver short mode range	6.01m (20') in air from the traced wire under test conditions			
Receiver open mode range	3.7m (12') in air from the traced wire under test conditions			
Receiver R-4000	■	■	■	■
Transmitter T-4000-A	■	■	■	■
110V Pigtail - banana plug cord set C2901	■	■	■	■
Alligator clip - banana plug cord set C2902	■	■	■	■
Grounding test lead 25' (7.6 m) MTL-G	■	■	■	■
Alligator clip for ground lead VRC-320	■	■	■	■
Clamp-on transmitter accessory A2202			■	■
Rechargeable battery pack B2024				■
Battery pack recharger B2025				■
Users manual	■	■	■	■
Carrying case	Soft SV-1000	Hard CC-AT-4000	Hard CC-AT-4000	Hard CC-AT-4000

For more detailed specifications see users manual.

AT-4000-A DETAILED SPECIFICATIONS

Specifications	Range
Transmitter operating voltage	9 - 300 V ac
Operating frequency	32.786 kHz
Receiver range short mode (in air)	6.01m (20') in air from the traced wire under test conditions
Receiver range open mode (in air)	3.7m (12') in air from the traced wire under test conditions
Operating temperature	-18°C to 49°C (0 to 120°F)
Storage temperature	-40° to 66°C (-40° to 150°F)
Case material	ABS
Case size	14 x 6.7mm (0.55" x 0.26")
Weight (AT-4005-A)	3.72 kg (8.2lbs)

R-4000 Receiver

Detectors	Electromagnetic Coil Array pick up for short mode. Electrostatic plate pick up for open mode.
Sensitivity	Low, mid, and high gain with precise sensitivity adjustment
Short mode performance	Over 6.01m (20') in air from the traced wire under test conditions.
Open mode performance	Over 3.7m (12') from the traced wire in air under test conditions.
50HZ, 60HZ, and 400HZ rejection	120db
Power source	9V alkaline battery
Display	10 LEDs
Case	Flame retardant ABS
Weight	143.5 g (0.32 lbs)

T-4000-A Transmitter

Operating voltage	9 - 300 V
Operating frequency	32.768 KHZ
Duty cycle	Transmit 2 pulses with a duration of 0.0625 seconds each, every 0.5 seconds
Case	Flame retardant ABS
Display	LCD
Weight	143.5 g (0.32 lbs)
Current output of the signal	Low mode: 11 mA average, 30 mA peak Medium mode: 12 mA average, 36 mA peak High mode: 13 mA average, 63 mA peak
Fuse	Fast acting 250 mA @ 1000V (6X46mm) P/N: FA6X46MM
Signal output (9v supply)	High setting: 0.74 V ac; Medium setting: 0.61 V ac; Low setting: 0.53 V ac
Battery	9V alkaline- 24 V jack will accept battery pack accessory (B2024 or B2025)

A2202 Clamp-on Transmitter Accessory

Operating frequency	32.768KHZ as supplied by T-4000
Case breakdown voltage	3000 V
Maximum wire size	2000 MCM or 5.08cm (2") diameter

T-4000-A B2024 Battery Pack

Type	Nickel-cadmium rechargeable (20 AA cells)
Capacity	24 V, 600 mah
Rechargeable time	14 hours
Fuse	Internal, self-resetting

B2025 Recharger / Converter

Input	115 V ac
Output	24 V dc @ 350 mah

For complete specifications please download the product datasheet and the users manual on www.Amprobe.com.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.