

LSW SERIES

Load Life : 105°C 3000 hours



◆SPECIFICATIONS

| Items | Characteristics | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------------------------------|--|------------|--------------------|-----------------------------------|--------------------|--|-----------------|------------------------------------|------|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|----|------|-----|-----|-----|-----|--|----------|----|----|----|----|----|----|-----|------|-----|-----|-----|----|-----|-----|------|-----|-----|-----|------|-----|------|------|------|---------|------|------|-----|-----|-----|---------|-----|-----|------|------|------|---------------|
| Category Temperature Range | -40~+105°C | -25~+105°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Rated Voltage Range | 10~100Vdc | 160~400Vdc | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Capacitance Tolerance | ±20% (20°C, 120Hz) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Leakage Current(MAX) | I=0.02CV or 5mA whichever is smaller. (After 5 minutes application of rated voltage) I=Leakage Current(μA) C=Capacitance(μF) V=Rated Voltage(Vdc) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Dissipation Factor(MAX) (tanδ) | <table border="1"> <thead> <tr> <th>Vdc \ φD</th> <th>36</th> <th>51</th> <th>64</th> <th>77</th> <th>90</th> </tr> </thead> <tbody> <tr> <td>10</td> <td>0.75</td> <td>1.0</td> <td>1.3</td> <td>1.5</td> <td>1.5</td> </tr> <tr> <td>16</td> <td>0.6</td> <td>0.7</td> <td>0.8</td> <td>1.0</td> <td>1.0</td> </tr> <tr> <td>25</td> <td>0.4</td> <td>0.5</td> <td>0.7</td> <td>0.8</td> <td>0.8</td> </tr> <tr> <td>35</td> <td>0.3</td> <td>0.5</td> <td>0.6</td> <td>0.7</td> <td>0.7</td> </tr> <tr> <td>50</td> <td>0.25</td> <td>0.3</td> <td>0.5</td> <td>0.6</td> <td>0.6</td> </tr> </tbody> </table> | Vdc \ φD | 36 | 51 | 64 | 77 | 90 | 10 | 0.75 | 1.0 | 1.3 | 1.5 | 1.5 | 16 | 0.6 | 0.7 | 0.8 | 1.0 | 1.0 | 25 | 0.4 | 0.5 | 0.7 | 0.8 | 0.8 | 35 | 0.3 | 0.5 | 0.6 | 0.7 | 0.7 | 50 | 0.25 | 0.3 | 0.5 | 0.6 | 0.6 | <table border="1"> <thead> <tr> <th>Vdc \ φD</th> <th>36</th> <th>51</th> <th>64</th> <th>77</th> <th>90</th> </tr> </thead> <tbody> <tr> <td>63</td> <td>0.2</td> <td>0.25</td> <td>0.3</td> <td>0.4</td> <td>0.4</td> </tr> <tr> <td>80</td> <td>0.2</td> <td>0.2</td> <td>0.25</td> <td>0.3</td> <td>0.3</td> </tr> <tr> <td>100</td> <td>0.15</td> <td>0.2</td> <td>0.25</td> <td>0.25</td> <td>0.25</td> </tr> <tr> <td>160~250</td> <td>0.15</td> <td>0.15</td> <td>0.2</td> <td>0.2</td> <td>0.2</td> </tr> <tr> <td>315~400</td> <td>0.2</td> <td>0.2</td> <td>0.25</td> <td>0.25</td> <td>0.25</td> </tr> </tbody> </table> | Vdc \ φD | 36 | 51 | 64 | 77 | 90 | 63 | 0.2 | 0.25 | 0.3 | 0.4 | 0.4 | 80 | 0.2 | 0.2 | 0.25 | 0.3 | 0.3 | 100 | 0.15 | 0.2 | 0.25 | 0.25 | 0.25 | 160~250 | 0.15 | 0.15 | 0.2 | 0.2 | 0.2 | 315~400 | 0.2 | 0.2 | 0.25 | 0.25 | 0.25 | (20°C, 120Hz) |
| Vdc \ φD | 36 | 51 | 64 | 77 | 90 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | 0.75 | 1.0 | 1.3 | 1.5 | 1.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16 | 0.6 | 0.7 | 0.8 | 1.0 | 1.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 25 | 0.4 | 0.5 | 0.7 | 0.8 | 0.8 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 35 | 0.3 | 0.5 | 0.6 | 0.7 | 0.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 50 | 0.25 | 0.3 | 0.5 | 0.6 | 0.6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Vdc \ φD | 36 | 51 | 64 | 77 | 90 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 63 | 0.2 | 0.25 | 0.3 | 0.4 | 0.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 80 | 0.2 | 0.2 | 0.25 | 0.3 | 0.3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 | 0.15 | 0.2 | 0.25 | 0.25 | 0.25 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 160~250 | 0.15 | 0.15 | 0.2 | 0.2 | 0.2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 315~400 | 0.2 | 0.2 | 0.25 | 0.25 | 0.25 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Endurance | <p>After applying rated voltage with rated ripple current for 3000 hours at 105°C, the capacitors shall meet the following requirements.</p> <table border="1"> <tr> <td>Capacitance Change</td> <td>Within ±15% of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 175% of the specified value.</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> </table> | | Capacitance Change | Within ±15% of the initial value. | Dissipation Factor | Not more than 175% of the specified value. | Leakage Current | Not more than the specified value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Capacitance Change | Within ±15% of the initial value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Dissipation Factor | Not more than 175% of the specified value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Leakage Current | Not more than the specified value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Shelf Life | <p>After storage for 500 hours with no voltage applied at 105°C, the capacitors shall be subjected to the voltage treatment in JIS C 5101-4 item 4.1 and shall be meet the following requirements.</p> <table border="1"> <tr> <td>Capacitance Change</td> <td>Within ±15% of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 150% of the specified value.</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> </table> | | Capacitance Change | Within ±15% of the initial value. | Dissipation Factor | Not more than 150% of the specified value. | Leakage Current | Not more than the specified value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Capacitance Change | Within ±15% of the initial value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Dissipation Factor | Not more than 150% of the specified value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Leakage Current | Not more than the specified value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

◆MULTIPLIER FOR RIPPLE CURRENT

| Frequency (Hz) | | 60(50) | 120(100) | 300 | 500 | 10k≤ |
|----------------|------------|--------|----------|------|------|------|
| Coefficient | 10~50Vdc | 0.80 | 1.00 | 1.03 | 1.04 | 1.08 |
| | 63~100Vdc | 0.80 | 1.00 | 1.04 | 1.05 | 1.10 |
| | 160~400Vdc | 0.80 | 1.00 | 1.06 | 1.10 | 1.18 |

◆PART NUMBER

□□□ LSW
□□□□□ M
□□□
□□
D×L
 Rated Voltage Series Capacitance Capacitance Tolerance Option Clamp Code Case Size

◆DIMENSIONS

| | | (mm) | | | | | | |
|--------|----|------|------|-----|-----|----|------|---|
| | | φD | W1 | W2 | W3 | W4 | W5 | F |
| I type | 36 | 24.0 | 30.0 | 3.5 | 7.0 | 10 | 12.7 | |
| | 51 | 34.0 | 40.0 | 3.5 | 6.0 | 12 | 21.8 | |
| | 64 | 40.0 | 45.0 | 4.5 | 7.0 | 12 | 28.2 | |
| | 77 | 47.0 | 53.0 | 4.5 | 6.0 | 12 | 31.4 | |
| Y type | 90 | 54.0 | 60.0 | 4.5 | 6.0 | 14 | 31.4 | |
| | 51 | 32.5 | 37.5 | 4.5 | 6.0 | 12 | 21.8 | |
| | 64 | 38.0 | 43.0 | 4.5 | 8.0 | 14 | 28.2 | |
| | 77 | 44.5 | 49.0 | 4.5 | 7.0 | 14 | 31.4 | |
| | 90 | 50.8 | 56.0 | 4.5 | 8.0 | 16 | 31.4 | |

◆STANDARD SIZE

| Cap(μF) \ Vdc | 10 | | 16 | | 25 | | 35 | | 50 | | 63 | | 80 | | |
|---------------|--------|------|--------|------|--------|------|--------|------|--------|------|--------|-------|--------|-------|-----|
| 3300 | | | | | | | | | | | | | 36×50 | 3.0 | |
| 3900 | | | | | | | | | | | | | 36×63 | 3.3 | |
| 4700 | | | | | | | | | | | | 36×50 | 3.2 | 36×83 | 3.6 |
| 5600 | | | | | | | | | | | | 36×63 | 3.5 | 36×83 | 3.9 |
| 6800 | | | | | | | 36×50 | 2.5 | 36×50 | 3.6 | 36×63 | 3.8 | 36×83 | 4.3 | |
| 8200 | | | | | | | 36×50 | 2.8 | 36×63 | 3.9 | 36×83 | 4.3 | 36×98 | 5.1 | |
| 10000 | | | | | | | 36×50 | 3.8 | 36×83 | 4.2 | 36×83 | 4.7 | 36×118 | 5.8 | |
| 12000 | | | | | | | 36×63 | 4.3 | 36×83 | 5.0 | 36×98 | 5.6 | 51×83 | 7.0 | |
| 15000 | | | | | 36×50 | 4.2 | 36×83 | 4.7 | 36×98 | 5.5 | 36×118 | 6.4 | 51×83 | 7.6 | |
| 18000 | | | | | 36×63 | 4.6 | 36×83 | 5.1 | 36×98 | 5.7 | 51×83 | 7.5 | 51×98 | 7.7 | |
| 22000 | | | 36×50 | 4.0 | 36×83 | 5.2 | 36×98 | 6.6 | 36×118 | 7.5 | 51×83 | 7.5 | 51×118 | 9.0 | |
| 27000 | 36×50 | 4.4 | 36×63 | 5.0 | 36×83 | 5.4 | 36×118 | 6.7 | 51×83 | 7.5 | 51×98 | 8.7 | 64×99 | 10.1 | |
| 33000 | 36×63 | 5.5 | 36×83 | 5.2 | 36×98 | 6.5 | 51×83 | 7.1 | 51×98 | 9.3 | 51×118 | 10.3 | 64×119 | 11.6 | |
| 39000 | 36×63 | 6.0 | 36×83 | 5.8 | 36×98 | 7.5 | 51×83 | 8.4 | 51×98 | 9.4 | 64×99 | 11.2 | 64×139 | 13.5 | |
| 47000 | 36×83 | 6.6 | 36×98 | 6.8 | 36×118 | 8.9 | 51×98 | 9.9 | 51×118 | 11.7 | 64×119 | 12.9 | 77×101 | 15.8 | |
| 56000 | 36×83 | 7.5 | 36×98 | 6.9 | 51×83 | 10.0 | 51×98 | 10.3 | 64×99 | 12.4 | 64×139 | 15.2 | 77×121 | 17.0 | |
| 68000 | 36×98 | 7.6 | 36×118 | 8.4 | 51×83 | 10.7 | 51×118 | 11.4 | 64×119 | 15.1 | 77×101 | 16.0 | 77×141 | 20.4 | |
| 82000 | 36×118 | 9.0 | 51×83 | 8.4 | 51×98 | 12.0 | 64×99 | 12.5 | 77×101 | 15.5 | 77×121 | 17.7 | 77×151 | 21.5 | |
| 100000 | 51×83 | 10.2 | 51×98 | 11.3 | 51×118 | 13.1 | 64×119 | 15.5 | 77×101 | 16.3 | 77×141 | 21.5 | 90×151 | 22.3 | |
| 120000 | 51×83 | 11.0 | 51×98 | 11.4 | 64×99 | 13.7 | 77×101 | 15.5 | 77×121 | 19.1 | 90×141 | 22.4 | | | |
| 150000 | 51×98 | 13.4 | 51×118 | 12.5 | 64×119 | 16.4 | 77×121 | 17.9 | 77×141 | 23.4 | | | | | |
| 180000 | 51×118 | 14.0 | 64×99 | 14.2 | 77×101 | 16.7 | 77×141 | 20.0 | 90×141 | 23.7 | | | | | |
| 220000 | 64×99 | 14.5 | 64×119 | 16.6 | 77×121 | 20.5 | 77×151 | 24.1 | | | | | | | |
| 270000 | 64×119 | 16.0 | 77×101 | 17.5 | 77×141 | 21.3 | 90×141 | 26.5 | | | | | | | |
| 330000 | 77×101 | 18.0 | 77×121 | 24.3 | 77×151 | 26.0 | | | | | | | | | |
| 390000 | 77×101 | 19.5 | 77×141 | 25.2 | 90×141 | 27.2 | | | | | | | | | |
| 470000 | 77×121 | 20.0 | 77×151 | 26.7 | | | | | | | | | | | |
| 560000 | 77×141 | 24.1 | 90×141 | 29.1 | | | | | | | | | | | |
| 680000 | 90×141 | 26.5 | | | | | | | | | | | | | |

| Cap(μF) \ Vdc | 100 | | 160 | | 200 | | 250 | | 315 | | 350 | | 400 | |
|---------------|--------|------|--------|------|--------|------|--------|------|--------|-----|--------|-----|--------|-----|
| 220 | | | | | | | | | | | 36×50 | 0.9 | 36×50 | 1.0 |
| 270 | | | | | | | | | 36×50 | 1.0 | 36×50 | 1.0 | 36×63 | 1.0 |
| 330 | | | | | | | | | 36×50 | 1.2 | 36×63 | 1.2 | 36×63 | 1.2 |
| 390 | | | | | | | | | 36×63 | 1.3 | 36×83 | 1.3 | 36×83 | 1.4 |
| 470 | | | | | | | 36×50 | 1.3 | 36×83 | 1.5 | 36×83 | 1.5 | 36×98 | 1.5 |
| 560 | | | | | 36×50 | 1.4 | 36×63 | 1.6 | 36×83 | 1.6 | 36×98 | 1.7 | 36×98 | 1.7 |
| 680 | | | | | 36×50 | 1.5 | 36×83 | 1.7 | 36×98 | 1.9 | 36×98 | 1.9 | 51×83 | 2.3 |
| 820 | | | 36×50 | 1.4 | 36×83 | 1.9 | 36×83 | 1.9 | 36×118 | 2.2 | 36×118 | 2.1 | 51×98 | 2.4 |
| 1000 | | | 36×63 | 1.9 | 36×83 | 2.2 | 36×98 | 2.3 | 51×83 | 2.3 | 51×98 | 2.5 | 51×118 | 2.7 |
| 1200 | | | 36×83 | 2.3 | 36×83 | 2.3 | 36×98 | 2.4 | 51×98 | 2.7 | 51×98 | 2.7 | 51×118 | 3.0 |
| 1500 | | | 36×83 | 2.6 | 36×98 | 2.9 | 36×118 | 2.9 | 51×98 | 3.1 | 51×118 | 3.3 | 64×99 | 3.5 |
| 1800 | | | 36×83 | 2.6 | 36×98 | 2.9 | 36×118 | 3.0 | 51×118 | 3.6 | 64×99 | 3.8 | 64×119 | 3.6 |
| 2200 | 36×50 | 2.9 | 36×98 | 3.2 | 36×118 | 3.3 | 51×98 | 3.8 | 64×99 | 4.2 | 64×119 | 4.6 | 77×101 | 4.1 |
| 2700 | 36×63 | 3.4 | 36×118 | 3.2 | 51×83 | 3.8 | 51×118 | 4.5 | 64×119 | 4.3 | 77×101 | 4.6 | 77×121 | 4.8 |
| 3300 | 36×83 | 3.9 | 36×118 | 3.7 | 51×98 | 4.7 | 64×99 | 5.2 | 77×101 | 4.9 | 77×121 | 5.3 | 77×141 | 5.7 |
| 3900 | 36×83 | 4.2 | 51×98 | 4.3 | 51×118 | 5.4 | 64×119 | 5.2 | 77×121 | 5.8 | 77×141 | 6.2 | 90×141 | 6.7 |
| 4700 | 36×83 | 4.6 | 51×98 | 4.8 | 64×99 | 6.2 | 64×119 | 5.7 | 77×121 | 6.3 | 90×141 | 7.4 | 90×141 | 7.4 |
| 5600 | 36×98 | 4.9 | 51×118 | 5.5 | 64×99 | 6.3 | 77×101 | 6.4 | 77×141 | 7.3 | 90×141 | 8.1 | | |
| 6800 | 36×118 | 5.5 | 64×99 | 6.3 | 64×119 | 7.3 | 77×121 | 7.6 | 90×141 | 8.9 | | | | |
| 8200 | 51×83 | 6.2 | 64×119 | 7.1 | 77×101 | 8.5 | 77×141 | 8.3 | | | | | | |
| 10000 | 51×98 | 6.7 | 77×101 | 7.9 | 77×121 | 9.5 | 90×141 | 9.9 | | | | | | |
| 12000 | 51×98 | 7.3 | 77×121 | 9.0 | 77×141 | 10.5 | 90×141 | 10.8 | | | | | | |
| 15000 | 51×118 | 8.6 | 77×141 | 11.3 | 90×141 | 12.5 | | | | | | | | |
| 18000 | 64×99 | 8.9 | 90×141 | 13.0 | 90×141 | 13.3 | | | | | | | | |
| 22000 | 64×119 | 10.3 | 90×141 | 14.3 | | | | | | | | | | |
| 27000 | 64×139 | 12.1 | | | | | | | | | | | | |
| 33000 | 77×121 | 14.1 | | | | | | | | | | | | |
| 39000 | 77×141 | 16.5 | | | | | | | | | | | | |
| 47000 | 77×141 | 18.3 | | | | | | | | | | | | |
| 56000 | 90×141 | 19.2 | | | | | | | | | | | | |
| 68000 | 90×151 | 20.1 | | | | | | | | | | | | |

↑ Ripple Current (A r.m.s./120Hz, 105°C)
 ↑ Case Size φD×L(mm)

◆Tightening torque of bolt and Permissible current of terminal

| Clamp Bolt | Recommended Tightening torque |
|------------|-------------------------------|
| M3 | 0.6 [N·m] |
| M4 | 1.3 [N·m] |

| Terminal | Recommended Tightening torque (Permissible Range) | Permissible Current of Terminal |
|----------|---|---------------------------------|
| M5 | 2.2(1.5~3.2) [N·m] | 60[A r.m.s.] |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Rubycon:

[400LSW2700MNB77X121](#) [35LSW6800MNB36X50](#) [315LSW1500MNB51X98](#) [25LSW18000MNB36X63](#)
[250LSW2700MNB51X118](#) [63LSW33000MNB51X118](#) [200LSW4700MNB64X99](#) [350LSW1200MNB51X98](#)
[350LSW1500MNB51X118](#) [80LSW12000MNB51X83](#) [315LSW270MNB36X50](#) [50LSW150000MNB77X141](#)
[400LSW680MNB51X83](#) [35LSW56000MNB51X98](#) [10LSW470000MNB77X121](#) [35LSW15000MNB36X83](#)
[25LSW82000MNB51X98](#) [250LSW2200MNB51X98](#) [350LSW270MNB36X50](#) [35LSW150000MNB77X121](#)
[10LSW47000MNB36X83](#) [200LSW12000MNB77X141](#) [16LSW39000MNB36X83](#) [100LSW47000MNB77X141](#)
[160LSW1800MNB36X83](#) [350LSW470MNB36X83](#) [16LSW120000MNB51X98](#) [80LSW4700MNB36X83](#)
[100LSW27000MNB64X139](#) [63LSW10000MNB36X83](#) [80LSW47000MNB77X101](#) [10LSW150000MNB51X98](#)
[80LSW10000MNB36X118](#) [400LSW390MNB36X83](#) [350LSW390MNB36X83](#) [160LSW4700MNB51X98](#)
[160LSW6800MNB64X99](#) [250LSW560MNB36X63](#) [35LSW10000MNB36X50](#) [10LSW680000MNB90X141](#)
[160LSW3900MNB51X98](#) [10LSW56000MNB36X83](#) [50LSW18000MNB36X98](#) [63LSW27000MNB51X98](#)
[10LSW120000MNB51X83](#) [80LSW100000MNB90X151](#) [25LSW68000MNB51X98](#) [100LSW39000MNB77X141](#)
[160LSW8200MNB64X119](#) [80LSW3300MNB36X50](#) [50LSW100000MNB77X101](#) [80LSW18000MNB51X98](#)
[10LSW330000MNB77X101](#) [80LSW56000MNB77X121](#) [250LSW820MNB36X83](#) [400LSW1000MNB51X118](#)
[16LSW33000MNB36X83](#) [10LSW68000MNB36X98](#) [100LSW2700MNB36X63](#) [350LSW680MNB36X98](#)
[10LSW33000MNB36X63](#) [80LSW5600MNB36X83](#) [315LSW3900MNB77X121](#) [50LSW47000MNB51X118](#)
[63LSW68000MNB77X101](#) [25LSW180000MNB77X101](#) [350LSW1000MNB51X98](#) [200LSW3300MNB51X98](#)
[50LSW15000MNB36X98](#) [315LSW560MNB36X83](#) [160LSW2700MNB36X118](#) [80LSW3900MNB36X63](#)
[35LSW82000MNB64X99](#) [63LSW82000MNB77X121](#) [250LSW4700MNB64X119](#) [50LSW10000MNB36X83](#)
[350LSW3300MNB77X121](#) [200LSW10000MNB77X121](#) [400LSW220MNB36X50](#) [16LSW47000MNB36X98](#)
[315LSW820MNB36X118](#) [100LSW10000MNB51X98](#) [200LSW820MNB36X83](#) [10LSW270000MNB64X119](#)
[160LSW1500MNB36X83](#) [16LSW150000MNB51X118](#) [10LSW560000MNB77X141](#) [25LSW39000MNB36X98](#)
[350LSW220MNB36X50](#) [100LSW68000MNB90X151](#) [35LSW47000MNB51X98](#) [200LSW1200MNB36X83](#)
[315LSW1800MNB51X118](#) [25LSW120000MNB64X99](#) [250LSW5600MNB77X101](#) [160LSW1000MNB36X63](#)
[10LSW39000MNB36X63](#) [35LSW33000MNB51X83](#) [400LSW3900MNB90X141](#) [50LSW12000MNB36X83](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.