

LSW SERIES

Load Life : 105°C 3000 hours



◆SPECIFICATIONS

Items	Characteristics																																																																										
Category Temperature Range	-40~+105°C	-25~+105°C																																																																									
Rated Voltage Range	10~100Vdc	160~400Vdc																																																																									
Capacitance Tolerance	±20% (20°C, 120Hz)																																																																										
Leakage Current(MAX)	I=0.02CV or 5mA whichever is smaller. (After 5 minutes application of rated voltage) I=Leakage Current(μA) C=Capacitance(μF) V=Rated Voltage(Vdc)																																																																										
Dissipation Factor(MAX) (tanδ)	<table border="1"> <thead> <tr> <th>Vdc \ φD</th> <th>36</th> <th>51</th> <th>64</th> <th>77</th> <th>90</th> </tr> </thead> <tbody> <tr> <td>10</td> <td>0.75</td> <td>1.0</td> <td>1.3</td> <td>1.5</td> <td>1.5</td> </tr> <tr> <td>16</td> <td>0.6</td> <td>0.7</td> <td>0.8</td> <td>1.0</td> <td>1.0</td> </tr> <tr> <td>25</td> <td>0.4</td> <td>0.5</td> <td>0.7</td> <td>0.8</td> <td>0.8</td> </tr> <tr> <td>35</td> <td>0.3</td> <td>0.5</td> <td>0.6</td> <td>0.7</td> <td>0.7</td> </tr> <tr> <td>50</td> <td>0.25</td> <td>0.3</td> <td>0.5</td> <td>0.6</td> <td>0.6</td> </tr> </tbody> </table>	Vdc \ φD	36	51	64	77	90	10	0.75	1.0	1.3	1.5	1.5	16	0.6	0.7	0.8	1.0	1.0	25	0.4	0.5	0.7	0.8	0.8	35	0.3	0.5	0.6	0.7	0.7	50	0.25	0.3	0.5	0.6	0.6	<table border="1"> <thead> <tr> <th>Vdc \ φD</th> <th>36</th> <th>51</th> <th>64</th> <th>77</th> <th>90</th> </tr> </thead> <tbody> <tr> <td>63</td> <td>0.2</td> <td>0.25</td> <td>0.3</td> <td>0.4</td> <td>0.4</td> </tr> <tr> <td>80</td> <td>0.2</td> <td>0.2</td> <td>0.25</td> <td>0.3</td> <td>0.3</td> </tr> <tr> <td>100</td> <td>0.15</td> <td>0.2</td> <td>0.25</td> <td>0.25</td> <td>0.25</td> </tr> <tr> <td>160~250</td> <td>0.15</td> <td>0.15</td> <td>0.2</td> <td>0.2</td> <td>0.2</td> </tr> <tr> <td>315~400</td> <td>0.2</td> <td>0.2</td> <td>0.25</td> <td>0.25</td> <td>0.25</td> </tr> </tbody> </table>	Vdc \ φD	36	51	64	77	90	63	0.2	0.25	0.3	0.4	0.4	80	0.2	0.2	0.25	0.3	0.3	100	0.15	0.2	0.25	0.25	0.25	160~250	0.15	0.15	0.2	0.2	0.2	315~400	0.2	0.2	0.25	0.25	0.25	(20°C, 120Hz)
Vdc \ φD	36	51	64	77	90																																																																						
10	0.75	1.0	1.3	1.5	1.5																																																																						
16	0.6	0.7	0.8	1.0	1.0																																																																						
25	0.4	0.5	0.7	0.8	0.8																																																																						
35	0.3	0.5	0.6	0.7	0.7																																																																						
50	0.25	0.3	0.5	0.6	0.6																																																																						
Vdc \ φD	36	51	64	77	90																																																																						
63	0.2	0.25	0.3	0.4	0.4																																																																						
80	0.2	0.2	0.25	0.3	0.3																																																																						
100	0.15	0.2	0.25	0.25	0.25																																																																						
160~250	0.15	0.15	0.2	0.2	0.2																																																																						
315~400	0.2	0.2	0.25	0.25	0.25																																																																						
Endurance	After applying rated voltage with rated ripple current for 3000 hours at 105°C, the capacitors shall meet the following requirements. <table border="1"> <tr> <td>Capacitance Change</td> <td>Within ±15% of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 175% of the specified value.</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> </table>		Capacitance Change	Within ±15% of the initial value.	Dissipation Factor	Not more than 175% of the specified value.	Leakage Current	Not more than the specified value.																																																																			
Capacitance Change	Within ±15% of the initial value.																																																																										
Dissipation Factor	Not more than 175% of the specified value.																																																																										
Leakage Current	Not more than the specified value.																																																																										
Shelf Life	After storage for 500 hours with no voltage applied at 105°C, the capacitors shall be subjected to the voltage treatment in JIS C 5101-4 item 4.1 and shall be meet the following requirements. <table border="1"> <tr> <td>Capacitance Change</td> <td>Within ±15% of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 150% of the specified value.</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> </table>		Capacitance Change	Within ±15% of the initial value.	Dissipation Factor	Not more than 150% of the specified value.	Leakage Current	Not more than the specified value.																																																																			
Capacitance Change	Within ±15% of the initial value.																																																																										
Dissipation Factor	Not more than 150% of the specified value.																																																																										
Leakage Current	Not more than the specified value.																																																																										

◆MULTIPLIER FOR RIPPLE CURRENT

Frequency (Hz)		60(50)	120(100)	300	500	10k≤
Coefficient	10~50Vdc	0.80	1.00	1.03	1.04	1.08
	63~100Vdc	0.80	1.00	1.04	1.05	1.10
	160~400Vdc	0.80	1.00	1.06	1.10	1.18

◆PART NUMBER



◆DIMENSIONS

		(mm)						
		φD	W1	W2	W3	W4	W5	F
I type	36	24.0	30.0	3.5	7.0	10	12.7	
	51	34.0	40.0	3.5	6.0	12	21.8	
	64	40.0	45.0	4.5	7.0	12	28.2	
	77	47.0	53.0	4.5	6.0	12	31.4	
Y type	90	54.0	60.0	4.5	6.0	14	31.4	
	51	32.5	37.5	4.5	6.0	12	21.8	
	64	38.0	43.0	4.5	8.0	14	28.2	
	77	44.5	49.0	4.5	7.0	14	31.4	
	90	50.8	56.0	4.5	8.0	16	31.4	

◆STANDARD SIZE

Cap(μF) \ Vdc	10		16		25		35		50		63		80		
3300													36×50	3.0	
3900													36×63	3.3	
4700												36×50	3.2	36×83	3.6
5600												36×63	3.5	36×83	3.9
6800							36×50	2.5	36×50	3.6	36×63	3.8	36×83	4.3	
8200							36×50	2.8	36×63	3.9	36×83	4.3	36×98	5.1	
10000							36×50	3.8	36×83	4.2	36×83	4.7	36×118	5.8	
12000							36×63	4.3	36×83	5.0	36×98	5.6	51×83	7.0	
15000					36×50	4.2	36×83	4.7	36×98	5.5	36×118	6.4	51×83	7.6	
18000					36×63	4.6	36×83	5.1	36×98	5.7	51×83	7.5	51×98	7.7	
22000			36×50	4.0	36×83	5.2	36×98	6.6	36×118	7.5	51×83	7.5	51×118	9.0	
27000	36×50	4.4	36×63	5.0	36×83	5.4	36×118	6.7	51×83	7.5	51×98	8.7	64×99	10.1	
33000	36×63	5.5	36×83	5.2	36×98	6.5	51×83	7.1	51×98	9.3	51×118	10.3	64×119	11.6	
39000	36×63	6.0	36×83	5.8	36×98	7.5	51×83	8.4	51×98	9.4	64×99	11.2	64×139	13.5	
47000	36×83	6.6	36×98	6.8	36×118	8.9	51×98	9.9	51×118	11.7	64×119	12.9	77×101	15.8	
56000	36×83	7.5	36×98	6.9	51×83	10.0	51×98	10.3	64×99	12.4	64×139	15.2	77×121	17.0	
68000	36×98	7.6	36×118	8.4	51×83	10.7	51×118	11.4	64×119	15.1	77×101	16.0	77×141	20.4	
82000	36×118	9.0	51×83	8.4	51×98	12.0	64×99	12.5	77×101	15.5	77×121	17.7	77×151	21.5	
100000	51×83	10.2	51×98	11.3	51×118	13.1	64×119	15.5	77×101	16.3	77×141	21.5	90×151	22.3	
120000	51×83	11.0	51×98	11.4	64×99	13.7	77×101	15.5	77×121	19.1	90×141	22.4			
150000	51×98	13.4	51×118	12.5	64×119	16.4	77×121	17.9	77×141	23.4					
180000	51×118	14.0	64×99	14.2	77×101	16.7	77×141	20.0	90×141	23.7					
220000	64×99	14.5	64×119	16.6	77×121	20.5	77×151	24.1							
270000	64×119	16.0	77×101	17.5	77×141	21.3	90×141	26.5							
330000	77×101	18.0	77×121	24.3	77×151	26.0									
390000	77×101	19.5	77×141	25.2	90×141	27.2									
470000	77×121	20.0	77×151	26.7											
560000	77×141	24.1	90×141	29.1											
680000	90×141	26.5													

Cap(μF) \ Vdc	100		160		200		250		315		350		400	
220											36×50	0.9	36×50	1.0
270									36×50	1.0	36×50	1.0	36×63	1.0
330									36×50	1.2	36×63	1.2	36×63	1.2
390									36×63	1.3	36×83	1.3	36×83	1.4
470							36×50	1.3	36×83	1.5	36×83	1.5	36×98	1.5
560					36×50	1.4	36×63	1.6	36×83	1.6	36×98	1.7	36×98	1.7
680					36×50	1.5	36×83	1.7	36×98	1.9	36×98	1.9	51×83	2.3
820			36×50	1.4	36×83	1.9	36×83	1.9	36×118	2.2	36×118	2.1	51×98	2.4
1000			36×63	1.9	36×83	2.2	36×98	2.3	51×83	2.3	51×98	2.5	51×118	2.7
1200			36×83	2.3	36×83	2.3	36×98	2.4	51×98	2.7	51×98	2.7	51×118	3.0
1500			36×83	2.6	36×98	2.9	36×118	2.9	51×98	3.1	51×118	3.3	64×99	3.5
1800			36×83	2.6	36×98	2.9	36×118	3.0	51×118	3.6	64×99	3.8	64×119	3.6
2200	36×50	2.9	36×98	3.2	36×118	3.3	51×98	3.8	64×99	4.2	64×119	4.6	77×101	4.1
2700	36×63	3.4	36×118	3.2	51×83	3.8	51×118	4.5	64×119	4.3	77×101	4.6	77×121	4.8
3300	36×83	3.9	36×118	3.7	51×98	4.7	64×99	5.2	77×101	4.9	77×121	5.3	77×141	5.7
3900	36×83	4.2	51×98	4.3	51×118	5.4	64×119	5.2	77×121	5.8	77×141	6.2	90×141	6.7
4700	36×83	4.6	51×98	4.8	64×99	6.2	64×119	5.7	77×121	6.3	90×141	7.4	90×141	7.4
5600	36×98	4.9	51×118	5.5	64×99	6.3	77×101	6.4	77×141	7.3	90×141	8.1		
6800	36×118	5.5	64×99	6.3	64×119	7.3	77×121	7.6	90×141	8.9				
8200	51×83	6.2	64×119	7.1	77×101	8.5	77×141	8.3						
10000	51×98	6.7	77×101	7.9	77×121	9.5	90×141	9.9						
12000	51×98	7.3	77×121	9.0	77×141	10.5	90×141	10.8						
15000	51×118	8.6	77×141	11.3	90×141	12.5								
18000	64×99	8.9	90×141	13.0	90×141	13.3								
22000	64×119	10.3	90×141	14.3										
27000	64×139	12.1												
33000	77×121	14.1												
39000	77×141	16.5												
47000	77×141	18.3												
56000	90×141	19.2												
68000	90×151	20.1												

↑ Ripple Current (A r.m.s./120Hz, 105°C)
 ↑ Case Size φD×L(mm)

◆Tightening torque of bolt and Permissible current of terminal

Clamp Bolt	Recommended Tightening torque
M3	0.6 [N·m]
M4	1.3 [N·m]

Terminal	Recommended Tightening torque (Permissible Range)	Permissible Current of Terminal
M5	2.2(1.5~3.2) [N·m]	60[A r.m.s.]

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Rubycon:

[400LSW2700MNB77X121](#) [35LSW6800MNB36X50](#) [315LSW1500MNB51X98](#) [25LSW18000MNB36X63](#)
[250LSW2700MNB51X118](#) [63LSW33000MNB51X118](#) [200LSW4700MNB64X99](#) [350LSW1200MNB51X98](#)
[350LSW1500MNB51X118](#) [80LSW12000MNB51X83](#) [315LSW270MNB36X50](#) [50LSW150000MNB77X141](#)
[400LSW680MNB51X83](#) [35LSW56000MNB51X98](#) [10LSW470000MNB77X121](#) [35LSW15000MNB36X83](#)
[25LSW82000MNB51X98](#) [250LSW2200MNB51X98](#) [350LSW270MNB36X50](#) [35LSW150000MNB77X121](#)
[10LSW47000MNB36X83](#) [200LSW12000MNB77X141](#) [16LSW39000MNB36X83](#) [100LSW47000MNB77X141](#)
[160LSW1800MNB36X83](#) [350LSW470MNB36X83](#) [16LSW120000MNB51X98](#) [80LSW4700MNB36X83](#)
[100LSW27000MNB64X139](#) [63LSW10000MNB36X83](#) [80LSW47000MNB77X101](#) [10LSW150000MNB51X98](#)
[80LSW10000MNB36X118](#) [400LSW390MNB36X83](#) [350LSW390MNB36X83](#) [160LSW4700MNB51X98](#)
[160LSW6800MNB64X99](#) [250LSW560MNB36X63](#) [35LSW10000MNB36X50](#) [10LSW680000MNB90X141](#)
[160LSW3900MNB51X98](#) [10LSW56000MNB36X83](#) [50LSW18000MNB36X98](#) [63LSW27000MNB51X98](#)
[10LSW120000MNB51X83](#) [80LSW100000MNB90X151](#) [25LSW68000MNB51X98](#) [100LSW39000MNB77X141](#)
[160LSW8200MNB64X119](#) [80LSW3300MNB36X50](#) [50LSW100000MNB77X101](#) [80LSW18000MNB51X98](#)
[10LSW330000MNB77X101](#) [80LSW56000MNB77X121](#) [250LSW820MNB36X83](#) [400LSW1000MNB51X118](#)
[16LSW33000MNB36X83](#) [10LSW68000MNB36X98](#) [100LSW2700MNB36X63](#) [350LSW680MNB36X98](#)
[10LSW33000MNB36X63](#) [80LSW5600MNB36X83](#) [315LSW3900MNB77X121](#) [50LSW47000MNB51X118](#)
[63LSW68000MNB77X101](#) [25LSW180000MNB77X101](#) [350LSW1000MNB51X98](#) [200LSW3300MNB51X98](#)
[50LSW15000MNB36X98](#) [315LSW560MNB36X83](#) [160LSW2700MNB36X118](#) [80LSW3900MNB36X63](#)
[35LSW82000MNB64X99](#) [63LSW82000MNB77X121](#) [250LSW4700MNB64X119](#) [50LSW10000MNB36X83](#)
[350LSW3300MNB77X121](#) [200LSW10000MNB77X121](#) [400LSW220MNB36X50](#) [16LSW47000MNB36X98](#)
[315LSW820MNB36X118](#) [100LSW10000MNB51X98](#) [200LSW820MNB36X83](#) [10LSW270000MNB64X119](#)
[160LSW1500MNB36X83](#) [16LSW150000MNB51X118](#) [10LSW560000MNB77X141](#) [25LSW39000MNB36X98](#)
[350LSW220MNB36X50](#) [100LSW68000MNB90X151](#) [35LSW47000MNB51X98](#) [200LSW1200MNB36X83](#)
[315LSW1800MNB51X118](#) [25LSW120000MNB64X99](#) [250LSW5600MNB77X101](#) [160LSW1000MNB36X63](#)
[10LSW39000MNB36X63](#) [35LSW33000MNB51X83](#) [400LSW3900MNB90X141](#) [50LSW12000MNB36X83](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.