


## Knife disconnect terminal block - PTTBS 2,5-2MTB - 3210400

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Knife disconnect terminal block, Double level with angled contour and two disconnect knives, Connection type: Push-in connection, Cross section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 26 - 12, Nominal current: 16 A, Nominal voltage: 400 V, Length: 127.5 mm, Width: 5.2 mm, Color: gray, Assembly: NS 35/7,5, NS 35/15

### Product Features

- The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- The compact design and front connection enable wiring in a confined space
- In addition to the testing facility in the double function shaft, all terminal blocks provide an additional test connection
- Convenient separation of circuits, thanks to lever-type disconnect knife
- Clear identification of the disconnect point, thanks to color highlighting



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 22.8 g   |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Poland   |

### Technical data

#### General

|  |                     |
|--|---------------------|
| Number of levels                       | 2                   |
| Number of connections                  | 4                   |
| Nominal cross section                  | 2.5 mm <sup>2</sup> |
| Color                                  | gray                |
| Insulating material                    | PA                  |
| Flammability rating according to UL 94 | V0                  |
| Rated surge voltage                    | 6 kV                |
| Pollution degree                       | 3                   |

# Knife disconnect terminal block - PTTBS 2,5-2MTB - 3210400

## Technical data

### General

|   |   |
|---|---|
| Overvoltage category  | III   |
| Insulating material group   | I   |
| Ambient temperature (operation)   | -60 °C ... 130 °C                                     |
| Connection in acc. with standard  | IEC 60947-7-1   |
| Maximum load current  | 16 A (with 4 mm <sup>2</sup> conductor cross section) |
| Nominal current I <sub>N</sub>  | 16 A  |
| Nominal voltage U <sub>N</sub>  | 400 V   |
| Open side panel   | ja  |
| Shock protection test specification   | DIN EN 50274 (VDE 0660-514):2002-11                   |
| Back of the hand protection   | guaranteed  |
| Finger protection   | guaranteed  |
| Surge voltage test setpoint   | 7.3 kV  |
| Result of surge voltage test  | Test passed   |
| Power frequency withstand voltage setpoint                                      | 1.89 kV   |
| Result of power-frequency withstand voltage test                                | Test passed   |
| Checking the mechanical stability of terminal points (5 x conductor connection) | Test passed   |
| Bending test rotation speed   | 10 rpm  |
| Bending test turns  | 135   |
| Bending test conductor cross section/weight                                     | 0.14 mm <sup>2</sup> / 0.2 kg                         |
|   | 2.5 mm <sup>2</sup> / 0.7 kg                          |
|   | 4 mm <sup>2</sup> / 0.9 kg                            |
| Result of bending test  | Test passed   |
| Conductor cross section tensile test  | 0.14 mm <sup>2</sup>                                  |
| Tractive force setpoint   | 10 N  |
| Conductor cross section tensile test  | 2.5 mm <sup>2</sup>                                   |
| Tractive force setpoint   | 50 N  |
| Conductor cross section tensile test  | 4 mm <sup>2</sup>                                     |
| Tractive force setpoint   | 60 N  |
| Tensile test result   | Test passed   |
| Tight fit on carrier  | NS 35   |
| Setpoint  | 1 N   |
| Result of tight fit test  | Test passed   |
| Result of voltage drop test   | Test passed   |
| Temperature-rise test   | Test passed   |
| Conductor cross section short circuit testing                                   | 2.5 mm <sup>2</sup>                                   |
| Short-time current  | 0.3 kA  |

## Knife disconnect terminal block - PTTBS 2,5-2MTB - 3210400

### Technical data

#### General

|   |  |
|---|--|
| Short circuit stability result  | Test passed                                    |
| Ageing test for screwless modular terminal block temperature cycles   | 192  |
| Result of aging test  | Test passed                                    |
| Proof of thermal characteristics (needle flame) effective duration    | 30 s   |
| Result of thermal test  | Test passed                                    |
| Test specification, oscillation, broadband noise                      | DIN EN 50155 (VDE 0115-200):2008-03            |
| Test spectrum   | Service life test category 2, bogie mounted    |
| Test frequency  | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level   | $6.12 \text{ (m/s}^2\text{)}^2/\text{Hz}$      |
| Acceleration  | 3.12 g   |
| Test duration per axis  | 5 h  |
| Test directions   | X-, Y- and Z-axis                              |
| Oscillation, broadband noise test result                              | Test passed                                    |
| Test specification, shock test  | DIN EN 50155 (VDE 0115-200):2008-03            |
| Shock form  | Half-sine                                      |
| Acceleration  | 30g  |
| Shock duration  | 18 ms  |
| Number of shocks per direction  | 3  |
| Test directions   | X-, Y- and Z-axis (pos. and neg.)              |
| Shock test result   | Test passed                                    |
| Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C   |
| Static insulating material application in cold                        | -60 °C   |

#### Dimensions

|                  |          |
|------------------|----------|
| Width            | 5.2 mm   |
| Length           | 127.5 mm |
| Height           | 63.10 mm |
| Height NS 35/7,5 | 64.3 mm  |
| Height NS 35/15  | 71.8 mm  |

#### Connection data

|                                       |                      |
|---------------------------------------|----------------------|
| Connection method                     | Push-in connection   |
| Connection in acc. with standard      | IEC 60947-7-1        |
| Conductor cross section solid min.    | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.    | 4 mm <sup>2</sup>    |
| Conductor cross section AWG min.      | 26                   |
| Conductor cross section AWG max.      | 12                   |
| Conductor cross section flexible min. | 0.14 mm <sup>2</sup> |

# Knife disconnect terminal block - PTTBS 2,5-2MTB - 3210400

## Technical data

### Connection data

|   |                      |
|---|----------------------|
| Conductor cross section flexible max.   | 2.5 mm <sup>2</sup>  |
| Min. AWG conductor cross section, flexible  | 26                   |
| Max. AWG conductor cross section, flexible  | 14                   |
| Conductor cross section flexible, with ferrule without plastic sleeve min.              | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max.              | 2.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min.                 | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.                 | 2.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 0.5 mm <sup>2</sup>  |
| Conductor cross section AWG min.  | 26                   |
| Conductor cross section AWG max.  | 12                   |
| Stripping length  | 8 mm ... 10 mm       |
| Internal cylindrical gage   | A3                   |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27141126 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 8.0 | 27141126 |

### ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC000902 |
|----------|----------|

## Approvals

### Approvals

---

#### Approvals

CSA / UL Recognized / cUL Recognized / cULus Recognized

---

#### Ex Approvals

---

#### Approvals submitted

---

### Approval details

# Knife disconnect terminal block - PTTBS 2,5-2MTB - 3210400

## Approvals

|                            |       |       |
|----------------------------|-------|-------|
| CSA                        |       |       |
|                            | B     | C     |
| mm <sup>2</sup> /AWG/kcmil | 26-12 | 26-12 |
| Nominal current IN         | 10 A  | 10 A  |
| Nominal voltage UN         | 300 V | 300 V |


|                            |       |       |   |
|----------------------------|-------|-------|---|
| UL Recognized              |       |       |   |
|                            |       | B     | C |
| mm <sup>2</sup> /AWG/kcmil | 26-12 | 26-12 |   |
| Nominal current IN         | 16 A  | 16 A  |   |
| Nominal voltage UN         | 300 V | 300 V |   |

|                            |       |       |   |
|----------------------------|-------|-------|---|
| cUL Recognized             |       |       |   |
|                            |       | B     | C |
| mm <sup>2</sup> /AWG/kcmil | 26-12 | 26-12 |   |
| Nominal current IN         | 16 A  | 16 A  |   |
| Nominal voltage UN         | 300 V | 300 V |   |

|                  |  |  |  |
|------------------|--|--|--|
| cULus Recognized |  |  |  |
|------------------|--|--|--|

## Drawings

Circuit diagram





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.