

## 14A, 50V, 0.100 Ohm, Logic Level, N-Channel Power MOSFETs

These are N-channel power MOSFETs manufactured using the MegaFET process. This process, which uses feature sizes approaching those of LSI integrated circuits, gives optimum utilization of silicon, resulting in outstanding performance. They were designed for use in applications such as switching regulators, switching converters, motor drivers and relay drivers. This performance is accomplished through a special gate oxide design which provides full rated conductance at gate bias in the 3V-5V range, thereby facilitating true on-off power control directly from logic level (5V) integrated circuits.

Formerly developmental type TA09870.

## Ordering Information


| PART NUMBER | PACKAGE  | BRAND   |
|-------------|----------|---------|
| RFD14N05L   | TO-251AA | 14N05L  |
| RFD14N05LSM | TO-252AA | 14N05L  |
| RFP14N05L   | TO-220AB | F14N05L |

NOTE: When ordering, use the entire part number. Add the suffix 9A to obtain the TO-252AA variant in the tape and reel, i.e., RFD14N05LSM9A.

## Features


- 14A, 50V
- $r_{DS(ON)} = 0.100\Omega$
- Temperature Compensating PSpice® Model
- Can be Driven Directly from CMOS, NMOS, and TTL Circuits
- Peak Current vs Pulse Width Curve
- UIS Rating Curve
- 175°C Operating Temperature
- Related Literature
  - TB334 "Guidelines for Soldering Surface Mount Components to PC Boards"

## Symbol




## Packaging


JEDEC TO-251AA



JEDEC TO-252AA



JEDEC TO-220AB



# RFD14N05L, RFD14N05LSM, RFP14N05L

## Absolute Maximum Ratings $T_C = 25^{\circ}\text{C}$ , Unless Otherwise Specified

|                                                                   | RFD14N05L, RFD14N05LSM,<br>RFP14N05L | UNITS                       |
|-------------------------------------------------------------------|--------------------------------------|-----------------------------|
| Drain to Source Voltage (Note 1) . . . . .                        | $V_{DSS}$                            | V                           |
| Drain to Gate Voltage ( $R_{GS} = 20k\Omega$ ) (Note 1) . . . . . | $V_{DGR}$                            | V                           |
| Gate to Source Voltage . . . . .                                  | $V_{GS}$                             | V                           |
| Continuous Drain Current . . . . .                                | $I_D$                                | A                           |
| Pulsed Drain Current (Note 3) . . . . .                           | $I_{DM}$                             | Refer to Peak Current Curve |
| Pulsed Avalanche Rating . . . . .                                 | $E_{AS}$                             | Refer to UIS Curve          |
| Power Dissipation . . . . .                                       | $P_D$                                | W                           |
| Derate above $25^{\circ}\text{C}$ . . . . .                       | 0.32                                 | $\text{W}/^{\circ}\text{C}$ |
| Operating and Storage Temperature . . . . .                       | $T_J, T_{STG}$                       | $^{\circ}\text{C}$          |
| Maximum Temperature for Soldering                                 |                                      |                             |
| Leads at 0.063in (1.6mm) from Case for 10s. . . . .               | $T_L$                                | $^{\circ}\text{C}$          |
| Package Body for 10s, See Techbrief 334 . . . . .                 | $T_{pkg}$                            | $^{\circ}\text{C}$          |

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

### NOTE:

1.  $T_J = 25^{\circ}\text{C}$  to  $150^{\circ}\text{C}$ .

## Electrical Specifications $T_C = 25^{\circ}\text{C}$ , Unless Otherwise Specified

| PARAMETER                              | SYMBOL          | TEST CONDITIONS                                                                               |                                                                        | MIN | TYP | MAX       | UNITS         |
|----------------------------------------|-----------------|-----------------------------------------------------------------------------------------------|------------------------------------------------------------------------|-----|-----|-----------|---------------|
| Drain to Source Breakdown Voltage      | $BV_{DSS}$      | $I_D = 250\mu A$ , $V_{GS} = 0V$ , Figure 13                                                  |                                                                        | 50  | -   | -         | V             |
| Gate Threshold Voltage                 | $V_{GS(TH)}$    | $V_{GS} = V_{DS}$ , $I_D = 250\mu A$ , Figure12                                               |                                                                        | 1   | -   | 2         | V             |
| Zero Gate Voltage Drain Current        | $I_{DSS}$       | $V_{DS} = 40V$ , $V_{GS} = 0V$                                                                |                                                                        | -   | -   | 1         | $\mu A$       |
|                                        |                 | $V_{DS} = 40V$ , $V_{GS} = 0V$ , $T_C = 150^{\circ}C$                                         |                                                                        | -   | -   | 50        | $\mu A$       |
| Gate to Source Leakage Current         | $I_{GSS}$       | $V_{GS} = \pm 10V$                                                                            |                                                                        | -   | -   | $\pm 100$ | nA            |
| Drain to Source On Resistance (Note 2) | $r_{DS(ON)}$    | $I_D = 14A$ , $V_{GS} = 5V$ , Figures 9, 11                                                   |                                                                        | -   | -   | 0.100     | $\Omega$      |
| Turn-On Time                           | $t_{(ON)}$      | $V_{DD} = 25V$ , $I_D = 7A$ ,<br>$R_L = 3.57\Omega$ , $V_{GS} = 5V$ ,<br>$R_{GS} = 0.6\Omega$ |                                                                        | -   | -   | 60        | ns            |
| Turn-On Delay Time                     | $t_{d(ON)}$     |                                                                                               |                                                                        | -   | 13  | -         | ns            |
| Rise Time                              | $t_r$           |                                                                                               |                                                                        | -   | 24  | -         | ns            |
| Turn-Off Delay Time                    | $t_{d(OFF)}$    |                                                                                               |                                                                        | -   | 42  | -         | ns            |
| Fall Time                              | $t_f$           |                                                                                               |                                                                        | -   | 16  | -         | ns            |
| Turn-Off Time                          | $t_{(OFF)}$     |                                                                                               |                                                                        | -   | -   | 100       | ns            |
| Total Gate Charge                      | $Q_{g(TOT)}$    | $V_{GS} = 0V$ to $10V$                                                                        | $V_{DD} = 40V$ , $I_D = 14A$ ,<br>$R_L = 2.86\Omega$<br>Figures 20, 21 | -   | -   | 40        | nC            |
| Gate Charge at 5V                      | $Q_{g(5)}$      | $V_{GS} = 0V$ to $5V$                                                                         |                                                                        | -   | -   | 25        | nC            |
| Threshold Gate Charge                  | $Q_{g(TH)}$     | $V_{GS} = 0V$ to $1V$                                                                         |                                                                        | -   | -   | 1.5       | nC            |
| Input Capacitance                      | $C_{ISS}$       | $V_{DS} = 25V$ , $V_{GS} = 0V$ , $f = 1MHz$<br>Figure 14                                      |                                                                        | -   | 670 | -         | pF            |
| Output Capacitance                     | $C_{OSS}$       |                                                                                               |                                                                        | -   | 185 | -         | pF            |
| Reverse Transfer Capacitance           | $C_{RSS}$       |                                                                                               |                                                                        | -   | 50  | -         | pF            |
| Thermal Resistance Junction to Case    | $R_{\theta JC}$ |                                                                                               |                                                                        | -   | -   | 3.125     | $^{\circ}C/W$ |
| Thermal Resistance Junction to Ambient | $R_{\theta JA}$ | TO-251 and TO-252                                                                             |                                                                        | -   | -   | 100       | $^{\circ}C/W$ |
|                                        | $R_{\theta JA}$ | TO-220                                                                                        |                                                                        | -   | -   | 80        | $^{\circ}C/W$ |

## Source to Drain Diode Specifications

| PARAMETER                              | SYMBOL   | TEST CONDITIONS                                                | MIN | TYP | MAX | UNITS |
|----------------------------------------|----------|----------------------------------------------------------------|-----|-----|-----|-------|
| Source to Drain Diode Voltage (Note 2) | $V_{SD}$ | $I_{SD} = 14\text{A}$                                          | -   | -   | 1.5 | V     |
| Diode Reverse Recovery Time            | $t_{rr}$ | $I_{SD} = 14\text{A}$ , $dI_{SD}/dt = 100\text{A}/\mu\text{s}$ | -   | -   | 125 | ns    |

### NOTES:

2. Pulse Test: Pulse Width  $\leq 300\text{ms}$ , Duty Cycle  $\leq 2\%$ .
3. Repetitive Rating: Pulse Width limited by max junction temperature. See Transient Thermal Impedance Curve (Figure 3) and Peak Current Capability Curve (Figure 5).

# Typical Performance Curves Unless Otherwise Specified




FIGURE 1. NORMALIZED POWER DISSIPATION vs CASE TEMPERATURE




FIGURE 2. MAXIMUM CONTINUOUS DRAIN CURRENT vs TEMPERATURE




FIGURE 3. NORMALIZED MAXIMUM TRANSIENT THERMAL IMPEDANCE




FIGURE 4. FORWARD BIAS SAFE OPERATING AREA





FIGURE 5. PEAK CURRENT CAPABILITY

**Typical Performance Curves** Unless Otherwise Specified (Continued)



NOTE: Refer to Fairchild Application Notes AN9321 and AN9322.

FIGURE 6. UNCLAMPED INDUCTIVE SWITCHING




FIGURE 7. SATURATION CHARACTERISTICS




FIGURE 8. TRANSFER CHARACTERISTICS




FIGURE 9. DRAIN TO SOURCE ON RESISTANCE vs GATE VOLTAGE AND DRAIN CURRENT




FIGURE 10. SWITCHING TIME vs GATE RESISTANCE




FIGURE 11. NORMALIZED DRAIN TO SOURCE ON RESISTANCE vs JUNCTION TEMPERATURE

# Typical Performance Curves Unless Otherwise Specified (Continued)




FIGURE 12. NORMALIZED GATE THRESHOLD VOLTAGE vs JUNCTION TEMPERATURE




FIGURE 13. NORMALIZED DRAIN TO SOURCE BREAKDOWN VOLTAGE vs JUNCTION TEMPERATURE





FIGURE 14. CAPACITANCE vs DRAIN TO SOURCE VOLTAGE



NOTE: Refer to Fairchild Application Notes AN7254 and AN7260,

FIGURE 15. TRANSCONDUCTANCE vs DRAIN CURRENT

## Test Circuits and Waveforms




FIGURE 16. UNCLAMPED ENERGY TEST CIRCUIT




FIGURE 17. UNCLAMPED ENERGY WAVEFORMS

Test Circuits and Waveforms (Continued)




FIGURE 18. SWITCHING TIME TEST CIRCUIT




FIGURE 19. RESISTIVE SWITCHING WAVEFORMS




FIGURE 20. GATE CHARGE TEST CIRCUIT




FIGURE 21. GATE CHARGE WAVEFORMS

## PSPICE Electrical Model

.SUBCKT RFP14N05L 2 1 3 ; rev 9/15/94

CA 12 8 1.464e-9  
CB 15 14 1.64e-9  
CIN 6 8 6.17e-10

DBODY 7 5 DBDMOD  
DBREAK 5 11 DBKMOD  
DPLCAP 10 5 DPLCAPMOD

EBREAK 11 7 17 18 65.35  
EDS 14 8 5 8 1  
EGS 13 8 6 8 1  
ESG 6 10 6 8 1  
EVTO 20 6 18 8 1

IT 8 17 1

LDRAIN 2 5 1e-9  
LGATE 1 9 5.68e-9  
LSOURCE 3 7 5.35e-9

MOS1 16 6 8 8 MOSMOD M = 0.99  
MOS2 16 21 8 8 MOSMOD M = 0.01

RBREAK 17 18 RBKMOD 1  
RDRAIN 50 16 RDSMOD 33.1e-3  
RGATE 9 20 5.85  
RIN 6 8 1e9  
RSCL1 5 51 RSCLMOD 1e-6  
RSCL2 5 50 1e3  
RSOURCE 8 7 RDSMOD 14.3e-3  
RVTO 18 19 RVTOMOD 1

S1A 6 12 13 8 S1AMOD  
S1B 13 12 13 8 S1BMOD  
S2A 6 15 14 13 S2AMOD  
S2B 13 15 14 13 S2BMOD


VBAT 8 19 DC 1  
VTO 21 6 0.485

ESCL 51 50 VALUE = {(V(5,51)/ABS(V(5,51)))\*(PWR(V(5,51)\*1e6/46,7))}

.MODEL DBDMOD D (IS = 2.23e-13 RS = 1.15e-2 TRS1 = 1.64e-3 TRS2 = 7.89e-6 CJO = 6.83e-10 TT = 3.68e-8)  
.MODEL DBKMOD D (RS = 3.8e-1 TRS1 = 1.89e-3 TRS2 = 1.13e-5)  
.MODEL DPLCAPMOD D (CJO = 25.7e-11 IS = 1e-30 N = 10)  
.MODEL MOSMOD NMOS (VTO = 1.935 KP = 18.89 IS = 1e-30 N = 10 TOX = 1 L = 1u W = 1u)  
.MODEL RBKMOD RES (TC1 = 7.18e-4 TC2 = 1.53e-6)  
.MODEL RDSMOD RES (TC1 = 4.45e-3 TC2 = 2.9e-5)  
.MODEL RSCLMOD RES (TC1 = 2.8e-3 TC2 = 6.0e-6)  
.MODEL RVTOMOD RES (TC1 = -1.7e-3 TC2 = -2.0e-6)  
.MODEL S1AMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = -3.55 VOFF = -1.55)  
.MODEL S1BMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = -1.55 VOFF = -3.55)  
.MODEL S2AMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = -2.55 VOFF = 2.45)  
.MODEL S2BMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = 2.45 VOFF = -2.55)

.ENDS

NOTE: For further discussion of the PSPICE model, consult **A New PSPICE Sub-circuit for the Power MOSFET Featuring Global Temperature Options**; authored by William J. Hepp and C. Frank Wheatley.



## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                                      |                     |               |                     |                 |
|--------------------------------------|---------------------|---------------|---------------------|-----------------|
| ACEx™                                | FAST®               | ISOPPLANAR™   | Power247™           | Stealth™        |
| ActiveArray™                         | FASTr™              | LittleFET™    | PowerEdge™          | SuperFET™       |
| Bottomless™                          | FPS™                | MICROCOUPLER™ | PowerSaver™         | SuperSOT™-3     |
| CoolFET™                             | FRFET™              | MicroFET™     | PowerTrench®        | SuperSOT™-6     |
| CROSSVOLT™                           | GlobalOptoisolator™ | MicroPak™     | QFET®               | SuperSOT™-8     |
| DOME™                                | GTO™                | MICROWIRE™    | QS™                 | SyncFET™        |
| EcoSPARK™                            | HiSeC™              | MSX™          | QT Optoelectronics™ | TinyLogic®      |
| E <sup>2</sup> CMOS™                 | I <sup>2</sup> C™   | MSXPro™       | Quiet Series™       | TINYOPTO™       |
| EnSigna™                             | i-Lo™               | OCX™          | RapidConfigure™     | TruTranslation™ |
| FACT™                                | ImpliedDisconnect™  | OCXPro™       | RapidConnect™       | UHC™            |
| FACT Quiet Series™                   |                     | OPTOLOGIC®    | µSerDes™            | UltraFET®       |
| Across the board. Around the world.™ |                     | OPTOPLANAR™   | SILENT SWITCHER®    | VCX™            |
| The Power Franchise®                 |                     | PACMAN™       | SMART START™        |                 |
| Programmable Active Droop™           |                     | POP™          | SPM™                |                 |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                                            |
|--------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                                    |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.                                                       |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.                                                   |





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.