



1 5/16" (33.3 mm) Low Cost Industrial Single Turn Wirewound, Bushing Mount Type Potentiometer



FEATURES

- Suitable model for all industrial applications
- Center tap available
- Continuous rotation and mechanical stops both standard
- Large electrical angle: 352° ± 2°
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912



RoHS COMPLIANT

| QUICK REFERENCE DATA | |
|----------------------|-----------------------------------|
| Sensor type | ROTATIONAL, single turn wirewound |
| Output type | Output by turrets |
| Market appliance | Industrial |
| Dimensions | 1 5/16" (33.3 mm) |

| ELECTRICAL SPECIFICATIONS | | |
|---------------------------------------|---|----------------|
| PARAMETER | MIL-PRF-12934 TEST PROCEDURES APPLY | |
| | STANDARD | SPECIAL |
| Total Resistance | 5 Ω to 20 kΩ | to 35 kΩ |
| Tolerance: 50 Ω and Above | ± 3 % | ± 1 % |
| Below 50 Ω | ± 5 % | ± 3 % |
| Linearity (independent) | STANDARD | BEST PRACTICAL |
| Total Resistance | | |
| 5 Ω to 20 Ω | ± 1.0 % | ± 0.75 % |
| 20 Ω to 200 Ω | ± 1.0 % | ± 0.50 % |
| 200 Ω and above | ± 0.5 % | ± 0.25 % |
| Noise | 100 Ω ENR | |
| Power Rating | 40 °C ambient 2.75 W derated to zero at 125 °C | |
| Electrical Angle | | |
| Continuous Rotation | 352° ± 2° | |
| Stops | 340° ± 5° | |
| Insulation Resistance | 1000 MΩ minimum at 500 V _{DC} | |
| Dielectric Strength | 1000 V _{RMS} , 60 Hz | |
| Absolute Minimum Resistance | 1.0 % of total resistance or 0.5 W whichever is greater | |
| Minimum Voltage | 0.5 % maximum | |
| Temperature Coefficient of Resistance | Refer to standard resistance element data | |


| MATERIAL SPECIFICATIONS | |
|----------------------------|---|
| Housing | Molded glass filled thermoplastic |
| Rear Lid | Glass filled thermoset plastic |
| Shaft | Stainless steel, non-magnetic |
| Terminals | Brass, plated for solderability, Non-passivated |
| Mount Hardware | |
| Lockwasher Internal Tooth: | Steel, nickel plated |
| Panel Nut: | Brass, nickel plated |

| ENVIRONMENTAL SPECIFICATIONS | |
|------------------------------|---------------------|
| Vibration | 15 g thru 2000 Hz |
| Shock | 50 g |
| Salt Spray | 48 h |
| Rotational Life | |
| Shaft Revolutions | 500 000 |
| Operating Temperature Range | - 55 °C to + 125 °C |

| ORDERING INFORMATION/DESCRIPTION | | | | | |
|---|---------------|---------------------------|--|-------------|------------------|
| 132 | B | 0 | 0 | 20K | BO10 |
| MODEL | BUSHING MOUNT | MECHANICAL OPTIONS | OTHER OPTIONAL FEATURES | OHMIC VALUE | PACKAGING |
| | | 0. Continuous 2. Stops | 0. Standard (end taps) 1. Center tap (within 5° of electrical center) | | Box of 10 pieces |
| Other characteristics will be standard as described on this specification sheet. If special characteristics are required such as special linearity tolerance, special resistance tolerance, non-linear functions, etc., please state these on your order. | | | | | |




| SAP PART NUMBERING GUIDELINES | | | | | |
|-------------------------------|----------|--------------------|--------------------|-------------|------------------|
| 132 | B | 2 | 1 | 103 | B10 |
| MODEL | STYLE | MECHANICAL OPTIONS | ELECTRICAL OPTIONS | OHMIC VALUE | PACKAGING |
| | | 2: With stops | 1: With center tap | 103: 10K | Box of 10 pieces |



| MECHANICAL SPECIFICATIONS | | |
|---------------------------|--|---|
| PARAMETER | | |
| Rotation | 360° (continuous) or 340° ± 5° (stops) | |
| Bearing Type | Sleeve | |
| Torque (maximums) | STARTING 1.0 oz. - in (72 g - cm) | RUNNING 0.7 oz. - in (50.40 g - cm) |
| Runouts (maximums) | | |
| Shaft Runout (TIR) | 0.002" (0.05 mm) | |
| Pilot Dia. Runout (TIR) | 0.003" (0.08 mm) | |
| Lateral Runout (TIR) | 0.005" (0.13 mm) | |
| Shaft End Play | 0.008" (0.20 mm) | |
| Shaft Radial Play | 0.003" (0.08 mm) | |
| Weight | 1.0 oz. maximum (28.35 g) | |
| Stop Strength | 8.0 in - lbs (9.21 kg - cm) (stops version only) | |

POWER RATING CHART



| MARKING | |
|---------------------|---|
| Unit Identification | Units shall be marked with Vishay Spectrol name, model number, resistance and tolerance, linearity, terminal identification, and data code Applicable test procedures: MIL-R-12934. Example of a marking for a standard part: 132-0-0-103 |

RESISTANCE ELEMENT DATA

| RESISTANCE VALUES (Ω) | RESOLUTION (%) | OHMS PER TURN | MAXIMUM CURRENT AT 40 °C AMBIENT (mA) | MAXIMUM VOLTAGE ACROSS COIL (V) | WIRE TEMP. COEF. (ppm/°C) |
|-----------------------|----------------|---------------|---------------------------------------|---------------------------------|---------------------------|
| 5 | 0.419 | 0.021 | 742 | 3.71 | 800 |
| 10 | 0.327 | 0.032 | 524 | 5.24 | 800 |
| 20 | 0.280 | 0.056 | 371 | 7.42 | 800 |
| 50 | 0.290 | 0.145 | 234 | 11.7 | 20 |
| 100 | 0.251 | 0.251 | 166 | 16.6 | 20 |
| 200 | 0.212 | 0.424 | 122 | 24.4 | 20 |
| 500 | 0.161 | 0.806 | 74.2 | 37.1 | 20 |
| 1K | 0.150 | 1.50 | 52.4 | 52.4 | 20 |
| 2K | 0.132 | 2.64 | 37.1 | 74.2 | 20 |
| 5K | 0.107 | 5.34 | 23.4 | 117 | 20 |
| 10K | 0.080 | 7.98 | 16.6 | 166 | 20 |
| 20K | 0.067 | 13.4 | 12.2 | 244 | 20 |
| 35K | 0.057 | 20.0 | 8.88 | 311 | 20 |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.