

# WA-HU HMI Series

NEW



WebAccess/HMI

intel Acronis WISE-PaaS/RMM iDoor R33138 CCC CE FCC UL

## Visualization Box HMI and Communication Gateway with WebAccess/HMI Runtime

### Features

#### Open HMI Application-Ready-Package with Embedded Automation Box PC

- Industrial fanless compact design with palm and regular form factor
- Flexible stand, wall, VESA, DIN rail mount options
- Powerful Intel Celeron/Core i3 processor performance
- 32GB industrial mSATA installed
- Microsoft Windows Embedded 7 Pro 64-bit installed
- Supports iDoor technology for diverse applications

#### WebAccess/HMI Runtime

- Includes HMI Runtime 1500 tags
- Supports 450 industrial communication protocol and drivers for PLC/devices
- Rich object library for easy application design
- Supports on-/off-line design simulation by the development tool

## Introduction

The WA-HU HMI series is a complete application-ready-package that includes an embedded automation box PC (in a palm-size or regular form factor), 32 GB mSATA, Microsoft Windows Embedded 7 Pro, and WebAccess/HMI Runtime. This provides users with an efficient, integrated HMI solution for production data visualization and protocol translation in the automation industry. The embedded automation box PC with Intel® Celeron®/Core™ i3 processor provides a high-performance system with various mount options for diverse field operations.

The built-in Open HMI Runtime software offers a rich object library, online/offline simulation, and over 450 industrial protocols and drivers. Open HMI Runtime is designed to enable a wide range of HMI control and visualization functions for creating powerful, user-friendly, reliable solutions for sophisticated applications.

#### Contents of the Open HMI Application-Ready-Package Solution for Industry 4.0

- Embedded automation box PC
- 32GB mSATA
- Microsoft Windows Embedded 7 Pro (64 bit)
- WebAccess/HMI Runtime 1500 tags

## Open HMI Solution Specifications

### Visualized Box HMI for Process Information

- Supports high resolution VGA and full HD HDMI output
- Multiple languages for HMI (up to 10 languages)
- Object library: includes default/common objects, object groups and global objects
- HMI Designer: a powerful develop tool supports online/offline design simulation
- User-customized picture/sounds database

### Application-Oriented HMI Functions

- Data log: up to 16 datalog blocks (saved as csv/txt file)
- Operation log: operation history for process parameter inspection (saved as csv file)
- Alarm: up to 16 alarm blocks, e-mail notification (supports SSL/TSL encryption)
- Recipe: up to 16 Recipe blocks
- Schedule: up to 80 sets
- Event: up to 36 sets
- User-customized data process: Macros
- Security Authority: 9 levels password

### Communication with Multiple Systems

- Rich interfaces such as RS-232/422/485, USB 3.0/2.0, Ethernet, and Audio I/O
- Maximum Serial/Ethernet Links: 4-links (serial), 16-links (Ethernet)
- Supports 450 communication protocols and drivers for industrial devices
- Gateway service by Modbus for HMI devices communication
- Flexible I/O expansion by iDoor technology

### Reliable Design for Field Operations

- Fanless compact design with higher reliability
- Stand, wall, VESA and Din-rail mounting for any field side installation
- Supports remote system status monitoring by WISE-PaaS/RMM
- Approved Certifications: BSMI, CCC, CE, FCC Class A, UL
- Wide operating temperature
- Vibration Protection with mSATA: 2 Grms (5~500 Hz)



For more Open HMI application stories and technical support documents, visit the Advantech website at <http://select.advantech.com/open-hmi-solutions>

## Configuration Options

Series	Visualization Box HMI and Communication Gateway		
<b>Part Number</b>	WA-HU2272G-J15H2AE	WA-HU2473G-J15H2AE	WA-HU2483G-315H2AE
<b>Embedded Automation PC</b>	UNO-2272G-J2AE	UNO-2473G-J3AE	UNO-2483G-434AE
<b>Operating System</b>	Microsoft WES 7 Pro (64 bit)		
<b>HMI Software</b>	WebAccess/HMI Runtime 1500 tags		
<b>Form Factor</b>	Palm size	Regular size	Regular size
<b>CPU</b>	Intel® Celeron® J1900 2.0 GHz	Intel® Celeron® J1900 2.4 GHz	Intel® Core™ i3-4010U 1.7 GHz
<b>Memory</b>	2G of DDR3L SDRAM	4G of DDR3L SDRAM	8G of DDR3L SDRAM
<b>Display Type</b>	HDMI: 1920 x 1080 @60Hz VGA: 2560 x 1600 @60Hz	HDMI: 1920 x 1080 @60Hz VGA: 2560 x 1600 @60Hz	HDMI: 3200 x 2000 @60Hz VGA: 1920 x 1200 @60Hz
<b>Storage</b>	1 x 32 GB mSATA		
<b>Expansion Slots</b>	2 x Mini PCIe	1 x Mini PCIe	2 x Mini PCIe
<b>Mounting</b>	Stand and wall DIN rail and VESA (with optional kit)		
<b>Network (LAN)</b>	1 x 10/100/1000 Base-T	2 x 10/100/1000 Base-T	4 x 10/100/1000 Base-T
<b>I/O</b>	1 x RS-232 (optional RS-422/485 via BIOS configuration), 2 x USB 2.0, 1 x USB 3.0	2 x RS-232, 2 x RS-422/485, 4 x USB 2.0, 1 x USB 3.0	2 x RS-232, 2 x RS-422/485, 2 x USB 2.0, 2 x USB 3.0
<b>iDoor Expansion</b>	1 x iDoor		
<b>Audio</b>	1 x Line Out	1 x Line In, 1 x Line Out	1 x Line In, 1 x Line Out
<b>DC Power Input (Voltage)</b>	24 V <sub>DC</sub> ± 20%	10 ~ 36 V <sub>DC</sub>	24 V <sub>DC</sub> ± 20%
<b>Power Consumption</b>	12 W	24 W	28 W
<b>Operating Temperature</b>	-10 ~ 55°C	-10 ~ 55°C	-20 ~ 60°C
<b>Dimensions</b>	157 x 88 x 50 mm	252 x 149 x 62 mm	252 x 149 x 62 mm
<b>Certification</b>	CE, FCC, UL, CCC, BSMI		

## Ordering Information

- WA-HU2483G-315H2AE** UNO-2483G-434AE, HMI Runtime 1500 tags, 32G mSATA, WES7P
- WA-HU2473G-J15H2AE** UNO-2473G-J3AE, HMI Runtime 1500 tags, 32G mSATA, WES7P
- WA-HU2272G-J15H2AE** UNO-2272G-J2AE, HMI Runtime 1500 tags, 32G mSATA, WES7P

## Accessories

- |                        |  |
|------------------------|--|
| <b>PWR-247-CE</b>      | 100-240V 60W 24V 2.5A power adapter for WAHU2272G/WA-HU2473G |
| <b>96PSA-A150W24T2</b> | 100-240V 150W 24V power adapter for WA-HU2483G               |
| <b>1702002600</b>      | Power Cable US Plug 1.8 M                                    |
| <b>1702002605</b>      | Power Cable EU Plug 1.8 M                                    |
| <b>1702031801</b>      | Power Cable UK Plug 1.8 M                                    |
| <b>1700000596-11</b>   | Power Cable China/Australia Plug 1.8 M                       |
| <b>UNO-2000G-DMKAE</b> | Din-rail kit for WA-HU2272G/WA-HU2473G/ WA-HU2483G           |
| <b>UNO-2000G-VMKAE</b> | VESA Mount kit for WA-HU2272G/WA-HU2473G/ WA-HU2483G         |

## Selected iDoor Modules

- |                       |   |
|-----------------------|---|
| <b>PCM-24D2R2-BE</b>  | 2-Ports Isolated RS-232 mPCIe, DB9                        |
| <b>PCM-24D2R4-BE</b>  | 2-Ports Isolated RS-422/485 mPCIe, DB9                    |
| <b>PCM-24D4R2-BE</b>  | 4-Ports Non-Isolated RS-232 mPCIe, DB37                   |
| <b>PCM-24D4R4-BE</b>  | 4-Ports Non-Isolated RS-422/485 mPCIe, DB37               |
| <b>PCM-27D24DI-AE</b> | 24-Channels Isolated Digital I/O with counter mPCIe, DB37 |
| <b>PCM-24U2U3-AE</b>  | USB 3.0, mPCIe, USB-A type x 2                            |
| <b>PCM-24S2WF-BE</b>  | 802.11 a/b/g/n 2T2R w/ Bluetooth 4.0, half-size mPCIe     |
| <b>PCM-24R1TP-AE</b>  | Intel® 82574L, GbE, RJ45 x 1                              |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

#### Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: [org@eplast1.ru](mailto:org@eplast1.ru)

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.