




## SERIES: VCD40 | DESCRIPTION: DC-DC CONVERTER

### FEATURES

- up to 40 W isolated output
- wide input (2:1)
- 2"x2" six sided shielded metal case
- single, dual, and triple regulated outputs
- 1500 V isolation
- short circuit, over voltage and over temperature protection
- wide temperature (-25~71°C)
- efficiency up to 92%




| MODEL          | input voltage |             | output voltage<br>(Vdc) | input current |                | output current |          | ripple and noise <sup>1</sup><br>max (mVp-p) | efficiency<br>typ (%) |
|----------------|---------------|-------------|-------------------------|---------------|----------------|----------------|----------|----------------------------------------------|-----------------------|
|                | typ (Vdc)     | range (Vdc) |                         | no load (mA)  | full load (mA) | max (mA)       | min (mA) |                                              |                       |
| VCD40-D12-S2R5 | 12            | 9~18        | 2.5                     | 200           | 2,367          | 10,000         | 0        | 50                                           | 88                    |
| VCD40-D12-S3R3 | 12            | 9~18        | 3.3                     | 200           | 3,090          | 10,000         | 0        | 50                                           | 89                    |
| VCD40-D12-S5   | 12            | 9~18        | 5                       | 200           | 3,745          | 8,000          | 0        | 50                                           | 89                    |
| VCD40-D12-S12  | 12            | 9~18        | 12                      | 200           | 3,703          | 3,333          | 0        | 75                                           | 90                    |
| VCD40-D12-S15  | 12            | 9~18        | 15                      | 200           | 3,702          | 2,666          | 0        | 75                                           | 90                    |
| VCD40-D12-D12  | 12            | 9~18        | ±12                     | 100           | 4,045          | ±1,800         | 90       | 120                                          | 89                    |
| VCD40-D12-D15  | 12            | 9~18        | ±15                     | 100           | 3,889          | ±1,400         | 70       | 150                                          | 90                    |
| VCD40-D12-T312 | 12            | 9~18        | 3.3/±12                 | 200           | 2,784          | 6000/±400      | 600/±40  | 100                                          | 88                    |
| VCD40-D12-T315 | 12            | 9~18        | 3.3/±15                 | 200           | 2,727          | 6000/±300      | 600/±30  | 100                                          | 88                    |
| VCD40-D12-T512 | 12            | 9~18        | 5/±12                   | 200           | 3,750          | 6000/±400      | 600/±40  | 100                                          | 88                    |
| VCD40-D12-T515 | 12            | 9~18        | 5/±15                   | 200           | 3,611          | 6000/±300      | 600/±30  | 100                                          | 90                    |
| VCD40-D24-S2R5 | 24            | 18~36       | 2.5                     | 100           | 1,184          | 10,000         | 0        | 50                                           | 88                    |
| VCD40-D24-S3R3 | 24            | 18~36       | 3.3                     | 100           | 1,545          | 10,000         | 0        | 50                                           | 89                    |
| VCD40-D24-S5   | 24            | 18~36       | 5                       | 100           | 1,831          | 8,000          | 0        | 50                                           | 91                    |
| VCD40-D24-S12  | 24            | 18~36       | 12                      | 100           | 1,811          | 3,333          | 0        | 75                                           | 92                    |
| VCD40-D24-S15  | 24            | 18~36       | 15                      | 100           | 1,810          | 2,666          | 0        | 75                                           | 92                    |
| VCD40-D24-D12  | 24            | 18~36       | ±12                     | 100           | 1,978          | ±1,800         | 90       | 120                                          | 91                    |
| VCD40-D24-D15  | 24            | 18~36       | ±15                     | 100           | 1,902          | ±1,400         | 70       | 150                                          | 92                    |
| VCD40-D24-T312 | 24            | 18~36       | 3.3/±12                 | 100           | 1,361          | 6000/±400      | 600/±40  | 100                                          | 90                    |
| VCD40-D24-T315 | 24            | 18~36       | 3.3/±15                 | 100           | 1,333          | 6000/±300      | 600/±30  | 100                                          | 90                    |
| VCD40-D24-T512 | 24            | 18~36       | 5/±12                   | 100           | 1,833          | 6000/±400      | 600/±40  | 100                                          | 90                    |
| VCD40-D24-T515 | 24            | 18~36       | 5/±15                   | 100           | 1,806          | 6000/±300      | 600/±30  | 100                                          | 90                    |
| VCD40-D48-S2R5 | 48            | 36~72       | 2.5                     | 50            | 585            | 10,000         | 0        | 50                                           | 89                    |
| VCD40-D48-S3R3 | 48            | 36~72       | 3.3                     | 50            | 764            | 10,000         | 0        | 50                                           | 90                    |
| VCD40-D48-S5   | 48            | 36~72       | 5                       | 60            | 926            | 8,000          | 0        | 50                                           | 90                    |
| VCD40-D48-S12  | 48            | 36~72       | 12                      | 60            | 916            | 3,333          | 0        | 75                                           | 91                    |
| VCD40-D48-S15  | 48            | 36~72       | 15                      | 60            | 906            | 2,666          | 0        | 75                                           | 92                    |
| VCD40-D48-D12  | 48            | 36~72       | ±12                     | 50            | 1,000          | ±1,800         | 90       | 120                                          | 90                    |
| VCD40-D48-D15  | 48            | 36~72       | ±15                     | 50            | 962            | ±1,400         | 70       | 150                                          | 91                    |

**MODEL**

|                | input voltage |             | output voltage | input current |                | output current |          | ripple and noise <sup>1</sup> | efficiency |
|----------------|---------------|-------------|----------------|---------------|----------------|----------------|----------|-------------------------------|------------|
|                | typ (Vdc)     | range (Vdc) | (Vdc)          | no load (mA)  | full load (mA) | max (mA)       | min (mA) | max (mVp-p)                   | typ (%)    |
| VCD40-D48-T312 | 48            | 36~72       | 3.3/±12        | 50            | 688            | 6000/±400      | 600/±40  | 100                           | 89         |
| VCD40-D48-T315 | 48            | 36~72       | 3.3/±15        | 50            | 690            | 6000/±300      | 600/±30  | 100                           | 89         |
| VCD40-D48-T512 | 48            | 36~72       | 5/±12          | 50            | 938            | 6000/±400      | 600/±40  | 100                           | 88         |
| VCD40-D48-T515 | 48            | 36~72       | 5/±15          | 50            | 903            | 6000/±300      | 600/±30  | 100                           | 90         |

notes: 1. ripple and noise are measured at 20 Hz BW

**PART NUMBER KEY****INPUT**

| parameter               | conditions/description  | min | typ | max | units |
|-------------------------|-------------------------|-----|-----|-----|-------|
| operating input voltage |                         | 9   | 12  | 18  | Vdc   |
|                         |                         | 18  | 24  | 36  | Vdc   |
|                         |                         | 36  | 48  | 72  | Vdc   |
| under voltage lockout   | 12 Vin power up 8.8 V   |     |     | 8.8 | Vdc   |
|                         | 12 Vin power down 8.0 V |     |     | 8.0 | Vdc   |
|                         | 24 Vin power up 17 V    |     |     | 17  | Vdc   |
|                         | 24 Vin power down 16 V  |     |     | 16  | Vdc   |
|                         | 48 Vin power up 34 V    |     |     | 34  | Vdc   |
|                         | 48 Vin power down 32 V  |     |     | 32  | Vdc   |
| input filter            | PI type                 |     |     |     |       |

**OUTPUT**

| parameter                    | conditions/description        | min  | typ | max  | units |
|------------------------------|-------------------------------|------|-----|------|-------|
| line regulation <sup>1</sup> | single and dual output models |      |     | ±0.5 | %     |
|                              | triple output models          |      |     | ±1.0 | %     |
|                              |                               |      |     | ±3.0 | %     |
| load regulation <sup>2</sup> | single and dual output models |      |     | ±0.5 | %     |
|                              |                               |      |     | ±1.0 | %     |
|                              | dual positive output models   | 3.3V |     | ±1.5 | %     |
|                              |                               | 5V   |     | ±4.0 | %     |
|                              | triple output models          |      |     | ±1.0 | %     |
|                              |                               |      |     | ±4.0 | %     |
| voltage accuracy             | single output models          |      |     | ±1.5 | %     |
|                              | dual positive output models   | 3.3V |     | ±1.5 | %     |
|                              |                               | 5V   |     | ±3.0 | %     |
|                              | triple output models          |      |     | ±1.5 | %     |
|                              |                               |      |     | ±5.0 | %     |

## OUTPUT

| parameter                     | conditions/description                     | min | typ | max   | units |
|-------------------------------|--------------------------------------------|-----|-----|-------|-------|
| cross regulation <sup>3</sup> | +3.3V                                      |     |     | ±1.0  | %     |
|                               | +5V                                        |     |     | ±4.0  | %     |
| voltage balance               | dual output models                         |     |     | ±2.0  | %     |
| transient response            | 75-100% step load change<br>±5% error band |     |     | 300   | µs    |
| external trim adjust range    | single and dual output models              |     | ±10 |       | %     |
|                               | dual positive output models                |     | ±5  |       | %     |
| current limit                 |                                            | 110 |     | 140   | %     |
| switching frequency           |                                            |     | 350 |       | kHz   |
| temperature coefficient       |                                            |     |     | ±0.02 | %/°C  |

Notes:

1. measured from high line to low line
2. measured from full load to 10% load
2. measured from max. load to 10% load, other output at 10% load

## PROTECTIONS

| parameter                   | conditions/description | min  | typ | max | units |
|-----------------------------|------------------------|------|-----|-----|-------|
| short circuit protection    | continuous, hiccup     |      |     |     |       |
| over temperature protection |                        |      | 110 |     | °C    |
| over-voltage protection     | zener diode clamp      | 2.5V |     | 3.6 | Vdc   |
|                             |                        | 3.3V |     | 3.9 | Vdc   |
|                             |                        | 5V   |     | 6.2 | Vdc   |
|                             |                        | 12V  |     | 15  | Vdc   |
|                             |                        | 15V  |     | 18  | Vdc   |

## SAFETY AND COMPLIANCE

| parameter             | conditions/description | min   | typ | max | units |
|-----------------------|------------------------|-------|-----|-----|-------|
| isolation voltage     |                        | 1,500 |     |     | Vdc   |
| insulation resistance |                        | 1,000 |     |     | MΩ    |
| RoHS compliant        | yes                    |       |     |     |       |


## ENVIRONMENTAL

| parameter                          | conditions/description | min | typ | max | units |
|------------------------------------|------------------------|-----|-----|-----|-------|
| operating temperature <sup>1</sup> |                        | -40 |     | 85  | °C    |
| case temperature <sup>1</sup>      |                        |     |     | 100 | °C    |
| storage temperature                |                        | -55 |     | 105 | °C    |

Notes:

1. measured from high line to low line

## DERATING CURVES




## MECHANICAL

| parameter     | conditions/description                       | min | typ | max | units |
|---------------|----------------------------------------------|-----|-----|-----|-------|
| dimensions    | 2 x 2 x 0.4 (50.8 x 50.8 x 10.2 mm)          |     |     |     | inch  |
| case material | black coated copper with non-conductive base |     |     |     |       |
| weight        |                                              |     | 65  |     | g     |

## MECHANICAL DRAWING

units: inches (mm)

tolerance: x.xx =  $\pm 0.02$ , x.xxx =  $\pm 0.010$ (x.x =  $\pm 0.5$ , x.xx =  $\pm 0.25$ )pin tolerance  $\pm 0.05$ mm

### PIN CONNECTIONS

|     | SINGLE OUTPUT | DUAL OUTPUT | DUAL POSITIVE | TRIPLE OUTPUT |
|-----|---------------|-------------|---------------|---------------|
| PIN | FUNCTION      | FUNCTION    | FUNCTION      | FUNCTION      |
| 1   | +Vin          | +Vin        | +Vin          | +Vin          |
| 2   | -Vin          | -Vin        | -Vin          | -Vin          |
| 3   | on/off        | on/off      | on/off        | on/off        |
| 4   | NC            | no pin      | +3.3Vo        | +Aux. out     |
| 5   | -sense        | +Vo         | com(5V RTN)   | common        |
| 6   | +sense        | common      | trim          | -Aux. out     |
| 7   | +Vo           | common      | NC            | +Vo           |
| 8   | -Vo           | -Vo         | +5 Vo         | -Vo (common)  |
| 9   | trim          | trim        | com(5V RTN)   | NC            |

### REMOTE ON/OFF CONTROL

|                       |                            |
|-----------------------|----------------------------|
| logic compatibility   | CMOS or Open Collector TTL |
| EC-on                 | >+5.5 Vdc or Open Circuit  |
| EC-off                | <1.8 Vdc                   |
| shutdown idle current | 10 mA                      |
| control common        | referenced to input minus  |

### TRIPLE OUTPUT LOADING TABLE<sup>1</sup>


| PIN | VOLTAGE  | AMPERES          |      |
|-----|----------|------------------|------|
|     |          | min <sup>2</sup> | typ  |
| 7   | +5       | 0.50             | 3.5  |
| 8,5 | $\pm 12$ | 0.10             | 0.31 |
| 8,5 | $\pm 15$ | 0.10             | 0.25 |

Notes:

- Maximum total power from all outputs is limited to 25 watts but no output should exceed its maximum current.
- Minimum current on each output is required to maintain specified regulation.

### EXTERNAL OUTPUT TRIMMING

Output may optionally be externally trimmed ( $\pm 10\%$ ) with a fixed resistor or an external trimpot as shown.



1. The value of Rtrim-up defined as:

$$R_{trim-up} = \left( \frac{R1 \times Vr}{Vo - Vo, nom} \right) - Rt \text{ (K}\Omega\text{)}$$

Where: R trim-up is the external resistor in Kohm.  
Vo,nom is the nominal output voltage.  
Vo is the desired output voltage.

R1 ,Rt and Vr are internal to the unit and are defined in Table 1.

For example, to trim-up the output voltage of 5.0V module (VCD40-D48-S5) by 5% to 5.25V, R trim-up is calculated as follows:

$$Vo - Vo, nom = 5.25 - 5.0 = 0.25V$$

$$R1 = 2.32 \text{ Kohm}$$

$$Rt = 8.2 \text{ Kohm}, Vr = 2.5$$

$$R_{trim-up} = \frac{2.32 \times 2.5}{0.25} - 8.2 = 15 \text{ (K}\Omega\text{)}$$

The value of R trim-down defined as:

$$R_{trim-down} = \frac{R1 \times (Vo - Vr)}{Vo, nom - Vo} - Rt \text{ (K}\Omega\text{)}$$

Where: R trim-down is the external resistor in Kohm.  
Vo,nom is the nominal output voltage.  
Vo is the desired output voltage.

R1 ,Rt and Vr are internal to the unit and are defined in Table 1.

For example, to trim-down the output voltage of 5.0V module (VCD40-D48-S5) by 5% to 4.75V, R trim-down is calculated as follows :

$$Vo, nom - Vo = 5.0 - 4.75 = 0.25 \text{ V}$$

$$R1 = 2.32 \text{ Kohm}$$

$$Rt = 8.2 \text{ Kohm}, Vr = 2.5$$

$$R_{trim-down} = \frac{2.32 \times (4.75 - 2.5)}{0.25} - 8.2 = 12.68 \text{ (K}\Omega\text{)}$$

Table 1 - Trim Resistor Values

| Model Number                 | Output Voltage(V) | R1 (Kohm) | Rt (Kohm) | Vr  |
|------------------------------|-------------------|-----------|-----------|-----|
| VCD40-D24-S5<br>VCD40-D48-S5 | 5.0               | 2.32      | 8.2       | 2.5 |

Table 2 - Trim Resistor Values

| Model Number                     | Output Voltage(V) | R1 (Kohm) | R2 (Kohm) | R3 (Kohm) | Rt (Kohm) | Vr   |
|----------------------------------|-------------------|-----------|-----------|-----------|-----------|------|
| VCD40-D24-S3R3<br>VCD40-D48-S3R3 | 3.3V              | 2.74      | 1.8       | 0.27      | 9.1       | 1.24 |
| VCD40-D24-S12<br>VCD40-D48-S12   | 12V               | 6.8       | 2.4       | 2.32      | 22        | 2.5  |
| VCD40-D24-S15<br>VCD40-D48-S15   | 15V               | 8.06      | 2.4       | 3.9       | 27        | 2.5  |

In order to trim the voltage up or down one needs to connect the trim resistor either between the trim pin and -Vo for trim-up and between trim pin and +Vo for trim-down. The output voltage trim range is  $\pm 10\%$ . This is shown in **Figures 1 and 2**:

2. The output Voltage 3.3V, 12V and 15V value of Rtrim are defined as below:

$$R_{trim-up} = \left( \frac{Vr \times R1 \times (R2 + R3)}{(Vo - Vo, nom) \times R2} \right) - Rt \text{ (K}\Omega\text{)}$$

$$R_{trim-down} = R1 \times \left( \frac{Vr \times R1}{(Vo, nom - Vo) \times R2} - 1 \right) - Rt \text{ (K}\Omega\text{)}$$

Where: R trim-up is the external resistor in Kohm.

Vo,nom is the nominal output voltage.

Vo is the desired output voltage.

R1, R2, R3, Rt and Vr are internal to the unit and are defined in **Table 2**.

Figure 1. Trim-up Voltage Setup





Figure 2. Trim-down Voltage Setup



## REVISION HISTORY

| rev. | description                                            | date       |
|------|--------------------------------------------------------|------------|
| 1.0  | initial release                                        | 06/28/2007 |
| 1.01 | layout update, addition of triple output loading table | 10/09/2009 |
| 1.02 | new template applied, V-Infinity branding removed      | 09/07/2012 |
| 1.03 | spec updated                                           | 04/01/2013 |

The revision history provided is for informational purposes only and is believed to be accurate.



**Headquarters**  
20050 SW 112th Ave.  
Tualatin, OR 97062  
**800.275.4899**

Fax 503.612.2383  
**cui.com**  
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.