

Surface Mount Type

Series: **FK** Type: **V**



■ Features

- Endurance: 2000 h to 5000 h at 105 °C
- Low impedance (40 % to 60 % less than FC series)
Miniaturized (30 % to 50 % less than FC series)
- Vibration-proof product is available upon request. (φ8 mm and larger)
- RoHS directive compliant

■ Specifications

| | | | | | | | | | | | |
|------------------------------------|---|--|----|----|----|----|----|----|----|-----|-----------------------------|
| Category Temp. Range | -55 °C to +105 °C | | | | | | | | | | |
| Rated W.V.Range | 6.3 V.DC to 100 V.DC | | | | | | | | | | |
| Nominal Cap.Range | 3.3 μF to 6800 μF | | | | | | | | | | |
| Capacitance Tolerance | ±20 % (120 Hz/+20 °C) | | | | | | | | | | |
| DC Leakage Current | I ≤ 0.01 CV or 3 (μA) After 2 minutes (Whichever is greater) | | | | | | | | | | |
| tan δ | Please see the attached standard products list | | | | | | | | | | |
| Characteristics at Low Temperature | W.V. (V) | 6.3 | 10 | 16 | 25 | 35 | 50 | 63 | 80 | 100 | (Impedance ratio at 120 Hz) |
| | Z(-25 °C)/Z(+20 °C) | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | |
| | Z(-40 °C)/Z(+20 °C) | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | |
| | Z(-55 °C)/Z(+20 °C) | 4 | 4 | 4 | 3 | 3 | 3 | 3 | 3 | 3 | |
| Endurance | After applying rated working voltage for 2000 hours at +105 °C±2 °C and then being stabilized at +20 °C, Capacitors shall meet the following limits. (≥ φ12.5 and suffix "G" in φ8×10.2, φ10×10.2 are 5000 hours) | | | | | | | | | | |
| | Capacitance change | ±30 % of initial measured value (Suffix "G" is 35 %) | | | | | | | | | |
| | tan δ | ≤ 200 % of initial specified value (Suffix "G" is 300 %) | | | | | | | | | |
| | DC leakage current | ≤ initial specified value | | | | | | | | | |
| Shelf Life | After storage for 1000 hours at +105 °C±2 °C with no voltage applied and then being stabilized at +20 °C, capacitors shall meet the limits specified in Endurance (With voltage treatment) | | | | | | | | | | |
| Resistance to Soldering Heat | After reflow soldering and then being stabilized at +20 °C, capacitors shall meet the following limits. | | | | | | | | | | |
| | Capacitance change | ±10 % of initial measured value | | | | | | | | | |
| | tan δ | ≤ initial specified value | | | | | | | | | |
| | DC leakage current | ≤ initial specified value | | | | | | | | | |

■ Frequency correction factor for ripple current

| | | | | | |
|-------------------|----------------|------|------|------|----------|
| Correction factor | Frequency (Hz) | | | | |
| | 50, 60 | 120 | 1 k | 10 k | 100 k to |
| | 0.70 | 0.75 | 0.90 | 0.95 | 1.00 |

■ Marking

Example: 6.3 V 22 μF, 6.3 V 3300 μF
Marking color : BLACK
 ≤ φ10

Capacitance (μF)
 Series identification
 Mark for Lead-Free Products Black Dot (Square)
 Lot number
 Rated Voltage Mark

≥ φ12.5

Capacitance (μF)
 Series identification
 Lot number
 Rated Voltage Mark

Rated Voltage Mark

| | | | |
|---|-------|----|-------|
| j | 6.3 V | H | 50 V |
| A | 10 V | J | 63 V |
| C | 16 V | K | 80 V |
| E | 25 V | 2A | 100 V |
| V | 35 V | | |

■ Dimensions in mm (not to scale)

(Unit : mm)

0.3 max.
 φD±0.5
 L
 H
 A±0.2
 B±0.2
 W
 Pressure Relief (φ10 and larger)
 () Reference size

| Size code | D | L | A,B | H | I | W | P | K |
|-----------|------|----------|------|-----------|-----|----------|-----|--------------------------------------|
| B | 4.0 | 5.8±0.3 | 4.3 | 5.5 max. | 1.8 | 0.65±0.1 | 1.0 | 0.35 ^{+1.5} _{-0.2} |
| C | 5.0 | 5.8±0.3 | 5.3 | 6.5 max. | 2.2 | 0.65±0.1 | 1.5 | 0.35 ^{+1.5} _{-0.2} |
| D | 6.3 | 5.8±0.3 | 6.6 | 7.8 max. | 2.6 | 0.65±0.1 | 1.8 | 0.35 ^{+1.5} _{-0.2} |
| D8 | 6.3 | 7.7±0.3 | 6.6 | 7.8 max. | 2.6 | 0.65±0.1 | 1.8 | 0.35 ^{+1.5} _{-0.2} |
| E | 8.0 | 6.2±0.3 | 8.3 | 9.5 max. | 3.4 | 0.65±0.1 | 2.2 | 0.35 ^{+1.5} _{-0.2} |
| F | 8.0 | 10.2±0.3 | 8.3 | 10.0 max. | 3.4 | 0.90±0.2 | 3.1 | 0.70±0.2 |
| G | 10.0 | 10.2±0.3 | 10.3 | 12.0 max. | 3.5 | 0.90±0.2 | 4.6 | 0.70±0.2 |
| H13 | 12.5 | 13.5±0.5 | 13.5 | 15.0 max. | 4.7 | 0.90±0.3 | 4.4 | 0.70±0.3 |
| J16 | 16.0 | 16.5±0.5 | 17.0 | 19.0 max. | 5.5 | 1.20±0.3 | 6.7 | 0.70±0.3 |
| K16 | 18.0 | 16.5±0.5 | 19.0 | 21.0 max. | 6.7 | 1.20±0.3 | 6.7 | 0.70±0.3 |

Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use. Should a safety concern arise regarding this product, please be sure to contact us immediately.

■ Standard Products

Endurance : 105 °C 2000 h (≥ ϕ12.5 : 5000 h)

| W.V. | Cap. (±20 %) | Case size | | | Specification | | | Part No. (RoHS:compliant) | Reflow | Min. |
|------|-----------------|-----------|--------|------------|---|---|-------------------------------|------------------------------|-------------|-----------------|
| | | Dia. | Length | *Size Code | Ripple Current (100 kHz) (+105 °C) (mA r.m.s.) | Impedance (100 kHz) (+20 °C) (Ω) | tan δ (120 Hz) (+20 °C) | | | Packageing Q'ty |
| (V) | (μF) | (mm) | (mm) | | | | | | Taping | |
| | | | | | | | | | (pcs) | |
| 6.3 | 22 | 4 | 5.8 | B | 90 | 1.35 | 0.26 | EEEFK0J220R | (1) | 2000 |
| | 47 | 4 | 5.8 | (B) | 90 | 1.35 | 0.26 | EEEFK0J470UR | (1) | 2000 |
| | | 5 | 5.8 | C | 160 | 0.70 | 0.26 | EEEFK0J470R | (1) | 1000 |
| | 100 | 5 | 5.8 | (C) | 160 | 0.70 | 0.26 | EEEFK0J101UR | (1) | 1000 |
| | | 6.3 | 5.8 | D | 240 | 0.36 | 0.26 | EEEFK0J101P | (1) | 1000 |
| | 220 | 6.3 | 5.8 | D | 240 | 0.36 | 0.26 | EEEFK0J221P | (1) | 1000 |
| | 330 | 6.3 | 7.7 | D8 | 280 | 0.34 | 0.26 | EEEFK0J331XP | (1) | 900 |
| | | 8 | 6.2 | E | 300 | 0.26 | 0.26 | EEEFK0J331P | (2) | 1000 |
| | 470 | 8 | 10.2 | F | 600 | 0.16 | 0.26 | EEEFK0J471P | (2) | 500 |
| | 1000 | 8 | 10.2 | F | 600 | 0.16 | 0.26 | EEEFK0J102P | (2) | 500 |
| 1500 | 10 | 10.2 | G | 850 | 0.08 | 0.26 | EEEFK0J152P | (2) | 500 | |
| 3300 | 12.5 | 13.5 | H13 | 1100 | 0.06 | 0.30 | EEVFK0J332Q | (3) | 200 | |
| 6800 | 16 | 16.5 | J16 | 1800 | 0.035 | 0.36 | EEVFK0J682M | (3) | 125 | |
| 10 | 22 | 4 | 5.8 | B | 90 | 1.35 | 0.19 | EEEFK1A220R | (1) | 2000 |
| | 33 | 4 | 5.8 | (B) | 90 | 1.35 | 0.19 | EEEFK1A330UR | (1) | 2000 |
| | | 5 | 5.8 | C | 160 | 0.70 | 0.19 | EEEFK1A330R | (1) | 1000 |
| | 150 | 6.3 | 5.8 | D | 240 | 0.36 | 0.19 | EEEFK1A151P | (1) | 1000 |
| | 220 | 6.3 | 7.7 | D8 | 280 | 0.34 | 0.19 | EEEFK1A221XP | (1) | 900 |
| | | 8 | 6.2 | E | 300 | 0.26 | 0.19 | EEEFK1A221P | (2) | 1000 |
| | 330 | 8 | 10.2 | F | 600 | 0.16 | 0.19 | EEEFK1A331P | (2) | 500 |
| | 470 | 8 | 10.2 | F | 600 | 0.16 | 0.19 | EEEFK1A471P | (2) | 500 |
| | 680 | 8 | 10.2 | F | 600 | 0.16 | 0.19 | EEEFK1A681P | (2) | 500 |
| | 1000 | 10 | 10.2 | G | 850 | 0.08 | 0.19 | EEEFK1A102P | (2) | 500 |
| 2200 | 12.5 | 13.5 | H13 | 1100 | 0.06 | 0.21 | EEVFK1A222Q | (3) | 200 | |
| 4700 | 16 | 16.5 | J16 | 1800 | 0.035 | 0.25 | EEVFK1A472M | (3) | 125 | |
| 6800 | 18 | 16.5 | K16 | 2060 | 0.033 | 0.29 | EEVFK1A682M | (3) | 125 | |
| 16 | 10 | 4 | 5.8 | B | 90 | 1.35 | 0.16 | EEEFK1C100R | (1) | 2000 |
| | 22 | 4 | 5.8 | (B) | 90 | 1.35 | 0.16 | EEEFK1C220UR | (1) | 2000 |
| | | 5 | 5.8 | C | 160 | 0.70 | 0.16 | EEEFK1C220R | (1) | 1000 |
| | 47 | 5 | 5.8 | (C) | 160 | 0.70 | 0.16 | EEEFK1C470UR | (1) | 1000 |
| | | 6.3 | 5.8 | D | 240 | 0.36 | 0.16 | EEEFK1C470P | (1) | 1000 |
| | 68 | 6.3 | 5.8 | D | 240 | 0.36 | 0.16 | EEEFK1C680P | (1) | 1000 |
| | 100 | 6.3 | 5.8 | D | 240 | 0.36 | 0.16 | EEEFK1C101P | (1) | 1000 |
| | 150 | 6.3 | 7.7 | D8 | 280 | 0.34 | 0.16 | EEEFK1C151XP | (1) | 900 |
| | 220 | 6.3 | 7.7 | D8 | 280 | 0.34 | 0.16 | EEEFK1C221XP | (1) | 900 |
| | | 8 | 6.2 | E | 300 | 0.26 | 0.16 | EEEFK1C221P | (2) | 1000 |
| | 330 | 8 | 10.2 | F | 600 | 0.16 | 0.16 | EEEFK1C331P | (2) | 500 |
| | 470 | 8 | 10.2 | F | 600 | 0.16 | 0.16 | EEEFK1C471P | (2) | 500 |
| | 680 | 10 | 10.2 | G | 850 | 0.08 | 0.16 | EEEFK1C681P | (2) | 500 |
| | 1500 | 12.5 | 13.5 | H13 | 1100 | 0.06 | 0.16 | EEVFK1C152Q | (3) | 200 |
| 3300 | 16 | 16.5 | J16 | 1800 | 0.035 | 0.20 | EEVFK1C332M | (3) | 125 | |
| 4700 | 18 | 16.5 | K16 | 2060 | 0.033 | 0.22 | EEVFK1C472M | (3) | 125 | |
| 25 | 10 | 4 | 5.8 | B | 90 | 1.35 | 0.14 | EEEFK1E100R | (1) | 2000 |
| | 22 | 5 | 5.8 | C | 160 | 0.70 | 0.14 | EEEFK1E220R | (1) | 1000 |
| | | 5 | 5.8 | (C) | 160 | 0.70 | 0.14 | EEEFK1E330UR | (1) | 1000 |
| | 33 | 6.3 | 5.8 | D | 240 | 0.36 | 0.14 | EEEFK1E330P | (1) | 1000 |
| | | 47 | 6.3 | 5.8 | D | 240 | 0.36 | 0.14 | EEEFK1E470P | (1) |
| | 68 | 6.3 | 5.8 | D | 240 | 0.36 | 0.14 | EEEFK1E680P | (1) | 1000 |
| | 100 | 6.3 | 7.7 | D8 | 280 | 0.34 | 0.14 | EEEFK1E101XP | (1) | 900 |
| | | 8 | 6.2 | E | 300 | 0.26 | 0.14 | EEEFK1E101P | (2) | 1000 |
| | 150 | 8 | 10.2 | F | 600 | 0.16 | 0.14 | EEEFK1E151P | (2) | 500 |
| | 220 | 8 | 10.2 | F | 600 | 0.16 | 0.14 | EEEFK1E221P | (2) | 500 |
| | 330 | 8 | 10.2 | F | 600 | 0.16 | 0.14 | EEEFK1E331P | (2) | 500 |
| | 470 | 10 | 10.2 | G | 850 | 0.08 | 0.14 | EEEFK1E471P | (2) | 500 |
| | 1000 | 12.5 | 13.5 | H13 | 1100 | 0.06 | 0.14 | EEVFK1E102Q | (3) | 200 |
| | 1500 | 16 | 16.5 | J16 | 1800 | 0.035 | 0.14 | EEVFK1E152M | (3) | 125 |
| 2200 | 16 | 16.5 | J16 | 1800 | 0.035 | 0.16 | EEVFK1E222M | (3) | 125 | |
| 3300 | 18 | 16.5 | K16 | 2060 | 0.033 | 0.18 | EEVFK1E332M | (3) | 125 | |

* Size code():Miniaturization product
 · Please refer to the page of "Reflow Profile" and "The Taping Dimensions".
 · When requesting vibration-proof product, please put the last "V" instead to "P"

Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use.
 Should a safety concern arise regarding this product, please be sure to contact us immediately.

■ Standard Products

Endurance : 105 °C 2000 h (≥ ϕ12.5 : 5000 h)

| W.V. | Cap. (±20 %) | Case size | | | Specification | | | Part No. (RoHS:compliant) | Reflow | Min. | |
|------|-----------------|-----------|--------|------------|---|---|-------------------------------|------------------------------|-------------|-----------------|------|
| | | Dia. | Length | *Size Code | Ripple Current (100 kHz) (+105 °C) (mA r.m.s.) | Impedance (100 kHz) (+20 °C) (Ω) | tan δ (120 Hz) (+20 °C) | | | Packageing Q'ty | |
| (V) | (μF) | (mm) | (mm) | | | | | | Taping | | |
| | | | | | | | | | (pcs) | | |
| 35 | 4.7 | 4 | 5.8 | B | 90 | 1.35 | 0.12 | EEEFK1V4R7R | (1) | 2000 | |
| | 10 | 4 | 5.8 | (B) | 90 | 1.35 | 0.12 | EEEFK1V100UR | (1) | 2000 | |
| | | 5 | 5.8 | C | 160 | 0.70 | 0.12 | EEEFK1V100R | (1) | 1000 | |
| | 22 | 5 | 5.8 | C | 160 | 0.70 | 0.12 | EEEFK1V220R | (1) | 1000 | |
| | 33 | 6.3 | 5.8 | D | 240 | 0.36 | 0.12 | EEEFK1V330P | (1) | 1000 | |
| | 47 | 6.3 | 5.8 | D | 240 | 0.36 | 0.12 | EEEFK1V470P | (1) | 1000 | |
| | 68 | 6.3 | 7.7 | D8 | 280 | 0.34 | 0.12 | EEEFK1V680XP | (1) | 900 | |
| | | | | | | | | | | | 8 |
| | 100 | 8 | 10.2 | F | 600 | 0.16 | 0.12 | EEEFK1V151P | (2) | 500 | |
| | | | | | | | | | | | 8 |
| | 220 | 8 | 10.2 | F | 600 | 0.16 | 0.12 | EEEFK1V331P | (2) | 500 | |
| | 330 | 10 | 10.2 | G | 850 | 0.08 | 0.12 | EEVFK1V471Q | (3) | 200 | |
| | 470 | 12.5 | 13.5 | H13 | 1100 | 0.06 | 0.12 | EEVFK1V681Q | (3) | 200 | |
| | 680 | 12.5 | 13.5 | H13 | 1100 | 0.06 | 0.12 | EEVFK1V102M | (3) | 125 | |
| 1000 | 16 | 16.5 | J16 | 1800 | 0.035 | 0.12 | EEVFK1V152M | (3) | 125 | | |
| 1500 | 16 | 16.5 | J16 | 1800 | 0.035 | 0.12 | EEVFK1V152M | (3) | 125 | | |
| 50 | 4.7 | 4 | 5.8 | B | 60 | 2.90 | 0.10 | EEEFK1H4R7R | (1) | 2000 | |
| | 10 | 5 | 5.8 | (C) | 85 | 1.52 | 0.10 | EEEFK1H100UR | (1) | 1000 | |
| | | 6.3 | 5.8 | D | 165 | 0.88 | 0.10 | EEEFK1H100P | (1) | 1000 | |
| | 22 | 6.3 | 5.8 | D | 165 | 0.88 | 0.10 | EEEFK1H220P | (1) | 1000 | |
| | 33 | 6.3 | 7.7 | D8 | 195 | 0.68 | 0.10 | EEEFK1H330XP | (1) | 900 | |
| | | | | | | | | | | | 8 |
| | 47 | 6.3 | 7.7 | D8 | 195 | 0.68 | 0.10 | EEEFK1H470XP | (1) | 900 | |
| | | | | | | | | | | | 8 |
| | 100 | 8 | 10.2 | F | 350 | 0.34 | 0.10 | EEEFK1H101P | (2) | 500 | |
| | 150 | 10 | 10.2 | G | 670 | 0.18 | 0.10 | EEEFK1H151P | (2) | 500 | |
| | 220 | 10 | 10.2 | G | 670 | 0.18 | 0.10 | EEEFK1H221P | (2) | 500 | |
| | 330 | 12.5 | 13.5 | H13 | 900 | 0.12 | 0.10 | EEVFK1H331Q | (3) | 200 | |
| | 390 | 12.5 | 13.5 | H13 | 900 | 0.12 | 0.10 | EEVFK1H391Q | (3) | 200 | |
| | 470 | 16 | 16.5 | J16 | 1610 | 0.073 | 0.10 | EEVFK1H471M | (3) | 125 | |
| 560 | 16 | 16.5 | J16 | 1610 | 0.073 | 0.10 | EEVFK1H561M | (3) | 125 | | |
| 680 | 16 | 16.5 | J16 | 1610 | 0.073 | 0.10 | EEVFK1H681M | (3) | 125 | | |
| 1000 | 16 | 16.5 | J16 | 1610 | 0.073 | 0.10 | EEVFK1H102M | (3) | 125 | | |
| 63 | 4.7 | 5 | 5.8 | C | 50 | 3.00 | 0.08 | EEEFK1J4R7R | (1) | 1000 | |
| | 10 | 6.3 | 5.8 | D | 80 | 1.50 | 0.08 | EEEFK1J100P | (1) | 1000 | |
| | | | | | | | | | | | 7.7 |
| | 22 | 8 | 6.2 | E | 120 | 1.20 | 0.08 | EEEFK1J220P | (2) | 1000 | |
| | | | | | | | | | | | 10.2 |
| | 47 | 8 | 10.2 | F | 250 | 0.65 | 0.08 | EEEFK1J470P | (2) | 500 | |
| | 68 | 8 | 10.2 | (F) | 250 | 0.65 | 0.08 | EEEFK1J680UP | (2) | 500 | |
| | 100 | 10 | 10.2 | G | 400 | 0.35 | 0.08 | EEEFK1J101P | (2) | 500 | |
| | 150 | 12.5 | 13.5 | H13 | 800 | 0.16 | 0.08 | EEVFK1J151Q | (3) | 200 | |
| | 220 | 12.5 | 13.5 | H13 | 800 | 0.16 | 0.08 | EEVFK1J221Q | (3) | 200 | |
| | 470 | 16 | 16.5 | J16 | 1410 | 0.082 | 0.08 | EEVFK1J471M | (3) | 125 | |
| | 680 | 18 | 16.5 | K16 | 1690 | 0.08 | 0.08 | EEVFK1J681M | (3) | 125 | |
| | 80 | 3.3 | 5 | 5.8 | C | 25 | 5.00 | 0.08 | EEEFK1K3R3R | (1) | 1000 |
| | | 4.7 | 6.3 | 5.8 | D | 40 | 3.00 | 0.08 | EEEFK1K4R7P | (1) | 1000 |
| 7.7 | | | | | | | | | | | |
| 10 | | 8 | 6.2 | E | 60 | 2.40 | 0.08 | EEEFK1K100P | (2) | 1000 | |
| | | | | | | | | | | | 10.2 |
| 33 | | 8 | 10.2 | F | 130 | 1.30 | 0.08 | EEEFK1K330P | (2) | 500 | |
| 47 | | 10 | 10.2 | G | 200 | 0.70 | 0.08 | EEEFK1K470P | (2) | 500 | |
| 68 | | 12.5 | 13.5 | H13 | 500 | 0.32 | 0.08 | EEVFK1K680Q | (3) | 200 | |
| 100 | | 12.5 | 13.5 | H13 | 500 | 0.32 | 0.08 | EEVFK1K101Q | (3) | 200 | |
| 150 | | 12.5 | 13.5 | H13 | 500 | 0.32 | 0.08 | EEVFK1K151Q | (3) | 200 | |
| 330 | | 16 | 16.5 | J16 | 793 | 0.17 | 0.08 | EEVFK1K331M | (3) | 125 | |
| 470 | | 18 | 16.5 | K16 | 917 | 0.153 | 0.08 | EEVFK1K471M | (3) | 125 | |

* Size code():Miniaturization product
 · Please refer to the page of "Reflow Profile" and "The Taping Dimensions".
 · When requesting vibration-proof product, please put the last "V" instead to "P"

■ Standard Products

Endurance : 105 °C 2000 h (≥ ϕ12.5 : 5000 h)

| W.V. | Cap. (±20 %) | Case size | | | Specification | | | Part No. (RoHS:compliant) | Reflow | Min. Packaging Q'ty |
|------|-----------------|-----------|--------|---------------|---|------------------------------------|-------------------------------|------------------------------|--------|------------------------|
| | | Dia. | Length | *Size Code | Ripple Current (100 kHz) (+105 °C) | Impedance (100 kHz) (+20 °C) | tan δ (120 Hz) (+20 °C) | | | Taping |
| (V) | (μF) | (mm) | (mm) | | (mA r.m.s.) | (Ω) | | | | (pcs) |
| 100 | 22 | 8 | 10.2 | F | 130 | 1.30 | 0.07 | EEEFK2A220P | (2) | 500 |
| | 33 | 10 | 10.2 | G | 200 | 0.70 | 0.07 | EEEFK2A330P | (2) | 500 |
| | 47 | 12.5 | 13.5 | H13 | 500 | 0.32 | 0.07 | EEVFK2A470Q | (3) | 200 |
| | 68 | 12.5 | 13.5 | H13 | 500 | 0.32 | 0.07 | EEVFK2A680Q | (3) | 200 |
| | 100 | 16 | 16.5 | J16 | 793 | 0.17 | 0.07 | EEVFK2A101M | (3) | 125 |
| | 150 | 16 | 16.5 | J16 | 793 | 0.17 | 0.07 | EEVFK2A151M | (3) | 125 |
| | 220 | 18 | 16.5 | K16 | 917 | 0.153 | 0.07 | EEVFK2A221M | (3) | 125 |
| | 330 | 18 | 16.5 | K16 | 917 | 0.153 | 0.07 | EEVFK2A331M | (3) | 125 |

* Size code():Miniaturization product
 · Please refer to the page of "Reflow Profile" and "The Taping Dimensions".

■ Endurance 5000 h Products

Endurance : 105 °C 5000 h

| W.V. | Cap. (±20 %) | Case size | | | Specification | | | Part No. (RoHS:compliant) | Reflow | Min. Packaging Q'ty |
|------|-----------------|-----------|--------|--------------|---|------------------------------------|-------------------------------|------------------------------|--------|------------------------|
| | | Dia. | Length | Size Code | Ripple Current (100 kHz) (+105 °C) | Impedance (100 kHz) (+20 °C) | tan δ (120 Hz) (+20 °C) | | | Taping |
| (V) | (μF) | (mm) | (mm) | | (mA r.m.s.) | (Ω) | | | | (pcs) |
| 6.3 | 470 | 8 | 10.2 | F | 600 | 0.16 | 0.26 | EEEFK0J471GP | (2) | 500 |
| | 1000 | 8 | 10.2 | F | 600 | 0.16 | 0.26 | EEEFK0J102GP | (2) | 500 |
| | 1500 | 10 | 10.2 | G | 850 | 0.08 | 0.26 | EEEFK0J152GP | (2) | 500 |
| 10 | 330 | 8 | 10.2 | F | 600 | 0.16 | 0.19 | EEEFK1A331GP | (2) | 500 |
| | 470 | 8 | 10.2 | F | 600 | 0.16 | 0.19 | EEEFK1A471GP | (2) | 500 |
| | 680 | 8 | 10.2 | F | 600 | 0.16 | 0.19 | EEEFK1A681GP | (2) | 500 |
| | 1000 | 10 | 10.2 | G | 850 | 0.08 | 0.19 | EEEFK1A102GP | (2) | 500 |
| 16 | 330 | 8 | 10.2 | F | 600 | 0.16 | 0.16 | EEEFK1C331GP | (2) | 500 |
| | 470 | 8 | 10.2 | F | 600 | 0.16 | 0.16 | EEEFK1C471GP | (2) | 500 |
| | 680 | 10 | 10.2 | G | 850 | 0.08 | 0.16 | EEEFK1C681GP | (2) | 500 |
| 25 | 150 | 8 | 10.2 | F | 600 | 0.16 | 0.14 | EEEFK1E151GP | (2) | 500 |
| | 220 | 8 | 10.2 | F | 600 | 0.16 | 0.14 | EEEFK1E221GP | (2) | 500 |
| | 330 | 8 | 10.2 | F | 600 | 0.16 | 0.14 | EEEFK1E331GP | (2) | 500 |
| | 470 | 10 | 10.2 | G | 850 | 0.08 | 0.14 | EEEFK1E471GP | (2) | 500 |
| 35 | 100 | 8 | 10.2 | F | 600 | 0.16 | 0.12 | EEEFK1V101GP | (2) | 500 |
| | 150 | 8 | 10.2 | F | 600 | 0.16 | 0.12 | EEEFK1V151GP | (2) | 500 |
| | 220 | 8 | 10.2 | F | 600 | 0.16 | 0.12 | EEEFK1V221GP | (2) | 500 |
| | 330 | 10 | 10.2 | G | 850 | 0.08 | 0.12 | EEEFK1V331GP | (2) | 500 |
| 50 | 100 | 8 | 10.2 | F | 350 | 0.34 | 0.10 | EEEFK1H101GP | (2) | 500 |
| | 150 | 10 | 10.2 | G | 670 | 0.18 | 0.10 | EEEFK1H151GP | (2) | 500 |
| | 220 | 10 | 10.2 | G | 670 | 0.18 | 0.10 | EEEFK1H221GP | (2) | 500 |

· Please refer to the page of "Reflow Profile" and "The Taping Dimensions".
 · When requesting vibration-proof product, please put the last "V" instead to "P"



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.