samtec

EDGE® RATE CONTACT

(0.80 mm) .0315"

HSEC8-DV SERIES

VERTICAL EDGE RATE® CARD SOCKET



HSEC8–149–01–L–DV–A

HSEC8–125–01–L–DV–A

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?HSEC8-DV

Insulator Material:
Black Liquid Crystal Polymer
Contact:
BeCu
Plating:
Au or Sn over
50 µ" (1.27 µm) Ni
Current Rating:
2.8 A per pin
(2 adjacent pins powered)
Operating Temp:
-55 °C to +125 °C
RoHS Compliant:
Yes

PROCESSING

Lead–Free Solderable:
Yes
SMT Lead Coplanarity:
(0.10 mm) .004" max (10-60)

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality

FILE NO. E111594

Card Mates:
(1.60 mm) .062" card,
(2.36 mm) .093" card,
HSC8

Cable Mates:
ECDP

10 YEAR MFG WITH 30 µ" GOLD
EXTENDED LIFE PRODUCT
HIGH MATING CYCLES

Mates with (1.60 mm) .062" or (2.36 mm) .093" cards



HIGH-SPEED CHANNEL PERFORMANCE

HSEC8-DV

Rating based on Samtec reference channel. For full SI performance data visit Samtec.com or contact SIG@samtec.com

28 Gbps

MISALIGNMENT MITIGATION



Custom designs compensate for misalignment.

HSEC8 – 1 – POSITIONS PER ROW – CARD THICKNESS – PLATING OPTION – DV – A – OTHER OPTION

POSITIONS PER ROW
09, 10, 13, 20, 25, 30, 37, 40, 49, 50, 60, 70, 80, 100
(13, 25, 49 only available with –L or –L2 option;
09 only available with –L2 option;
37 only available with –L option)

CARD THICKNESS
–01
= (1.60 mm) .062" thick card
–03
= (2.36 mm) .093" thick card

PLATING OPTION
–L
= 10 µ" (0.25 µm) Gold on contact, Matte Tin on tail
–S
= 30 µ" (0.76 µm) Gold on contact, Matte Tin on tail

OTHER OPTION
–K
= (7.01 mm) .276" DIA Polyimide Film Pick & Place Pad; with –01 card,
= (6.25 mm) .246" DIA Polyimide Film Pick & Place Pad; with –03 card
–BL
= Board Locks –01 card only (Weld tab standard)
–L
= Latching Option; –01 card only (13, 25, 37, 49 only) (Weld tab standard)
–L2
= ECDP Latching; –01 card only (09, 13, 25, 49 only) (For use with ECDP) (Weld tab standard)
–WT
= Weld tab
–TR
= Tape & Reel (09 - 70 only)
–FR
= Full Reel Tape & Reel Packaging (Must order max. quantities per reel. Contact Samtec for parts per reel) (09 - 70 only)

CABLE	CONNECTOR
ECDP–04	HSEC8–109–L2
ECDP–08	HSEC8–113–L2
ECDP–16	HSEC8–125–L2
ECDP–32	HSEC8–149–L2

POSITIONS PER ROW	A	B
09*†	(4.50) .177	(11.80) .465
13*†	(6.10) .240	(15.00) .591
25*†	(6.10) .240	(24.60) .969
37†	(18.10) .713	(34.20) 1.346
40	(18.90) .744	(36.60) 1.441
49*†	(22.90) .902	(43.80) 1.724
50	(22.90) .902	(44.60) 1.756
60	(26.90) 1.059	(52.60) 2.071
70†	(26.90) 1.059	(60.60) 2.386
80†	(26.90) 1.059	(68.60) 2.701
100†	(26.90) 1.059	(84.60) 3.331

Positions where no dimensions are given do not have keying feature.
* Mates with ECDP Series.
† Available with –01 Card Only.



09, 13, 25, 37, 100



10, 20 & 30

Notes:
While optimized for 50 Ω applications, this connector with alternative signal/ground patterns may also perform well in certain 75 Ω applications.

Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

All parts within this catalog are built to Samtec's specifications.
Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.