


## FLORENTINA-1-O


~45° + 15° oval beam

### TECHNICAL SPECIFICATIONS:

Dimensions	39.7 mm
Height	13 mm
Fastening	tape
ROHS compliant	yes 

### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
ROSE-CMC-O	Single lens	PC	clear	
FLORENTINA-1-HLD	Holder	PC	black	
ROSE-TAPE	Tape	PU tape	black	











### ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FCA15452_FLORENTINA-1-O	Single lens	840		60	7.9
» Box size: 480 x 280 x 300 mm					





#### PHOTOMETRIC DATA (MEASURED):

<p><b>bridgelux</b></p> <p>LED                    Bridgelux SMD 5050            FWHM                42.0 + 24.0°            Efficiency            71 %            Peak intensity      2 cd/lm            LEDs/each optic    1            Light colour        White            Required components:                      C15427_FLORENTINA-1-SHD-60</p>		
<p><b>CREE</b></p> <p>LED                    XHP35 HD            FWHM                42.0 + 21.0°            Efficiency            71 %            Peak intensity      2.3 cd/lm            LEDs/each optic    1            Light colour        White            Required components:                      C15427_FLORENTINA-1-SHD-60</p>		
<p><b>CREE</b></p> <p>LED                    XHP35 HI            FWHM                28.0°            Efficiency            72 %            Peak intensity      2.7 cd/lm            LEDs/each optic    1            Light colour        White            Required components:</p>		
<p><b>CREE</b></p> <p>LED                    XP-G2            FWHM                44.0 + 18.0°            Efficiency            73 %            Peak intensity      2.8 cd/lm            LEDs/each optic    1            Light colour        White            Required components:                      C15427_FLORENTINA-1-SHD-60</p>		



#### PHOTOMETRIC DATA (MEASURED):





LED XP-L HD  
 FWHM 43.0 + 19.0°  
 Efficiency 71 %  
 Peak intensity 2.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60





LED XP-L2  
 FWHM 43.0 + 20.0°  
 Efficiency 69 %  
 Peak intensity 2.3 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60



LED XT-E  
 FWHM 44.0 + 16.0°  
 Efficiency 71 %  
 Peak intensity 2.9 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60



LED LG 5630  
 FWHM 45.0 + 17.0°  
 Efficiency 77 %  
 Peak intensity 2.9 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C16701\_FLORENTINA-1-SHD-60-WHT






#### PHOTOMETRIC DATA (MEASURED):



##### LG Innotek

LED LG 5630  
 FWHM 45.0 + 16.0°  
 Efficiency 75 %  
 Peak intensity 2.9 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60





##### LUMILEDS

LED LUXEON 3030 2D (Round LES)  
 FWHM 45.0 + 14.0°  
 Efficiency 75 %  
 Peak intensity 3.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





##### LUMILEDS

LED LUXEON 5050 Round LES  
 FWHM 42.0 + 22.0°  
 Efficiency 72 %  
 Peak intensity 2.2 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60











##### LUMILEDS

LED LUXEON TX  
 FWHM 44.0 + 17.0°  
 Efficiency 72 %  
 Peak intensity 2.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60



#### PHOTOMETRIC DATA (MEASURED):


<p><b>NICHIA</b></p> <p>LED NF2x757G            FWHM 45.0 + 15.0°            Efficiency 75 %            Peak intensity 3.2 cd/lm            LEDs/each optic 1            Light colour White            Required components:            C16701_FLORENTINA-1-SHD-60-WHT</p>		
<p><b>NICHIA</b></p> <p>LED NF2x757G            FWHM 44.0 + 15.0°            Efficiency 76 %            Peak intensity 3.3 cd/lm            LEDs/each optic 1            Light colour White            Required components:            C15427_FLORENTINA-1-SHD-60</p>		
<p><b>NICHIA</b></p> <p>LED NVSW319B            FWHM 43.0 + 20.0°            Efficiency 74 %            Peak intensity 2.5 cd/lm            LEDs/each optic 1            Light colour White            Required components:            C15427_FLORENTINA-1-SHD-60</p>		
<p><b>NICHIA</b></p> <p>LED NVSxx19B/NVSxx19C            FWHM 44.0 + 17.0°            Efficiency 72 %            Peak intensity 2.8 cd/lm            LEDs/each optic 1            Light colour White            Required components:            C15427_FLORENTINA-1-SHD-60</p>		

#### PHOTOMETRIC DATA (MEASURED):

#### OSRAM

Opto Semiconductors



LED OSLOM Square CSSRM2/CSSRM3  
 FWHM 44.0 + 17.0°  
 Efficiency 74 %  
 Peak intensity 2.9 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60



#### OSRAM



Opto Semiconductors

LED OSLOM SSL 150  
 FWHM 45.0 + 15.0°  
 Efficiency 72 %  
 Peak intensity 3.3 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60





#### SAMSUNG

LED LM561B  
 FWHM 45.0 + 15.0°  
 Efficiency 75 %  
 Peak intensity 3.1 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60



SEOUL SEMICONDUCTOR

LED SEOUL 5630  
 FWHM 45.0 + 15.0°  
 Efficiency 77 %  
 Peak intensity 3.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60




### PHOTOMETRIC DATA (MEASURED):

 SEOUL SEMICONDUCTOR			
LED	Z8Y22P		
FWHM	44.0 + 17.0°		
Efficiency	69 %		
Peak intensity	2.7 cd/lm		
LEDs/each optic	1		
Light colour	White		
Required components:			
	C15427_FLORENTINA-1-SHD-60		

### PHOTOMETRIC DATA (SIMULATED):



LED XP-G2 HE  
FWHM 42.0 + 22.0°  
Efficiency 82 %  
Peak intensity 2.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
C15427\_FLORENTINA-1-SHD-60





#### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.