

# MMBZ52xxELT1G Series, SZMMBZ52xxELT1G Series

## Zener Voltage Regulators

### 225 mW SOT-23 Surface Mount

This series of Zener diodes is offered in the convenient, surface mount plastic SOT-23 package. These devices are designed to provide voltage regulation with minimum space requirement. They are well suited for applications such as cellular phones, hand held portables, and high density PC boards.

#### Features

- 225 mW Rating on FR-4 or FR-5 Board
- Zener Voltage Range – 2.4 V to 91 V
- Package Designed for Optimal Automated Board Assembly
- Small Package Size for High Density Applications
- ESD Rating of Class 3 (>16 kV) per Human Body Model
- Peak Power – 225 W (8 x 20  $\mu$ s)
- AEC-Q101 Qualified and PPAP Capable
- SZ Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements
- Pb-Free Packages are Available

#### Mechanical Characteristics:

**CASE:** Void-free, transfer-molded, thermosetting plastic case

**FINISH:** Corrosion resistant finish, easily solderable

**MAXIMUM CASE TEMPERATURE FOR SOLDERING PURPOSES:**

260°C for 10 Seconds

**POLARITY:** Cathode indicated by polarity band

**FLAMMABILITY RATING:** UL 94 V-0

#### MAXIMUM RATINGS

| Rating   | Symbol          | Max            | Unit        |
|--|-----------------|----------------|-------------|
| Peak Power Dissipation @ 20 $\mu$ s (Note 1)<br>@ $T_L \leq 25^\circ\text{C}$                              | $P_{pk}$        | 225            | W           |
| Total Power Dissipation on FR-5 Board,<br>(Note 2) @ $T_A = 25^\circ\text{C}$<br>Derated above 25°C        | $P_D$           | 225<br>1.8     | mW<br>mW/°C |
| Thermal Resistance, Junction-to-Ambient  | $R_{\theta JA}$ | 556            | °C/W        |
| Total Power Dissipation on Alumina<br>Substrate, (Note 3) @ $T_A = 25^\circ\text{C}$<br>Derated above 25°C | $P_D$           | 300<br>2.4     | mW<br>mW/°C |
| Thermal Resistance, Junction-to-Ambient  | $R_{\theta JA}$ | 417            | °C/W        |
| Junction and Storage Temperature Range   | $T_J, T_{stg}$  | -65 to<br>+150 | °C          |


Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Nonrepetitive current pulse per Figure 9.
2. FR-5 = 1.0 X 0.75 X 0.62 in.
3. Alumina = 0.4 X 0.3 X 0.024 in., 99.5% alumina.



ON Semiconductor®

<http://onsemi.com>



#### MARKING DIAGRAM



Bxx = Device Code  
xx = (Refer to page 2)  
M = Date Code\*  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation may vary depending upon manufacturing location.

#### ORDERING INFORMATION

| Device          | Package             | Shipping†              |
|-----------------|---------------------|------------------------|
| MMBZ52xxELT1G   | SOT-23<br>(Pb-Free) | 3000 / Tape &<br>Reel  |
| SZMMBZ52xxELT1G | SOT-23<br>(Pb-Free) | 3000 / Tape &<br>Reel  |
| MMBZ52xxELT3G   | SOT-23<br>(Pb-Free) | 10000 / Tape &<br>Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

#### DEVICE MARKING INFORMATION


See specific marking information in the device marking column of the Electrical Characteristics table on page 2 of this data sheet.

## MMBZ52xxELT1G Series, SZMMBZ52xxELT1G Series

### ELECTRICAL CHARACTERISTICS

(Pinout: 1-Anode, 2-No Connection, 3-Cathode) ( $T_A = 25^\circ\text{C}$  unless otherwise noted,  $V_F = 0.95\text{ V Max. @ } I_F = 10\text{ mA}$ )

| Symbol   | Parameter                          |
|----------|------------------------------------|
| $V_Z$    | Reverse Zener Voltage @ $I_{ZT}$   |
| $I_{ZT}$ | Reverse Current                    |
| $Z_{ZT}$ | Maximum Zener Impedance @ $I_{ZT}$ |
| $I_{ZK}$ | Reverse Current                    |
| $Z_{ZK}$ | Maximum Zener Impedance @ $I_{ZK}$ |
| $I_R$    | Reverse Leakage Current @ $V_R$    |
| $V_R$    | Reverse Voltage                    |
| $I_F$    | Forward Current                    |
| $V_F$    | Forward Voltage @ $I_F$            |



### ELECTRICAL CHARACTERISTICS (Pinout: 1-Anode, 2-NC, 3-Cathode) ( $V_F = 0.9\text{ V Max @ } I_F = 10\text{ mA}$ for all types.)

| Device*          | Device Marking | Zener Voltage (Note 4) |     |       |            | Zener Impedance     |                     |      | Leakage Current |     |
|------------------|----------------|------------------------|-----|-------|------------|---------------------|---------------------|------|-----------------|-----|
|                  |                | $V_Z$ (V)              |     |       | @ $I_{ZT}$ | $Z_{ZT}$ @ $I_{ZT}$ | $Z_{ZK}$ @ $I_{ZK}$ |      | $I_R$ @ $V_R$   |     |
|                  |                | Min                    | Nom | Max   | mA         | $\Omega$            | $\Omega$            | mA   | $\mu\text{A}$   | V   |
| MMBZ5221ELT1/T3G | BE2            | 2.28                   | 2.4 | 2.52  | 20         | 30                  | 1200                | 0.25 | 100             | 1   |
| MMBZ5226ELT1/T3G | BE7            | 3.13                   | 3.3 | 3.47  | 20         | 28                  | 1600                | 0.25 | 25              | 1   |
| MMBZ5228ELT1/T3G | BE9            | 3.70                   | 3.9 | 4.10  | 20         | 23                  | 1900                | 0.25 | 10              | 1   |
| MMBZ5229ELT1/T3G | BF1            | 4.08                   | 4.3 | 4.52  | 20         | 22                  | 2000                | 0.25 | 5               | 1   |
| MMBZ5230ELT1/T3G | BF2            | 4.46                   | 4.7 | 4.94  | 20         | 19                  | 1900                | 0.25 | 5               | 2   |
| MMBZ5231ELT1/T3G | BF3            | 4.84                   | 5.1 | 5.36  | 20         | 17                  | 1600                | 0.25 | 5               | 2   |
| MMBZ5232ELT1/T3G | BF4            | 5.32                   | 5.6 | 5.88  | 20         | 11                  | 1600                | 0.25 | 5               | 3   |
| MMBZ5234ELT1/T3G | BF6            | 5.89                   | 6.2 | 6.51  | 20         | 7                   | 1000                | 0.25 | 5               | 4   |
| MMBZ5235ELT1/T3G | BF7            | 6.46                   | 6.8 | 7.14  | 20         | 5                   | 750                 | 0.25 | 3               | 5   |
| MMBZ5236ELT1/T3G | BF8            | 7.12                   | 7.5 | 7.88  | 20         | 6                   | 500                 | 0.25 | 3               | 6   |
| MMBZ5237ELT1/T3G | BF9            | 7.79                   | 8.2 | 8.61  | 20         | 8                   | 500                 | 0.25 | 3               | 6.5 |
| MMBZ5239ELT1/T3G | BG2            | 8.65                   | 9.1 | 9.55  | 20         | 10                  | 600                 | 0.25 | 3               | 7   |
| MMBZ5240ELT1/T3G | BG3            | 9.50                   | 10  | 10.50 | 20         | 17                  | 600                 | 0.25 | 3               | 8   |
| MMBZ5242ELT1/T3G | BG5            | 11.40                  | 12  | 12.60 | 20         | 30                  | 600                 | 0.25 | 1               | 9.1 |
| MMBZ5243ELT1/T3G | BG6            | 12.35                  | 13  | 13.65 | 9.5        | 13                  | 600                 | 0.25 | 0.5             | 9.9 |
| MMBZ5244ELT1/T3G | BG7            | 13.30                  | 14  | 14.70 | 9          | 15                  | 600                 | 0.25 | 0.1             | 10  |
| MMBZ5245ELT1/T3G | BG8            | 14.25                  | 15  | 15.75 | 8.5        | 16                  | 600                 | 0.25 | 0.1             | 11  |
| MMBZ5246ELT1G†   | BG9            | 15.20                  | 16  | 16.80 | 7.8        | 17                  | 600                 | 0.25 | 0.1             | 12  |
| MMBZ5248ELT1/T1G | BH2            | 17.10                  | 18  | 18.90 | 7          | 21                  | 600                 | 0.25 | 0.1             | 14  |
| MMBZ5250ELT1/T3G | BH4            | 19.00                  | 20  | 21.00 | 6.2        | 25                  | 600                 | 0.25 | 0.1             | 15  |

4. Zener voltage is measured with a pulse test current  $I_Z$  at an ambient temperature of  $25^\circ\text{C}$ .

\*Includes SZ-prefix devices where applicable.

†MMBZ5246EL, MMBZ5252EL, and MMBZ5265EL Not Available in 10,000/Tape & Reel.

## MMBZ52xxELT1G Series, SZMMBZ52xxELT1G Series

**ELECTRICAL CHARACTERISTICS** (continued) (Pinout: 1-Anode, 2-NC, 3-Cathode) ( $V_F = 0.9$  V Max @  $I_F = 10$  mA for all types.)

| Device*          | Device Marking | Zener Voltage (Note 5) |     |       |                   | Zener Impedance                   |                                   |      | Leakage Current                 |    |
|------------------|----------------|------------------------|-----|-------|-------------------|-----------------------------------|-----------------------------------|------|---------------------------------|----|
|                  |                | V <sub>Z</sub> (V)     |     |       | @ I <sub>ZT</sub> | Z <sub>ZT</sub> @ I <sub>ZT</sub> | Z <sub>ZK</sub> @ I <sub>ZK</sub> |      | I <sub>R</sub> @ V <sub>R</sub> |    |
|                  |                | Min                    | Nom | Max   | mA                | Ω                                 | Ω                                 | mA   | μA                              | V  |
| MMBZ5252ELT1G†   | BH6            | 22.80                  | 24  | 25.20 | 5.2               | 33                                | 600                               | 0.25 | 0.1                             | 18 |
| MMBZ5253ELT1/T3G | BH7            | 23.75                  | 25  | 26.25 | 5                 | 35                                | 600                               | 0.25 | 0.1                             | 19 |
| MMBZ5254ELT1/T3G | BH8            | 25.65                  | 27  | 28.35 | 4.6               | 41                                | 600                               | 0.25 | 0.1                             | 21 |
| MMBZ5255ELT1/T3G | BH9            | 26.60                  | 28  | 29.40 | 4.5               | 44                                | 600                               | 0.25 | 0.1                             | 21 |
| MMBZ5256ELT1/T3G | BJ1            | 28.50                  | 30  | 31.50 | 4.2               | 49                                | 600                               | 0.25 | 0.1                             | 23 |
| MMBZ5257ELT1/T3G | BJ2            | 31.35                  | 33  | 34.65 | 3.8               | 58                                | 700                               | 0.25 | 0.1                             | 25 |
| MMBZ5258ELT1/T3G | BJ3            | 34.20                  | 36  | 37.80 | 3.4               | 70                                | 700                               | 0.25 | 0.1                             | 27 |
| MMBZ5261ELT1G    | BJ6            | 49.35                  | 47  | 44.65 | 2.7               | 105                               | 1000                              | 0.25 | 0.1                             | 36 |
| MMBZ5262ELT1/T3G | BJ7            | 48.45                  | 51  | 53.55 | 2.5               | 125                               | 1100                              | 0.25 | 0.1                             | 37 |
| MMBZ5263ELT1/T3G | BJ8            | 53.20                  | 56  | 58.80 | 2.2               | 150                               | 1300                              | 0.25 | 0.1                             | 43 |
| MMBZ5265ELT1G†   | BK1            | 58.90                  | 62  | 65.10 | 2                 | 185                               | 1400                              | 0.25 | 0.1                             | 47 |


5. Zener voltage is measured with a pulse test current  $I_Z$  at an ambient temperature of 25°C.

\*Includes SZ-prefix devices where applicable.


†MMBZ5246EL, MMBZ5252EL, and MMBZ5265EL Not Available in 10,000/Tape & Reel.

# MMBZ52xxELT1G Series, SZMMBZ52xxELT1G Series


## TYPICAL CHARACTERISTICS




**Figure 1. Temperature Coefficients**  
(Temperature Range -55°C to +150°C)



**Figure 2. Temperature Coefficients**  
(Temperature Range -55°C to +150°C)



**Figure 3. Effect of Zener Voltage on Zener Impedance**



**Figure 4. Typical Forward Voltage**

# MMBZ52xxELT1G Series, SZMMBZ52xxELT1G Series

## TYPICAL CHARACTERISTICS




Figure 5. Typical Capacitance




Figure 6. Typical Leakage Current




Figure 7. Zener Voltage versus Zener Current ( $V_Z$  Up to 12 V)




Figure 8. Zener Voltage versus Zener Current (12 V to 91 V)





Figure 9.  $8 \times 20 \mu\text{s}$  Pulse Waveform

# MMBZ52xxELT1G Series, SZMMBZ52xxELT1G Series

## PACKAGE DIMENSIONS

SOT-23 (TO-236)  
CASE 318-08  
ISSUE AP



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | MILLIMETERS |      |      | INCHES |       |       |
|-----|-------------|------|------|--------|-------|-------|
|     | MIN         | NOM  | MAX  | MIN    | NOM   | MAX   |
| A   | 0.89        | 1.00 | 1.11 | 0.035  | 0.040 | 0.044 |
| A1  | 0.01        | 0.06 | 0.10 | 0.001  | 0.002 | 0.004 |
| b   | 0.37        | 0.44 | 0.50 | 0.015  | 0.018 | 0.020 |
| c   | 0.09        | 0.13 | 0.18 | 0.003  | 0.005 | 0.007 |
| D   | 2.80        | 2.90 | 3.04 | 0.110  | 0.114 | 0.120 |
| E   | 1.20        | 1.30 | 1.40 | 0.047  | 0.051 | 0.055 |
| e   | 1.78        | 1.90 | 2.04 | 0.070  | 0.075 | 0.081 |
| L   | 0.10        | 0.20 | 0.30 | 0.004  | 0.008 | 0.012 |
| L1  | 0.35        | 0.54 | 0.69 | 0.014  | 0.021 | 0.029 |
| HE  | 2.10        | 2.40 | 2.64 | 0.083  | 0.094 | 0.104 |
| θ   | 0°          | ---  | 10°  | 0°     | ---   | 10°   |

STYLE 8:

1. ANODE
2. NO CONNECTION
3. CATHODE

### SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** orderlit@onsemi.com

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local Sales Representative



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.