

## Sensor/Actuator cable - SAC-8P-10,0-542/ FR SH SCO BK - 1406084

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Sensor/Actuator cable, 8-position, PVC, yellow, shielded, Free cable end, on Socket angled M12-SPEEDCON, A-coded, Cable length: 10 m



### Key commercial data

|                      |                                                                                                         |
|----------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit         | 1 PCE                                                                                                   |
| GTIN                 | <br>4 046356 799638 |
| Custom tariff number | 85444290                                                                                                |
| Country of origin    | UNITED STATES                                                                                           |

### Technical data

#### Dimensions

|                 |      |
|-----------------|------|
| Length of cable | 10 m |
|-----------------|------|

#### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |
| Degree of protection            | IP65                             |
|                                 | IP67                             |

#### General

|                       |                                       |
|-----------------------|---------------------------------------|
| Rated current at 40°C | 2 A                                   |
| Rated voltage         | 30 V                                  |
| Number of positions   | 8                                     |
| Contact resistance    | ≤ 5 mΩ                                |
| Insulation resistance | ≥ 100 MΩ                              |
| Standards/regulations | M12 plug-in connector IEC 61076-2-101 |
| Coding                | A - standard                          |

## Sensor/Actuator cable - SAC-8P-10,0-542/ FR SH SCO BK - 1406084

### Technical data

#### General

|                             |                                             |
|-----------------------------|---------------------------------------------|
| Surge voltage category      | II                                          |
| Pollution degree            | 3                                           |
| Insertion/withdrawal cycles | ≥ 100                                       |
| Torque                      | 0.4 Nm (M12 plug-in connector)              |
| Contact material            | CuZn                                        |
| Contact surface material    | Ni/Au                                       |
| Contact carrier material    | TPU GF                                      |
| Material of grip body       | TPU, hardly inflammable, self-extinguishing |
| Material, knurls            | Zinc die-cast, nickel-plated                |
| Sealing material            | NBR                                         |
| Status display              | No                                          |

#### Line characteristics

|                                               |                                                    |
|-----------------------------------------------|----------------------------------------------------|
| Cable type                                    | PVC yellow 105 °C                                  |
| Cable type (abbreviation)                     | 542                                                |
| UL AWM style                                  | 2517 (105°C/300 V)                                 |
| AWG signal line                               | 24                                                 |
| Core diameter including insulation            | 1.12 mm ±0.03 mm                                   |
| Wire colors                                   | white, brown, green, yellow, gray, pink, blue, red |
| Overall twist                                 | 8 wires around filler to the core                  |
| Shielding                                     | Tinned copper braided shield                       |
| Optical shield covering                       | 85 %                                               |
| External sheath, color                        | yellow                                             |
| External cable diameter D                     | 6.3 mm ± 0.2 mm                                    |
| Minimum bending radius, flexible installation | 12 x D                                             |
| Cable weight                                  | 58 kg/km                                           |
| Outer sheath, material                        | PVC                                                |
| Material, filler                              | PP                                                 |
| Material conductor insulation                 | PVC                                                |
| Conductor material                            | Tin-plated Cu litz wires                           |
| Nominal voltage, cabel                        | 300 V                                              |
| Other resistance                              | UV resistant                                       |
| Ambient temperature (operation)               | -30 °C ... 105 °C (cable, fixed installation)      |

### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060306 |
|------------|----------|

## Sensor/Actuator cable - SAC-8P-10,0-542/ FR SH SCO BK - 1406084

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.1 | 27060306 |
| eCl@ss 5.0 | 27061801 |
| eCl@ss 5.1 | 27061801 |
| eCl@ss 6.0 | 27061801 |
| eCl@ss 7.0 | 27061801 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001855 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC001855 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |

### Approvals

#### Approvals

#### Approvals

UL Listed / cUL Listed / cULus Listed

#### Ex Approvals

#### Approvals submitted

#### Approval details

|                                                                                               |     |
|-----------------------------------------------------------------------------------------------|-----|
| UL Listed  |     |
| Nominal current I <sub>N</sub>                                                                | 2 A |

## Sensor/Actuator cable - SAC-8P-10,0-542/ FR SH SCO BK - 1406084

### Approvals

|                    |      |
|--------------------|------|
| Nominal voltage UN | 30 V |
|--------------------|------|

|                                                                                              |      |
|----------------------------------------------------------------------------------------------|------|
| cUL Listed  |      |
| Nominal current IN                                                                           | 2 A  |
| Nominal voltage UN                                                                           | 30 V |

|                                                                                                |  |
|------------------------------------------------------------------------------------------------|--|
| cULus Listed  |  |
|------------------------------------------------------------------------------------------------|--|

### Accessories

#### Accessories

##### Fuse

Fuse clip - SAC-M12-EXCLIP-F - 1558991



Fuse clip for the socket side of various M12 sensor/actuator connectors prevents plug-in connections being interrupted without using a tool

### Marking

Insert label - PABA WH/15 - 1013151



Insert label, Strip, white, Unlabeled, Can be labeled with: Plotter, Mounting type: Thread on, Cable diameter: 0.6-50 mm, Lettering field: 15 x 4 mm

## Sensor/Actuator cable - SAC-8P-10,0-542/ FR SH SCO BK - 1406084

### Accessories

#### Insert label - PABA YE/15 - 1013698



Insert label, Strip, yellow, Unlabeled, Can be labeled with: Plotter, Mounting type: Thread on, Cable diameter: 0.6-50 mm, Lettering field: 15 x 4 mm

---

#### Insert label - PABA RD/15 - 1013944



Insert label, Strip, red, Unlabeled, Can be labeled with: Plotter, Mounting type: Thread on, Cable diameter: 0.6-50 mm, Lettering field: 15 x 4 mm

---

#### Conductor marker carrier - PATG 2/15 - 1013038



Conductor marker carrier, transparent, Unlabeled, Mounting type: Slide on, Cable diameter: 2-4 mm, Lettering field: 4 x 15 mm

---

#### Conductor marker carrier - PATG 3/15 - 1013041



Conductor marker carrier, transparent, Unlabeled, Mounting type: Slide on, Cable diameter: 4-7 mm, Lettering field: 4 x 15 mm

---

#### Conductor marker carrier - PATG 4/15 - 1013054



Conductor marker carrier, transparent, Unlabeled, Mounting type: Slide on, Cable diameter: 6-10 mm, Lettering field: 4 x 15 mm

## Sensor/Actuator cable - SAC-8P-10,0-542/ FR SH SCO BK - 1406084

### Accessories

Marker pen - B-STIFT - 1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

---

### Protection and sealing elements

Screw plug - PROT-M12 MS-PA-CHAIN - 1430899

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



---

### Tools

Cable-cutting tool - CUTFOX-S VDE - 1212207



Diagonal cutter for copper and aluminum conductors, VDE-tested

---

Stripping tool - WIREFOX SAC - 1212623



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

---

Stripping tool - WIREFOX 10 - 1212150



Stripping tool, for cables and conductors from 0.02 - 10 mm<sup>2</sup>, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm<sup>2</sup> stranded/1.5 mm<sup>2</sup> solid, replaceable stripping blade

## Sensor/Actuator cable - SAC-8P-10,0-542/ FR SH SCO BK - 1406084

### Accessories

---

Torque screwdriver - TSD 04 SAC - 1208429



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

---

Torque screwdriver - TSD-M 1,2NM - 1212224



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

---

Adapter insert - TSD-M SAC-BIT ADAPTER - 1212600



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

---

Tool - SAC BIT M12-D15 - 1208432




Nut for assembling sensor/actuator cables with M12 connector and for M12 connectors with QUICKON fast connection technology, for 4 mm hexagonal drive

---

### Drawings


## Sensor/Actuator cable - SAC-8P-10,0-542/ FR SH SCO BK - 1406084

Schematic diagram




Pin assignment M12 socket, 8-pos., A-coded, view female side

Dimensioned drawing



M12 x 1 socket, angled, shielded

Circuit diagram



Contact assignment of the M12 socket



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.