Audio Transformer

PC Mount

T Y - 1 4 2 P



Description:

These transformers operate in the 200 Hz to 15,000 Hz range, making them suitable for a broad application spectrum in the audio industry. These devices are used in line matching, telephone coupling, pulse trigger, driver, interstage, output, isolation and input applications.

Operating Temperature Range: 0º C to 105º C

Electrical Specifications at 25º C:

1. Primary Impedance:	10000Ω CT + 15% with 600Ω load
2. Secondary Impedance:	2000Ω CT
3. Output:	100mW
4. Primary DC Unbalance:	4 Ma
5. Frequency Response:	± 2db from 200 to 15,000 Hz
6. Impedance Matching:	10% over full frequency range
7. Longitudinal Balance	> 45db
8. Insertion Loss @ 1K Hz:	< 1.5db
9. Return Loss:	> 26db
10. Total Harmonic Distortion	< 0.5% between 275Hz and3.5KHz
11. DCR:	
Primary (1-3)	750Ω Nominal
Secondary (4-6)	217Ω Nominal
12. Turns Ratio:	2.24 : 1
13. Dielectric Strength	1500V Pri to Sec to Core

Construction:

Bobbin has plug-in terminals which are spaced to provide fixed mounting centers. Pins are a rugged .042" square, minimizing the incidence of bent pins from handling.

Outline Dimensions:

A. Dimensions: As figures show
B. PIN DIM. : .0375" x .020"
C. Weight. : 0.51 oz.



Schematic:



RoHS Compliance: As of manufacturing date February 2005, all standardproducts meet the requirements of 2002/95/EC, known as the RoHS initiative.

*Upon printing, this document is considered "uncontrolled".Please contact Triad Magnetics' website for the most current version.

web:www.TriadMagnetics.com
Phone 951-277-0757
Fax 951-277-2757

22520B Temescal Canyon Road
Corona ,California
92883

Publish Date: June 20, 2006

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.

Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.