





PRODUCT NO.  
10074141-001LF  
10074141-003LF



PIN DEFINITION




| ESATA | NAME | TYPE |
|-------|------|------|
| P1    | GND  |      |
| P2    | A+   |      |
| P3    | A-   |      |
| P4    | GND  |      |
| P5    | B-   |      |
| P6    | B+   |      |
| P7    | GND  |      |

RECOMMEND P.C. BOARD LAYOUT  
PCB TOLERANCE:±0.05

| mat'l. code | 14        | surface | sg         | tolerance | projection | product family |
|-------------|-----------|---------|------------|-----------|------------|----------------|
| lfr         | ecp no    | dr      | date       | ISO 1302  | ISO 406    | ISO 101        |
| A           | 107-1074S | LNK     | 2007-05-23 | angles    | .XX±0.38   | MM             |
| B           | 108-1082S | LNK     | 2008-04-28 | linear    | .XX±0.25   | MM             |
| C           | 110-0184S | LNK     | 2010-12-14 | 0°±2°     | .XXX±0.100 | scale 2:1      |
| D           | 100544QS  | LNK     | 2011-08-31 | STERLING  | LNK        | 2007-05-21     |
| E           | 100544QS  | LNK     | 2011-10-17 | ENG       | LNK        | 2016-03-03     |
| F           | 100544QS  | LNK     | 2012-06-08 | CH        | LNK        | 2016-03-03     |
| G           | 100544QS  | LNK     | 2016-03-03 | PP        | LNK        | 2016-03-03     |
| sheet       | revision  | G       | G          | 107       | 109        | 111            |
| index       | sheet     | 1       | 2          | 3         | 106        | 108            |
|             |           |         |            |           | 110        | 112            |
|             |           |         |            |           | 114        | 116            |
|             |           |         |            |           | 118        | 120            |
|             |           |         |            |           | 122        | 124            |
|             |           |         |            |           | 126        | 130            |
|             |           |         |            |           | 132        | 134            |
|             |           |         |            |           | 136        | 138            |

NOTES:  
1. MATERIAL: HOUSING-THERMAL/PLASTIC HIGH TEMP WITH 30% G/F UL94 V-0  
CONTACT-SOLDER ALLOY  
SHELL/BOARD LOCK COPPER ALLOY  
2. FINISH: 500" MIN. MATT TIN PLATING ON SOLDER TAILS  
SHELL/BOARD LOCK:50" MIN. NICKEL PLATING OVER ALL  
3. THE HOUSING WILL WITHSTAND TO 260C FOR 10 SEC  
IN A WAVE SOLDER APPLICATION WITH A 1.6MM PCB  
4. PRODUCT SPEC : GS-12-386  
5. PACKING SPEC : GS-14-1109  
6. PRODUCT NUMBERING:  
10074141-0 0 X X LF LEAD FREE  
7. A SYMBOL Δ WILL BE NEXT TO ANY DIMENSION, VIEW OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION


PDFfill PDF Editor with Free Writer and Tools



PIN DEFINITION

| NAME | TYPE |
|------|------|
| P1   | GND  |
| P2   | A+   |
| P3   | A-   |
| P4   | GND  |
| P5   | B-   |
| P6   | B+   |
| P7   | GND  |





PDFFill PDF Editor with Free Writer and Tools



P.C. BOARD MOUNTING DIMENSIONS T=1.60mm  
PCB TOLERANCE: ±0.05

- NOTES:
1. MATERIAL:  
HOUSING: THERMAL PLASTIC HIGH TEMP WITH 30% G/F UL94 V-0  
CONTACT: COPPER ALLOY  
SHELL: BOARD LOCK: COPPER ALLOY  
COLOR: BLACK
  2. FINISH:  
CONTACT: GOLD PLATING ON CONTACT AREA  
100μ" MIN. WATT TIN PLATING ON SOLDERMATS  
50μ" MIN. NICKEL UNDERPLATING OVER ALL  
BOARD LOCK: 50μ" MIN. WATT TIN PLATING OVER ALL  
SHELL/BOARD LOCK: 50μ" MIN. NICKEL PLATING OVER ALL  
3. SOLDER APPLICATION: 100μ" MIN. WATT TIN PLATING OVER ALL  
N/A WIRE SOLDER APPLICATION WITH A 1.0MM PCB
  4. PRODUCT SPEC: GS-12-386
  5. PRODUCT SPEC: GS-14-1109
  6. A SYMBOL Δ WILL BE NEXT TO ANY DIMENSION, VIEW OR NOTE, WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION

| mat'l. code | 14         | surface | sg         | tolerance                             | projection                                                          | product family | 533                          |
|-------------|------------|---------|------------|---------------------------------------|---------------------------------------------------------------------|----------------|------------------------------|
| lfr         | ecn no     | dr      | date       | ISO 1302                              | ISO 406                                                             | ISO 101        | 101                          |
| A           | 107-1074S  | LNK     | 2007-05-23 | tolerances unless otherwise specified | .XX±0.38                                                            | MM             |                              |
| B           | 108-1082S  | LNK     | 2008-04-28 | linear                                | .XX±0.25                                                            | MM             |                              |
| C           | 110-0184S  | LNK     | 2010-12-14 | 0°±2°                                 | .XXX±0.100                                                          | scale 2:1      |                              |
| D           | 1-00544QS  | LNK     | 2011-08-31 | STERLING                              | LNK                                                                 | 2007-05-21     |                              |
| E           | EX-5-0078H | HKL     | 2011-10-17 | ENG                                   | HKLIM                                                               | 2016-03-03     |                              |
| F           | EX-5-0118H | HKL     | 2012-06-08 | CH                                    | HKLIM                                                               | 2016-03-03     |                              |
| G           | EX-5-240H  | HKL     | 2016-03-03 | QPP                                   | KPTAY                                                               | 2016-03-03     |                              |
| sheet       | revision   | G       | G          | G                                     | 107 109 111 113 115 117 119 121 123 125 127 129 131 133 135 137 139 | type           | PRODUCT-CUSTOMER.DRW Drawing |
| index       | sheet      | 1       | 2          | 3                                     | 106 108 110 112 114 116 118 120 122 124 126 128 130 132 134 136 138 | sheet no       | 10074141                     |
|             |            |         |            |                                       |                                                                     | sheet 2 of 3   | size A3                      |



PIN DEFINITION

| ESATA | NAME | TYPE |
|-------|------|------|
| P1    | GND  |      |
| P2    | A+   |      |
| P3    | A-   |      |
| P4    | GND  |      |
| P5    | B-   |      |
| P6    | B+   |      |
| P7    | GND  |      |

P.C. BOARD MOUNTING DIMENSIONS T=1.60mm

PCB TOLERANCE: ±0.05

PDFill PDF Editor with Free Writer and Tools

| mat'l. code | 14            | surface    | ISO 1302                              | ISO 406    | ISO 101 | projection              | product family                          | 533 |
|-------------|---------------|------------|---------------------------------------|------------|---------|-------------------------|-----------------------------------------|-----|
| lfr         | ecn no        | date       | tolerances unless otherwise specified |            |         |                         |                                         |     |
| A           | 107-1074S.LIN | 2007-05-23 | angles                                | .XX±0.38   |         | MM                      | E-SATA_UP_RIGHT                         |     |
| B           | 108-1082S.LIN | 2008-04-28 | linear                                | .XX±0.25   |         |                         | DIP_TYPE                                |     |
| C           | 110-0184S.LIN | 2010-12-14 | 0°±2°                                 | .XXX±0.100 |         | scale 2:1               |                                         |     |
| D           | 1-00544QS.LIN | 2011-08-31 | STERLING.LIN                          | 2007-05-21 |         |                         |                                         |     |
| E           | EX-S-007881   | 2011-10-17 | ENG                                   | 2016-03-03 |         |                         |                                         |     |
| F           | EX-S-011878   | 2012-06-08 | CH                                    | 2016-03-03 |         |                         |                                         |     |
| G           | EX-S-23409    | 2016-03-03 | QPP                                   | 2016-03-03 |         |                         |                                         |     |
| sheet       | revision      | 1          | 2                                     | 3          | 107 109 | 111 113 115 117 119     | 121 123 125 127 129 131 133 135 137 139 | 141 |
| index       | sheet         | G          | G                                     | G          | 106 108 | 110 112 114 116 118 120 | 122 124 126 128 130 132 134 136 138     |     |

- NOTES:
1. MATERIAL: THERMOPLASTIC HIGH TEMP WITH 30% G/F UL94 V-0
  2. FINISH: CONTRACT GOLD PLATING ON CONTACT AREA
  3. THE HOUSING WILL WITHSTAND TO 260C FOR 10 SEC IN A WAVE SOLDER APPLICATION WITH A 1.5MM PCB
  4. PRODUCT SPEC : 05-12-386
  5. PACKING SPEC : 05-14-1109
  6. A SYMBOL  $\Delta$  WILL BE NEXT TO ANY DIMENSION, VIEW OR NOTE, WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION

- 1: 15μ" GOLD PLATING  
2: 6μ" GOLD PLATING
- PACKING: TRAY PACKING  
BLANK: TRAY PACKING
- 2: LEAD FREE



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.