



RADIAL LEAD ALUMINUM ELECTROLYTIC CAPACITORS

ZLJ


ZLJ SERIES

UPGRADE

105°C High Ripple Current, Long Life, Low Impedance

•Load Life : 105°C 6000~10000 hours.

RoHS Compliance




◆SPECIFICATIONS

Item	Characteristics																																																																			
Category Temperature Range	-40~+105°C																																																																			
Rated Voltage Range	6.3~100Vdc																																																																			
Capacitance Tolerance	±20% (20°C, 120Hz)																																																																			
Leakage Current (MAX)	I=0.01CV or 3 μ A whichever is greater. (After 2 minutes) I=Leakage Current (μ A) C=Capacitance (μ F) V=Rated Voltage (Vdc)																																																																			
Dissipation Factor (MAX)	<table border="1"> <thead> <tr> <th>(Vdc) Rated Voltage</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>80</th> <th>100</th> <th>(20°C, 120Hz)</th> </tr> </thead> <tbody> <tr> <td>tan δ</td> <td>0.22</td> <td>0.19</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> <td>0.10</td> <td>0.09</td> <td>0.08</td> <td>0.08</td> <td></td> </tr> </tbody> </table> <p>When capacitance is over 1000μF, tanδ shall be added 0.02 to the listed value with increase of every 1000μF.</p>	(Vdc) Rated Voltage	6.3	10	16	25	35	50	63	80	100	(20°C, 120Hz)	tan δ	0.22	0.19	0.16	0.14	0.12	0.10	0.09	0.08	0.08																																														
(Vdc) Rated Voltage	6.3	10	16	25	35	50	63	80	100	(20°C, 120Hz)																																																										
tan δ	0.22	0.19	0.16	0.14	0.12	0.10	0.09	0.08	0.08																																																											
Endurance	<p>After applying rated voltage with rated ripple current for specified time at 105°C, the capacitors shall meet the following requirements.</p> <table border="1"> <thead> <tr> <th rowspan="2">Capacitance Change</th> <th rowspan="2">Within ±25% of the initial value. (6.3Vdc, 10Vdc: ±30%)</th> <th rowspan="2">Dissipation Factor</th> <th rowspan="2">Not more than 200% of the specified value.</th> <th rowspan="2">Leakage Current</th> <th rowspan="2">Not more than the specified value.</th> <th colspan="3">Life Time (hrs)</th> </tr> <tr> <th>Case Size</th> <th>6.3Vdc</th> <th>10~50Vdc</th> <th>63~100Vdc</th> </tr> </thead> <tbody> <tr> <td>φD ≤ 6.3</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>6000</td> <td>7000</td> <td>6000</td> </tr> <tr> <td>8X11.5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>8000</td> <td>9000</td> <td>8000</td> </tr> <tr> <td>10X12.5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>9000</td> <td>9000</td> <td>9000</td> </tr> <tr> <td>8X16, 8X20</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>9000</td> <td>10000</td> <td>9000</td> </tr> <tr> <td>10X16, 10X20, 10X25</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="3">10000</td> </tr> <tr> <td>φD ≥ 12.5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="3"></td> </tr> </tbody> </table>	Capacitance Change	Within ±25% of the initial value. (6.3Vdc, 10Vdc: ±30%)	Dissipation Factor	Not more than 200% of the specified value.	Leakage Current	Not more than the specified value.	Life Time (hrs)			Case Size	6.3Vdc	10~50Vdc	63~100Vdc	φD ≤ 6.3						6000	7000	6000	8X11.5						8000	9000	8000	10X12.5						9000	9000	9000	8X16, 8X20						9000	10000	9000	10X16, 10X20, 10X25						10000			φD ≥ 12.5								
Capacitance Change	Within ±25% of the initial value. (6.3Vdc, 10Vdc: ±30%)							Dissipation Factor	Not more than 200% of the specified value.	Leakage Current	Not more than the specified value.	Life Time (hrs)																																																								
		Case Size	6.3Vdc	10~50Vdc	63~100Vdc																																																															
φD ≤ 6.3						6000	7000	6000																																																												
8X11.5						8000	9000	8000																																																												
10X12.5						9000	9000	9000																																																												
8X16, 8X20						9000	10000	9000																																																												
10X16, 10X20, 10X25						10000																																																														
φD ≥ 12.5																																																																				
Low Temperature Stability Impedance Ratio (MAX)	<table border="1"> <thead> <tr> <th>Rated Voltage (Vdc)</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>80</th> <th>100</th> <th>(20°C, 120Hz)</th> </tr> </thead> <tbody> <tr> <td>Z(-25°C)/Z(20°C)</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td></td> </tr> <tr> <td>Z(-40°C)/Z(20°C)</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td></td> </tr> </tbody> </table>	Rated Voltage (Vdc)	6.3	10	16	25	35	50	63	80	100	(20°C, 120Hz)	Z(-25°C)/Z(20°C)	2	2	2	2	2	2	2	2	2		Z(-40°C)/Z(20°C)	3	3	3	3	3	3	3	3	3																																			
Rated Voltage (Vdc)	6.3	10	16	25	35	50	63	80	100	(20°C, 120Hz)																																																										
Z(-25°C)/Z(20°C)	2	2	2	2	2	2	2	2	2																																																											
Z(-40°C)/Z(20°C)	3	3	3	3	3	3	3	3	3																																																											

◆MULTIPLIER FOR RIPPLE CURRENT

Frequency (Hz)		120	1k	10k	100k ≤
Coefficient	8.2~39 μ F	0.42	0.70	0.90	1.00
	47~270 μ F	0.50	0.73	0.92	1.00
	330~680 μ F	0.55	0.77	0.94	1.00
	820~1800 μ F	0.60	0.80	0.96	1.00
	2200~8200 μ F	0.70	0.85	0.98	1.00

◆DIMENSIONS (mm)



φD	5	6.3	8	10	12.5	16	18
φd	0.5		0.6			0.8	
F	2.0	2.5	3.5	5.0		7.5	
α	L ≤ 16: α = 1.5						L ≥ 20: α = 2.0

◆PART NUMBER

□□□	ZLJ	□□□□□	M	□□□	□□□	D X L
Rated Voltage	Series	Capacitance	Capacitance Tolerance	Option	Lead Forming	Case Size

*Specifications subject to change without notice.



RADIAL LEAD ALUMINUM ELECTROLYTIC CAPACITORS

ZLJ

◆STANDARD SIZE

Rated Voltage (Vdc)	Capacitance (μF)	Size φDXL(mm)	Rated ripple current (mAr.m.s./105°C, 100kHz)	Impedance (Ω MAX)	
				20°C,100kHz	-10°C,100kHz
6.3	220	5X11	345	0.4	1.2
	470	6.3X11	540	0.17	0.51
	820	8X11.5	945	0.075	0.23
	1000	8X16	1250	0.059	0.18
	1200	10X12.5	1330	0.053	0.16
	1500	8X20	1500	0.041	0.13
	1800	10X16	1760	0.038	0.12
	2700	10X20	1960	0.028	0.084
	3300	10X25	2250	0.024	0.072
	3900	12.5X20	2480	0.025	0.075
	4700	12.5X25	2900	0.019	0.057
	5600	12.5X30	3450	0.018	0.054
	6800	12.5X35	3570	0.016	0.048
	6800	16X20	3250	0.021	0.063
8200	16X25	3630	0.017	0.051	
10	150	5X11	450	0.4	1.2
	330	6.3X11	700	0.17	0.51
	560	8X11.5	1200	0.075	0.23
	680	8X16	1600	0.059	0.18
	820	10X12.5	1700	0.053	0.16
	1000	8X20	1960	0.041	0.13
	1200	10X16	2000	0.038	0.12
	1800	10X20	2500	0.028	0.084
	2200	10X25	2900	0.024	0.072
	2700	12.5X20	2600	0.025	0.075
	3300	12.5X25	3200	0.019	0.057
	4700	12.5X30	3660	0.018	0.054
	4700	16X20	3330	0.021	0.063
	5600	12.5X35	4120	0.016	0.048
5600	16X25	3810	0.017	0.051	
16	120	5X11	450	0.4	1.2
	270	6.3X11	700	0.17	0.51
	470	8X11.5	1200	0.075	0.23
	560	8X16	1600	0.059	0.18
	680	8X16	1600	0.059	0.18
	680	10X12.5	1700	0.053	0.16
	820	8X20	1960	0.041	0.13
	1000	8X20	1960	0.041	0.13
	1000	10X16	2000	0.038	0.12
	1500	10X20	2500	0.028	0.084
	1800	10X25	2900	0.024	0.072
	2200	12.5X20	2600	0.025	0.075
	2700	12.5X25	3200	0.019	0.057
	3300	12.5X30	3660	0.018	0.054
3300	16X20	3330	0.021	0.063	
3900	12.5X35	4120	0.016	0.048	
4700	16X25	3810	0.017	0.051	
25	68	5X11	450	0.4	1.2
	150	6.3X11	700	0.17	0.51
	330	8X11.5	1200	0.075	0.23
	390	8X16	1600	0.059	0.18
	470	10X12.5	1700	0.053	0.16
	560	8X20	1960	0.041	0.13
	680	10X16	2000	0.038	0.12
	1000	10X20	2500	0.028	0.084
	1200	10X25	2900	0.024	0.072
	1500	12.5X20	2600	0.025	0.075
	1800	12.5X25	3200	0.019	0.057
	2200	12.5X30	3660	0.018	0.054
	2200	16X20	3330	0.021	0.063
	2700	12.5X35	4120	0.016	0.048
3300	16X25	3810	0.017	0.051	
35	47	5X11	450	0.4	1.2
	100	6.3X11	700	0.17	0.51
	180	8X11.5	1200	0.075	0.23
	220	8X16	1600	0.059	0.18
	220	10X16	1760	0.038	0.12

Rated Voltage (Vdc)	Capacitance (μF)	Size φDXL(mm)	Rated ripple current (mAr.m.s./105°C, 100kHz)	Impedance (Ω MAX)		
				20°C,100kHz	-10°C,100kHz	
35	270	8X16	1600	0.059	0.18	
	270	10X12.5	1700	0.053	0.16	
	330	8X20	1960	0.041	0.13	
	330	10X12.5	1700	0.053	0.16	
	390	8X20	1960	0.041	0.13	
	390	10X16	2000	0.038	0.12	
	470	10X16	2000	0.038	0.12	
	560	10X20	2500	0.028	0.084	
	680	10X25	2900	0.024	0.072	
	820	12.5X20	2600	0.025	0.075	
	1000	12.5X20	2600	0.025	0.075	
	1200	12.5X25	3200	0.019	0.057	
	1500	12.5X30	3660	0.018	0.054	
	1500	16X20	3330	0.021	0.063	
	1800	12.5X35	4120	0.016	0.048	
	1800	16X25	3810	0.017	0.051	
	50	27	5X11	310	0.48	1.5
		56	6.3X11	500	0.22	0.66
100		8X11.5	950	0.12	0.36	
120		8X11.5	1300	0.11	0.33	
120		8X16	1230	0.082	0.25	
150		10X12.5	1280	0.073	0.22	
180		8X16	1700	0.081	0.24	
180		8X20	1580	0.058	0.18	
220		10X12.5	1700	0.071	0.21	
220		10X16	1650	0.053	0.16	
270		8X20	2100	0.058	0.17	
330		10X16	2100	0.052	0.16	
330		10X20	2060	0.038	0.12	
390		10X25	2420	0.032	0.1	
470		10X20	2500	0.037	0.11	
470		12.5X16	2200	0.04	0.12	
470		12.5X20	2300	0.03	0.1	
560		10X25	2900	0.031	0.093	
680		12.5X20	2700	0.029	0.087	
680		12.5X25	2800	0.025	0.08	
820		12.5X30	3370	0.023	0.074	
820		16X20	3070	0.026	0.084	
1000		12.5X25	3000	0.022	0.066	
1000		12.5X30	3500	0.02	0.06	
1000	12.5X35	3810	0.021	0.067		
1000	16X25	3510	0.022	0.07		
1200	12.5X35	4000	0.017	0.051		
1200	16X20	3100	0.023	0.069		
1500	12.5X40	4500	0.019	0.057		
1500	16X25	3600	0.018	0.054		
1500	18X20	3200	0.029	0.087		
2200	16X31.5	4100	0.018	0.054		
2200	18X25	3700	0.022	0.066		
2700	16X35.5	4400	0.016	0.048		
2700	16X40	4800	0.014	0.042		
2700	18X31.5	4200	0.019	0.057		
3300	18X35.5	4600	0.016	0.048		
3900	18X40	5000	0.014	0.042		
63	18	5X11	240	0.71	3.2	
	47	6.3X11	420	0.28	1.3	
	82	8X11.5	720	0.18	0.79	
	100	8X11.5	1000	0.13	0.39	
	100	8X16	990	0.13	0.58	
	120	8X16	1300	0.095	0.29	
	120	10X12.5	990	0.11	0.44	
	150	8X20	1200	0.096	0.43	
	150	10X12.5	1300	0.08	0.24	
	180	8X20	1600	0.069	0.21	
180	10X16	1200	0.076	0.31		
220	10X16	1700	0.058	0.17		

*Specifications subject to change without notice.



RADIAL LEAD ALUMINUM ELECTROLYTIC CAPACITORS

ZLJ

◆STANDARD SIZE

Rated Voltage (Vdc)	Capacitance (μF)	Size φDXL(mm)	Rated ripple current (mAr.m.s./105°C, 100kHz)	Impedance (Ω MAX)	
				20°C,100kHz	-10°C,100kHz
63	270	10X20	1570	0.056	0.23
	270	12.5X16	1570	0.072	0.27
	330	10X20	2000	0.042	0.13
	330	10X25	1990	0.046	0.19
	330	12.5X16	1900	0.045	0.14
	390	10X25	2400	0.035	0.11
	390	12.5X20	1990	0.041	0.13
	470	12.5X20	2400	0.033	0.099
	470	12.5X25	2460	0.031	0.093
	560	12.5X30	2760	0.028	0.084
	560	16X20	2380	0.032	0.096
	680	12.5X25	2800	0.025	0.075
	680	12.5X35	3040	0.024	0.072
	820	12.5X30	3200	0.022	0.066
	820	16X20	2900	0.025	0.075
	820	16X25	2890	0.025	0.075
	1000	12.5X35	3500	0.018	0.054
	1000	16X25	3200	0.02	0.06
	1200	12.5X40	3800	0.021	0.063
	1200	18X20	3000	0.032	0.096
	1500	16X31.5	3500	0.02	0.06
	1500	18X25	3200	0.024	0.072
1800	16X35.5	3800	0.017	0.051	
1800	18X31.5	3700	0.02	0.06	
2200	16X40	4100	0.015	0.045	
2200	18X35.5	3900	0.017	0.051	
2700	18X40	4300	0.015	0.045	
80	●12	5X11	235	0.72	3.2 NEW
	12	5X11	220	1.2	5.4
	●27	6.3X11	390	0.34	1.5 NEW
	27	6.3X11	370	0.46	2.1
	●47	8X11.5	650	0.2	0.9 NEW
	47	8X11.5	620	0.29	1.3
	56	8X16	780	0.2	0.9
	68	10X12.5	780	0.17	0.66
	82	8X16	820	0.14	0.63 NEW
	82	8X20	1040	0.16	0.66
	100	10X12.5	860	0.14	0.56 NEW
	100	10X16	1040	0.11	0.47
	120	8X20	1090	0.12	0.54 NEW
	150	10X16	1150	0.09	0.36 NEW
	150	10X20	1430	0.084	0.34
	150	12.5X16	1430	0.11	0.34
	180	10X25	1620	0.069	0.28
	220	10X20	1570	0.068	0.28 NEW
	220	12.5X16	1430	0.09	0.27 NEW
	220	12.5X20	1750	0.062	0.18
	270	10X25	1780	0.055	0.22 NEW
	270	12.5X25	2210	0.047	0.14
	330	12.5X20	1800	0.048	0.15 NEW
	330	12.5X30	2400	0.042	0.13
	330	16X20	1950	0.048	0.15
	390	12.5X25	2210	0.038	0.12 NEW
	390	12.5X35	2600	0.036	0.11
	470	12.5X30	2520	0.033	0.11 NEW
	470	12.5X40	2860	0.032	0.095
	470	16X20	2150	0.036	0.12 NEW
	470	16X25	2430	0.038	0.12
	470	18X20	2270	0.045	0.14
560	12.5X35	2860	0.026	0.078 NEW	
560	16X31.5	2640	0.032	0.095	
680	12.5X40	3150	0.026	0.078 NEW	
680	16X25	2620	0.028	0.084 NEW	
680	18X20	2280	0.032	0.096 NEW	
680	18X20	2280	0.032	0.096 NEW	
680	16X35.5	2860	0.029	0.086 NEW	
680	18X20	2280	0.032	0.096 NEW	
680	16X35.5	2860	0.029	0.086 NEW	
680	18X25	2500	0.036	0.11	

Rated Voltage (Vdc)	Capacitance (μF)	Size φDXL(mm)	Rated ripple current (mAr.m.s./105°C, 100kHz)	Impedance (Ω MAX)	
				20°C,100kHz	-10°C,100kHz
80	820	16X31.5	2900	0.022	0.066 NEW
	820	16X40	3510	0.027	0.081
	820	18X31.5	2860	0.03	0.09
	1000	16X35.5	3150	0.02	0.06 NEW
	1000	18X25	2750	0.027	0.081 NEW
	1000	18X35.5	3510	0.027	0.081
	1200	16X40	3710	0.018	0.054 NEW
	1200	18X31.5	3150	0.02	0.06 NEW
	1200	18X40	3860	0.026	0.076
	1500	18X35.5	3710	0.018	0.054 NEW
	1800	18X40	4060	0.017	0.051 NEW
	●8.2	5X11	235	0.72	3.2 NEW
	8.2	5X11	220	1.2	5.4
	●18	6.3X11	390	0.34	1.5 NEW
	18	6.3X11	370	0.46	2.1
	●33	8X11.5	650	0.2	0.9 NEW
	33	8X11.5	620	0.29	1.3
	●47	8X16	820	0.14	0.63 NEW
	47	8X16	780	0.2	0.9
	●56	10X12.5	860	0.14	0.56 NEW
	56	10X12.5	780	0.17	0.66
	●68	8X20	1090	0.12	0.54 NEW
68	8X20	1040	0.16	0.66	
●82	10X16	1150	0.09	0.36 NEW	
82	10X16	1040	0.11	0.47	
100	10X20	1430	0.084	0.34	
100	12.5X16	1430	0.11	0.34	
120	10X20	1570	0.068	0.28 NEW	
120	10X25	1620	0.069	0.28	
120	12.5X16	1430	0.09	0.27 NEW	
150	10X25	1780	0.055	0.22 NEW	
150	12.5X20	1750	0.062	0.18	
180	12.5X20	1800	0.048	0.15 NEW	
●220	12.5X25	2210	0.038	0.12 NEW	
220	12.5X25	2210	0.047	0.14	
●270	12.5X30	2520	0.033	0.11 NEW	
270	12.5X30	2400	0.042	0.13	
270	16X20	1950	0.048	0.15	
330	12.5X35	2600	0.036	0.11	
330	16X20	2150	0.036	0.12 NEW	
390	12.5X35	2860	0.026	0.078 NEW	
390	12.5X40	2860	0.032	0.095	
●390	16X25	2620	0.028	0.084 NEW	
390	16X25	2430	0.038	0.12	
●390	18X20	2280	0.032	0.096 NEW	
390	18X20	2270	0.045	0.14	
470	12.5X40	3150	0.026	0.078 NEW	
470	16X31.5	2640	0.032	0.095	
470	18X25	2500	0.036	0.11	
560	16X31.5	2900	0.022	0.066 NEW	
560	16X35.5	2860	0.029	0.086	
560	18X25	2750	0.027	0.081 NEW	
560	18X31.5	2860	0.03	0.09	
680	16X35.5	3150	0.02	0.06 NEW	
680	16X40	3510	0.027	0.081	
680	18X31.5	3150	0.02	0.06 NEW	
680	18X35.5	3510	0.027	0.081	
820	16X40	3710	0.018	0.054 NEW	
820	18X35.5	3710	0.018	0.054 NEW	
820	18X40	3860	0.026	0.076	
1000	18X40	4060	0.017	0.051 NEW	

● : OPTION has EFU.

*Specifications subject to change without notice.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Rubycon:

[100ZLJ100M10X20](#) [100ZLJ100M12.5X16](#) [100ZLJ120M10X25](#) [100ZLJ150M12.5X20](#) [100ZLJ18M6.3X11](#)
[100ZLJ220M12.5X25](#) [80ZLJ680M18X25](#) [80ZLJ68M10X12.5](#) [80ZLJ820M16X40](#) [80ZLJ820M18X31.5](#) [80ZLJ82M8X20](#)
[80ZLJ470M16X25](#) [80ZLJ470M18X20](#) [80ZLJ47M8X11.5](#) [80ZLJ560M16X31.5](#) [80ZLJ56M8X16](#) [80ZLJ680M16X35.5](#)
[80ZLJ270M12.5X25](#) [80ZLJ27M6.3X11](#) [80ZLJ330M12.5X30](#) [80ZLJ330M16X20](#) [80ZLJ390M12.5X35](#)
[80ZLJ470M12.5X40](#) [80ZLJ1200M18X40](#) [80ZLJ12M5X11](#) [80ZLJ150M10X20](#) [80ZLJ150M12.5X16](#) [80ZLJ180M10X25](#)
[80ZLJ220M12.5X20](#) [63ZLJ820M12.5X30](#) [63ZLJ820M16X20](#) [63ZLJ820M16X25](#) [63ZLJ82M8X11.5](#)
[80ZLJ1000M18X35.5](#) [80ZLJ100M10X16](#) [63ZLJ470M12.5X25](#) [63ZLJ47M6.3X11](#) [63ZLJ560M12.5X30](#)
[63ZLJ560M16X20](#) [63ZLJ680M12.5X25](#) [63ZLJ680M12.5X35](#) [63ZLJ330M10X20](#) [63ZLJ330M10X25](#)
[63ZLJ330M12.5X16](#) [63ZLJ390M10X25](#) [63ZLJ390M12.5X20](#) [63ZLJ470M12.5X20](#) [63ZLJ2200M16X40](#)
[63ZLJ2200M18X35.5](#) [63ZLJ220M10X16](#) [63ZLJ2700M18X40](#) [63ZLJ270M10X20](#) [63ZLJ270M12.5X16](#)
[63ZLJ150M8X20](#) [63ZLJ1800M16X35.5](#) [63ZLJ1800M18X31.5](#) [63ZLJ180M10X16](#) [63ZLJ180M8X20](#) [63ZLJ18M5X11](#)
[63ZLJ1200M18X20](#) [63ZLJ120M10X12.5](#) [63ZLJ120M8X16](#) [63ZLJ1500M16X31.5](#) [63ZLJ1500M18X25](#)
[63ZLJ150M10X12.5](#) [6.3ZLJ820M8X11.5](#) [63ZLJ1000M12.5X35](#) [63ZLJ1000M16X25](#) [63ZLJ100M8X11.5](#)
[63ZLJ100M8X16](#) [63ZLJ1200M12.5X40](#) [6.3ZLJ4700M12.5X25](#) [6.3ZLJ470M6.3X11](#) [6.3ZLJ5600M12.5X30](#)
[6.3ZLJ6800M12.5X35](#) [6.3ZLJ6800M16X20](#) [6.3ZLJ8200M16X25](#) [6.3ZLJ1500M8X20](#) [6.3ZLJ1800M10X16](#)
[6.3ZLJ220M5X11](#) [6.3ZLJ2700M10X20](#) [6.3ZLJ3300M10X25](#) [6.3ZLJ3900M12.5X20](#) [50ZLJ680M12.5X20](#)
[50ZLJ680M12.5X25](#) [50ZLJ820M12.5X30](#) [50ZLJ820M16X20](#) [6.3ZLJ1000M8X16](#) [6.3ZLJ1200M10X12.5](#)
[50ZLJ390M10X25](#) [50ZLJ470M10X20](#) [50ZLJ470M12.5X16](#) [50ZLJ470M12.5X20](#) [50ZLJ560M10X25](#) [50ZLJ56M6.3X11](#)
[50ZLJ270M8X20](#) [50ZLJ27M5X11](#) [50ZLJ3300M18X35.5](#) [50ZLJ330M10X16](#) [50ZLJ330M10X20](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.