




## Hyperfast Rectifier, 15 A FRED Pt®



### FEATURES

- Hyperfast recovery time, extremely low  $Q_{rr}$
- Low forward voltage drop
- 175 °C operating junction temperature
- Low leakage current
- Designed and qualified according to JEDEC®-JESD 47
- Meets MSL level 1, per J-STD-020, LF maximum peak of 245 °C
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

### DESCRIPTION / APPLICATIONS

State of the art hyperfast recovery rectifiers designed with optimized performance of forward voltage drop, hyperfast recover time, and soft recovery.

The planar structure and the platinum doped life time control guarantee the best overall performance, ruggedness and reliability characteristics.

These devices are intended for use in PFC Boost stage in the AC/DC section of SMPS, inverters or as freewheeling diodes.

The extremely optimized stored charge and low recovery current minimize the switching losses and reduce over dissipation in the switching element and snubbers.

### PRIMARY CHARACTERISTICS

|                       |   |
|-----------------------|---|
| $I_{F(AV)}$           | 15 A                                    |
| $V_R$                 | 600 V                                   |
| $V_F$ at $I_F$        | 1.55 V                                  |
| $t_{rr}$ (typ.)       | 18 ns                                   |
| $T_J$ max.            | 175 °C                                  |
| Package               | D <sup>2</sup> PAK (TO-263AB), TO-262AA |
| Circuit configuration | Single                                  |

### ABSOLUTE MAXIMUM RATINGS

| PARAMETER                                   | SYMBOL         | TEST CONDITIONS       | MAX.        | UNITS |
|---|----------------|-----------------------|-------------|-------|
| Repetitive peak reverse voltage             | $V_{RRM}$      |                       | 600         | V     |
| Average rectified forward current           | $I_{F(AV)}$    | $T_C = 127\text{ °C}$ | 15          | A     |
| Non-repetitive peak surge current           | $I_{FSM}$      | $T_C = 25\text{ °C}$  | 120         |       |
| Operating junction and storage temperatures | $T_J, T_{Stg}$ |                       | -65 to +175 | °C    |

### ELECTRICAL SPECIFICATIONS ( $T_J = 25\text{ °C}$ unless otherwise specified)

| PARAMETER                           | SYMBOL        | TEST CONDITIONS   | MIN. | TYP.        | MAX.      | UNITS         |
|-------------------------------------|---------------|---|------|-------------|-----------|---------------|
| Breakdown voltage, blocking voltage | $V_{BR}, V_R$ | $I_R = 100\text{ }\mu\text{A}$                                  | 600  | -           | -         | V             |
| Forward voltage                     | $V_F$         | $I_F = 15\text{ A}$<br>$I_F = 15\text{ A}, T_J = 150\text{ °C}$ | -    | 2.5<br>1.55 | 3.4<br>2  |               |
| Reverse leakage current             | $I_R$         | $V_R = V_R$ rated<br>$T_J = 150\text{ °C}, V_R = V_R$ rated     | -    | 0.02<br>40  | 36<br>250 | $\mu\text{A}$ |
| Junction capacitance                | $C_T$         | $V_R = 600\text{ V}$  | -    | 12          | -         | pF            |
| Series inductance                   | $L_S$         | Measured lead to lead 5 mm from package body                    | -    | 8.0         | -         | nH            |



| DYNAMIC RECOVERY CHARACTERISTICS (T <sub>J</sub> = 25 °C unless otherwise specified) |                  |  |   |      |      |       |    |
|--|------------------|--|---|------|------|-------|----|
| PARAMETER  | SYMBOL           | TEST CONDITIONS  | MIN.  | TYP. | MAX. | UNITS |    |
| Reverse recovery time  | t <sub>rr</sub>  | I <sub>F</sub> = 1 A, di <sub>F</sub> /dt = 100 A/μs, V <sub>R</sub> = 30 V  | -   | 17   | 23   | ns    |    |
|  |                  | I <sub>F</sub> = 15 A, di <sub>F</sub> /dt = 100 A/μs, V <sub>R</sub> = 30 V | -   | 18   | 30   |       |    |
|  |                  | T <sub>J</sub> = 25 °C   | -   | 20   | -    |       |    |
|  |                  | T <sub>J</sub> = 125 °C  | -   | 45   | -    |       |    |
| Peak recovery current  | I <sub>RRM</sub> | T <sub>J</sub> = 25 °C   | -   | 2.7  | -    | A     |    |
|  |                  | T <sub>J</sub> = 125 °C  | -   | 5.5  | -    |       |    |
| Reverse recovery charge  | Q <sub>rr</sub>  | T <sub>J</sub> = 25 °C   | -   | 26   | -    | nC    |    |
|  |                  | T <sub>J</sub> = 125 °C  | -   | 130  | -    |       |    |
| Reverse recovery time  | t <sub>rr</sub>  | T <sub>J</sub> = 125 °C  | I <sub>F</sub> = 15 A<br>di <sub>F</sub> /dt = 800 A/μs<br>V <sub>R</sub> = 390 V | -    | 32   | -     | ns |
| Peak recovery current  | I <sub>RRM</sub> |  |   | -    | 17   | -     | A  |
| Reverse recovery charge  | Q <sub>rr</sub>  |  |   | -    | 290  | -     | nC |

| THERMAL - MECHANICAL SPECIFICATIONS            |                                   |   |                |  |            |                        |
|--|-----------------------------------|---|----------------|--|------------|------------------------|
| PARAMETER                                      | SYMBOL                            | TEST CONDITIONS                             | MIN.           | TYP.                                     | MAX.       | UNITS                  |
| Maximum junction and storage temperature range | T <sub>J</sub> , T <sub>Stg</sub> |   | -65            | -  | 175        | °C                     |
| Thermal resistance, junction to case           | R <sub>thJC</sub>                 |   | -              | 1.3                                      | 1.51       | °C/W                   |
| Thermal resistance, junction to ambient        | R <sub>thJA</sub>                 | Typical socket mount                        | -              | -  | 70         |                        |
| Thermal resistance, case to heatsink           | R <sub>thCS</sub>                 | Mounting surface, flat, smooth, and greased | -              | 0.5                                      | -          |                        |
| Weight   |                                   |   | -              | 2.0                                      | -          | g                      |
|  |                                   |   | -              | 0.07                                     | -          | oz.                    |
| Mounting torque                                |                                   |   | 6<br>(5)       | -  | 12<br>(10) | kgf · cm<br>(lbf · in) |
|  |                                   |   | Marking device | Case style D <sup>2</sup> PAK (TO-263AB) | ETX1506S   |                        |
|  |                                   | Case style TO-262                           | ETX1506-1      |  |            |                        |




Fig. 1 - Typical Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage




Fig. 4 - Max. Thermal Impedance  $Z_{thJC}$  Characteristics




Fig. 5 - Maximum Allowable Case Temperature vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Typical Reverse Recovery vs.  $di_F/dt$





Fig. 8 - Typical Stored Charge vs.  $di_F/dt$



(1)  $di_F/dt$  - rate of change of current through zero crossing

(2)  $I_{RRM}$  - peak reverse recovery current

(3)  $t_{rr}$  - reverse recovery time measured from zero crossing point of negative going  $I_F$  to point where a line passing through  $0.75 I_{RRM}$  and  $0.50 I_{RRM}$  extrapolated to zero current.

(4)  $Q_{rr}$  - area under curve defined by  $t_{rr}$  and  $I_{RRM}$


$$Q_{rr} = \frac{t_{rr} \times I_{RRM}}{2}$$

(5)  $di_{(rec)M}/dt$  - peak rate of change of current during  $t_b$  portion of  $t_{rr}$

Fig. 9 - Reverse Recovery Waveform and Definitions



## ORDERING INFORMATION TABLE




- 1** - Vishay Semiconductors product
- 2** - Circuit configuration  
E = single diode
- 3** - T = TO-220
- 4** - X = hyperfast recovery time
- 5** - Current code (15 = 15 A)
- 6** - Voltage code (06 = 600 V)
- 7** - • S = D<sup>2</sup>PAK (TO-263AB)  
• -1 = TO-262AA
- 8** - • None = tube (50 pieces)  
• TRL = tape and reel (left oriented, for D<sup>2</sup>PAK (TO-263AB) package)  
• TRR = tape and reel (right oriented, for D<sup>2</sup>PAK (TO-263AB) package)
- 9** - -M3 = halogen-free, RoHS-compliant and terminations lead (Pb)-free

| ORDERING INFORMATION (Example) |                   |                        |                         |
|--------------------------------|-------------------|------------------------|-------------------------|
| PREFERRED P/N                  | QUANTITY PER TUBE | MINIMUM ORDER QUANTITY | PACKAGING DESCRIPTION   |
| VS-ETX1506S-M3                 | 50                | 1000                   | Antistatic plastic tube |
| VS-ETX1506-1-M3                | 50                | 1000                   | Antistatic plastic tube |
| VS-ETX1506STRR-M3              | 800               | 800                    | 13" diameter reel       |
| VS-ETX1506STRL-M3              | 800               | 800                    | 13" diameter reel       |

| LINKS TO RELATED DOCUMENTS |                               |  |
|----------------------------|-------------------------------|--|
| Dimensions                 | D <sup>2</sup> PAK (TO-263AB) | <a href="http://www.vishay.com/doc?96164">www.vishay.com/doc?96164</a> |
|                            | TO-262AA                      | <a href="http://www.vishay.com/doc?96165">www.vishay.com/doc?96165</a> |
| Part marking information   | D <sup>2</sup> PAK (TO-263AB) | <a href="http://www.vishay.com/doc?95444">www.vishay.com/doc?95444</a> |
|                            | TO-262AA                      | <a href="http://www.vishay.com/doc?95443">www.vishay.com/doc?95443</a> |
| Packaging information      | D <sup>2</sup> PAK (TO-263AB) | <a href="http://www.vishay.com/doc?96424">www.vishay.com/doc?96424</a> |



## TO-262



Example: This is a xxxxxx-1 <sup>(1)</sup> with assembly lot code AC, assembled on WW 19, 2001 in the assembly line "X"


### Note

<sup>(1)</sup> If part number contain "H" as last digit, product is AEC-Q101 qualified

| ENVIRONMENTAL NAMING CODE (Z) | PRODUCT DEFINITION  |
|-------------------------------|---|
| A                             | Termination lead (Pb)-free                                  |
| B                             | Totally lead (Pb)-free                                      |
| E                             | RoHS-compliant and termination lead (Pb)-free               |
| F                             | RoHS-compliant and totally lead (Pb)-free                   |
| M                             | Halogen-free, RoHS-compliant and termination lead (Pb)-free |
| N                             | Halogen-free, RoHS-compliant and totally lead (Pb)-free     |
| G                             | Green   |



## D<sup>2</sup>PAK



Example: This is a xxxxxx <sup>(1)</sup> with assembly lot code AC, assembled on WW 02, 2010

### Note

<sup>(1)</sup> If part number contain "H" as last digit, product is AEC-Q101 qualified

| ENVIRONMENTAL NAMING CODE (Z) | PRODUCT DEFINITION   |
|-------------------------------|--|
| A                             | Termination lead (Pb)-free                                   |
| B                             | Totally lead (Pb)-free                                       |
| E                             | RoHS-compliant and termination lead (Pb)-free                |
| F                             | RoHS-compliant and totally lead (Pb)-free                    |
| M                             | Halogen-free, RoHS-compliant, and termination lead (Pb)-free |
| N                             | Halogen-free, RoHS-compliant, and totally lead (Pb)-free     |
| G                             | Green  |

### D<sup>2</sup>PAK

**DIMENSIONS** in millimeters and inches

Conforms to JEDEC<sup>®</sup> outline D<sup>2</sup>PAK (SMD-220)



| SYMBOL | MILLIMETERS |       | INCHES |       | NOTES | SYMBOL | MILLIMETERS |       | INCHES    |       | NOTES |
|--------|-------------|-------|--------|-------|-------|--------|-------------|-------|-----------|-------|-------|
|        | MIN.        | MAX.  | MIN.   | MAX.  |       |        | MIN.        | MAX.  | MIN.      | MAX.  |       |
| A      | 4.06        | 4.83  | 0.160  | 0.190 |       | D1     | 6.86        | 8.00  | 0.270     | 0.315 | 3     |
| A1     | 0.00        | 0.254 | 0.000  | 0.010 |       | E      | 9.65        | 10.67 | 0.380     | 0.420 | 2, 3  |
| b      | 0.51        | 0.99  | 0.020  | 0.039 |       | E1     | 7.90        | 8.80  | 0.311     | 0.346 | 3     |
| b1     | 0.51        | 0.89  | 0.020  | 0.035 | 4     | e      | 2.54 BSC    |       | 0.100 BSC |       |       |
| b2     | 1.14        | 1.78  | 0.045  | 0.070 |       | H      | 14.61       | 15.88 | 0.575     | 0.625 |       |
| b3     | 1.14        | 1.73  | 0.045  | 0.068 | 4     | L      | 1.78        | 2.79  | 0.070     | 0.110 |       |
| c      | 0.38        | 0.74  | 0.015  | 0.029 |       | L1     | -           | 1.65  | -         | 0.066 | 3     |
| c1     | 0.38        | 0.58  | 0.015  | 0.023 | 4     | L2     | 1.27        | 1.78  | 0.050     | 0.070 |       |
| c2     | 1.14        | 1.65  | 0.045  | 0.065 |       | L3     | 0.25 BSC    |       | 0.010 BSC |       |       |
| D      | 8.51        | 9.65  | 0.335  | 0.380 | 2     | L4     | 4.78        | 5.28  | 0.188     | 0.208 |       |

**Notes**


- (1) Dimensioning and tolerancing per ASME Y14.5 M-1994
- (2) Dimension D and E do not include mold flash. Mold flash shall not exceed 0.127 mm (0.005") per side. These dimensions are measured at the outmost extremes of the plastic body
- (3) Thermal pad contour optional within dimension E, L1, D1 and E1
- (4) Dimension b1 and c1 apply to base metal only
- (5) Datum A and B to be determined at datum plane H
- (6) Controlling dimension: inches
- (7) Outline conforms to JEDEC<sup>®</sup> outline TO-263AB



### TO-262AA

**DIMENSIONS** in millimeters and inches

Modified JEDEC® outline TO-262



| SYMBOL | MILLIMETERS |       | INCHES    |       | NOTES |
|--------|-------------|-------|-----------|-------|-------|
|        | MIN.        | MAX.  | MIN.      | MAX.  |       |
| A      | 4.06        | 4.83  | 0.160     | 0.190 |       |
| A1     | 2.03        | 3.02  | 0.080     | 0.119 |       |
| b      | 0.51        | 0.99  | 0.020     | 0.039 |       |
| b1     | 0.51        | 0.89  | 0.020     | 0.035 | 4     |
| b2     | 1.14        | 1.78  | 0.045     | 0.070 |       |
| b3     | 1.14        | 1.73  | 0.045     | 0.068 | 4     |
| c      | 0.38        | 0.74  | 0.015     | 0.029 |       |
| c1     | 0.38        | 0.58  | 0.015     | 0.023 | 4     |
| c2     | 1.14        | 1.65  | 0.045     | 0.065 |       |
| D      | 8.51        | 9.65  | 0.335     | 0.380 | 2     |
| D1     | 6.86        | 8.00  | 0.270     | 0.315 | 3     |
| E      | 9.65        | 10.67 | 0.380     | 0.420 | 2, 3  |
| E1     | 7.90        | 8.80  | 0.311     | 0.346 | 3     |
| e      | 2.54 BSC    |       | 0.100 BSC |       |       |
| L      | 13.46       | 14.10 | 0.530     | 0.555 |       |
| L1     | -           | 1.65  | -         | 0.065 | 3     |
| L2     | 3.56        | 3.71  | 0.140     | 0.146 |       |

**Notes**

- (1) Dimensioning and tolerancing as per ASME Y14.5M-1994
- (2) Dimension D and E do not include mold flash. Mold flash shall not exceed 0.127 mm (0.005") per side. These dimensions are measured at the outmost extremes of the plastic body
- (3) Thermal pad contour optional within dimension E, L1, D1 and E1
- (4) Dimension b1 and c1 apply to base metal only
- (5) Controlling dimension: inches
- (6) Outline conform to JEDEC® TO-262 except A1 (max.), b (min., max.), b1 (min.), b2 (max.), c (min.), c1(min.), c2 (max.), D (min.), E (max.), L1 (max.), L2 (min., max.)



# D<sup>2</sup>PAK (TO-263AB)


## CARRIER TAPE FOR TAPE AND REEL LEFT in millimeters



### Note

(1) For dimensions, see next pages

## CARRIER TAPE FOR TAPE AND REEL RIGHT in millimeters




### Note


(1) For dimensions, see next pages



### REEL FOR CARRIER TAPE in millimeters




### CARRIER TAPE AND REEL PACKAGING D<sup>2</sup>PAK (TO-263AB)





### COVER TAPE FOR CARRIER TAPE in millimeters



| APPLICATION                      | COVER TAPE WIDTH<br>W | COVER TAPE THICKNESS<br>T | CARRIER TAPE WIDTH | MATERIAL                                 |
|----------------------------------|-----------------------|---------------------------|--------------------|--|
| D <sup>2</sup> PAK<br>(TO-263AB) | 21.3 ± 0.1            | 0.060 ± 0.01              | 24                 | Antistatic/treated/transparent/polyester |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.