

3M™ Mini D Ribbon (MDR) Cable Assembly

.050" High Speed Digital Data Transmission System - 26 Position

14X26-SZLB-XXX-0LC



- Supports Industrial CameraLink™ in Automated Imaging Association for camera to frame grabber communications
- 11 shielded twin-ax pairs and four drain wires
- Entire cable bundle is shielded with foil and braid for additional signal protection
- Rugged MDR ribbon type contact
- Rugged thumbscrew retention
- EMI shielded junction shell in either plastic or overmolded construction
- See the Regulatory Information Appendix (RIA) in the “RoHS compliance” section of www.3Mconnector.com for compliance information (RIA E1 & C1 apply)

Date Modified: May 18, 2011

TS-1001-C
Sheet 1 of 4

Physical

Connector Contact Plating

Wiping Area: 30 μ " [0.76 μ m] Min. Gold

Shell Color: Beige

Shell Material: Overmold Option: Polyvinyl Chloride (PVC);
Shell Kit Option: Polyester Elastomer

Cable Color: Beige

Cable Jacket Material: Polyvinyl Chloride (PVC)

Cable Flammability: AWM VW-1

Electrical

Voltage Rating: 30 V

Current Rating: 1 A

Insulation Resistance: $> 1 \times 10^8 \Omega$ at @ 100 V_{DC}

Withstanding Voltage: 350 V_{rms} for 1 minute

Individually Shielded Twisted Pairs

Characteristic Impedance: 100 \pm 10 Ω

Conductor Size: 28 AWG Stranded

Propagation Velocity: 1.25 ns/ft [4.1 ns/m]

Skew (within pair): 50 ps/meter maximum

Skew (channel skew per chipset): 50 ps/meter maximum

Environmental

Temperature Rating: -20°C to +75°C

UL File No.: E86982

CameraLink is a trademark of the Automated Imaging Association.

3M™ Mini D Ribbon (MDR) Cable Assembly

.050" High Speed Digital Data Transmission System - 26 Position

14X26-SZLB-XXX-0LC

Discrete #4 - 40 Thumbscrew Shell Kit



Overmold #4 - 40 Thumbscrew Shell



mm
[Inch]

| Tolerance Unless Noted | | |
|------------------------|-----|------|
| | 0.0 | 0.00 |
| mm | ±.1 | ±.01 |

[] Dimensions for Reference only



| Assembly Length Tolerance | |
|---------------------------|------------------|
| Cable Length | Tolerance |
| 0.5 to 1.5 meters | -0 + .05 meters |
| 2 to 10 meters | -0 +3% of length |

TS-1001-C
Sheet 2 of 4

3M™ Mini D Ribbon (MDR) Cable Assembly

.050" High Speed Digital Data Transmission System - 26 Position

14X26-SZLB-XXX-0LC

mm
[Inch]

| Tolerance Unless Noted | | |
|------------------------|-----|------|
| | 0.0 | 0.00 |
| mm | ±.1 | ±.01 |

[] Dimensions for Reference only



Generic End Detail
MDR 26 Position Plug
(Both Ends)



| Shell Option (see ordering information) | Dimensions | |
|--|------------------|-----------------|
| | B | C |
| T = Overmold #4-40 Thumbscrew Shell | 40.2 [1.58] | 14.0 [.55] |
| B = Discrete #4-40 Thumbscrew Shell Kit | 39.4 [1.55] | 12.8 [.51] |

Ordering Information

14X26-SZLB-XXX-0LC

Shell Retention Options:

B = Discrete #4-40 Thumbscrew shell kit

T = Overmold #4-40 Thumbscrew shell

Length:

| | |
|------------------|------------------|
| 050 = 0.5 meters | 450 = 4.5 meters |
| 100 = 1 meters | 500 = 5 meters |
| 150 = 1.5 meters | 600 = 6 meters |
| 200 = 2 meters | 700 = 7 meters |
| 250 = 2.5 meters | 800 = 8 meters |
| 300 = 3 meters | 900 = 9 meters |
| 350 = 3.5 meters | A00 = 10 meters |
| 400 = 4 meters | |

TS-1001-C
Sheet 3 of 4

3M™ Mini D Ribbon (MDR) Cable Assembly

.050" High Speed Digital Data Transmission System - 26 Position

14X26-SZLB-XXX-0LC

| Cable Assembly and Camera Link Pinouts | | | | | | |
|--|-------------------------|---------------------|-----------------------------|---|-------------------------|---------------------|
| Medium and Full Configurations | | | | Base Configuration | | |
| Two Channel Link Chips | | | | One Channel Link Chip + Camera Control + Serial Communication | | |
| Camera Connector | Frame Grabber Connector | Channel Link Signal | Cable Name (Reference only) | Camera Connector | Frame Grabber Connector | Channel Link Signal |
| 1 | 1 | inner shield | inner shield | 1 | 1 | inner shield |
| 14 | 14 | inner shield | inner shield | 14 | 14 | inner shield |
| 2 | 25 | Y0- | Pair 1- | 2 | 25 | X0- |
| 15 | 12 | Y0+ | Pair 1+ | 15 | 12 | X0+ |
| 3 | 24 | Y1- | Pair 2- | 3 | 24 | X1- |
| 16 | 11 | Y1+ | Pair 2+ | 16 | 11 | X1+ |
| 4 | 23 | Y2- | Pair 3- | 4 | 23 | X2- |
| 17 | 10 | Y2+ | Pair 3+ | 17 | 10 | X2+ |
| 5 | 22 | Yclk- | Pair 4- | 5 | 22 | Xclk- |
| 18 | 9 | Yclk+ | Pair 4+ | 18 | 9 | Xclk+ |
| 6 | 21 | Y3- | Pair 5- | 6 | 21 | X3- |
| 19 | 8 | Y3+ | Pair 5+ | 19 | 8 | X3+ |
| 7 | 20 | 100 ohm | Pair 6+ | 7 | 20 | SerTC+ |
| 20 | 7 | terminated | Pair 6- | 20 | 7 | SerTC- |
| 8 | 19 | Z0- | Pair 7- | 8 | 19 | SerTFG- |
| 21 | 6 | Z0+ | Pair 7+ | 21 | 6 | SerTFG+ |
| 9 | 18 | Z1- | Pair 8- | 9 | 18 | CC1- |
| 22 | 5 | Z1+ | Pair 8+ | 22 | 5 | CC1+ |
| 10 | 17 | Z2- | Pair 9+ | 10 | 17 | CC2+ |
| 23 | 4 | Z2+ | Pair 9- | 23 | 4 | CC2- |
| 11 | 16 | Zclk- | Pair 10- | 11 | 16 | CC3- |
| 24 | 3 | Zclk+ | Pair 10+ | 24 | 3 | CC3+ |
| 12 | 15 | Z3- | Pair 11+ | 12 | 15 | CC4+ |
| 25 | 2 | Z3+ | Pair 11- | 25 | 2 | CC4- |
| 13 | 13 | inner shield | inner shield | 13 | 13 | inner shield |
| 26 | 26 | inner shield | inner shield | 26 | 26 | inner shield |

Notes:

1. All pairs are individually shielded with aluminum foil.
2. Pair shields are wrapped aluminum out and are in contact with four internal drains (logic ground).
3. Outer braid and foil (chassis ground) are isolated from inner drains (logic ground).
4. Cable assembly compatible with Camera Link Base, Medium and Full configurations.

TS-1001-C
Sheet 4 of 4

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

**3M Electronics Solutions Division**

6801 River Place Blvd.
Austin, TX 78726-9000
U.S.A.
1-800-225-5373
www.3Mconnector.com

Please recycle. Printed in USA.
© 3M 2010. All rights reserved.
RIA-2217B-E

3M is a trademark of 3M Company.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.