

NOTES:

1. MATERIALS AND FINISHES:
BODY - BeCu, GOLD PLATING
CONTACT - BeCu, GOLD PLATING
INSULATOR - PTFE , NATURAL

2. ELECTRICAL:
A. IMPEDANCE: 50 OHM
B. FREQUENCY RANGE: DC - 26.5 GHz
C. VSWR(RETURN LOSS): 35 dB MIN @ DC - 4 GHz
26 dB MIN @ 4 - 10 GHz
25 dB MIN @ 10 - 26.5 GHz
D. DIELECTRIC WITHSTANDING VOLTAGE: 500 VRMS, MIN.

3. MECHANICAL:
A. DURABILITY:
SMA SIDE: 500 CYCLES MIN.
SMP SIDE: 100 MATING CYCLES MIN. WHEN MATED WITH FULL DETENT JACK
500 MATING CYCLES MIN. WHEN MATED WITH LIMITED DETENT JACK
1000 MATING CYCLES MIN. WHEN MATED WITH SMOOTH BORE JACK
B. TEMPERATURE RANGE: -65° C TO +165° C

4. PACKAGING:
A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL RF, AD-SMAJSMPP-2 & DATE CODE"

THIRD ANGLE PROJ.

REVISIONS

REV	DESCRIPTION	DATE	ECN	APPR
A	RELEASE TO MFG.	31-Jul-19	12436	SV

SCALE 4.000

1/4-36UNS-2A

5.50 [7/32"] HEX.

INTERFACE PER MIL-STD-348 SERIES: SMA JACK

4.7 [.185]

15.16 [.597]

2.95 [.116]

INTERFACE PER MIL-STD-348 SERIES: SMP PLUG

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: <0.5mm ± 0.05mm 0.5 - 6mm ±0.1mm 6 - 30mm ±0.2mm 30 - 120mm ± 0.3mm ANGLES ±1° NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	MATERIAL SEE NOTES	DRAWN M. ZHANG	DATE 31-Jul-19	TITLE SMA (F) JACK TO SMP (F) PLUG ADAPTER	Amphenol RF www.amphenolrf.com	
	REFERENCE	ENGINEER S. VO	DATE 19-Feb-19			
	EAR# 8842	APPROVED S. HSIEH	DATE 05-Aug-19			
	REF: --	CAD FILE		SCALE: 16.0:1.0	SHEET 2 OF 2	DRAWING NO. AD-SMAJSMPP-2
	CONFIGURATION LEVEL: In Work			DWG SIZE B	REV A	ITEM NO. AD-SMAJSMPP-2
		FINISH				PART NO. AD-SMAJSMPP-2



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.