




#### FEATURES

Metallized Polypropylene - High Capacitance - Low ESR

#### APPLICATIONS

Switching Power Supplies - UPS - DC Link - Motor Speed Controls - Solar Heaters - Power Converters

|  |                            |   |            |                                 |  |                                      |            |
|--|----------------------------|---|------------|---------------------------------|--|--------------------------------------|------------|
| <b>Operating Temperature Range</b>   |                            | <b>-40°C to +100°C</b><br>Above +85°C applied voltage must be de-rated by 1.5%/°C             |            |                                 |  |                                      |            |
| <b>Capacitance Tolerance</b>   |                            | ±10% at 1 kHz, 25°C<br>±5% optional   |            |                                 |  |                                      |            |
| <b>Surge Voltage</b>   | <b>VDC</b>                 | <b>250</b>  | <b>330</b> | <b>400</b>                      | <b>600</b>   | <b>700</b>                           | <b>850</b> |
|  | <b>Non-repetitive SVDC</b> | 400   | 400        | 600                             | 800  | 1000                                 | 1200       |
| <b>AC voltage</b>  | <b>VDC</b>                 | <b>250</b>  | <b>330</b> | <b>400</b>                      | <b>600</b>   | <b>700</b>                           | <b>850</b> |
|  | <b>VAC</b>                 | 160   | 220        | 250                             | 330  | 400                                  | 500        |
| <b>Dissipation Factor (MAX) Tan δ at 1 kHz and 25°C</b>  |                            | <b>C ≤ 5uF</b>  |            | <b>5uF &lt; C ≤ 25uF</b>        |  | <b>C &gt; 75uF</b>                   |            |
|  |                            | .06%  |            | .1%                             |  | .15%                                 |            |
| <b>Insulation Resistance</b><br>After 1 minute of 100VDC applied between the terminals at 25°C                           |                            | 30000 MΩxμF<br>"Not to exceed 3GΩ"  |            |                                 |  |                                      |            |
| <b>Self Inductance</b>   |                            | <1 nano-Henry per mm of lead spacing  |            |                                 |  |                                      |            |
| <b>Long term stability</b>   |                            | Capacitance variation <1% MAX after 2 years   |            |                                 |  |                                      |            |
| <b>Dielectric Strength</b>   |                            | <b>Terminal to Terminal</b>   |            |                                 | <b>Terminal to case</b>  |                                      |            |
|  |                            | 160% of VDC VDC applied for 10 Seconds and 25°C or 200% of VDC applied for 2 Seconds and 25°C |            |                                 | 3KVAC at 50/60 Hz applied between the terminals and case for 60 Seconds and 25°C |                                      |            |
| <b>Life Expectancy</b>   |                            | ≥100000 with VDC<br>≥30000 with VAC   |            |                                 |  |                                      |            |
| <b>Failure quota</b>   |                            | 300/billion component hours   |            |                                 |  |                                      |            |
| <b>Damp Heat Test</b>  |                            | <b>Test Condition</b>   |            | <b>Performance requirements</b> |  |                                      |            |
|  |                            | Temperature= +40°C ±2°C   |            | <b>Max Capacitance change</b>   |  | ≤ 2% of initially measured valued    |            |
|  |                            | Relative Humidity=93 ±2%  |            | <b>DF Change</b>                |  | ≤ 200% of initially specified valued |            |
| <b>Resistance to soldering Heat</b><br>Solder bath temperature: +260°C +/- 5°C<br>Exposure time: 10 seconds +/- 1 second |                            | Test length= 56 days  |            | <b>Insulation resistance</b>    |  | ≥ 50% of minimum specified value     |            |
|  |                            | <b>Max Capacitance change</b>   |            | ≤1% of initially measured value |  |                                      |            |
|  |                            | <b>DF Change</b>  |            | ≤ .1% at 1kHz                   |  |                                      |            |
| <b>Insulation resistance</b>   |                            | ≥50% of minimum specified value   |            |                                 |  |                                      |            |
| <b>Construction</b>  |                            | Metallized Polypropylene film   |            |                                 |  |                                      |            |
| <b>Electrodes</b>  |                            | Vacuum deposited Metal layers   |            |                                 |  |                                      |            |
| <b>Coating</b>   |                            | Flame retardant tape wrap (UL510) with epoxy end fill (UL94V-0)                               |            |                                 |  |                                      |            |
| <b>Lead terminations</b>   |                            | Lead free tinned copper leads   |            |                                 |  |                                      |            |



# PHC

High Frequency Metallized Polypropylene Axial Lead

| WVDC | Capacitance (μF) | IC PART NUMBER | dv/dt (v/μ sec.) | Maximum RMS Ripple Current (A) 100 kHz, +70°C | Typical ESR (mΩ) 100 kHz, +25°C | Dims DxL (mm) |
|------|------------------|----------------|------------------|---|---------------------------------|---------------|
| 250  | 1                | 105PHC250K     | 50               | 4.5   | 7.6                             | 11x29         |
| 250  | 1.5              | 155PHC250K     | 50               | 5.5   | 6.1                             | 13x29         |
| 250  | 2                | 205PHC250K     | 50               | 6   | 4.9                             | 14.5x29       |
| 250  | 2                | 205PHC250KG    | 40               | 6   | 5.1                             | 12.5x34       |
| 250  | 2.2              | 225PHC250KG    | 50               | 6.5   | 5                               | 15x29         |
| 250  | 2.2              | 225PHC250K     | 40               | 6   | 5.7                             | 13x34         |
| 250  | 2.5              | 255PHC250KG    | 50               | 7   | 4.8                             | 15.5x29       |
| 250  | 2.5              | 255PHC250K     | 40               | 7   | 5.4                             | 14x55         |
| 250  | 3                | 305PHC250KG    | 50               | 7.5   | 4.4                             | 17x29         |
| 250  | 3                | 305PHC250K     | 40               | 7   | 4.8                             | 15x34         |
| 250  | 3.3              | 335PHC250K     | 40               | 8   | 4.4                             | 15.5x34       |
| 250  | 4                | 405PHC250K     | 40               | 9   | 3.8                             | 17x34         |
| 250  | 4.7              | 475PHC250KJ    | 40               | 10  | 3.5                             | 18x34         |
| 250  | 5                | 505PHC250K     | 40               | 10  | 3.4                             | 18.5x34       |
| 250  | 6.8              | 685PHC250K     | 40               | 10.5  | 3.1                             | 21x34         |
| 250  | 10               | 106PHC250K     | 40               | 10.5  | 2.5                             | 24x34         |
| 250  | 10               | 106PHC250KN    | 25               | 10.5  | 3.3                             | 21.5x46       |
| 250  | 15               | 156PHC250K     | 25               | 14  | 2.7                             | 25.5x46       |
| 250  | 20               | 206PHC250K     | 25               | 14  | 5                               | 29x46         |
| 250  | 22               | 226PHC250KN    | 25               | 14  | 4.7                             | 30.5x46       |
| 250  | 25               | 256PHC250K     | 25               | 14  | 4.4                             | 32x46         |
| 250  | 30               | 306PHC250K     | 20               | 14  | 4.5                             | 31x55         |
| 250  | 30               | 306PHC250KS    | 15               | 14  | 5.3                             | 29.5x59       |
| 250  | 33               | 336PHC250KR    | 20               | 14  | 4.3                             | 32.5x55       |
| 250  | 33               | 336PHC250KS    | 15               | 14  | 5                               | 31x59         |
| 250  | 40               | 406PHC250K     | 20               | 14  | 3.9                             | 36x55         |
| 250  | 40               | 406PHC250KS    | 15               | 14  | 4.5                             | 33.5x59       |
| 250  | 50               | 506PHC250K     | 20               | 14  | 3.5                             | 40x55         |
| 250  | 50               | 506PHC250KS    | 15               | 14  | 3.9                             | 37x59         |
| 250  | 60               | 606PHC250KS    | 15               | 14  | 3.5                             | 40x59         |
| 330  | 0.68             | 684PHC330KG    | 60               | 4.5   | 9.1                             | 11x29         |
| 330  | 1                | 105PHC330KG    | 60               | 5.5   | 6.9                             | 12.5x29       |
| 330  | 1.5              | 155PHC330KG    | 60               | 6.5   | 5.5                             | 15x29         |
| 330  | 1.5              | 155PHC330KJ    | 45               | 6   | 6.3                             | 13.5x34       |
| 330  | 2                | 205PHC330KG    | 60               | 7.5   | 4.7                             | 16.5x29       |
| 330  | 2                | 205PHC330KJ    | 45               | 7   | 5.7                             | 15x34         |
| 330  | 2.2              | 225PHC330KG    | 60               | 8   | 4.3                             | 17.5x29       |
| 330  | 2.2              | 225PHC330KJ    | 45               | 7.5   | 5.3                             | 15.5x34       |
| 330  | 2.5              | 255PHC330KJ    | 45               | 8   | 5                               | 16.5x34       |
| 330  | 3                | 305PHC330KJ    | 45               | 9   | 4.4                             | 18.5x34       |
| 330  | 3.3              | 335PHC330KJ    | 45               | 9   | 4.3                             | 19x34         |
| 330  | 4                | 405PHC330KJ    | 45               | 10.5  | 3.8                             | 20.5x34       |
| 330  | 4.7              | 475PHC330KJ    | 45               | 10.5  | 3.3                             | 22x34         |
| 330  | 4.7              | 475PHC330KN    | 30               | 10.5  | 4.2                             | 19x46         |
| 330  | 5                | 505PHC330KJ    | 45               | 10.5  | 3.2                             | 22.5x34       |
| 330  | 5                | 505PHC330KN    | 30               | 10.5  | 4.1                             | 19.5x46       |
| 330  | 6.8              | 685PHC330KN    | 30               | 10.5  | 3.6                             | 22x46         |
| 330  | 10               | 106PHC330KN    | 30               | 11  | 6.7                             | 26x46         |
| 330  | 15               | 156PHC330KN    | 30               | 13  | 5.4                             | 31x46         |
| 330  | 15               | 156PHC330KR    | 25               | 12.5  | 6                               | 28x55         |
| 330  | 15               | 156PHC330KS    | 20               | 12  | 6.8                             | 26.5x59       |
| 330  | 20               | 206PHC330KR    | 25               | 14  | 5.1                             | 31.5x55       |
| 330  | 20               | 206PHC330KS    | 20               | 13.5  | 5.8                             | 30x59         |
| 330  | 22               | 226PHC330KR    | 25               | 14  | 4.8                             | 33x55         |
| 330  | 22               | 226PHC330KS    | 20               | 14  | 5.4                             | 31x59         |
| 330  | 25               | 256PHC330KR    | 25               | 14  | 4.5                             | 35x55         |
| 330  | 25               | 256PHC330KS    | 20               | 14  | 5                               | 33x59         |
| 330  | 30               | 306PHC330KR    | 25               | 14  | 4.1                             | 38x55         |

| WVDC | Capacitance (μF) | IC PART NUMBER | dv/dt (v/μ sec.) | Maximum RMS Ripple Current (A) 100 kHz, +70°C | Typical ESR (mΩ) 100 kHz, +25°C | Dims DxL (mm) |
|------|------------------|----------------|------------------|---|---------------------------------|---------------|
| 330  | 30               | 306PHC330KS    | 20               | 14  | 4.5                             | 36x59         |
| 330  | 33               | 336PHC330KR    | 25               | 14  | 3.9                             | 39.5x55       |
| 330  | 33               | 336PHC330KS    | 20               | 14  | 4.3                             | 37.5x59       |
| 330  | 35               | 356PHC330KR    | 25               | 14  | 3.8                             | 41x55         |
| 330  | 35               | 356PHC330KS    | 20               | 14  | 4.2                             | 38.5x59       |
| 330  | 40               | 406PHC330KS    | 20               | 14  | 3.9                             | 41x59         |
| 400  | 0.47             | 474PHC400K     | 75               | 4   | 8.6                             | 11x29         |
| 400  | 0.68             | 684PHC400KG    | 75               | 5.5   | 7.1                             | 13x29         |
| 400  | 0.68             | 684PHC400K     | 55               | 5   | 8.9                             | 12x34         |
| 400  | 1                | 105PHC400KG    | 75               | 6.5   | 5.8                             | 15x29         |
| 400  | 1                | 105PHC400K     | 55               | 6   | 6.7                             | 13x34         |
| 400  | 1.5              | 155PHC400KG    | 75               | 7.5   | 4.7                             | 17.5x29       |
| 400  | 1.5              | 155PHC400K     | 55               | 7   | 5.6                             | 15.5x34       |
| 400  | 2                | 205PHC400K     | 55               | 9   | 4.6                             | 17.5x34       |
| 400  | 2.2              | 225PHC400K     | 55               | 9   | 4.4                             | 18.5x34       |
| 400  | 2.5              | 255PHC400K     | 55               | 9.5   | 4.2                             | 19x34         |
| 400  | 3                | 305PHC400K     | 55               | 10.5  | 3.8                             | 21x34         |
| 400  | 3.3              | 335PHC400K     | 55               | 10.5  | 3.7                             | 22x34         |
| 400  | 3.3              | 335PHC400KN    | 40               | 10.5  | 4.3                             | 19x46         |
| 400  | 4                | 405PHC400KJ    | 55               | 10.5  | 3.3                             | 24x34         |
| 400  | 4                | 405PHC400K     | 40               | 10.5  | 3.8                             | 20.5x46       |
| 400  | 4.7              | 475PHC400K     | 40               | 9.5   | 7.6                             | 22x46         |
| 400  | 5                | 505PHC400K     | 40               | 10  | 7.4                             | 22.5x46       |
| 400  | 6.8              | 685PHC400K     | 40               | 11  | 6.4                             | 26x46         |
| 400  | 10               | 106PHC400KN    | 40               | 13  | 5.4                             | 31x46         |
| 400  | 10               | 106PHC400K     | 30               | 12  | 6.3                             | 27x55         |
| 400  | 10               | 106PHC400KS    | 25               | 11  | 7.1                             | 26x59         |
| 400  | 15               | 156PHC400K     | 30               | 14  | 5                               | 33x55         |
| 400  | 15               | 156PHC400KS    | 25               | 14  | 5.6                             | 31x59         |
| 400  | 20               | 206PHC400K     | 30               | 14  | 4.3                             | 37x55         |
| 400  | 20               | 206PHC400KS    | 25               | 14  | 4.7                             | 35x59         |
| 400  | 22               | 226PHC400KR    | 30               | 14  | 4.1                             | 39x55         |
| 400  | 22               | 226PHC400KS    | 25               | 14  | 4.5                             | 37x59         |
| 400  | 25               | 256PHC400K     | 30               | 14  | 3.8                             | 41.5x55       |
| 400  | 25               | 256PHC400KS    | 25               | 14  | 4.2                             | 39x59         |
| 600  | 0.33             | 334PHC600KG    | 95               | 4   | 9.5                             | 12x29         |
| 600  | 0.47             | 474PHC600KG    | 95               | 5   | 8.3                             | 13.5x29       |
| 600  | 0.47             | 474PHC600K     | 75               | 5   | 9.4                             | 12.5x34       |
| 600  | 0.68             | 684PHC600KG    | 95               | 6   | 6.8                             | 16x29         |
| 600  | 0.68             | 684PHC600K     | 75               | 6   | 7.8                             | 14x34         |
| 600  | 1                | 105PHC600K     | 75               | 8   | 6.1                             | 17.5x34       |
| 600  | 1.5              | 155PHC600K     | 75               | 9   | 4.9                             | 20x34         |
| 600  | 2                | 205PHC600KJ    | 75               | 10.5  | 4.1                             | 23x34         |
| 600  | 2                | 205PHC600K     | 55               | 10  | 5.3                             | 20x46         |
| 600  | 2.2              | 225PHC600KJ    | 75               | 10.5  | 3.8                             | 24x34         |
| 600  | 2.2              | 225PHC600K     | 55               | 10  | 4.8                             | 21x46         |
| 600  | 2.5              | 255PHC600K     | 55               | 10.5  | 4.4                             | 22x46         |
| 600  | 3                | 305PHC600K     | 55               | 10.5  | 4.2                             | 24x46         |
| 600  | 3.3              | 335PHC600K     | 55               | 10.5  | 3.8                             | 25x46         |
| 600  | 4                | 405PHC600K     | 55               | 13.5  | 3.6                             | 27x46         |
| 600  | 4.7              | 475PHC600K     | 55               | 12  | 6.4                             | 29x46         |
| 600  | 4.7              | 475PHC600KR    | 50               | 11.5  | 7.7                             | 26.5x55       |
| 600  | 4.7              | 475PHC600KS    | 40               | 11  | 8.6                             | 24.5x59       |
| 600  | 5                | 505PHC600KN    | 55               | 12.5  | 6.3                             | 29.5x46       |
| 600  | 5                | 505PHC600K     | 50               | 12  | 7.4                             | 27x55         |
| 600  | 5                | 505PHC600KS    | 40               | 11.5  | 8.3                             | 25x59         |
| 600  | 6.8              | 685PHC600K     | 50               | 12.5  | 6.5                             | 30x55         |
| 600  | 6.8              | 685PHC600KS    | 40               | 12  | 7.3                             | 28.5x59       |

# PHC

High Frequency Metallized Polypropylene Axial Lead

| WVDC | Capacitance (μF) | IC PART NUMBER | dv/dt (v/μ sec.) | Maximum RMS Ripple Current (A) 100 kHz, +70°C | Typical ESR (mΩ) 100 kHz, +25°C | Dims DxL (mm) |
|------|------------------|----------------|------------------|---|---------------------------------|---------------|
| 600  | 10               | 106PHC600K     | 50               | 14  | 5.4                             | 35x55         |
| 600  | 10               | 106PHC600KS    | 40               | 14  | 6.1                             | 33.5x59       |
| 600  | 12.5             | 126PHC600K     | 50               | 14  | 4.9                             | 40.5x55       |
| 600  | 12.5             | 126PHC600KS    | 40               | 14  | 5.5                             | 37.5x59       |
| 600  | 15               | 156PHC600KS    | 40               | 14  | 5.1                             | 41x59         |
| 700  | 0.22             | 224PHC700KG    | 135              | 4   | 10.7                            | 12.5x29       |
| 700  | 0.22             | 224PHC700KJ    | 105              | 3.5   | 11.6                            | 11.5x34       |
| 700  | 0.33             | 334PHC700KG    | 135              | 5   | 8.5                             | 15x29         |
| 700  | 0.33             | 334PHC700KJ    | 105              | 5   | 9.4                             | 13.5x34       |
| 700  | 0.47             | 474PHC700KG    | 135              | 6.5   | 6.9                             | 17x29         |
| 700  | 0.47             | 474PHC700K     | 105              | 6.5   | 7.7                             | 15.5x34       |
| 700  | 0.68             | 684PHC700K     | 105              | 8   | 6                               | 17.5x34       |
| 700  | 1                | 105PHC700K     | 105              | 10  | 4.5                             | 21.5x34       |
| 700  | 1                | 105PHC700KN    | 70               | 9   | 6.6                             | 18x46         |
| 700  | 1.2              | 125PHC700K     | 105              | 10.5  | 3.9                             | 24x34         |
| 700  | 1.2              | 125PHC700KN    | 70               | 9   | 6.3                             | 20x46         |
| 700  | 1.5              | 155PHC700K     | 70               | 10.5  | 5.6                             | 21.5x46       |
| 700  | 2                | 205PHC700K     | 70               | 12  | 4.8                             | 24.5x46       |
| 700  | 2.2              | 225PHC700K     | 70               | 12.5  | 4.5                             | 25.5x46       |
| 700  | 2.5              | 255PHC700K     | 70               | 13.5  | 4                               | 27x46         |
| 700  | 3                | 305PHC700K     | 70               | 12  | 6.1                             | 29x46         |
| 700  | 3.3              | 335PHC700K     | 70               | 12  | 5.9                             | 30.5x46       |
| 700  | 4                | 405PHC700K     | 70               | 13.5  | 5.4                             | 33.5x46       |
| 700  | 4                | 405PHC700KR    | 60               | 12.5  | 6.7                             | 29x55         |
| 700  | 4                | 405PHC700KS    | 45               | 12  | 7.7                             | 27.5x59       |
| 700  | 4.7              | 475PHC700K     | 60               | 13  | 6.1                             | 31x55         |
| 700  | 4.7              | 475PHC700KS    | 45               | 12  | 7                               | 29.5x59       |
| 700  | 5                | 505PHC700K     | 60               | 13.5  | 5.8                             | 32x55         |
| 700  | 5                | 505PHC700KS    | 45               | 12.5  | 6.6                             | 30.5x59       |
| 700  | 6.8              | 685PHC700K     | 60               | 14  | 5.1                             | 37x55         |
| 700  | 6.8              | 685PHC700KS    | 45               | 14  | 5.8                             | 35x59         |
| 700  | 8.2              | 825PHC700K     | 60               | 14  | 4.6                             | 41x55         |
| 700  | 8.2              | 825PHC700KS    | 45               | 14  | 5.3                             | 38x59         |

| WVDC | Capacitance (μF) | IC PART NUMBER | dv/dt (v/μ sec.) | Maximum RMS Ripple Current (A) 100 kHz, +70°C | Typical ESR (mΩ) 100 kHz, +25°C | Dims DxL (mm) |
|------|------------------|----------------|------------------|---|---------------------------------|---------------|
| 700  | 10               | 106PHC700KS    | 45               | 14  | 4.9                             | 41.5x59       |
| 850  | 0.1              | 104PHC850KG    | 375              | 3.5   | 12.9                            | 11.5x29       |
| 850  | 0.15             | 154PHC850KG    | 375              | 4.5   | 9.8                             | 13x29         |
| 850  | 0.15             | 154PHC850K     | 300              | 4.5   | 10.8                            | 12x34         |
| 850  | 0.22             | 224PHC850KG    | 375              | 5.5   | 7.7                             | 15x29         |
| 850  | 0.22             | 224PHC850K     | 300              | 5.5   | 8.4                             | 13.5x34       |
| 850  | 0.33             | 334PHC850KG    | 375              | 7   | 5.9                             | 17.5x29       |
| 850  | 0.33             | 334PHC850K     | 300              | 7   | 6.6                             | 16x34         |
| 850  | 0.47             | 474PHC850K     | 300              | 9   | 5.4                             | 18.5x34       |
| 850  | 0.68             | 684PHC850K     | 300              | 10  | 4.3                             | 21.5x34       |
| 850  | 0.68             | 684PHC850KN    | 200              | 9   | 5.4                             | 18x46         |
| 850  | 1                | 105PHC850KJ    | 300              | 13  | 3.2                             | 26x34         |
| 850  | 1                | 105PHC850K     | 200              | 10.5  | 4.3                             | 21.5x46       |
| 850  | 1.5              | 155PHC850K     | 200              | 14  | 3.5                             | 25.5x46       |
| 850  | 2                | 205PHC850K     | 200              | 14  | 2.9                             | 29x46         |
| 850  | 2.2              | 225PHC850K     | 200              | 14  | 2.9                             | 30x46         |
| 850  | 2.2              | 225PHC850KR    | 125              | 14  | 3.8                             | 26.5x55       |
| 850  | 2.2              | 225PHC850KS    | 110              | 14  | 4.3                             | 25x59         |
| 850  | 2.5              | 255PHC850K     | 200              | 14  | 2.7                             | 32x46         |
| 850  | 2.5              | 255PHC850KR    | 125              | 14  | 3.6                             | 28x55         |
| 850  | 2.5              | 255PHC850KS    | 110              | 14  | 4.1                             | 26.5x59       |
| 850  | 3                | 305PHC850K     | 200              | 14  | 2.4                             | 34.5x46       |
| 850  | 3                | 305PHC850KR    | 125              | 14  | 3.2                             | 30.5x55       |
| 850  | 3                | 305PHC850KS    | 110              | 14  | 3.6                             | 29x59         |
| 850  | 3.3              | 335PHC850K     | 125              | 14  | 3.1                             | 32x55         |
| 850  | 3.3              | 335PHC850KS    | 110              | 14  | 3.5                             | 30x59         |
| 850  | 4                | 405PHC850K     | 125              | 14  | 2.8                             | 35x55         |
| 850  | 4                | 405PHC850KS    | 110              | 14  | 3.1                             | 33x59         |
| 850  | 4.7              | 475PHC850K     | 125              | 14  | 2.5                             | 37x55         |
| 850  | 4.7              | 475PHC850KS    | 110              | 14  | 2.8                             | 35.5x59       |
| 850  | 5                | 505PHC850K     | 125              | 14  | 2.4                             | 38x55         |
| 850  | 5                | 505PHC850KS    | 110              | 14  | 2.7                             | 36.5x59       |
| 850  | 6.8              | 685PHC850KS    | 110              | 14  | 2.3                             | 41.5x59       |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.