

# pixhawk® 4

***The most advanced development kit for the PX4® autopilot***

## **Product features**

- A new and small form factor
- More computing power and 2X the RAM than previous versions
- New sensors with higher temperature stability
- Integrated vibrations isolation
- Increased ease-of-use: pre-installed with most recent PX4 (v1.8)
- Additional ports for better integration and expansion



## **Product description**

Pixhawk® 4 is the latest update to the successful family of Pixhawk flight controllers. It is designed and developed in collaboration with Holybro and the PX4 team, optimized to run the full Dronecode stack and comes preinstalled with the latest PX4 firmware (v1.8).

It features the currently most advanced processor technology from STMicroelectronics®, sensor technology from Bosch®, InvenSense®, and a NuttX real-time operating system, delivering incredible performance, flexibility, and reliability for controlling any autonomous vehicle.

The Pixhawk 4's microcontroller now has a 2MB flash memory and 512KB RAM. With the increased power and RAM resources, developers can be more productive and efficient with their development work. More complex algorithms and models can be implemented on the autopilot.

High-performance, low-noise IMUs on board are designed for stabilization applications. Data-ready signals from all sensors are routed to separate interrupt and timer capture pins on the autopilot, permitting precise time-stamping of sensor data. Newly designed vibration isolations enables more accurate readings, allowing vehicles to reach better overall flight performances.

The two external SPI buses and six associated chip select lines allow to add additional sensors and SPI-interfaced payload. There are total of four I2C buses, two dedicated for external use and two grouped with serial ports for GPS/compass modules.

The Pixhawk 4 autopilot development kit is perfect for developers at corporate research labs, startups, and for academics (research, professors, students).

# pixhawk<sup>®</sup> 4

## Technical specifications

- Main FMU Processor: STM32F765
  - 32 Bit Arm<sup>®</sup> Cortex<sup>®</sup>-M7, 216MHz, 2MB memory, 512KB RAM
- IO Processor: STM32F100
  - 32 Bit Arm<sup>®</sup> Cortex<sup>®</sup>-M3, 24MHz, 8KB SRAM
- On-board sensors
  - Accel/Gyro: ICM-20689
  - Accel/Gyro: BMI055
  - Mag: IST8310
  - Barometer: MS5611
- GPS: ublox Neo-M8N GPS/GLONASS receiver; integrated magnetometer IST8310

## Electrical data

### Voltage Ratings:

- Power module output: 4.9~5.5V
- Max input voltage: 6V
- Max current sensing: 120A
- USB Power Input: 4.75~5.25V
- Servo Rail Input: 0~36V

## Mechanical data

- Dimensions: 44x84x12mm
- Weight: 15.8g

## Interfaces

- 8-16 PWM servo outputs (8 from IO, 8 from FMU)
- 3 dedicated PWM/Capture inputs on FMU
- Dedicated R/C input for CPPM
- Dedicated R/C input for Spektrum / DSM and S.Bus with analog / PWM RSSI input
- Dedicated S.Bus servo output
- 5 general purpose serial ports
  - 2 with full flow control
  - 1 with separate 1.5A current limit
- 3 I2C ports
- 4 SPI buses
  - 1 internal high speed SPI sensor bus with 4 chip selects and 6 DRDYS
  - 1 internal low noise SPI bus dedicated for Barometer with 2 chip selects, no DRDYS
  - 1 internal SPI bus dedicated for FRAM
  - Supports dedicated SPI calibration EEPROM located on sensor module
  - 1 external SPI buses
- Up to 2 CANBuses for dual CAN with serial ESC
  - Each CANBus has individual silent controls or ESC RX-MUX control
- Analog inputs for voltage / current of 2 batteries
- 2 additional analog inputs

## Environmental data, quality & reliability

- Operating temp. ~40~85C
- Storage temp. -40~85C
- CE
- FCC
- RoHS compliant (lead-free)

### For more information visit:

[www.dronecode.org](http://www.dronecode.org)  
[www.pixhawk.org](http://www.pixhawk.org)

### Legal notice:

PX4 is a registered Trademark of the Dronecode Foundation. All rights reserved.

Pixhawk is a Registered Trademark of Lorenz Meier. All rights reserved.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.