

EasyView™ Dual Input Thermometers

Choice of Basic Type K or Datalogger model
Datalogger model (EA15) compatible with 7 Types of Thermocouples

Features:

- Compact and rugged design features large backlit display
- Displays [T1 plus T2] or [T1-T2 plus T1] or [T1-T2 plus T2]
- Selectable units of °F, °C, K (Kelvin)
- Wide temperature range with 0.1°/1° resolution
- Timer function displays elapsed time plus the time when MIN and MAX readings are taken
- Data Hold function freezes reading on display
- Auto Power off to save battery life
- Low battery and overrange indication
- Records Max/Min readings for later recall
- Complete with built-in stand, protective holster, two Type K bead wire temperature probes (-22 to 572°F/-30 to 300°C), and 6 AAA batteries



EA10 Type K Dual Input Thermometer

EA15 Dual Input, 7 Thermocouple Type Thermometer Datalogger. Software included

Model EA10

Features:

- Basic Type K Dual input
- OFFSET key used for zero function to make relative measurements

Model EA15

Features:

- Dual input accepts Types J, K, E, T, R, S, and N thermocouples
- Built-in datalogger stores up to 8800 data sets
- RS-232 port to transfer data to PC for analysis
- Real Time Clock
- Includes Windows[®] 95/98/NT/2000/ME/XP/7 compatible software and cable

| Specifications | EA10 | EA15 |
|-------------------|----------------------------------|---|
| Thermocouple Type | EA10 | EA15 |
| J | — | -200 to 1994°F (-150 to 1090°C) |
| K | -200 to 1999°F (-200 to 1360°C) | -200 to 1999.9°F (-150 to 1370°C) |
| T | — | -200 to 752°F (-150 to 400°C) |
| E | — | -200 to 1598°F (-150 to 870°C) |
| R | — | 35 to 1999.9°F (2 to 1767°C) |
| S | — | 35 to 1999.9°F (2 to 1767°C) |
| N | — | -200 to 1999.9°F (-150 to 1300°C) |
| Resolution | 0.1° | 0.1° |
| Basic Accuracy | ±0.3% (+2°F/+1°C) | ±0.05% rdg (+1.5°F/+0.75°C) Types J,K,E,T,N ±0.05% rdg (+4°F/+2°C) Types R,S |
| Dimensions | 6 x 2.8 x 1.5" (152 x 72 x 37mm) | 6 x 2.8 x 1.5" (152 x 72 x 37mm) |
| Weight | 8.3oz (235g) | 8.3oz (235g) |

Ordering Information:

- EA10EasyView[®] Dual K Thermometer
 EA10-NISTEA10 with Certificate of Calibration Traceable to NIST
 EA15EasyView[®] Dual Input 7 Thermocouple Type Temperature Datalogger
 EA15-NISTEA15 with Certificate of Calibration Traceable to NIST
 409996Soft Vinyl Pouch





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.