

## Network cable - NBC-500,0-94B - 1410276

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Network cable, Ethernet, 8-wire, shielded, PUR, halogen-free, RAL 5021 (water blue), 26 AWG, 4 x 2 x 0.14 mm², cable length: 500 m

RoHS

**Ethernet**

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc                                                                                                    |
| GTIN         | <br>4 046356 893589 |
| GTIN         | 4046356893589                                                                                           |

### Technical data

#### Dimensions

|                 |       |
|-----------------|-------|
| Length of cable | 500 m |
|-----------------|-------|

#### Ambient conditions

|                                 |                                                 |
|---------------------------------|-------------------------------------------------|
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation)    |
|                                 | -20 °C ... 80 °C (cable, flexible installation) |

#### General data

|                      |                                |
|----------------------|--------------------------------|
| Rated voltage        | 30 V AC                        |
|                      | 30 V DC                        |
| Number of positions  | 8                              |
| Signal type/category | Ethernet CAT5 (IEC 11801:2002) |

#### Standards and Regulations

|                   |                                     |
|-------------------|-------------------------------------|
| Flame resistance  | IEC 60332-1-2                       |
| Resistance to oil | in accordance with DIN EN 60811-2-1 |
| Halogen-free      | according to IEC 60754-1            |

#### Cable

|                           |                          |
|---------------------------|--------------------------|
| Cable type                | Ethernet, flexible, CAT5 |
| Cable type (abbreviation) | 94B                      |

# Network cable - NBC-500,0-94B - 1410276

## Technical data

### Cable

|                                                      |                                                                            |
|------------------------------------------------------|----------------------------------------------------------------------------|
| UL AWM style                                         | 20963 (80°C/30 V)                                                          |
| Signal type/category                                 | Ethernet CAT5 (IEC 11801), 1 Gbps                                          |
| Cable structure                                      | 4x2xAWG26/7; SF/UTP                                                        |
| Conductor cross section                              | 4x 2x 0.14 mm <sup>2</sup>                                                 |
| AWG signal line                                      | 26                                                                         |
| Conductor structure signal line                      | 7x 0.16 mm                                                                 |
| Core diameter including insulation                   | 0.96 mm                                                                    |
| Wire colors                                          | white/blue-blue, white/orange-orange, white/green-green, white/brown-brown |
| Twisted pairs                                        | 2 cores to the pair                                                        |
| Overall twist                                        | 4 pairs for core                                                           |
| Shielding                                            | Aluminum-coated foil, tinned copper braided shield                         |
| Optical shield covering                              | 70 %                                                                       |
| External sheath, color                               | water blue RAL 5021                                                        |
| Outer sheath thickness                               | 1.05 mm                                                                    |
| External cable diameter D                            | 6.4 mm ±0.2 mm                                                             |
| Minimum bending radius, fixed installation           | 4 x D                                                                      |
| Minimum bending radius, flexible installation        | 8 x D                                                                      |
| Tensile strength GRP                                 | ≤ 100 N                                                                    |
| Cable weight                                         | 47 kg/km                                                                   |
| Outer sheath, material                               | PUR                                                                        |
| Material conductor insulation                        | Foamed PE                                                                  |
| Conductor material                                   | Bare Cu litz wires                                                         |
| Insulation resistance                                | ≥ 500 MΩ*km                                                                |
| Loop resistance                                      | ≤ 290.00 Ω/km                                                              |
| Cable capacity                                       | 48 nF/km (at 1 kHz)                                                        |
| Wave impedance                                       | 100 Ω ±5 Ω (at 100 MHz)                                                    |
| Near end crosstalk attenuation (NEXT)                | 71.3 dB (with 1 MHz)                                                       |
|                                                      | 62.3 dB (at 4 MHz)                                                         |
|                                                      | 56.3 dB (at 10 MHz)                                                        |
|                                                      | 53.2 dB (at 16 MHz)                                                        |
|                                                      | 51.8 dB (at 20 MHz)                                                        |
|                                                      | 48.9 dB (at 31.25 MHz)                                                     |
|                                                      | 44.4 dB (at 62.5 MHz)                                                      |
|                                                      | 41.3 dB (at 100 MHz)                                                       |
| Power-summed near end crosstalk attenuation (PSNEXT) | 62.3 dB (with 1 MHz)                                                       |
|                                                      | 53.3 dB (at 4 MHz)                                                         |
|                                                      | 47.3 dB (at 10 MHz)                                                        |
|                                                      | 44.2 dB (at 16 MHz)                                                        |
|                                                      | 42.8 dB (at 20 MHz)                                                        |
|                                                      | 39.9 dB (at 31.25 MHz)                                                     |

## Network cable - NBC-500,0-94B - 1410276

### Technical data

#### Cable

|                                         |                                                 |
|-----------------------------------------|-------------------------------------------------|
|                                         | 35.4 dB (at 62.5 MHz)                           |
|                                         | 32.3 dB (at 100 MHz)                            |
| Attenuation                             | 3.2 dB (with 1 MHz)                             |
|                                         | 6 dB (at 4 MHz)                                 |
|                                         | 9.5 dB (at 10 MHz)                              |
|                                         | 12.1 dB (at 16 MHz)                             |
|                                         | 13.6 dB (at 20 MHz)                             |
|                                         | 17.1 dB (at 31.25 MHz)                          |
|                                         | 24.8 dB (at 62.5 MHz)                           |
|                                         | 32 dB (at 100 MHz)                              |
| Return loss (RL)                        | 23 dB (at 4 MHz)                                |
|                                         | 24.1 dB (at 8 MHz)                              |
|                                         | 25 dB (at 10 MHz)                               |
|                                         | 25 dB (at 16 MHz)                               |
|                                         | 25 dB (at 20 MHz)                               |
|                                         | 23.6 dB (at 31.25 MHz)                          |
|                                         | 21.5 dB (at 62.5 MHz)                           |
|                                         | 20.1 dB (at 100 MHz)                            |
| Signal runtime                          | 5.3 ns/m                                        |
| Coupling resistance                     | ≤ 100.00 mΩ/m (at 10 MHz)                       |
| Nominal voltage, cable                  | ≤ 100 V                                         |
| Test voltage Core/Core                  | 700 V (50 Hz, 1 min.)                           |
| Test voltage Core/Shield                | 700 V (50 Hz, 1 min.)                           |
| Flame resistance                        | according to IEC 60332-1-2                      |
| Halogen-free                            | according to IEC 60754-1                        |
| Resistance to oil                       | according to EN 60811-2-1                       |
| Ambient temperature (operation)         | -40 °C ... 80 °C (cable, fixed installation)    |
|                                         | -20 °C ... 80 °C (cable, flexible installation) |
| Ambient temperature (installation)      | -20 °C ... 80 °C                                |
| Ambient temperature (storage/transport) | -20 °C ... 80 °C                                |

#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Drawings

## Network cable - NBC-500,0-94B - 1410276

Cable cross section



Ethernet, flexible, CAT5 [94B]

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.