

Lower Voltage Ceramic Singlelayer DC Disc Capacitors 1 kV_{DC} to 3 kV_{DC} Low Dissipation Factor


RoHS
COMPLIANT

FEATURES

- Low losses
- High stability
- Low DF minimizes self heating at HF
- Ideal for high switching to 100 kHz
- Radial leads
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

APPLICATIONS

- SMPS
- HF ballast
- Snubber and HV circuits

DESIGN

The capacitors consist of a ceramic disc of which both sides are silver-plated. Connection leads are made of tinned copper having diameters of 0.022" (0.51 mm) or 0.025" (0.64 mm).

The capacitors may be supplied with radial kinked or straight leads having lead spacing of 0.250" (6.35 mm) or 0.375" (9.5 mm).

The standard tolerances are $\pm 5\%$, $\pm 10\%$.

Coating is made of flammable retardant epoxy resin in accordance with "UL 94 V-0".

CAPACITANCE RANGE

10 pF to 6800 pF

RATED VOLTAGE

1000 V_{DC} (500 V_{RMS})
 2000 V_{DC} (1000 V_{RMS})
 3000 V_{DC} (1500 V_{RMS})

DIELECTRIC STRENGTH BETWEEN LEADS

Component test:

1000 V_{DC} 2500 V_{DC}, 2 s
 2000 V_{DC} 4000 V_{DC}, 2 s
 3000 V_{DC} 6000 V_{DC}, 2 s

CERAMIC DIELECTRIC

C0G, N1500, N2000, N2200, N2500, N2800 (Class 1)

| QUICK REFERENCE DATA | | | |
|----------------------------|--|------|------|
| DESCRIPTION | VALUE | | |
| Ceramic Class | 1 | | |
| Ceramic Dielectric | C0G, N1500, N2000, N2200, N2500, N2800 | | |
| Voltage (V _{DC}) | 1000 | 2000 | 3000 |
| Min. Capacitance (pF) | 10 | 10 | 10 |
| Max. Capacitance (pF) | 6800 | 6800 | 4700 |
| Mounting | Radial | | |

INSULATION RESISTANCE

Min. 50 000 M Ω

TOLERANCE ON CAPACITANCE

$\pm 5\%$, $\pm 10\%$

DISSIPATION FACTOR

0.1 % max. at 1 kHz; 1 V

CATEGORY TEMPERATURE RANGE

-55 °C to +125 °C

CLIMATIC CATEGORY ACC. TO EN 60068-1

55/125/21

OPERATING TEMPERATURE RANGE

-55 °C to +105 °C



| ORDERING INFORMATION, CERAMIC 1 kV_{DC} LOW DISSIPATION FACTOR | | | | | | | | | | | |
|---|--------------|--|---|---|--|-----------|--------------|------|------------------|-------------|-------------|
| C (pF) | TOL. (%) | D _{max.} DIAMETER INCH (mm) | T _{max.} THICKNESS INCH (mm) | LS LEAD SPACE INCH (mm) ± 1 mm | LO LEAD OFFSET INCH (mm) ± 0.5 mm | WIRE SIZE | | FIG. | ORDERING CODE | | |
| | | | | | | AWG | INCH (mm) | | | | |
| C0G (NPO) | | | | | | | | | | | |
| 10 | ± 5 | 0.250 (6.4) | 0.156 (4.0) | 0.250 (6.4) | 0.043 (1.1) | 22 | 0.025 (0.64) | 1 | 561R1DF0Q10 | | |
| 12 | | | | | 0.051 (1.3) | | | | 561R1DF0Q12 | | |
| N1500 | | | | | | | | | | | |
| 22 | ± 5 | 0.250 (6.4) | 0.156 (4.0) | 0.250 (6.4) | 0.043 (1.1) | 22 | 0.025 (0.64) | 1 | 561R1DF0Q22 | | |
| 47 | | | | | 0.071 (1.8) | | | | 561R1DF0Q47 | | |
| 56 | | | | | 0.055 (1.4) | | | | 561R1DF0Q56 | | |
| 68 | | | | | 0.059 (1.5) | | | | 561R1DF0Q68 | | |
| 82 | | | | | 0.047 (1.2) | | | | 561R1DF0Q82 | | |
| N2200 | | | | | | | | | | | |
| 33 | ± 10 | 0.250 (6.4) | 0.156 (4.0) | 0.250 (6.4) | 0.043 (1.1) | 22 | 0.025 (0.64) | 1 | 561R1DF0Q33 | | |
| N2000 | | | | | | | | | | | |
| 100 | ± 10 | 0.250 (6.4) | 0.156 (4.0) | 0.250 (6.4) | 0.059 (1.5) | 22 | 0.025 (0.64) | 1 | 561R1DF0T10 | | |
| 120 | | | | | 0.055 (1.4) | | | | 561R1DF0T12 | | |
| 150 | | | | | 0.043 (1.1) | | | | 561R1DF0T15 | | |
| 180 | | | | | 0.043 (1.1) | | | | 561R1DF0T18 | | |
| N2500 | | | | | | | | | | | |
| 220 | ± 10 | 0.250 (6.4) | 0.156 (4.0) | 0.250 (6.4) | 0.059 (1.5) | 22 | 0.025 (0.64) | 1 | 561R1DF0T22 | | |
| 270 | | | | | 0.043 (1.1) | | | | 561R1DF0T27 | | |
| N2800 | | | | | | | | | | | |
| 330 | ± 10 | 0.250 (6.4) | 0.156 (4.0) | 0.250 (6.4) | 0.047 (1.2) | 22 | 0.025 (0.64) | 1 | 561R1DF0T33 | | |
| 390 | | | | | 0.047 (1.2) | | | | 561R1DF0T39 | | |
| 470 | | | | | 0.290 (7.4) | | | | 0.059 (1.5) | 561R1DF0T47 | |
| 560 | | | | | | | | | 0.055 (1.4) | 561R1DF0T56 | |
| 680 | | 0.047 (1.2) | | | | | | | 561R1DF0T68 | | |
| 820 | | 0.043 (1.1) | | | | | | | 561R1DF0T82 | | |
| 1000 | | 0.370 (9.4) | | | 0.055 (1.4) | | | | 561R1DF0D10 | | |
| 1200 | | | | | 0.047 (1.2) | | | | 561R1DF0D12 | | |
| 1500 | | | | | 0.047 (1.2) | | | | 561R1DF0D15 | | |
| 1800 | | | | | 0.051 (1.3) | | | | 561R1DF0D18 | | |
| 2200 | | 0.460 (11.7) | | | 0.047 (1.2) | | | | 561R1DF0D22 | | |
| 2700 | | 0.490 (12.4) | | | 0.047 (1.2) | | | | 561R1DF0D27 | | |
| 3300 | | 0.530 (13.5) | | | 0.047 (1.2) | | | | 561R1DF0D33 | | |
| 3900 | | 0.560 (14.2) | | | 0.156 (4.0) | | | | 0.375 (9.5) | 0.047 (1.2) | 561R1DF0D39 |
| 4700 | | 0.630 (16.0) | | | | | | | | 0.047 (1.2) | 561R1DF0D47 |
| 5600 | | 0.680 (17.3) | | | | | | | | 0.047 (1.2) | 561R1DF0D56 |
| 6800 | 0.760 (19.3) | 0.047 (1.2) | 561R1DF0D68 | | | | | | | | |

Note

- Alternate lead spacings of 5 mm, 7.5 mm or 10 mm are available on request.



| ORDERING INFORMATION, CERAMIC 2 kV _{DC} LOW DISSIPATION FACTOR | | | | | | | | | | |
|---|-------------|--|---|---|--|-----------|--------------|------|------------------|-------------|
| C (pF) | TOL. (%) | D _{max.} DIAMETER INCH (mm) | T _{max.} THICKNESS INCH (mm) | LS LEAD SPACE INCH (mm) ± 1 mm | LO LEAD OFFSET INCH (mm) ± 0.5 mm | WIRE SIZE | | FIG. | ORDERING CODE | |
| | | | | | | AWG | INCH (mm) | | | |
| N1500 | | | | | | | | | | |
| 33 | ± 5 | 0.290 (7.4) | 0.195 (5.0) | 0.250 (6.4) | 0.098 (2.5) | 20 | 0.032 (0.81) | 1 | 564R2DF0Q33 | |
| 39 | | | 0.180 (4.6) | | 0.083 (2.1) | | | | 564R2DF0Q39 | |
| 47 | | | 0.170 (4.3) | | 0.071 (1.8) | | | | 564R2DF0Q47 | |
| N2000 | | | | | | | | | | |
| 56 | ± 5 | 0.290 (7.4) | 0.210 (5.3) | 0.250 (6.4) | 0.110 (2.8) | 20 | 0.032 (0.81) | 1 | 564R2DF0Q56 | |
| 68 | | | 0.190 (4.8) | | 0.091 (2.3) | | | | 564R2DF0Q68 | |
| 82 | | | 0.175 (4.5) | | 0.075 (1.9) | | | | 564R2DF0Q82 | |
| 100 | | | 0.170 (4.3) | | 0.071 (1.8) | | | | 564R2DF0T10 | |
| N2500 | | | | | | | | | | |
| 120 | ± 10 | 0.290 (7.4) | 0.185 (4.7) | 0.250 (6.4) | 0.087 (2.2) | 20 | 0.032 (0.81) | 1 | 564R2DF0T12 | |
| 150 | | | 0.170 (4.3) | | 0.071 (1.8) | | | | 564R2DF0T15 | |
| 180 | | | 0.185 (4.7) | | 0.071 (1.8) | | | | 564R2DF0T18 | |
| 270 | | | 0.330 (8.4) | | 0.170 (4.3) | | | | 0.079 (2.0) | 564R2DF0T27 |
| 470 | | | 0.400 (10.2) | | 0.170 (4.3) | | | | 0.075 (1.9) | 564R2DF0T47 |
| N2800 | | | | | | | | | | |
| 220 | ± 10 | 0.290 (7.4) | 0.170 (4.3) | 0.250 (6.4) | 0.087 (2.2) | 20 | 0.032 (0.81) | 1 | 564R2DF0T22 | |
| 330 | | 0.330 (8.4) | 0.185 (4.7) | | 0.083 (2.1) | | | | 564R2DF0T33 | |
| 390 | | 0.330 (8.4) | 0.175 (4.5) | | 0.075 (1.9) | | | | 564R2DF0T39 | |
| 560 | | 0.400 (10.2) | 0.185 (4.7) | | 0.087 (2.2) | | | | 564R2DF0T56 | |
| 680 | | 0.400 (10.2) | 0.170 (4.3) | | 0.075 (1.9) | | | | 564R2DF0T68 | |
| 820 | | 0.430 (10.9) | 0.175 (4.5) | | 0.075 (1.9) | | | | 564R2DF0T82 | |
| 1000 | | 0.460 (11.7) | 0.170 (4.3) | | 0.075 (1.9) | | | | 564R2DF0D10 | |
| 1500 | | 0.530 (13.5) | | | 0.071 (1.8) | | | | 564R2DF0D15 | |
| 1800 | | 0.560 (14.2) | 0.170 (4.3) | | 0.071 (1.8) | | | | 564R2DF0D18 | |
| 2200 | | 0.680 (17.3) | 0.180 (4.6) | | 0.375 (9.5) | | | | 0.083 (2.1) | 564R2DF0D22 |
| 2300 | | | 0.175 (4.5) | 0.079 (2.0) | | | | | 564R2DF0D23 | |
| 2400 | | | 0.175 (4.5) | 0.075 (1.9) | | | | | 564R2DF0D24 | |
| 2700 | | | 0.170 (4.3) | 0.071 (1.8) | | | | | 564R2DF0D27 | |
| 3300 | | | 0.720 (18.3) | 0.170 (4.3) | | | | | 0.071 (1.8) | 564R2DF0D33 |
| 3900 | | | 0.790 (20.1) | 0.170 (4.3) | | | | | 0.075 (1.9) | 564R2DF0D39 |
| 4700 | | 0.900 (22.9) | 0.180 (4.6) | 0.083 (2.1) | 564R2DF0D47 | | | | | |
| 5600 | | 0.900 (22.9) | 0.170 (4.3) | 0.075 (1.9) | 564R2DF0D56 | | | | | |
| 6800 | | 0.950 (24.1) | 0.170 (4.3) | 0.071 (1.8) | 564R2DF0D68 | | | | | |

Note

- Alternate lead spacings of 5 mm, 7.5 mm or 10 mm are available on request.



| ORDERING INFORMATION, CERAMIC 3 kV _{DC} LOW DISSIPATION FACTOR | | | | | | | | | | |
|---|-------------|--|---|---|--|-----------|--------------|------|------------------|-------------|
| C (pF) | TOL. (%) | D _{max.} DIAMETER INCH (mm) | T _{max.} THICKNESS INCH (mm) | LS LEAD SPACE INCH (mm) ± 1 mm | LO LEAD OFFSET INCH (mm) ± 0.5 mm | WIRE SIZE | | FIG. | ORDERING CODE | |
| | | | | | | AWG | INCH (mm) | | | |
| N1500 | | | | | | | | | | |
| 10 | ± 5 | 0.290 (7.4) | 0.185 (4.7) | 0.250 (6.4) | 0.087 (2.2) | 20 | 0.032 (0.81) | 1 | 564R3DF0Q10 | |
| 27 | | | 0.220 (5.6) | | 0.122 (3.1) | | | | 564R3DF0Q27 | |
| 33 | | | 0.195 (5.0) | | 0.098 (2.5) | | | | 564R3DF0Q33 | |
| 39 | | | 0.190 (4.8) | | 0.094 (2.4) | | | | 564R3DF0Q39 | |
| 47 | | | 0.225 (5.7) | | 0.126 (3.2) | | | | 564R3DF0Q47 | |
| N2200 | | | | | | | | | | |
| 12 | ± 5 | 0.290 (7.4) | 0.210 (5.3) | 0.250 (6.4) | 0.110 (2.8) | 20 | 0.032 (0.81) | 1 | 564R3DF0Q12 | |
| 22 | | 0.330 (8.4) | 0.210 (5.3) | | 0.110 (2.8) | | | | 564R3DF0Q22 | |
| N2000 | | | | | | | | | | |
| 56 | ± 5 | 0.290 (7.4) | 0.210 (5.3) | 0.250 (6.4) | 0.110 (2.8) | 20 | 0.032 (0.81) | 1 | 564R3DF0Q56 | |
| 68 | | | 0.190 (4.8) | | 0.098 (2.5) | | | | 564R3DF0Q68 | |
| 82 | | | 0.185 (4.7) | | 0.091 (2.3) | | | | 564R3DF0Q82 | |
| N2500 | | | | | | | | | | |
| 100 | ± 10 | 0.290 (7.4) | 0.205 (5.2) | 0.250 (6.4) | 0.106 (2.7) | 20 | 0.032 (0.81) | 1 | 564R3DF0T10 | |
| 120 | | 0.290 (7.4) | 0.190 (4.8) | | 0.091 (2.3) | | | | 564R3DF0T12 | |
| 220 | | 0.330 (8.4) | 0.190 (4.8) | | 0.091 (2.3) | | | | 564R3DF0T22 | |
| N2800 | | | | | | | | | | |
| 150 | ± 10 | 0.290 (7.4) | 0.200 (5.1) | 0.250 (6.4) | 0.091 (2.3) | 20 | 0.032 (0.81) | 1 | 564R3DF0T15 | |
| 180 | | 0.290 (7.4) | 0.190 (4.8) | | 0.091 (2.3) | | | | 564R3DF0T18 | |
| 270 | | 0.330 (8.4) | 0.205 (5.2) | | 0.110 (2.8) | | | | 564R3DF0T27 | |
| 330 | | 0.330 (8.4) | 0.190 (4.8) | | 0.091 (2.3) | | | | 564R3DF0T33 | |
| 390 | | 0.400 (10.2) | 0.215 (5.5) | | 0.102 (2.6) | | | | 564R3DF0T39 | |
| 470 | | 0.400 (10.2) | 0.195 (5.0) | | 0.087 (2.2) | | | | 564R3DF0T47 | |
| 560 | | 0.430 (10.9) | 0.200 (5.1) | | 0.102 (2.6) | | | | 564R3DF0T56 | |
| 680 | | 0.460 (11.7) | 0.195 (5.0) | | 0.087 (2.2) | | | | 564R3DF0T68 | |
| 820 | | 0.490 (12.5) | 0.195 (5.0) | | 0.102 (2.6) | | | | 564R3DF0T82 | |
| 1000 | | 0.530 (13.5) | 0.190 (4.8) | 0.091 (2.3) | 564R3DF0D10 | | | | | |
| 1200 | | 0.560 (14.2) | 0.190 (4.8) | 0.375 (9.5) | 0.091 (2.3) | | | | 564R3DF0D12 | |
| 1500 | | 0.620 (15.8) | | | 0.091 (2.3) | | | | 564R3DF0D15 | |
| 1800 | | 0.680 (17.3) | | | 0.098 (2.5) | | | | 564R3DF0D18 | |
| 2200 | | 0.720 (18.3) | | | 0.094 (2.4) | | | | 564R3DF0D22 | |
| 2700 | | 0.790 (20.1) | | | 0.190 (4.8) | | | | 0.087 (2.2) | 564R3DF0D27 |
| 3300 | | 0.900 (22.9) | | | 0.200 (5.1) | | | | 0.102 (2.6) | 564R3DF0D33 |
| 4700 | | 0.950 (24.1) | | | 0.185 (4.7) | | | | 0.087 (2.2) | 564R3DF0D47 |

Note

- Alternate lead spacings of 5 mm, 7.5 mm or 10 mm are available on request.

TAPE AND REEL OPTIONS

Part number codes and specifications for tape and reel packaging are found in the general information document - find web-link below.



Power Rating - 1DFO Series 500 V_{RMS} Low DF - Note 1




Note 2

Power Rating - 2DFO Series 1000 V_{RMS} Low DF - Note 1



Note 2

Power Rating - 3DFO Series 1500 V_{RMS} Low DF - Note 1



Note 2

Note 1

Power ratings are based on still air 60 °C ambient with additional 30 °C rise due to self heating. Thermal effects such as forced air cooling, component encapsulation or other heat-sinking techniques will alter ratings. Actual circuit for application recommended.

Note 2

For convenience, power rating charts are shown to 100 kHz. Higher frequency operation is permissible with appropriate derating. Consult us for application suggestions.

Temperature Characteristics for 1DFO, 2DFO & 3DFO Series



RELATED DOCUMENTS

General Information

www.vishay.com/doc?23140



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.