

Achieve low insertion forces and convenient blind-mating to industry-standard tabs on PCBs, switches, capacitors, relays and other devices in consumer, industrial, HVAC and automotive aftermarket applications with Molex's Quixon™ Quick-Disconnect Terminals, featuring a flexing beam and side-relief cuts

Quixon™ quick-disconnect terminals expand Molex's existing AviKrimp™ (Series 19275, 19277), InsulKrimp™ (Series 19274, 19276) and Krimptite™ (Series 19273) quick disconnect terminal offers lower insertion force and greater blind-mate capability versus standard AviKrimp, InsulKrimp and Krimptite terminals.

Quixon quick-disconnect terminals are available in loose piece or on continuous plastic strip and Mylar tape for semi- or fully- automatic termination. Quixon quick-disconnect terminals meet UL requirements when used with Molex recommended tooling; however, terminals may be crimped with a variety of industry-standard tooling.

Quixon quick-disconnect terminals mate to industrystandard tabs offered by Molex (Series 19705, 19708, 19713, 19711). For additional information visit: www.molex.com/link/quixon.html.

FEATURES AND BENEFITS

- Flexing beam with standard dimple provides low insertion force to mate easily with UL-compliant male tabs while maintaining a high retention force
- Side-relief cut design makes blind mating easy by accommodating a slight angle during mating
- Flared-barrel entry for easy wire insertion captures all the wire strands and funnels them into the crimp barrel
- Un-insulated, partially or fully insulated versions available provides customers a choice for their applications and safety requirements
- Comes standard on AviKrimp™ terminal with a Brass sleeve on the barrel to provide strain relief and meet the double-crimp VDE, IEC and DIN requirement with a metal ferrule that crimps onto the wire insulation
- Terminals mate to industry-standard tabs, 6.35 by 0.81mm (.250 by .032") enabling universal use in numerous applications

Quixon™ Quick-Disconnect Terminals

- 19273 Quixon™ Krimptite™ Terminals (Un-insulated)**
- 19274 Quixon™ InsulKrimp™ Terminals (Partially Insulated)**
- 19275 Quixon™ AviKrimp™ Terminals (Partially Insulated)**
- 19276 Quixon™ InsulKrimp™ Terminals (Fully Insulated)**
- 19277 Quixon™ AviKrimp™ Terminals (Fully Insulated)**



*Quixon Fully-Insulated Quick-Disconnect Terminals
(Red = 18 to 22 AWG; Blue = 14 to 16 AWG; Yellow = 10 to 12 AWG)*

SPECIFICATIONS

Reference Information

Packaging:
Box, Molded Strip on Reels or
Mylar Tape on Reels

UL File No.:
E79133 (when terminated with
Molex tooling)

CSA File No.: LR18689

Mates With:
Wire-to-Wire Tabs
(Series 19022, 19024, 19023, 19025)
Wire-to-Board Tabs
(Series 19705, 19708, 19713, 19711)

Electrical

Voltage Rating:
AviKrimp™ 300V
InsulKrimp™ 600V

Amperage Rating (@ 75°C Ambient):
18 to 22 AWG — 7.0A
14 to 16 AWG — 15.0A
10 to 12 AWG — 24.0A

Physical

Terminal Material: Brass

Insulation Materials:
Nylon 94V-2 Rated
(Series 19275, 19276, 19277)
PVC 94V-0 Rated
(Series 19274)

Plating: Matte Tin (Sn)

Operating Temperature: -55 to +105°C

APPLICATIONS

- Industrial Markets
 - PCB Connections
 - Switches
 - Terminal Blocks
- Automotive Aftermarket
 - Gauges
 - Modules
- Consumer Industry
 - White Goods
 - Brown Goods
- HVAC
 - Relays
 - Capacitors
 - Contactors



Quixon™ Quick-Disconnect Terminals

- 19273 Quixon™ Krimptite™ Terminals (Un-insulated)
- 19274 Quixon™ InsulKrimp™ Terminals (Partially Insulated)
- 19275 Quixon™ AviKrimp™ Terminals (Partially Insulated)
- 19276 Quixon™ InsulKrimp™ Terminals (Fully Insulated)
- 19277 Quixon™ AviKrimp™ Terminals (Fully Insulated)

ORDERING INFORMATION

Krimptite™ Style (Un-insulated)

Wire Range AWG mm²	Order No.	
	Loose Piece	Mylar Tape
18 - 22 AWG 1.50 - 0.25mm²	19273-0007	19273-0009
14 - 16 AWG 2.50 - 1.00mm²	19273-0008	19273-0010

InsulKrimp™ Style

Wire Range AWG mm²	Insulation	Color	Order No.			
			Loose Piece	Mylar Tape	Molded Strip	Metal Strip
18 - 22 AWG 1.50 - 0.25mm²	Partial	Red	19274-0002	19274-0003	N/A	19274-0001
	Full		19276-0002	19276-0003	19276-0001	N/A
14 - 16 AWG 2.50 - 1.00mm²	Partial	Blue	19274-0005	19274-0006	N/A	19274-0004
	Full		19276-0005	19276-0006	19276-0004	N/A
10 - 12 AWG 3.00 - 5.00mm²		Yellow	19276-0008	19276-0009	19276-0007	

AviKrimp™ Style

Wire Range AWG mm²	Insulation	Color	Order No.		
			Loose Piece	Mylar Tape	Metal Strip
18 - 22 AWG 1.50 - 0.25mm²	Partial	Red	19275-0002	19275-0003	19275-0001
	Full		19277-0002	19277-0003	19277-0001
14 - 16 AWG 2.50 - 1.00mm²	Partial	Blue	19275-0005	19275-0006	19275-0004
	Full		19277-0005	19277-0006	19277-0004
10 - 12 AWG 3.00 - 5.00mm²		Yellow	19277-0008	19277-0009	19277-0007

Application Tooling Cross Reference Chart

Quixon Order No.	ATP Die Set	Applicator	Quixon Order No.	ATP Die Set	Applicator	Quixon Order No.	Applicator
19274-0003	19288-0048	63885-0800	19275-0003	19288-0048	63885-0800	19276-0001	63883-7000
19276-0003	19288-0049	63885-7000	19277-0003	19288-0028	63885-2000	19276-0004	63883-4200
19274-0006	19288-0104	N/A	19275-0006	19288-0145	63885-0900	19276-0007	63883-2800
19276-0006	19288-0145	63885-4200	19277-0006	19288-0130	63885-0200	19277-0001	63881-2000
19276-0009	19027-0014	63885-2800	19277-0009	19027-0019	63885-2100	19277-0004	63881-0200
19274-0001	N/A	63881-0800	19275-0001	N/A	63881-0800	19277-0007	63881-2100
19274-0004		63881-0900	19275-0004		63881-0900		



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.