

Features

Regulated Converters

- 2:1 and 4:1 Wide Input Voltage Ranges
- 1kVDC, 2kVDC & 3kVDC Isolation
- UL94V-0 Package Material
- Continuous Short Circuit Protection
- Low Noise
- No External Capacitor needed
- Efficiency to 83 %

Description

High power-density, an industrial temperature range of -40°C to +85°C and extra features like Remote-On-Off- control are just some of the characteristics of this converter, ideal for highly sophisticated industrial designs. The RS series is available with isolation of 2kV or 3kV by choosing option "/H2" or "/H3" in which case it is also ideal for medical applications which additionally require EN-60601-1 certification.

Selection Guide 5V, 12V, 24V and 48V Input Types

Part Number	Input Voltage Range (VDC)	Rated Output Voltage (VDC)	Output Current at Full Load (mA)	Efficiency typ. (%)	Max Capacitive Load
SIP8					
RS-xx3.3S (H2/H3)	4.5-9, 9-18 18-36, 36-72	3.3	500	68-69 70-73	4700µF
RS-xx05S (H2/H3)	4.5-9, 9-18 18-36, 36-72	5	400	73-75 78	1000µF
RS-xx09S (H2/H3)	4.5-9, 9-18 18-36, 36-72	9	222	74-78 81	1000µF
RS-xx12S (H2/H3)	4.5-9, 9-18 18-36, 36-72	12	166	75-80 83	1000µF
RS-xx15S (H2/H3)	4.5-9, 9-18 18-36, 36-72	15	134	75-80 83	1000µF
RS-xx3.3D (H2/H3)	4.5-9, 9-18 18-36, 36-72	±3.3	±250	68-69 70-73	±2200µF
RS-xx05D (H2/H3)	4.5-9, 9-18 18-36, 36-72	±5	±200	73-75 78	±680µF
RS-xx09D (H2/H3)	4.5-9, 9-18 18-36, 36-72	±9	±111	74-78 81	±680µF
RS-xx12D (H2/H3)	4.5-9, 9-18 18-36, 36-72	±12	±83	75-80 83	±680µF
RS-xx15D (H2/H3)	4.5-9, 9-18 18-36, 36-72	±15	±67	75-80 83	±680µF
RS-xx3.3SZ (H2/H3)	9-36 18-72	3.3	500	75 75	4700µF
RS-xx05SZ (H2/H3)	9-36 18-72	5	400	80 80	1000µF
RS-xx09SZ (H2/H3)	9-36 18-72	9	222	80 80	1000µF
RS-xx12SZ (H2/H3)	9-36 18-72	12	166	83 83	1000µF
RS-xx15SZ (H2/H3)	9-36 18-72	15	134	84 84	1000µF
RS-xx3.3DZ (H2/H3)	9-36 18-72	±3.3	±250	73 73	±2200µF
RS-xx05DZ (H2/H3)	9-36 18-72	±5	±200	77 77	±680µF
RS-xx09DZ (H2/H3)	9-36 18-72	±9	±111	80 80	±680µF
RS-xx12DZ (H2/H3)	9-36 18-72	±12	±83	81 81	±680µF
RS-xx15DZ (H2/H3)	9-36 18-72	±15	±67	83 83	±680µF

No suffix is standard isolation (1kVDC) e.g., RS-0505S

*add suffix /H2 or /H3 for 2kVDC or 3kVDC isolation, e.g., RS-0505S/H2, RS-0505DZ/H3


ECONOLINE

DC/DC-Converter

with 3 year Warranty

RECOM

2 Watt SIP8 Isolated Single & Dual Output




UL-60950-1 Certified
EN-60950-1 Certified
EN-60601-1 Certified*
(* /H suffix)

RS

Derating-Graph (Ambient Temperature)

RS-S(Z)_D(Z)



2:1 Input
(RS-S/D)
xx = 4.5-9Vin = 05
xx = 9-18Vin = 12
xx = 18-36Vin = 24
xx = 36-72Vin = 48

4:1 Input
(RS-SZ/DZ)
xx = 9-36Vin = 24
xx = 18-72Vin = 48

Specifications (measured at $T_A = 25^\circ\text{C}$, nominal input voltage, full load and after warm-up time unless otherwise specified)

Input Voltage Range		2:1 and 4:1		
Output Accuracy		±2% typ.		
Line Voltage Regulation		±0.5% max.		
Load Voltage Regulation		20%-100% Load	±0.5% max.	
Minimum Load		10% ⁽²⁾		
Output Ripple and Noise (20MHz limited)		50mVp-p max.		
Switching Frequency		Full Load	100kHz min. / 300kHz max.	
Efficiency at Full Load		See Selection Guide		
Quiescent Current		RS-05xxS_D	40mA typ.	
Nominal input Voltage		RS-12xxS_D	32mA typ.	
(Standard, /H2 and /H3)		RS-24xxS_D, SZ_DZ	25mA typ.	
		RS-48xxS_D, SZ_DZ	15mA typ.	
Isolation Voltage	Standard	(tested for 1 second)	1000VDC	
		(rated for 1 minute**)	500VAC / 60Hz	
	/H2 Version	(tested for 1 second)	2000VDC	
		(rated for 1 minute**)	1000VAC / 60Hz	
	/H3 Version	(tested for 1 second)	3000VDC	
		(rated for 1 minute**)	1500VAC / 60Hz	
Isolation Capacitance	Standard	2:1 Single	10pF min. / 40pF typ. / 60pF max.	
	/H2 and /H3	2:1 Single	5pF min. / 30pF typ. / 60pF max.	
	Standard	2:1 Dual	120pF min. / 170pF typ. / 250pF max.	
	/H2 and /H3	2:1 Dual	5pF min. / 30pF typ. / 60pF max.	
	Standard	4:1 Single/Dual	200pF max.	
	/H2 and /H3	4:1 Single/Dual	30pF max	
Isolation Resistance		1GΩ min.		
Short Circuit Protection		Continuous		
Operating Temperature Range		2:1	−40°C to +85°C	
(No Derating)		4:1	−40°C to +75°C	
Storage Temperature Range		−55°C to +125°C		
Relative Humidity		95% RH		
Package Weight		4.7g		
Packing Quantity		22 pcs per Tube		
MTBF (+25°C) (+85°C)		Detailed Information see Application Notes chapter "MTBF"	using MIL-HDBK 217F	1398 x 10 ³ hours
			using MIL-HDBK 217F	210 x 10 ³ hours
Certifications				
EN General Safety		Report: SPCLVD1605077-10	EN60950-1, AM2:2013	
EN Medical Safety		Report: MDD1205098-3 + RM1205098-3	IEC/EN 60601-1 3rd Edition	
			Medical Report + ISO14971 Risk Assessment	
UL General Safety		Report: E224736-A35	UL60950-1, 2nd Edition 2014	
			CSA C22.2 60950-1-07, 2nd Edition 2014	


**Any data referred to in this datasheet are of indicative nature and based on our practical experience only. For further details, please refer to our Application Notes.

Notes


Note 1:	Maximum capacitive load is defined as the capacitive load that will allow start up in under 1 second without damage to the converter
Note 2:	The RS series requires a minimum of 10% load on the output to maintain specified regulation. Operating under no-load conditions will not damage these devices; however, they may not meet all listed specifications.

Typical Characteristics

RS-24xx




RS-05xx types




Package Style and Pinning (mm)


8 PIN SIP Package




Single Output




Dual Output



XX.X ± 0.5 mm
XX.XX ± 0.25 mm



Recommended Footprint Details



Pin Connections

Pin #	Single	Dual
1	-Vin	-Vin
2	+Vin	+Vin
3	CTRL	CTRL
5	NC	NC
6	+Vout	+Vout
7	-Vout	Com
8	NC*	-Vout

NC = No Connection

NC* = NC, but no external Connection allowed.

Pin 8 (NC*) This pin is used internally and must have no external connection.


Pin 5 (NC) Not connected internally.

Pin 3 (CTRL)


This pin provides an Off function which puts the converter into a low power mode. When the pin is 'high' the converter is OFF and when the pin is high 'Z' the converter is ON. There is no allowed low state for this pin.

Application Examples

ON/OFF CONTROL



I = 3V
O = 0.5V or GND



Remote ON/OFF

ON: open or high impedance

OFF: external 5~12 Vdc and 1N4148+ 68Ω resistor



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.