



TGA2814-SM

3.1–3.5 GHz 80 W GaN Power Amplifier

General Description

Qorvo's TGA2814-SM is a high-power, S-band amplifier fabricated on Qorvo's production 0.25 μm GaN on SiC process (QGaN25). The TGA2814-SM covers 3.1–3.5 GHz and provides >80 W of saturated output power, 24 dB of large-signal gain, and achieves 55 % power-added efficiency.



The TGA2814-SM can also support a variety of operating conditions to best support system requirements. With good thermal properties, it can support a range of bias voltages and performs well under pulse operation.

With DC blocking capacitors on both RF ports, which are matched to 50 ohms, the TGA2814-SM is ideal for both commercial and military radar systems.

Lead-free and RoHS compliant.

Evaluation boards are available on request.

Functional Block Diagram



Product Features

- Frequency Range: 3.1–3.5 GHz
- Output Power: 49.5 dBm (at Pin = 25 dBm)
- Power Gain >24 dB (at Pin = 25 dBm)
- PAE: 55% (at Pin = 25 dBm)
- Bias: $V_D = 30\text{ V}$, $I_{DQ} = 200\text{ mA}$
- Package Dimensions: 7.0 x 7.0 x 0.85 mm

Applications

- Military Radar
- Commercial Radar

Ordering Information

Part	Description
TGA2814-SM	3.1–3.5 GHz 80 W GaN Power Amplifier
TGA2814-SM EVB	TGA2814-SM Evaluation Board

Absolute Maximum Ratings

Parameter	Value/Range
Drain Voltage (V_D)	40 V
Gate Voltage Range (V_G)	–8 to 0 V
Drain Current (I_D)	8.5 A
Gate Current (I_G)	See graph pg. 10
Power Dissipation (P_{DISS})	166 W
Input Power, CW, 50 Ω , 85 °C, (P_{IN})	30 dBm
Input Power, V_{SWR} 3:1, V_D = 30 V, PW = 15 ms, DC = 30%, 85 °C, (P_{IN})	27 dBm
Storage Temperature	–55 to 150 °C

Note:

1. Max. Input Power ratings based on die data

Operation of this device outside the parameter ranges given above may cause permanent damage. These are stress ratings only, and functional operation of the device at these conditions is not implied.

Recommended Operating Conditions

Parameter	Value/Range
Drain Voltage (V_D)	30 V
Drain Current (I_{DQ})	200 mA
Drain Current Under RF Drive (I_{D_Drive})	5500 mA
Gate Voltage Range (V_G)	–2.9 to –2.0 V (Typ.)







Electrical specifications are measured at specified test conditions. Specifications are not guaranteed over all recommended operating conditions.

Electrical Specifications







Test conditions unless otherwise noted: 25 °C, V_D = 30 V, I_{DQ} = 200 mA, PW = 100 μ s, DC = 10 %

Parameter	Min	Typical	Max	Units
Operational Frequency Range	3.1		3.5	GHz
Input Return Loss (at I_{DQ} = 400 mA)		>12		dB
Output Return Loss (at I_{DQ} = 400 mA)		>7		dB
Small Signal Gain (at I_{DQ} = 400 mA)		>26		dB
Power Gain @ Saturation (P_{in} = 24 dBm)		>24		dB
Output Power @ Saturation (P_{in} = 24 dBm)		>49.5		dBm
Power Added Efficiency (P_{in} = 24 dBm)		>55		%
Output Power Temperature Coefficient		–0.006		dBm/°C

Typical Performance – Small Signal









Typical Performance – Small Signal








Typical Performance – Large Signal

Test conditions unless otherwise noted: 25 °C, $V_D = 30$ V, $I_{DQ} = 200$ mA, $PW = 100$ μ s, $DC = 10$ %








Typical Performance – Large Signal

Test conditions unless otherwise noted: 25 °C, $V_D = 30$ V, $I_{DQ} = 200$ mA, PW = 100 μ s, DC = 10 %








Typical Performance – Large Signal

Test conditions unless otherwise noted: 25 °C, $V_D = 30$ V, $I_{DQ} = 200$ mA, $PW = 100$ μ s, $DC = 10$ %





Typical Performance – Large Signal

Test conditions unless otherwise noted: 25 °C, $V_D = 30$ V, $I_{DQ} = 200$ mA, $PW = 100$ μ s, $DC = 10$ %



Typical Performance – Large Signal

Test conditions unless otherwise noted: 25 °C, $V_D = 30$ V, $I_{DQ} = 200$ mA, $PW = 100$ μ s, $DC = 10$ %





Thermal and Reliability Information

Parameter	Test Conditions	Value	Units
Thermal Resistance (θ_{JC}) ⁽¹⁾	$T_{BASE} = 85^\circ\text{C}$, $V_D = 30\text{ V}$, $I_{DQ} = 200\text{mA}$, Quiescent operation (DC only, no RF)	0.29	$^\circ\text{C/W}$
Channel Temperature (T_{CH})		86.7	$^\circ\text{C}$
Thermal Resistance (θ_{JC}) ⁽¹⁾	$T_{BASE} = 85^\circ\text{C}$, $V_D = 30\text{ V}$, $I_D = 5.3\text{ A}$, $P_{IN} = 25\text{ dBm}$, $P_{OUT} = 49.5\text{ dBm}$, $PW = 100\text{ }\mu\text{s}$, $DC = 10\%$, $P_{DISS} = 58\text{ W}$	0.47	$^\circ\text{C/W}$
Channel Temperature (T_{CH})		112.4	$^\circ\text{C}$
Thermal Resistance (θ_{JC}) ⁽¹⁾	$T_{BASE} = 85^\circ\text{C}$, $V_D = 32\text{ V}$, $I_D = 5.7\text{ A}$, $P_{IN} = 25\text{ dBm}$, $P_{OUT} = 50.0\text{ dBm}$, $PW = 100\text{ }\mu\text{s}$, $DC = 10\%$, $P_{DISS} = 72\text{ W}$	0.50	$^\circ\text{C/W}$
Channel Temperature (T_{CH})		120.8	$^\circ\text{C}$


Notes:

1. Thermal resistance referenced back of the package.
2. IR scan equivalent. Refer to the following document: [GaN Device Channel Temperature, Thermal Resistance, and Reliability Estimates](#).

Power Dissipation and Max. Gate Current



Application Circuit




Bias-up Procedure

- Set I_D limit to 6 A, I_G limit to 30 mA
- Apply -5.0 V to V_G
- Apply +30 V to V_D
- Adjust V_G more positive until $I_{DQ} = 200$ mA ($V_G \sim -2.90$ V Typical)
- Apply RF signal

Bias-down Procedure

- Turn off RF signal
- Reduce V_G to -5.0 V. Ensure $I_{DQ} \sim 0$ mA
- Set V_D to 0 V
- Turn off V_D supply
- Turn off V_G supply


Evaluation Board, Mounting Detail, Bill of Materials



RF Layer is 0.008" thick Rogers Corp. RO40003C ($\epsilon_r = 3.35$). Metal layers are 0.5 oz. copper. The microstrip line at the connector interface is optimized for the Southwest Microwave end launch connector 1092-02A-5.

Reference Des.	Component	Value	Manuf.	Part Number
C1, C2	Surface Mount Cap	10 uF, 20 %, 50 V (1206), X5R	Various	
C3–C10	Surface Mount Cap	1000 pF, 10 %, 50 V (0402), X7R	Various	
C11–C14	Surface Mount Cap	1.0 uF, 10 %, 25 V (0402), X7R	Various	
R1, R2	Surface Mount Res	0 Ohm, 5 % (0603)	Various	

Mechanical Drawing




DIMENSIONS ARE IN MILLIMETERS
PACKAGE LEADS ARE GOLD PLATED.
PART IS MOLD ENCAPSULATED
YY IS THE CALENDAR YEAR
WW IS THE WEEK NUMBER
MXXX IS THE BATCH ID

Pad Descriptions

Pad No.	Symbol	Description
1-5, 8-12, 14, 16, 18-21, 24-29, 32-37, 40-43, 45, 47, 49	GND	Ground connection.
6, 7	RF Input	50 Ohm RF input. Pad is capacitively coupled to block on-chip DC voltages.
13, 48	V_{G1}	1 st Stage Gate Voltage; bias network is required; must be biased from both sides (V_{G1} and V_{G2} can be tied together in application)
15, 46	V_{D1}	1 st Stage Drain Voltage; bias network is required; must be biased from both sides (V_{D1} and V_{D2} can be tied together in application)
17, 44	V_{G2}	2 nd Stage Gate Voltage; bias network is required; must be biased from both sides (V_{G1} and V_{G2} can be tied together in application)
22, 23, 38, 39	V_{D2}	2 nd Stage Drain Voltage; bias network is required; must be biased from both sides (V_{D1} and V_{D2} can be tied together in application)
30, 31	RF Output	50 Ohm RF output. Pad is capacitively coupled to block on-chip DC voltages

Recommended Soldering Temperature Profile



Handling Precautions

Parameter	Rating	Standard
ESD – Human Body Model (HBM)	0B	ANSI/ESDA/JEDEC JS-001
ESD – Charge Device Model (CDM)	C3	ANSI/ESDA/JEDEC JS-002
MSL Rating	1	JEDEC IPC/JEDEC J-STD-020



Caution!
ESD-Sensitive Device

Solderability

Compatible with the latest version of J-STD-020, Lead-free solder, 260 °C

RoHS Compliance

This part is compliant with 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄O₂) Free
- PFOS Free
- SVHC Free

Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations:

Web: www.qorvo.com

Tel: 1-844-890-8163

Email: customer.support@qorvo.com

Important Notice

The information contained herein is believed to be reliable; however, Qorvo makes no warranties regarding the information contained herein and assumes no responsibility or liability whatsoever for the use of the information contained herein. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for Qorvo products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. **THIS INFORMATION DOES NOT CONSTITUTE A WARRANTY WITH RESPECT TO THE PRODUCTS DESCRIBED HEREIN, AND QORVO HEREBY DISCLAIMS ANY AND ALL WARRANTIES WITH RESPECT TO SUCH PRODUCTS WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

Without limiting the generality of the foregoing, Qorvo products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Copyright 2019 © Qorvo, Inc. | Qorvo is a registered trademark of Qorvo, Inc.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.