



# CSD17577Q5A 30-V N-Channel NexFET™ Power MOSFET

## 1 Features


- Low  $Q_g$  and  $Q_{gd}$
- Low Thermal Resistance
- Avalanche Rated
- Pb Free Terminal Plating
- RoHS Compliant
- Halogen Free
- SON 5 mm × 6 mm Plastic Package

## 2 Applications

- Point of Load Synchronous Buck in Networking, Telecom, and Computing Systems
- Optimized for Control, and Sync FET Applications

## 3 Description

This 30 V, 3.5 mΩ, SON 5 mm × 6 mm NexFET™ power MOSFET is designed to minimize resistance in power conversion applications.



### Product Summary

| $T_A = 25^\circ\text{C}$ |                               | TYPICAL VALUE           |     | UNIT |
|--------------------------|-------------------------------|-------------------------|-----|------|
| $V_{DS}$                 | Drain-to-Source Voltage       | 30                      |     | V    |
| $Q_g$                    | Gate Charge Total (4.5 V)     | 13                      |     | nC   |
| $Q_{gd}$                 | Gate Charge Gate-to-Drain     | 2.8                     |     | nC   |
| $R_{DS(on)}$             | Drain-to-Source On-Resistance | $V_{GS} = 4.5\text{ V}$ | 4.8 | mΩ   |
|                          |                               | $V_{GS} = 10\text{ V}$  | 3.5 | mΩ   |
| $V_{GS(th)}$             | Threshold Voltage             | 1.4                     |     | V    |

### Ordering Information<sup>(1)</sup>

| Device       | Qty  | Media        | Package                      | Ship          |
|--------------|------|--------------|------------------------------|---------------|
| CSD17577Q5A  | 2500 | 13-Inch Reel | SON 5 × 6 mm Plastic Package | Tape and Reel |
| CSD17577Q5AT | 250  | 7-Inch Reel  |                              |               |

(1) For all available packages, see the orderable addendum at the end of the data sheet.


### Absolute Maximum Ratings

| $T_A = 25^\circ\text{C}$ |                                                                                         | VALUE      | UNIT |
|--------------------------|-----------------------------------------------------------------------------------------|------------|------|
| $V_{DS}$                 | Drain-to-Source Voltage                                                                 | 30         | V    |
| $V_{GS}$                 | Gate-to-Source Voltage                                                                  | ±20        | V    |
| $I_D$                    | Continuous Drain Current (Package limited)                                              | 60         | A    |
|                          | Continuous Drain Current (Silicon limited), $T_C = 25^\circ\text{C}$                    | 83         |      |
|                          | Continuous Drain Current <sup>(1)</sup>                                                 | 22         |      |
| $I_{DM}$                 | Pulsed Drain Current <sup>(2)</sup>                                                     | 280        | A    |
| $P_D$                    | Power Dissipation <sup>(1)</sup>                                                        | 3          | W    |
|                          | Power Dissipation, $T_C = 25^\circ\text{C}$                                             | 53         |      |
| $T_J$ ,<br>$T_{stg}$     | Operating Junction and Storage Temperature Range                                        | –55 to 150 | °C   |
| $E_{AS}$                 | Avalanche Energy, single pulse<br>$I_D = 28$ , $L = 0.1\text{ mH}$ , $R_G = 25\ \Omega$ | 39         | mJ   |


(1) Typical  $R_{\theta JA} = 40^\circ\text{C/W}$  on a 1-inch<sup>2</sup>, 2-oz. Cu pad on a 0.06-inch thick FR4 PCB.

(2) Max  $R_{\theta JC} = 2.8^\circ\text{C/W}$ , pulse duration ≤100 μs, duty cycle ≤1%

**$R_{DS(on)}$  vs  $V_{GS}$**



**Gate Charge**



## Table of Contents

|                                                 |          |                                                                 |           |
|-------------------------------------------------|----------|-----------------------------------------------------------------|-----------|
| <b>1 Features</b> .....                         | <b>1</b> | 6.1 Trademarks .....                                            | <b>7</b>  |
| <b>2 Applications</b> .....                     | <b>1</b> | 6.2 Electrostatic Discharge Caution .....                       | <b>7</b>  |
| <b>3 Description</b> .....                      | <b>1</b> | 6.3 Glossary .....                                              | <b>7</b>  |
| <b>4 Revision History</b> .....                 | <b>2</b> | <b>7 Mechanical, Packaging, and Orderable Information</b> ..... | <b>8</b>  |
| <b>5 Specifications</b> .....                   | <b>3</b> | 7.1 Q5A Package Dimensions .....                                | <b>8</b>  |
| 5.1 Electrical Characteristics .....            | <b>3</b> | 7.2 Recommended PCB Pattern .....                               | <b>9</b>  |
| 5.2 Thermal Information .....                   | <b>3</b> | 7.3 Recommended Stencil Opening .....                           | <b>9</b>  |
| 5.3 Typical MOSFET Characteristics .....        | <b>4</b> | 7.4 Q5A Tape and Reel Information .....                         | <b>10</b> |
| <b>6 Device and Documentation Support</b> ..... | <b>7</b> |                                                                 |           |

## 4 Revision History

| DATE        | REVISION | NOTES            |
|-------------|----------|------------------|
| August 2014 | *        | Initial release. |

## 5 Specifications

### 5.1 Electrical Characteristics

(T<sub>A</sub> = 25°C unless otherwise stated)

| PARAMETER               |                                  | TEST CONDITIONS                                                                                 | MIN  | TYP | MAX  | UNIT |
|-------------------------|----------------------------------|-------------------------------------------------------------------------------------------------|------|-----|------|------|
| STATIC CHARACTERISTICS  |                                  |                                                                                                 |      |     |      |      |
| BV <sub>DSS</sub>       | Drain-to-Source Voltage          | V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA                                                  | 30   |     |      | V    |
| I <sub>DSS</sub>        | Drain-to-Source Leakage Current  | V <sub>GS</sub> = 0 V, V <sub>DS</sub> = 24 V                                                   |      |     | 1    | μA   |
| I <sub>GSS</sub>        | Gate-to-Source Leakage Current   | V <sub>DS</sub> = 0 V, V <sub>GS</sub> = 20 V                                                   |      |     | 100  | nA   |
| V <sub>GS(th)</sub>     | Gate-to-Source Threshold Voltage | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA                                     | 1.1  | 1.4 | 1.8  | V    |
| R <sub>DS(on)</sub>     | Drain-to-Source On-Resistance    | V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 10 A                                                  | 4.8  |     | 5.8  | mΩ   |
|                         |                                  | V <sub>GS</sub> = 10 V, I <sub>D</sub> = 18 A                                                   | 3.5  |     | 4.2  | mΩ   |
| g <sub>fs</sub>         | Transconductance                 | V <sub>DS</sub> = 3 V, I <sub>D</sub> = 18 A                                                    | 79   |     |      | S    |
| DYNAMIC CHARACTERISTICS |                                  |                                                                                                 |      |     |      |      |
| C <sub>iss</sub>        | Input Capacitance                | V <sub>GS</sub> = 0 V, V <sub>DS</sub> = 15 V, f = 1 MHz                                        | 1780 |     | 2310 | pF   |
| C <sub>oss</sub>        | Output Capacitance               |                                                                                                 | 208  |     | 270  | pF   |
| C <sub>rss</sub>        | Reverse Transfer Capacitance     |                                                                                                 | 79   |     | 102  | pF   |
| R <sub>G</sub>          | Series Gate Resistance           |                                                                                                 | 1.4  |     | 2.8  | Ω    |
| Q <sub>g</sub>          | Gate Charge Total (4.5 V)        | V <sub>DS</sub> = 15 V, I <sub>D</sub> = 18 A                                                   | 13   |     | 17   | nC   |
| Q <sub>g</sub>          | Gate Charge Total (10 V)         |                                                                                                 | 27   |     | 35   | nC   |
| Q <sub>gd</sub>         | Gate Charge Gate-to-Drain        |                                                                                                 | 2.8  |     |      | nC   |
| Q <sub>gs</sub>         | Gate Charge Gate-to-Source       |                                                                                                 | 5.1  |     |      | nC   |
| Q <sub>g(th)</sub>      | Gate Charge at V <sub>th</sub>   |                                                                                                 | 2.5  |     |      | nC   |
| Q <sub>oss</sub>        | Output Charge                    | V <sub>DS</sub> = 15 V, V <sub>GS</sub> = 0 V                                                   | 6    |     |      | nC   |
| t <sub>d(on)</sub>      | Turn On Delay Time               | V <sub>DS</sub> = 15 V, V <sub>GS</sub> = 10 V,<br>I <sub>DS</sub> = 18 A, R <sub>G</sub> = 0 Ω | 3    |     |      | ns   |
| t <sub>r</sub>          | Rise Time                        |                                                                                                 | 12   |     |      | ns   |
| t <sub>d(off)</sub>     | Turn Off Delay Time              |                                                                                                 | 18   |     |      | ns   |
| t <sub>f</sub>          | Fall Time                        |                                                                                                 | 2    |     |      | ns   |
| DIODE CHARACTERISTICS   |                                  |                                                                                                 |      |     |      |      |
| V <sub>SD</sub>         | Diode Forward Voltage            | I <sub>SD</sub> = 18 A, V <sub>GS</sub> = 0 V                                                   | 0.8  |     | 1    | V    |
| Q <sub>rr</sub>         | Reverse Recovery Charge          | V <sub>DS</sub> = 15 V, I <sub>F</sub> = 18 A,<br>di/dt = 300 A/μs                              | 8.2  |     |      | nC   |
| t <sub>rr</sub>         | Reverse Recovery Time            |                                                                                                 | 9.3  |     |      | ns   |

### 5.2 Thermal Information

(T<sub>A</sub> = 25°C unless otherwise stated)


| THERMAL METRIC   |                                                          | MIN | TYP | MAX | UNIT |
|------------------|----------------------------------------------------------|-----|-----|-----|------|
| R <sub>θJC</sub> | Junction-to-Case Thermal Resistance <sup>(1)</sup>       |     |     | 2.8 | °C/W |
| R <sub>θJA</sub> | Junction-to-Ambient Thermal Resistance <sup>(1)(2)</sup> |     |     | 50  |      |

- (1) R<sub>θJC</sub> is determined with the device mounted on a 1-inch<sup>2</sup> (6.45-cm<sup>2</sup>), 2-oz. (0.071-mm thick) Cu pad on a 1.5-inches × 1.5-inches (3.81-cm × 3.81-cm), 0.06-inch (1.52-mm) thick FR4 PCB. R<sub>θJC</sub> is specified by design, whereas R<sub>θJA</sub> is determined by the user's board design.
- (2) Device mounted on FR4 material with 1-inch<sup>2</sup> (6.45-cm<sup>2</sup>), 2-oz. (0.071-mm thick) Cu.



M0137-01

Max  $R_{\theta JA} = 50^{\circ}\text{C/W}$   
when mounted on  
1 inch<sup>2</sup> (6.45 cm<sup>2</sup>) of  
2-oz. (0.071-mm thick)  
Cu.




M0137-02

Max  $R_{\theta JA} = 140^{\circ}\text{C/W}$   
when mounted on a  
minimum pad area of  
2-oz. (0.071-mm thick)  
Cu.

### 5.3 Typical MOSFET Characteristics

( $T_A = 25^{\circ}\text{C}$  unless otherwise stated)



## Typical MOSFET Characteristics (continued)

( $T_A = 25^\circ\text{C}$  unless otherwise stated)




Figure 2. Saturation Characteristics




Figure 3. Transfer Characteristics




Figure 4. Gate Charge




Figure 5. Capacitance




Figure 6. Threshold Voltage vs Temperature






Figure 7. On-State Resistance vs Gate-to-Source Voltage

## Typical MOSFET Characteristics (continued)


( $T_A = 25^\circ\text{C}$  unless otherwise stated)




**Figure 8. Normalized On-State Resistance vs Temperature**




**Figure 9. Typical Diode Forward Voltage**



**Figure 10. Maximum Safe Operating Area**



**Figure 11. Single Pulse Unclamped Inductive Switching**



**Figure 12. Maximum Drain Current vs Temperature**

## 6 Device and Documentation Support

### 6.1 Trademarks

NexFET is a trademark of Texas Instruments.

### 6.2 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

### 6.3 Glossary


[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

## 7 Mechanical, Packaging, and Orderable Information


The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

### 7.1 Q5A Package Dimensions



| DIM      | MILLIMETERS |      |      |
|----------|-------------|------|------|
|          | MIN         | NOM  | MAX  |
| A        | 0.90        | 1.00 | 1.10 |
| b        | 0.33        | 0.41 | 0.51 |
| c        | 0.20        | 0.25 | 0.34 |
| D1       | 4.80        | 4.90 | 5.00 |
| D2       | 3.61        | 3.81 | 4.02 |
| E        | 5.90        | 6.00 | 6.10 |
| E1       | 5.70        | 5.75 | 5.80 |
| E2       | 3.38        | 3.58 | 3.78 |
| E3       | 3.03        | 3.13 | 3.23 |
| e        | 1.17        | 1.27 | 1.37 |
| e1       | 0.27        | 0.37 | 0.47 |
| e2       | 0.15        | 0.25 | 0.35 |
| H        | 0.41        | 0.56 | 0.71 |
| K        | 1.10        | —    | —    |
| L        | 0.51        | 0.61 | 0.71 |
| L1       | 0.06        | 0.13 | 0.20 |
| $\theta$ | 0°          | —    | 12°  |

## 7.2 Recommended PCB Pattern




## Recommended PCB Pattern (continued)


| DIM | MILLIMETERS |       | INCHES |       |
|-----|-------------|-------|--------|-------|
|     | MIN         | MAX   | MIN    | MAX   |
| F1  | 6.205       | 6.305 | 0.244  | 0.248 |
| F2  | 4.46        | 4.56  | 0.176  | 0.18  |
| F3  | 4.46        | 4.56  | 0.176  | 0.18  |
| F4  | 0.65        | 0.7   | 0.026  | 0.028 |
| F5  | 0.62        | 0.67  | 0.024  | 0.026 |
| F6  | 0.63        | 0.68  | 0.025  | 0.027 |
| F7  | 0.7         | 0.8   | 0.028  | 0.031 |
| F8  | 0.65        | 0.7   | 0.026  | 0.028 |
| F9  | 0.62        | 0.67  | 0.024  | 0.026 |
| F10 | 4.9         | 5     | 0.193  | 0.197 |
| F11 | 4.46        | 4.56  | 0.176  | 0.18  |

For recommended circuit layout for PCB designs, see application note [SLPA005](#) – *Reducing Ringing Through PCB Layout Techniques*.

## 7.3 Recommended Stencil Opening



## 7.4 Q5A Tape and Reel Information



M0138-01

### Notes:

- 10-sprocket hole-pitch cumulative tolerance  $\pm 0.2$
- Camber not to exceed 1 mm in 100 mm, noncumulative over 250 mm
- Material: black static-dissipative polystyrene
- All dimensions are in mm (unless otherwise specified).
- $A0$  and  $B0$  measured on a plane 0.3 mm above the bottom of the pocket.

## PACKAGING INFORMATION

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)          | Lead/Ball Finish<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|--------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| CSD17577Q5A      | ACTIVE        | VSONP        | DQJ                | 8    | 2500           | Pb-Free (RoHS<br>Exempt) | CU SN                   | Level-1-260C-UNLIM   | -40 to 85    | CSD17577                | <a href="#">Samples</a> |
| CSD17577Q5AT     | ACTIVE        | VSONP        | DQJ                | 8    | 250            | Pb-Free (RoHS<br>Exempt) | CU SN                   | Level-1-260C-UNLIM   | -40 to 85    | CSD17577                | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Pb-Free (RoHS Exempt):** This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**TAPE AND REEL INFORMATION**


\*All dimensions are nominal

| Device       | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|--------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| CSD17577Q5A  | VSONP        | DQJ             | 8    | 2500 | 330.0              | 12.4               | 6.3     | 5.3     | 1.2     | 8.0     | 12.0   | Q1            |
| CSD17577Q5AT | VSONP        | DQJ             | 8    | 250  | 180.0              | 12.4               | 6.3     | 5.3     | 1.2     | 8.0     | 12.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device       | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|--------------|--------------|-----------------|------|------|-------------|------------|-------------|
| CSD17577Q5A  | VSONP        | DQJ             | 8    | 2500 | 340.0       | 340.0      | 38.0        |
| CSD17577Q5AT | VSONP        | DQJ             | 8    | 250  | 190.0       | 190.0      | 30.0        |

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

### Products

|                              |                                                                                      |
|------------------------------|--------------------------------------------------------------------------------------|
| Audio                        | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                               |
| Amplifiers                   | <a href="http://amplifier.ti.com">amplifier.ti.com</a>                               |
| Data Converters              | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>                       |
| DLP® Products                | <a href="http://www.dlp.com">www.dlp.com</a>                                         |
| DSP                          | <a href="http://dsp.ti.com">dsp.ti.com</a>                                           |
| Clocks and Timers            | <a href="http://www.ti.com/clocks">www.ti.com/clocks</a>                             |
| Interface                    | <a href="http://interface.ti.com">interface.ti.com</a>                               |
| Logic                        | <a href="http://logic.ti.com">logic.ti.com</a>                                       |
| Power Mgmt                   | <a href="http://power.ti.com">power.ti.com</a>                                       |
| Microcontrollers             | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a>                   |
| RFID                         | <a href="http://www.ti-rfid.com">www.ti-rfid.com</a>                                 |
| OMAP Applications Processors | <a href="http://www.ti.com/omap">www.ti.com/omap</a>                                 |
| Wireless Connectivity        | <a href="http://www.ti.com/wirelessconnectivity">www.ti.com/wirelessconnectivity</a> |

### Applications

|                               |                                                                                          |
|-------------------------------|------------------------------------------------------------------------------------------|
| Automotive and Transportation | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>                         |
| Communications and Telecom    | <a href="http://www.ti.com/communications">www.ti.com/communications</a>                 |
| Computers and Peripherals     | <a href="http://www.ti.com/computers">www.ti.com/computers</a>                           |
| Consumer Electronics          | <a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>                   |
| Energy and Lighting           | <a href="http://www.ti.com/energy">www.ti.com/energy</a>                                 |
| Industrial                    | <a href="http://www.ti.com/industrial">www.ti.com/industrial</a>                         |
| Medical                       | <a href="http://www.ti.com/medical">www.ti.com/medical</a>                               |
| Security                      | <a href="http://www.ti.com/security">www.ti.com/security</a>                             |
| Space, Avionics and Defense   | <a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a> |
| Video and Imaging             | <a href="http://www.ti.com/video">www.ti.com/video</a>                                   |

### TI E2E Community

[e2e.ti.com](http://e2e.ti.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.