

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0424109176

Status:

Active

Overview:

[modular_plugs_jacks](#)

Description:

Modular Jack, Vertical, 8/2, Panel Stops

Documents:

[3D Model](#)

[Drawing \(PDF\)](#)

[Product Specification PS-42410 \(PDF\)](#)

[RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA	LR19980
UL	E107635

General

Product Family	Modular Jacks/Plugs
Series	42410
Comments	Flush Mount Flangeless 2 PCB Thick
Component Type	PCB Jack
Magnetic	No
Overview	modular_plugs_jacks
Performance Category	3
Power over Ethernet (PoE)	N/A
Product Name	RJ45

Physical

Color - Resin	Black
Durability (mating cycles max)	500
Flammability	94V-0
Inverted / Top Latch	N/A
Lightpipes/LEDs	None
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Polyester
Orientation	Vertical (Top Entry)
PCB Retention	Yes
PCB Thickness Recommended (in)	0.062 In
PCB Thickness Recommended (mm)	1.60 mm
Packaging Type	Tray
Pitch - Mating Interface (in)	0.050 In
Pitch - Mating Interface (mm)	1.27 mm
Plating min: Mating (µin)	50
Plating min: Mating (µm)	1.25
Plating min: Termination (µin)	100
Plating min: Termination (µm)	2.5
Ports	1
Positions / Loaded Contacts	8/2
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-40°C to +80°C
Termination Interface: Style	Through Hole
Wire/Cable Type	N/A

Electrical

Current - Maximum per Contact	1.5A
Shielded	No
Voltage - Maximum	125V




image - Reference only

Series

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Halogen-Free
Status
Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[42410Series](#)

Mates With
FCC 68 Plugs

Solder Process Data

Duration at Max. Process Temperature (seconds)	5
Lead-free Process Capability	Wave Capable (TH only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	235

Material Info

Reference - Drawing Numbers

Packaging Specification	PK-42410-492
Product Specification	PS-42410
Sales Drawing	SDA-42410-****
Test Summary	TS-42878-001

This document was generated on 06/07/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

SIZE 4 VERTICAL MODJACK ASSEMBLIES

Y-NOT TOOLED

ASSEMBLY ITEM NUMBER

EXTERNAL CONNECTOR SIZE

NUMBER OF POSITIONS

P.C. BOARD THICKNESS

MOUNTING EARS OPTION

TERMINAL PLATING OPTION

42410-4168

4 POS. BODY

4

.062/(1.57)

YES

A

42410-4170

↑

↑

.062/(1.57)

NO

A

42410-4264

↓

↓

.125/(3.18)

YES

A

42410-4266

4 POS. BODY

4

.125/(3.18)

NO

A

42410-4312

4 POS. BODY

2

.062/(1.57)

YES

A

42410-4314

↑

↑

.062/(1.57)

NO

A

42410-4408

↓

↓

.125/(3.18)

YES

A

42410-4410

4 POS. BODY

2

.125/(3.18)

NO

A

SIZE 6 VERTICAL MODJACK ASSEMBLIES

Y-NOT TOOLED

ASSEMBLY ITEM NUMBER

EXTERNAL CONNECTOR SIZE

NUMBER OF POSITIONS

P.C. BOARD THICKNESS

MOUNTING EARS OPTION

TERMINAL PLATING OPTION

42410-6168

6 POS. BODY

6

.062/(1.57)

YES

A

42410-6170

↑

↑

.062/(1.57)

NO

A

42410-6264

↓

↓

.125/(3.18)

YES

A

42410-6266

6 POS. BODY

6

.125/(3.18)

NO

A

42410-6312

6 POS. BODY

4

.062/(1.57)

YES

A

42410-6314

↑

↑

.062/(1.57)

NO

A

42410-6320

↑

↑

.062/(1.57)

YES

B

42410-6408

↓

↓

.125/(3.18)

YES

A

42410-6410

6 POS. BODY

4

.125/(3.18)

NO

A

42410-6456

6 POS. BODY

2

.062/(1.57)

YES

A

42410-6458

↑

↑

.062/(1.57)

NO

A

42410-6552

↓

↓

.125/(3.18)

YES

A

42410-6554

6 POS. BODY

2

.125/(3.18)

NO

A

SIZE 8 VERTICAL MODJACK ASSEMBLIES

Y-NOT TOOLED

ASSEMBLY ITEM NUMBER

EXTERNAL CONNECTOR SIZE

NUMBER OF POSITIONS

P.C. BOARD THICKNESS

KEYING OPTION

MOUNTING EARS OPTION

TERMINAL PLATING OPTION

42410-8312

8 POS. BODY

8

.062/(1.57)

NO

YES

A

42410-8314

↑

↑

.062/(1.57)

NO

NO

A

42410-8360

↑

↑

.062/(1.57)

YES

YES

A

42410-8362

↑

↑

.062/(1.57)

YES

NO

A

42410-8504

.125/(3.18)

NO

YES

A

42410-8506

.125/(3.18)

NO

NO

A

42410-8552

↓

↓

.125/(3.18)

YES

YES

A

42410-8554

8 POS. BODY

8

.125/(3.18)

YES

NO

A

42410-8600

8 POS. BODY

6

.062/(1.57)

NO

YES

A

42410-8602

↑

↑

.062/(1.57)

NO

NO

A

42410-8648

↑

↑

.062/(1.57)

YES

YES

A

42410-8650

↑

↑

.062/(1.57)

YES

NO

A

42410-8792

.125/(3.18)

NO

YES

A

42410-8794

.125/(3.18)

NO

NO

A

42410-8840

↓

↓

.125/(3.18)

YES

YES

A

42410-8842

8 POS. BODY

6

.125/(3.18)

YES

NO

A

42410-8888

8 POS. BODY

4

.062/(1.57)

NO

YES

A

42410-8890

↑

↑

.062/(1.57)

NO

NO

A

42410-8936

↑

↑

.062/(1.57)

YES

YES

A

42410-8938

↑

↑

.062/(1.57)

YES

NO

A

42410-9080

.125/(3.18)

NO

YES

A

42410-9082

.125/(3.18)

NO

NO

A

42410-9128

↓

↓

.125/(3.18)

YES

YES

A

42410-9130

8 POS. BODY

4

.125/(3.18)

YES

NO

A

42410-9176

8 POS. BODY

2

.062/(1.57)

NO

YES

A

42410-9178

↑

↑

.062/(1.57)

NO

NO

A

42410-9224

↑

↑

.062/(1.57)

YES

YES

A

42410-9226

↑

↑

.062/(1.57)

YES

NO

A

42410-9368

.125/(3.18)

NO

YES

A

42410-9370

.125/(3.18)

NO

NO

A

42410-9416

↓

↓

.125/(3.18)

YES

YES

A

42410-9418

8 POS. BODY

2

.125/(3.18)

YES

NO

A

SEE SHEET ONE

EC NO: UCP2004-167

DRAWN: SCHMIDT 2004/03/03

CHECK: SCHMIDT 2004/03/03

APPROVE: SCHMIDT 2004/03/03

REV: N

QUALITY SYMBOLS

▽.0

▽.0

GENERAL TOLERANCES (UNLESS SPECIFIED)

mmINCH

4 PLACES ±---±---

3 PLACES ±---±---

2 PLACES ±---±---

1 PLACE ±---±---

ANGULAR ±1/2°

DRAFT WHERE APPLICABLE

MUST REMAIN WITHIN DIMENSIONS

SCALE ---INCH

DESIGN UNITS IN/MM

DRAWN BY DATE

GLT 1990/10/12

CHECKED BY DATE

BAP 1990/10/12

APPROVED BY DATE

RAS 1990/10/12

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

THIRD ANGLE PROJECTION

REVISE ON CAD ONLY

ASSEMBLY, VERTICAL MODULAR JACKS

MATERIAL NO. DOCUMENT NO. SHEET NO.

SEE CHART SDA-42410-**** 4 OF 4

MOLEX MOLEX INCORPORATED

D

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.