

# 3SMAJ5913B THRU 3SMAJ5956B

## 3.0 Watt Surface Mount Silicon Zener Diodes

### Features

- 3.3thru 200 Volt Voltage Range
- Low Inductance, Low Profile Mounting
- Glass Passivated Junction
- High specified maximum current(I<sub>ZM</sub>)when adequately heat sinking
- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)
- Halogen free available upon request by adding suffix "-HF"
- Surface Mount Application

### Mechanical Data


- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Terminals solderable per MIL-STD-750, Method 2026
- Polarity is indicated by cathode band.
- Packaging: Standard 12mm Tape (see EIA 481)
- Maximum temperature for soldering: 260 °C for 10 seconds.

### Maximum Ratings @ 25°C Unless Otherwise Specified

|                                     |                                   |                 |           |
|-------------------------------------|-----------------------------------|-----------------|-----------|
| Maximum Forward Voltage             | V <sub>F</sub>                    | 1.5V            | (Note: 2) |
| Steady State Power Dissipation      | P <sub>d</sub>                    | 3.0W            | (Note: 3) |
| Operation and Storage Temperature   | T <sub>J</sub> , T <sub>STG</sub> | -55°C to +150°C |           |
| Thermal Resistance Junction to Lead | R <sub>thJL</sub>                 | 25°C/W          |           |


- Note: 1. High Temperature Solder Exemptions Applied, see EU Directive Annex 7.  
 2. Forward Current @ 200mA.  
 3. Mounted on 5.0mm<sup>2</sup> (1oz thick) land areas.  
 Lead temperature at T<sub>L</sub>=75°C

### DO-214AC (SMA) (LEAD FRAME)



| DIM | DIMENSIONS |      |      |      | NOTE |
|-----|------------|------|------|------|------|
|     | INCHES     |      | MM   |      |      |
| A   | .079       | .096 | 2.00 | 2.44 |      |
| B   | .050       | .064 | 1.27 | 1.63 |      |
| C   | .002       | .008 | .05  | .20  |      |
| D   | ---        | .02  | ---  | .51  |      |
| E   | .030       | .060 | .76  | 1.52 |      |
| F   | .065       | .091 | 1.65 | 2.32 |      |
| G   | .189       | .220 | 4.80 | 5.59 |      |
| H   | .157       | .181 | 4.00 | 4.60 |      |
| J   | .090       | .115 | 2.25 | 2.92 |      |

#### SUGGESTED SOLDER PAD LAYOUT



### 3SMAJ5913B thru 3SMAJ5956B

Micro Commercial Components

ELECTRICAL CHARACTERISTICS ( $T_L=30C$  unless otherwise noted) ( $V_F=1.5$ Volts Max @  $I_F=200$ mA for all types.)

| MCC PART NUMBER | ZENER VOLTAGE $V_Z (1)$ | TEST CURRENT $I_{ZT}$ | MAXIMUM DYNAMIC IMPEDANCE $Z_{ZT} @ I_{ZT}$ | KNEE CURRENT $I_{ZK}$ | KNEE IMPEDANCE $Z_{ZK}$ | MAXIMUM REVERSE CURRENT $I_R$ | REVERSE VOLTAGE $V_R$ | Maximum DC Zener Current $I_{ZM}$ | DEVICE MARKING |
|-----------------|-------------------------|-----------------------|---|-----------------------|-------------------------|-------------------------------|-----------------------|-----------------------------------|----------------|
|                 | VOLTS                   | mA                    | OHMS  | mA                    | OHMS                    | $\mu$ A                       | VOLTS                 | mA                                |                |
| 3SMAJ5913B      | 3.3                     | 113.6                 | 10  | 1                     | 500                     | 100                           | 1                     | 908                               | H13B           |
| 3SMAJ5914B      | 3.6                     | 104.2                 | 9   | 1                     | 500                     | 75                            | 1                     | 832                               | H14B           |
| 3SMAJ5915B      | 3.9                     | 96.1                  | 7.5   | 1                     | 500                     | 25                            | 1                     | 768                               | H15B           |
| 3SMAJ5916B      | 4.3                     | 87.2                  | 6   | 1                     | 500                     | 5                             | 1                     | 696                               | H16B           |
| 3SMAJ5917B      | 4.7                     | 79.8                  | 5   | 1                     | 500                     | 5                             | 1.5                   | 638                               | H17B           |
| 3SMAJ5918B      | 5.1                     | 73.5                  | 4   | 1                     | 350                     | 5                             | 2                     | 588                               | H18B           |
| 3SMAJ5919B      | 5.6                     | 66.9                  | 2   | 1                     | 250                     | 5                             | 3                     | 534                               | H19B           |
| 3SMAJ5920B      | 6.2                     | 60.5                  | 2   | 1                     | 200                     | 5                             | 4                     | 482                               | H20B           |
| 3SMAJ5921B      | 6.8                     | 55.1                  | 2.5   | 1                     | 200                     | 5                             | 5.2                   | 440                               | H21B           |
| 3SMAJ5922B      | 7.5                     | 50                    | 3   | 0.5                   | 400                     | 5                             | 6                     | 400                               | H22B           |
| 3SMAJ5923B      | 8.2                     | 45.7                  | 3.5   | 0.5                   | 400                     | 5                             | 6.5                   | 364                               | H23B           |
| 3SMAJ5924B      | 9.1                     | 41.2                  | 4   | 0.5                   | 500                     | 5                             | 7                     | 328                               | H24B           |
| 3SMAJ5925B      | 10                      | 37.5                  | 4.5   | 0.25                  | 500                     | 5                             | 8                     | 300                               | H25B           |
| 3SMAJ5926B      | 11                      | 34.1                  | 5.5   | 0.25                  | 550                     | 1                             | 8.4                   | 272                               | H26B           |
| 3SMAJ5927B      | 12                      | 31.2                  | 6.5   | 0.25                  | 550                     | 1                             | 9.1                   | 250                               | H27B           |
| 3SMAJ5928B      | 13                      | 28.8                  | 7   | 0.25                  | 550                     | 1                             | 9.9                   | 230                               | H28B           |
| 3SMAJ5929B      | 15                      | 25                    | 9   | 0.25                  | 600                     | 1                             | 11.4                  | 200                               | H29B           |
| 3SMAJ5930B      | 16                      | 23.4                  | 10  | 0.25                  | 600                     | 1                             | 12.2                  | 186                               | H30B           |
| 3SMAJ5931B      | 18                      | 20.8                  | 12  | 0.25                  | 650                     | 1                             | 13.7                  | 166                               | H31B           |
| 3SMAJ5932B      | 20                      | 18.7                  | 14  | 0.25                  | 650                     | 1                             | 15.2                  | 150                               | H32B           |
| 3SMAJ5933B      | 22                      | 17                    | 17.5  | 0.25                  | 650                     | 1                             | 16.7                  | 136                               | H33B           |
| 3SMAJ5934B      | 24                      | 15.6                  | 19  | 0.25                  | 700                     | 1                             | 18.2                  | 124                               | H34B           |
| 3SMAJ5935B      | 27                      | 13.9                  | 23  | 0.25                  | 700                     | 1                             | 20.6                  | 110                               | H35B           |
| 3SMAJ5936B      | 30                      | 12.5                  | 28  | 0.25                  | 750                     | 1                             | 22.8                  | 100                               | H36B           |
| 3SMAJ5937B      | 33                      | 11.4                  | 33  | 0.25                  | 800                     | 1                             | 25.1                  | 90                                | H37B           |
| 3SMAJ5938B      | 36                      | 10.4                  | 38  | 0.25                  | 850                     | 1                             | 27.4                  | 82                                | H38B           |
| 3SMAJ5939B      | 39                      | 9.6                   | 45  | 0.25                  | 900                     | 1                             | 29.7                  | 76                                | H39B           |
| 3SMAJ5940B      | 43                      | 8.7                   | 53  | 0.25                  | 950                     | 1                             | 32.7                  | 68                                | H40B           |
| 3SMAJ5941B      | 47                      | 8                     | 67  | 0.25                  | 1000                    | 1                             | 35.8                  | 62                                | H41B           |
| 3SMAJ5942B      | 51                      | 7.3                   | 70  | 0.25                  | 1100                    | 1                             | 38.8                  | 58                                | H42B           |
| 3SMAJ5943B      | 56                      | 6.7                   | 86  | 0.25                  | 1300                    | 1                             | 42.6                  | 52                                | H43B           |
| 3SMAJ5944B      | 62                      | 6                     | 100   | 0.25                  | 1500                    | 1                             | 47.1                  | 48                                | H44B           |
| 3SMAJ5945B      | 68                      | 5.5                   | 120   | 0.25                  | 1700                    | 1                             | 51.7                  | 44                                | H45B           |
| 3SMAJ5946B      | 75                      | 5                     | 140   | 0.25                  | 2000                    | 1                             | 56                    | 40                                | H46B           |
| 3SMAJ5947B      | 82                      | 4.6                   | 160   | 0.25                  | 2500                    | 1                             | 62.2                  | 36                                | H47B           |
| 3SMAJ5948B      | 91                      | 4.1                   | 200   | 0.25                  | 3000                    | 1                             | 69.2                  | 32                                | H48B           |
| 3SMAJ5949B      | 100                     | 3.7                   | 250   | 0.25                  | 3100                    | 1                             | 76                    | 30                                | H49B           |
| 3SMAJ5950B      | 110                     | 3.4                   | 300   | 0.25                  | 4000                    | 1                             | 83.6                  | 26                                | H50B           |
| 3SMAJ5951B      | 120                     | 3.1                   | 380   | 0.25                  | 4500                    | 1                             | 91.2                  | 24                                | H51B           |
| 3SMAJ5952B      | 130                     | 2.9                   | 450   | 0.25                  | 5000                    | 1                             | 98.8                  | 22                                | H52B           |
| 3SMAJ5953B      | 150                     | 2.5                   | 600   | 0.25                  | 6000                    | 1                             | 114                   | 20                                | H53B           |
| 3SMAJ5954B      | 160                     | 2.3                   | 700   | 0.25                  | 6500                    | 1                             | 121.6                 | 18                                | H54B           |
| 3SMAJ5955B      | 180                     | 2.1                   | 900   | 0.25                  | 7000                    | 1                             | 136.8                 | 16                                | H55B           |
| 3SMAJ5956B      | 200                     | 1.9                   | 1200  | 0.25                  | 8000                    | 1                             | 152                   | 14                                | H56B           |

Note 1: TOLERANCE AND VOLTAGE DESIGNATION - The type numbers listed indicate a tolerance of +/- 5%.

RATING AND CHARACTERISTICS CURVES  
**3SMAJ5913B thru 3SMAJ5956B**




Fig. 1-STEADY STATE POWER DERATING




Fig. 2-ZENER VOLTAGE- 3 TO 12 VOLTS



Fig. 3-ZENER VOLTAGE-10 TO 200 VOLTS




Fig. 4-EFFECT OF ZENER CURRENT






Fig. 7-VZ = 12 THRU 40 VOLTS



Micro Commercial Components

### Ordering Information :

| Device         | Packing                 |
|----------------|-------------------------|
| Part Number-TP | Tape&Reel: 7.5Kpcs/Reel |

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.