

**2.0A HIGH EFFICIENCY SCHOTTKY BARRIER RECTIFIER**  
**POWERDI®123**
**Features**

- Guard Ring Die Construction for Transient Protection
- Low Power Loss, High Efficiency
- Low  $V_F$  and Low Leakage Current
- Patented Interlocking Clip Design for High Surge Current Capacity
- **Lead Free Finish, RoHS Compliant (Note 1)**
- **"Green" Molding Compound (No Br, Sb)**
- **Qualified to AEC-Q101 Standards for High Reliability**

**Mechanical Data**

- Case: POWERDI®123
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminal Connections: Cathode Band
- Terminals: Finish – Matte Tin annealed over Copper Leadframe. Solderable per MIL-STD-202, Method 208 ③
- Weight: 0.01 grams (approximate)



Top View

**Ordering Information** (Note 2)

| Part Number | Case        | Packaging        |
|-------------|-------------|------------------|
| DFLS230LH-7 | POWERDI®123 | 3000/Tape & Reel |

Notes: 1. EU Directive 2002/95/EC (RoHS). All applicable RoHS exemptions applied, see EU Directive 2002/95/EC Annex Notes  
 2. For packaging details, go to our website at <http://www.diodes.com>.

**Marking Information**


F03H = Product Type Marking Code  
 YM = Date Code Marking  
 Y = Year (ex: T = 2006)  
 M = Month (ex: 9 = September)

## Date Code Key

| Year | 2005 | 2006 | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 |
|------|------|------|------|------|------|------|------|------|
| Code | S    | T    | U    | V    | W    | X    | Y    | Z    |

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code  | 1   | 2   | 3   | 4   | 5   | 6   | 7   | 8   | 9   | O   | N   | D   |

POWERDI is a registered trademark of Diodes Incorporated.

DFLS230LH

Document number: DS30583 Rev. 5 - 2

1 of 4

[www.diodes.com](http://www.diodes.com)

May 2011

© Diodes Incorporated

## Maximum Ratings @T<sub>A</sub> = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.  
 For capacitance load, derate current by 20%.

| Characteristic                                                                                      | Symbol              | Value | Unit |
|-----------------------------------------------------------------------------------------------------|---------------------|-------|------|
| Peak Repetitive Reverse Voltage                                                                     | V <sub>RRM</sub>    | 30    | V    |
| Working Peak Reverse Voltage                                                                        | V <sub>RWM</sub>    |       |      |
| DC Blocking Voltage                                                                                 | V <sub>R</sub>      |       |      |
| RMS Reverse Voltage                                                                                 | V <sub>R(RMS)</sub> | 21    | V    |
| Average Forward Current                                                                             | I <sub>F(AV)</sub>  | 2.0   | A    |
| Non-Repetitive Peak Forward Surge Current 8.3ms<br>Single Half Sine-Wave Superimposed on Rated Load | I <sub>FSM</sub>    | 75    | A    |

## Thermal Characteristics

| Characteristic                                          | Symbol           | Typ         | Max | Unit |
|---------------------------------------------------------|------------------|-------------|-----|------|
| Thermal Resistance Junction to Soldering Point (Note 3) | R <sub>θJS</sub> | —           | 6   | °C/W |
| Operating Temperature Range                             | T <sub>J</sub>   | -65 to +150 |     | °C   |
| Storage Temperature Range                               | T <sub>STG</sub> | -65 to +150 |     | °C   |

## Electrical Characteristics @T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                     | Symbol             | Min | Typ | Max           | Unit | Test Condition                                                                              |
|------------------------------------|--------------------|-----|-----|---------------|------|---------------------------------------------------------------------------------------------|
| Reverse Breakdown Voltage (Note 4) | V <sub>(BR)R</sub> | 30  | —   | —             | V    | I <sub>R</sub> = 200μA                                                                      |
| Forward Voltage                    | V <sub>F</sub>     | —   | —   | 0.45<br>0.375 | V    | I <sub>F</sub> = 2A, T <sub>J</sub> = 25°C<br>I <sub>F</sub> = 2A, T <sub>J</sub> = 125°C   |
| Leakage Current (Note 4)           | I <sub>R</sub>     | —   | —   | 0.200<br>15   | mA   | V <sub>R</sub> = 30V, T <sub>J</sub> = 25°C<br>V <sub>R</sub> = 30V, T <sub>J</sub> = 100°C |
| Total Capacitance                  | C <sub>T</sub>     | —   | 85  | —             | pF   | V <sub>R</sub> = 10V, f = 1.0MHz                                                            |

- Notes:
3. Theoretical R<sub>θJS</sub> calculated from the top center of the die straight down to the PCB/cathode tab solder junction.
  4. Short duration pulse test used to minimize self-heating effect.
  5. Part mounted on FR-4 board with 2 oz., minimum recommended copper pad layout which can be found on our website at <http://www.diodes.com>.  
T<sub>A</sub> = 25°C




Fig. 1 Typical Forward Characteristics







Fig. 2 Typical Reverse Characteristics

POWERDI is a registered trademark of Diodes Incorporated.




## Package Outline Dimensions



| POWERDI®123          |      |      |      |
|----------------------|------|------|------|
| Dim                  | Min  | Max  | Typ  |
| A                    | 3.50 | 3.90 | 3.70 |
| B                    | 2.60 | 3.00 | 2.80 |
| C                    | 1.63 | 1.93 | 1.78 |
| D                    | 0.93 | 1.00 | 0.98 |
| E                    | 0.85 | 1.25 | 1.00 |
| H                    | 0.15 | 0.25 | 0.20 |
| L                    | 0.40 | 0.50 | 0.45 |
| L1                   | -    | -    | 1.35 |
| L2                   | -    | -    | 1.10 |
| L3                   | -    | -    | 0.20 |
| All Dimensions in mm |      |      |      |

## Suggested Pad Layout



| Dimensions | Value (in mm) |
|------------|---------------|
| G          | 1.0           |
| X1         | 2.2           |
| X2         | 0.9           |
| Y1         | 1.4           |
| Y2         | 1.4           |

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2011, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.