



SIGN	DATE	DESCRIPTION	APPROVER
△	2009.6.08	Add UL standard	Jacke
△	2009.6.08	The current rating and operating temperature are changed	Jacke
△	2009.6.08	Corrected dimension △ from 2.3mm to 2.5mm	Jacke
△	2010.01.22	The demension is changed from 1.60mm to 1.10mm	Jacke
△	2010.01.22	The demension is changed from 0.40mm to 0.20~0.30mm	Jacke
△	2010.03.31	The material is changed from Brass to Copper	Jacke
△	2010.04.01	The design is changed	Jacke

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

**Material**

- Item (a) Contact pin: Copper Tin plated
  - Item (b) Terminal (housing): Thermoplastic (UL94V-0)
  - Item (c) Terminal (cover): Thermoplastic (UL94V-0)
- Electrica cULus
- Voltage rating: 300VAC
  - △ ● Current rating: 8A
  - Wire range:
    - Solid wire(AWG):
    - Stranded wire(AWG):
  - Withstanding Voltage: 1.6KV
  - Operating temperature: -40°C to +115°C
  - △ ● Soldering temperature: 250°C±10°C/5 Sec
  - △ ● Safety Approval: us

**VL xx 1 3 x 0 xxxx G**

- G: Pb<40000ppm
- |                  |                     |                                                                        |
|------------------|---------------------|------------------------------------------------------------------------|
| POLES            | COLOR               | 000 0 "@ " logo                                                        |
| 04 2x2 CONTACTS  | 0 Black (RAL9005)   | 000 A "ANY" logo                                                       |
| 06 2x3 CONTACTS  | 2 Red (RAL3001/D)   | Any special item by customer request, please contact sales department. |
| ...              | 3 Orange(RAL2011/P) |                                                                        |
| 48 2x24 CONTACTS | 4 Yellow(RAL1018/A) |                                                                        |
|                  | 5 Green(RAL6018/T)  |                                                                        |
|                  | 6 Blue (RAL5015/A)  |                                                                        |
|                  | 8 Grey(RAL7035/D)   |                                                                        |

Poles	04	06	08	10	12	14	16	18	20	22	24	26
Dim L	8.5	12.0	15.5	19.0	22.5	26.0	29.5	33.0	36.5	40.0	43.5	47.0
Dim B	3.50	7.00	10.5	14.0	17.5	21.0	24.5	28.0	31.5	35.0	38.5	42.0
TOL	±0.15						±0.20					
Poles	28	30	32	34	36	38	40	42	44	46	48	
Dim L	50.5	54.0	57.5	61.0	64.5	68.0	71.5	75.0	78.5	82.0	85.5	
Dim B	45.5	49.0	52.5	56.0	59.5	63.0	66.5	70.0	73.5	77.0	80.5	
TOL	±0.25						±0.30					

<b>ANYTEK</b>				<b>CUSTOMER COPY</b>			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		VL-3.5mm Vertical Series "B Type"					
PART NO.		VLxx13x0xxxxG			DWG NO.		8VL0401
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Jacke	Jacke			X. ±0.50
			2010.03.31	2010.01.22			X.X ±0.30
							X.XX ±0.10
							X° ±1°
				SHEET: 01/01		REV.: D	



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.