

# Compact Ultrasonic Sensor

## E4E2

CSM\_E4E2\_DS\_E\_2\_1

### Compact, Through-beam, Ultrasonic Sensor

CE

- Provides stable detection of transparent films, transparent bottles, PET bottles, and other similar workpieces.
- Compact design with built-in amplifier allows easy mounting on small conveyor lines.
- Detects as far as 500 mm away.
- Equipped with stability indicator.



 Refer to *Safety Precautions* on page 3.

For the most recent information on models that have been certified for safety standards, refer to your OMRON website.

### Ordering Information


| Sensing method | Sensing distance |  |  |        | Output configuration                       | Model                 |
|----------------|------------------|--|--|--------|--------------------------------------------|-----------------------|
| Through-beam   |                  |  |  |        | NPN open collector<br>NO (normally open)   | <b>E4E2-TS50C1 2M</b> |
|                |                  |  |  | 500 mm | NPN open collector<br>NC (normally closed) | <b>E4E2-TS50C2 2M</b> |

## Ratings and Specifications


| Item                                           | Model | E4E2-TS50C□                                                                                             |
|------------------------------------------------|-------|---------------------------------------------------------------------------------------------------------|
| Sensing distance                               |       | 500 mm                                                                                                  |
| Standard sensing object                        |       | 40 × 40 × 2 mm SPCC plate                                                                               |
| Response frequency                             |       | 20 Hz max.                                                                                              |
| Power supply voltage (operating voltage range) |       | 24 VDC (21.6 to 26.4 V) with a max. ripple (p-p) 10%                                                    |
| Current consumption                            |       | E4E2-TS50TC1 Emitter: 25 mA max. at 24 VDC<br>E4E2-TS50RC1 Receiver: 15 mA max. at 24 VDC               |
| Control output                                 |       | NPN open collector, Load voltage: 26.4 VDC max., Load current: 100 mA max. (Residual voltage: 1 V max.) |
| Indicators                                     |       | Emitter: Power indicator (red)<br>Receiver: Operation indicator (red), Stability indicator (green)      |
| Ambient temperature                            |       | Operating: 0 to 50°C, Storage: -10 to 55°C (with no icing or condensation)                              |
| Ambient humidity                               |       | Operating and storage: 35% to 85% (with no condensation)                                                |
| Insulation resistance                          |       | 100 MΩ min. (at 500 VDC) between current-carrying parts and case                                        |
| Dielectric strength                            |       | 1,500 VAC (50/60 Hz) for 1 min between current-carrying parts and case                                  |
| Vibration resistance                           |       | Destruction: 10 to 55 Hz, 1.5-mm double amplitude for 2 hours each in X, Y, and Z directions            |
| Shock resistance                               |       | Destruction: 500 m/s <sup>2</sup> three times each in X, Y, and Z directions                            |
| Degree of protection                           |       | IP64 (IEC)                                                                                              |
| Connection method                              |       | Pre-wired (Standard cable length: 2 m)                                                                  |
| Weight (packed state)                          |       | Approx. 160 g (Emitter and Receiver)                                                                    |
| Materials                                      |       | Case: ABS resin, Oscillator surface: Epoxy resin                                                        |
| Accessories                                    |       | Mounting Bracket (with screws), adjustment screwdriver, instruction sheet                               |

## Engineering Data (Reference Value)


### Sensing Range Diagram



### Sensing Distance and Sensing Object Size



### Parallel Movement



## I/O Circuit Diagram

| Output configuration | Model       | Operating mode | Timing chart                                                                                                              | Output circuit |
|----------------------|-------------|----------------|---------------------------------------------------------------------------------------------------------------------------|----------------|
| NPN output           | E4E2-TS50C1 | No-incident ON | Incident sound: ON<br>No incident sound: OFF<br>Control output (NPN open collector): ON<br>Operation indicator (red): ON  |                |
|                      | E4E2-TS50C2 | Incident ON    | Incident sound: ON<br>No incident sound: OFF<br>Control output (NPN open collector): ON<br>Operation indicator (red): OFF |                |

## Safety Precautions

Refer to the *Technical Guide*.



### WARNING

This product is not designed or rated for ensuring safety of persons. Do not use it for such purpose.



### Precautions for Correct Use

Do not use the product in atmospheres or environments that exceed product ratings.

#### • Designing the System

##### Power ON

The E4E2 needs a maximum of 100 ms to be ready to operate after the E4E2 is turned ON. If power is supplied to the E4E2 and the load independently, be sure to turn ON the E4E2 first.

#### • Installation

##### Mounting

Mount the Emitter and Receiver so that they face each other in a straight line, and so that they are within the specified sensing distance.

##### Mutual Interference

If more than one Sensor is closely mounted together or used in a narrow space, mutual interference of the Sensors will result.

#### • Adjustment

##### Sensitivity Adjuster

- Check the power indicator (red) of the Emitter, then turn the sensitivity adjuster (ADJ) clockwise as far as it will go.
- Be sure not to turn the sensitivity adjuster excessively. If the sensitivity adjuster is turned beyond the permissible range, no sensitivity adjustment will be possible.

##### Indicators


- The green indicator on the Receiver shows stability during sound input. Adjust the mounting shaft so that this indicator light brightly when there is no sensing object present.
- While passing a sensing object through the path, adjust the operation indicator (red) on the Receiver so that it light and goes out correctly.

# Dimensions

Tolerance class IT16 applies to dimensions in this data sheet unless otherwise specified.


## Emitter

### E4E2-TS50TC1



## Receiver

### E4E2-TS50RC1



## Terms and Conditions Agreement

### Read and understand this catalog.

Please read and understand this catalog before purchasing the products. Please consult your OMRON representative if you have any questions or comments.

### Warranties.

(a) Exclusive Warranty. Omron's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Omron (or such other period expressed in writing by Omron). Omron disclaims all other warranties, express or implied.

(b) Limitations. OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS. BUYER ACKNOWLEDGES THAT IT ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE.

Omron further disclaims all warranties and responsibility of any type for claims or expenses based on infringement by the Products or otherwise of any intellectual property right. (c) Buyer Remedy. Omron's sole obligation hereunder shall be, at Omron's election, to (i) replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product, (ii) repair the non-complying Product, or (iii) repay or credit Buyer an amount equal to the purchase price of the non-complying Product; provided that in no event shall Omron be responsible for warranty, repair, indemnity or any other claims or expenses regarding the Products unless Omron's analysis confirms that the Products were properly handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Omron before shipment. Omron Companies shall not be liable for the suitability or unsuitability or the results from the use of Products in combination with any electrical or electronic components, circuits, system assemblies or any other materials or substances or environments. Any advice, recommendations or information given orally or in writing, are not to be construed as an amendment or addition to the above warranty.

See <http://www.omron.com/global/> or contact your Omron representative for published information.

### Limitation on Liability; Etc.

OMRON COMPANIES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY.

Further, in no event shall liability of Omron Companies exceed the individual price of the Product on which liability is asserted.

### Suitability of Use.

Omron Companies shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in the Buyer's application or use of the Product. At Buyer's request, Omron will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases.

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY OR IN LARGE QUANTITIES WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT(S) IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

### Programmable Products.

Omron Companies shall not be responsible for the user's programming of a programmable Product, or any consequence thereof.

### Performance Data.

Data presented in Omron Company websites, catalogs and other materials is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of Omron's test conditions, and the user must correlate it to actual application requirements. Actual performance is subject to the Omron's Warranty and Limitations of Liability.

### Change in Specifications.

Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our practice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the Product may be changed without any notice. When in doubt, special part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Omron's representative at any time to confirm actual specifications of purchased Product.

### Errors and Omissions.

Information presented by Omron Companies has been checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors or omissions.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.