


Features

- ◆ Smallest encapsulated 20W Converter!
Ultra compact size: 1.0" x 1.0" x 0.4"
- ◆ Shielded metal case with isolated baseplate
- ◆ Wide 2:1 input voltage ranges
- ◆ Very high efficiency up to 90%
- ◆ Output voltage adjustable
- ◆ Remote On/Off control
- ◆ Operating temp. range -40°C to $+75^{\circ}\text{C}$
and up to 85°C with heat-sink
- ◆ I/O isolation voltage 1500 VDC
- ◆ Input filter meets EN 55022 class A
without external components
- ◆ No minimum load required
- ◆ Lead free design, RoHS compliant
- ◆ 3-year product warranty



The THN-20 series is the latest generation of high performance dc-dc converter modules with highest power density. The product achieves 20W output power while it comes in a metal case with dimensions of only 1.0"x 1.0"x 0.4".

All models have an wide 2:1 input voltage range and precisely regulated output voltages, even under no load conditions. Highest efficiency of up to 90% makes this product very reliable and applicable in temperature ranges of up to 75°C or 85°C with optional mounted heat sink. Together with low input current characteristics at minimal load and remote On/Off control these converters are the ideal solution for battery-operated systems. Typical applications are in mobile equipments, instrumentation, distributed power architectures in communication and industrial electronics and everywhere where space on the PCB is critical.

Models

| Order code | Input voltage range | Output voltage | Output current max. | Efficiency typ. |
|-------------|---------------------------------|----------------|---------------------|-----------------|
| THN 20-1210 | 9 – 18 VDC (12 VDC nominal) | 3.3 VDC | 4500 mA | 86 % |
| THN 20-1211 | | 5.0 VDC | 4000 mA | 90 % |
| THN 20-1212 | | 12 VDC | 1670 mA | 89 % |
| THN 20-1213 | | 15 VDC | 1330 mA | 89 % |
| THN 20-1222 | | ± 12 VDC | ± 833 mA | 89 % |
| THN 20-1223 | | ± 15 VDC | ± 667 mA | 89 % |
| THN 20-2410 | 18 – 36 VDC (24 VDC nominal) | 3.3 VDC | 4500 mA | 86 % |
| THN 20-2411 | | 5.0 VDC | 4000 mA | 90 % |
| THN 20-2412 | | 12 VDC | 1670 mA | 90 % |
| THN 20-2413 | | 15 VDC | 1330 mA | 90 % |
| THN 20-2422 | | ± 12 VDC | ± 833 mA | 90 % |
| THN 20-2423 | | ± 15 VDC | ± 667 mA | 90 % |
| THN 20-4810 | 36 – 75 VDC (48 VDC nominal) | 3.3 VDC | 4500 mA | 86 % |
| THN 20-4811 | | 5.0 VDC | 4000 mA | 90 % |
| THN 20-4812 | | 12 VDC | 1670 mA | 90 % |
| THN 20-4813 | | 15 VDC | 1330 mA | 90 % |
| THN 20-4822 | | ± 12 VDC | ± 833 mA | 90 % |
| THN 20-4823 | | ± 15 VDC | ± 667 mA | 90 % |

Input Specifications

| | |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Input current at no load (at nominal input voltage) | 12 V models: 10 mA typ. 24 V models: 6 mA typ. 48 V models: 4 mA typ. |
| Input current at full load (at nominal input voltage) | 12 V; 3.3 VDC models: 1510 mA typ. 12 V; other models: 1960 mA typ. 24 V; 3.3 VDC models: 755 mA typ.. 24 V; other models: 970 mA typ.. 48 V; 3.3 VDC models: 375 mA typ. 48 V; other models: 485 mA typ. |
| Start-up voltage / under voltage shut down | 12 Vin models: 9 VDC / 8 VDC 24 Vin models: 18 VDC / 16 VDC 48 Vin models: 36 VDC / 33 VDC |
| Surge voltage (1 sec. max.) | 12 Vin models: 25 V max. 24 Vin models: 50 V max. 48 Vin models: 100 V max. |
| Reflected input ripple current | 30 mA _{p-p} typ. |
| Conducted noise (input) | EN 55022 class A, FCC part 15, level A without external components |
| ESD (electrostatic discharge) | EN 61000-4-2, air ±8 kV, contact ±6 kV, perf. criteria A |
| Radiated immunity | EN 61000-4-3, 10 V/m, perf. criteria A |
| Fast transient / Surge | EN 61000-4-4, ±2 kV, perf. criteria A EN 61000-4-5, ±2 kV perf. criteria A With external input capacitor e.g. Nippon chemi-con KY 200 µF, 100 V, ESR 48 mOhm |
| Conducted immunity | EN 61000-4-6, 10 V _{rms} , perf. criteria A |

Output Specifications

| | |
|---------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Voltage set accuracy | ±1 % |
| Output voltage adjustment range | ±10 % for single output models only. Trim up via resistor over Trim and -V _{out} Trim down via resistor over Trim and +V _{out} (Resistor values tba, 0 Ohm=max. adjustment) |
| Regulation | – Input variation (V _{min} – V _{max}) single output models: 0.2 % max. dual output models: 0.5 % max. – Load variation (0 – 100%) single output models: 0.2 % max. dual output models balanced load: 1.0 % max. dual output models unbalanced load (25% /100%): 5.0 % max. |
| Minimum load | not required |
| Ripple and noise (20 MHz bandwidth) | 3.3 & 5.0 VDC models: 75 mV _{p-p} typ. other models: 100 mV _{p-p} typ. measured with a 1µF M/C and a 10µF T/C |
| Temperature coefficient | ±0.02 %/K |
| Output current limitation | at 150 % of I _{out} max., foldback |
| Short circuit protection | indefinite, automatic recovery |
| Over voltage protection | 3.3 VDC models: 3.7 – 5.4 V _{out} 5 VDC models: 5.6 – 7.0 V _{out} 12 VDC models: 13.5 – 19.6 V _{out} 15 VDC models: 16.8 – 20.5 V _{out} |
| Start up time (nominal Vin and constant resistive load) | 30 ms typ. (for power on and remote on) |
| Transient response setting time | 250 µs typ. (25% load step change) |

Output Specifications

| | | |
|----------------------|----------------------|---------------------------|
| Max. capacitive load | 3.3 VDC models: | 7'000 μ F |
| | 5 VDC models: | 5'000 μ F |
| | 12 VDC models: | 850 μ F |
| | 15 VDC models: | 700 μ F |
| | \pm 12 VDC models: | 500 μ F (each output) |
| | \pm 15 VDC models: | 350 μ F (each output) |

General Specifications

| | | |
|-----------------------------------------------------------------------|-------------------------------------|------------------------------------------------------------------------------|
| Temperature ranges | - Operating without heat sink | -40°C to +75°C (with derating) |
| | - Operating with heat sink | -40°C to +85°C (with derating) |
| | - Case temperature | +105°C max. |
| | - Storage | -55°C to +125°C |
| Power derating | - Operating without heat sink | 2.0 %/K above 60°C |
| | - Operating with heat sink | 2.0 %/K above 70°C |
| Thermal inpedance | - Natural convection | 17.6°C/W |
| | - Natural convection with heat sink | 14.8°C/W |
| Humidity (non condensing) | | 5 % to 95 % rel H max. |
| Reliability, calculated MTBF (MIL-HDBK-217F, at +25°C, ground benign) | | >550'000 h |
| Isolation voltage (60sec.) | - Input/Output | 1'500 VDC |
| Isolation capacitance | - Input/Output | 1000 pF typ. |
| Isolation resistance | - Input/Output (500 VDC) | >1'000 MOhm |
| Remote On/Off | - On: | 3.0 ... 15 VDC or open circuit |
| | - Off: | 0 ... 1.2 VDC or short circuit pin 6 and pin 2 |
| | - Off idle current: | 1.5 mA |
| Switching frequency (fixed) | | 330 kHz typ. (pulse width modulation PWM) |
| Vibration and thermal shock | | EN 61373, MIL-STD-810E |
| Safety standards | | UL /cUL 60950-1, EN 60950-1, IEC 60950-1 |
| Safety approvals | - UL/cUL | www.ul.com -> certifications -> File e188913 |


Physical Specifications

| | | |
|--------------------------|---------|--------------------------------------------------------------------------------------------------------------|
| Casing material | | nickel coated copper |
| Baseplate | | non conductive FR4 |
| Potting material | | silicone (UL 94V-0 rated) |
| Weight | | 15 g (0.53 oz) |
| Soldering temperature | | max. 265°C / 10 sec. |
| Environmental compliance | - Reach | www.tracopower.com/products/thn20-reach.pdf |
| | - RoHS | RoHS directive 2011/65/EU |

Application note: www.tracopower.com/products/thn20-application.pdf

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Outline Dimensions




| Pin-Out | | |
|---------|---------------|------------|
| Pin | Single | Dual |
| 1 | +Vin (Vcc) | +Vin (Vcc) |
| 2 | -Vin (GND) | -Vin (GND) |
| 3 | + Vout | + Vout |
| 4 | Trim | Common |
| 5 | -Vout | -Vout |
| 6 | Remote On/Off | |



Dimensions in [mm], () = Inch
 Pin diameter \varnothing 1.0 (0.04)
 Pin pitch tolerances: ± 0.25 (± 0.01)
 Tolerances: ± 0.5 (± 0.02)

Heat-Sink (Option)

Order code: THN-HS1
 (cont.: heat-sink, thermal pad, 2 clamps)
Material: Aluminum
Finish: Anodic treatment (black)
Weight: 8 g (0.28 oz) without converter
 Thermal impedance after assembling: 14.8 K/W



Note:
 The product label on converter has to be removed before mounting the heat-sink.
 For volume orders converters will be supplied with heat-sink already mounted. Please contact factory for quotation.
 Separate heat-sinks are only available for prototypes and small quantity orders.



Specifications can be changed without notice! Make sure you are using the latest documentation, downloadable at www.tracopower.com



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.