



N-channel 200 V, 0.11 Ω , 15 A, MESH OVERLAY™ Power MOSFETs in D²PAK, DPAK, TO-220FP and TO-220 packages



Features

| Type | V _{DS} | R _{DS(on)} max. | I _D | Package |
|-----------|-----------------|--------------------------|----------------|--------------------|
| STB19NF20 | 200 V | 0.16 Ω | 15 A | D ² PAK |
| STD19NF20 | | | | DPAK |
| STF19NF20 | | | | TO-220FP |
| STP19NF20 | | | | TO-220 |

- Extremely high dv/dt capability
- Gate charge minimized
- Very low intrinsic capacitance

Applications

- Switching applications

Description

These Power MOSFETs are designed using STMicroelectronics' consolidated strip-layout-based MESH OVERLAY™ process. The result is a product that matches or improves on the performance of comparable standard parts from other manufacturers.

Product status links

[STB19NF20](#)

[STD19NF20](#)

[STF19NF20](#)

[STP19NF20](#)

1 Electrical ratings

Table 1. Absolute maximum ratings

| Symbol | Parameter | Value | | Unit |
|--------------------------------|---|----------------------------------|---------------------|------|
| | | D ² PAK, DPAK, TO-220 | TO-220FP | |
| V _{DS} | Drain-source voltage | 200 | | |
| V _{GS} | Gate-source voltage | ±20 | | V |
| I _D | Drain current (continuous) at T _C = 25 °C | 15 | 15 ⁽¹⁾ | A |
| | Drain current (continuous) at T _C = 100 °C | 9.45 | 9.45 ⁽¹⁾ | |
| I _{DM} ⁽²⁾ | Drain current (pulsed) | 60 | 60 ⁽¹⁾ | A |
| P _{TOT} | Total dissipation at T _{case} = 25 °C | 90 | 25 | W |
| V _{ISO} | Insulation withstand voltage (RMS) from all three leads to external heat sink (t = 1 s, T _C = 25 °C) | | 2.5 | kV |
| dv/dt ⁽³⁾ | Peak diode recovery voltage slope | 15 | | V/ns |
| T _{stg} | Storage temperature range | -55 to 150 | | °C |
| T _j | Operating junction temperature range | | | |

1. This value is limited by package.
2. Pulse width is limited by safe operating area.
3. I_{SD} ≤ 15 A, di/dt ≤ 300 A/μs, V_{DD} = 80 % V_{(BR)DSS}

Table 2. Thermal data

| Symbol | Parameter | Value | | | | Unit |
|-------------------------------------|-------------------------------------|--------------------|------|--------|----------|------|
| | | D ² PAK | DPAK | TO-220 | TO-220FP | |
| R _{thj-case} | Thermal resistance junction-case | 1.39 | | | 5 | °C/W |
| R _{thj-pcb} ⁽¹⁾ | Thermal resistance junction-pcb | 35 | 50 | | | |
| R _{thj-amb} | Thermal resistance junction-ambient | | | 62.5 | | |

1. When mounted on an 1-inch² FR-4, 2oz Cu board

Table 3. Avalanche characteristics

| Symbol | Parameter | Value | Unit |
|-----------------|--|-------|------|
| I _{AR} | Avalanche current, repetitive or not repetitive (pulse width limited by T _{jmax}) | 15 | A |
| E _{AS} | Single-pulse avalanche energy (starting T _j = 25 °C, I _D = I _{AR} , V _{DD} = 50 V) | 110 | mJ |

2 Electrical characteristics

($T_{\text{case}} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)

Table 4. Static

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|-----------------------------|-----------------------------------|---|------|------|-----------|---------------|
| $V_{(\text{BR})\text{DSS}}$ | Drain-source breakdown voltage | $V_{\text{GS}} = 0\text{ V}$, $I_{\text{D}} = 1\text{ mA}$ | 200 | | | V |
| I_{DSS} | Zero gate voltage drain current | $V_{\text{GS}} = 0\text{ V}$, $V_{\text{DS}} = 200\text{ V}$ | | | 1 | μA |
| | | $V_{\text{GS}} = 0\text{ V}$, $V_{\text{DS}} = 200\text{ V}$, $T_{\text{C}} = 125\text{ }^{\circ}\text{C}^{(1)}$ | | | 10 | |
| I_{GSS} | Gate-body leakage current | $V_{\text{DS}} = 0\text{ V}$, $V_{\text{GS}} = \pm 20\text{ V}$ | | | ± 100 | nA |
| $V_{\text{GS(th)}}$ | Gate threshold voltage | $V_{\text{DS}} = V_{\text{GS}}$, $I_{\text{D}} = 250\text{ }\mu\text{A}$ | 2 | 3 | 4 | V |
| $R_{\text{DS(on)}}$ | Static drain-source on-resistance | $V_{\text{GS}} = 10\text{ V}$, $I_{\text{D}} = 7.5\text{ A}$ | | 0.11 | 0.16 | Ω |

1. Defined by design, not subject to production test.

Table 5. Dynamic

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|-------------------|------------------------------|--|------|------|------|-------------|
| C_{iss} | Input capacitance | $V_{\text{DS}} = 25\text{ V}$, $f = 1\text{ MHz}$, $V_{\text{GS}} = 0\text{ V}$ | - | 800 | - | pF |
| C_{oss} | Output capacitance | | - | 165 | - | |
| C_{riss} | Reverse transfer capacitance | | - | 26 | - | |
| Q_{g} | Total gate charge | $V_{\text{DD}} = 160\text{ V}$, $I_{\text{D}} = 15\text{ A}$, $V_{\text{GS}} = 0\text{ to }10\text{ V}$ (see Figure 16. Test circuit for gate charge behavior) | - | 24 | - | nC |
| Q_{gs} | Gate-source charge | | - | 4.4 | - | |
| Q_{gd} | Gate-drain charge | | - | 11.6 | - | |

Table 6. Switching times

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---------------------|---------------------|---|------|------|------|------|
| $t_{\text{d(on)}}$ | Turn-on delay time | $V_{\text{DD}} = 100\text{ V}$, $I_{\text{D}} = 7.5\text{ A}$, $R_{\text{G}} = 4.7\text{ }\Omega$, $V_{\text{GS}} = 10\text{ V}$ (see Figure 15. Test circuit for resistive load switching times and Figure 20. Switching time waveform) | - | 11.5 | - | ns |
| t_{r} | Rise time | | - | 22 | - | |
| $t_{\text{d(off)}}$ | Turn-off delay time | | - | 19 | - | |
| t_{f} | Fall time | | - | 11 | - | |

Table 7. Source-drain diode

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|------------------------|-------------------------------|--|------|------|------|------|
| I_{SD} | Source-drain current | | - | | 15 | A |
| $I_{\text{SDM}}^{(1)}$ | Source-drain current (pulsed) | | - | | 60 | A |
| $V_{\text{SD}}^{(2)}$ | Forward on voltage | $I_{\text{SD}} = 15\text{ A}$, $V_{\text{GS}} = 0\text{ V}$ | - | | 1.6 | V |

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|-----------|--------------------------|--|------|------|------|---------------|
| t_{rr} | Reverse recovery time | $I_{SD} = 15 \text{ A}$, $di/dt = 100 \text{ A}/\mu\text{s}$, $V_{DD} = 50 \text{ V}$ (see Figure 17. Test circuit for inductive load switching and diode recovery times) | - | 125 | | ns |
| Q_{rr} | Reverse recovery charge | | - | 0.55 | | μC |
| I_{RRM} | Reverse recovery current | | - | 8.8 | | A |
| t_{rr} | Reverse recovery time | $I_{SD} = 15 \text{ A}$, $di/dt = 100 \text{ A}/\mu\text{s}$, $V_{DD} = 50 \text{ V}$, $T_j = 150 \text{ }^\circ\text{C}$ (see Figure 17. Test circuit for inductive load switching and diode recovery times) | - | 148 | | ns |
| Q_{rr} | Reverse recovery charge | | - | 0.73 | | μC |
| I_{RRM} | Reverse recovery current | | - | 9.9 | | A |

1. Pulse width is limited by safe operating area.
2. Pulse test: pulse duration = 300 μs , duty cycle 1.5%.

2.1 Electrical characteristics (curves)







Figure 1. Safe operating area for D²PAK, DPAK and TO-220

Figure 2. Thermal impedance for D²PAK, DPAK and TO-220

Figure 3. Safe operating area for TO-220FP

Figure 4. Thermal impedance for TO-220FP

Figure 5. Output characteristics

Figure 6. Transfer characteristics










Figure 7. Static drain-source on-resistance

Figure 8. Normalized $V_{(BR)DSS}$ vs temperature

Figure 9. Gate charge vs gate-source voltage

Figure 10. Capacitance variations

Figure 11. Normalized gate threshold voltage vs temperature

Figure 12. Normalized on-resistance vs temperature


Figure 13. Source-drain diode forward characteristics

Figure 14. Maximum avalanche energy vs temperature


3 Test circuits

Figure 15. Test circuit for resistive load switching times


AM01468v1

Figure 16. Test circuit for gate charge behavior


AM01469v1

Figure 17. Test circuit for inductive load switching and diode recovery times


AM01470v1

Figure 18. Unclamped inductive load test circuit


AM01471v1

Figure 19. Unclamped inductive waveform


AM01472v1

Figure 20. Switching time waveform


AM01473v1


4 Ordering information

Table 8. Order codes

| Order code | Marking | Package | Packing |
|------------|---------|--------------------|---------------|
| STB19NF20 | 19NF20 | D ² PAK | Tape and reel |
| STD19NF20 | | DPAK | |
| STF19NF20 | | TO-220FP | Tube |
| STP19NF20 | | TO-220 | |

5 Package information


In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

5.1 D²PAK (TO-263) type A package information
Figure 21. D²PAK (TO-263) type A package outline


0079457_25

Table 9. D²PAK (TO-263) type A package mechanical data

| Dim. | mm | | |
|------|-------|------|-------|
| | Min. | Typ. | Max. |
| A | 4.40 | | 4.60 |
| A1 | 0.03 | | 0.23 |
| b | 0.70 | | 0.93 |
| b2 | 1.14 | | 1.70 |
| c | 0.45 | | 0.60 |
| c2 | 1.23 | | 1.36 |
| D | 8.95 | | 9.35 |
| D1 | 7.50 | 7.75 | 8.00 |
| D2 | 1.10 | 1.30 | 1.50 |
| E | 10.00 | | 10.40 |
| E1 | 8.30 | 8.50 | 8.70 |
| E2 | 6.85 | 7.05 | 7.25 |
| e | | 2.54 | |
| e1 | 4.88 | | 5.28 |
| H | 15.00 | | 15.85 |
| J1 | 2.49 | | 2.69 |
| L | 2.29 | | 2.79 |
| L1 | 1.27 | | 1.40 |
| L2 | 1.30 | | 1.75 |
| R | | 0.40 | |
| V2 | 0° | | 8° |


5.2 D²PAK (TO-263) type B package information
Figure 22. D²PAK (TO-263) type B package outline


0079457_25_B

Table 10. D²PAK (TO-263) type B mechanical data

| Dim. | mm | | |
|------|----------|------|-------|
| | Min. | Typ. | Max. |
| A | 4.36 | | 4.56 |
| A1 | 0 | | 0.25 |
| b | 0.70 | | 0.90 |
| b1 | 0.51 | | 0.89 |
| b2 | 1.17 | | 1.37 |
| b3 | 1.36 | | 1.46 |
| c | 0.38 | | 0.694 |
| c1 | 0.38 | | 0.534 |
| c2 | 1.19 | | 1.34 |
| D | 8.60 | | 9.00 |
| D1 | 6.90 | | 7.50 |
| E | 10.15 | | 10.55 |
| E1 | 8.10 | | 8.70 |
| e | 2.54 BSC | | |
| H | 15.00 | | 15.60 |
| L | 1.90 | | 2.50 |
| L1 | | | 1.65 |
| L2 | | | 1.78 |
| L3 | | 0.25 | |
| L4 | 4.78 | | 5.28 |


Figure 23. D²PAK (TO-263) recommended footprint (dimensions are in mm)



Footprint

5.3 DPAK (TO-252) type A2 package information

Figure 24. DPAK (TO-252) type A2 package outline




0068772_type-A2_rev25

Table 11. DPAK (TO-252) type A2 mechanical data

| Dim. | mm | | |
|------|-------|-------|-------|
| | Min. | Typ. | Max. |
| A | 2.20 | | 2.40 |
| A1 | 0.90 | | 1.10 |
| A2 | 0.03 | | 0.23 |
| b | 0.64 | | 0.90 |
| b4 | 5.20 | | 5.40 |
| c | 0.45 | | 0.60 |
| c2 | 0.48 | | 0.60 |
| D | 6.00 | | 6.20 |
| D1 | 4.95 | 5.10 | 5.25 |
| E | 6.40 | | 6.60 |
| E1 | 5.10 | 5.20 | 5.30 |
| e | 2.159 | 2.286 | 2.413 |
| e1 | 4.445 | 4.572 | 4.699 |
| H | 9.35 | | 10.10 |
| L | 1.00 | | 1.50 |
| L1 | 2.60 | 2.80 | 3.00 |
| L2 | 0.65 | 0.80 | 0.95 |
| L4 | 0.60 | | 1.00 |
| R | | 0.20 | |
| V2 | 0° | | 8° |

5.4 DPAK (TO-252) type C2 package information

Figure 25. DPAK (TO-252) type C2 package outline




0068772_C2_25

Table 12. DPAK (TO-252) type C2 mechanical data

| Dim. | mm | | |
|------|----------|-------|-------|
| | Min. | Typ. | Max. |
| A | 2.20 | 2.30 | 2.38 |
| A1 | 0.90 | 1.01 | 1.10 |
| A2 | 0.00 | | 0.10 |
| b | 0.72 | | 0.85 |
| b4 | 5.13 | 5.33 | 5.46 |
| c | 0.47 | | 0.60 |
| c2 | 0.47 | | 0.60 |
| D | 6.00 | 6.10 | 6.20 |
| D1 | 5.10 | | 5.60 |
| E | 6.50 | 6.60 | 6.70 |
| E1 | 5.20 | | 5.50 |
| e | 2.186 | 2.286 | 2.386 |
| H | 9.80 | 10.10 | 10.40 |
| L | 1.40 | 1.50 | 1.70 |
| L1 | 2.90 REF | | |
| L2 | 0.90 | | 1.25 |
| L3 | 0.51 BSC | | |
| L4 | 0.60 | 0.80 | 1.00 |
| L6 | 1.80 BSC | | |
| θ1 | 5° | 7° | 9° |
| θ2 | 5° | 7° | 9° |
| V2 | 0° | | 8° |


Figure 26. DPAK (TO-252) recommended footprint (dimensions are in mm)




FP_0068772_25

5.5 D²PAK and DPAK packing information

Figure 27. Tape outline



AM08852v1

Figure 28. Reel outline


AM06038v1

Table 13. D²PAK tape and reel mechanical data


| Tape | | | Reel | | | |
|------|------|------|--------------------------------|------|------|------|
| Dim. | mm | | Dim. | mm | | |
| | Min. | Max. | | Min. | Max. | |
| A0 | 10.5 | 10.7 | A | | 330 | |
| B0 | 15.7 | 15.9 | B | 1.5 | | |
| D | 1.5 | 1.6 | C | 12.8 | 13.2 | |
| D1 | 1.59 | 1.61 | D | 20.2 | | |
| E | 1.65 | 1.85 | G | 24.4 | 26.4 | |
| F | 11.4 | 11.6 | N | 100 | | |
| K0 | 4.8 | 5.0 | T | | 30.4 | |
| P0 | 3.9 | 4.1 | Base quantity Bulk quantity | | | |
| P1 | 11.9 | 12.1 | | | | 1000 |
| P2 | 1.9 | 2.1 | | | | 1000 |
| R | 50 | | | | | |
| T | 0.25 | 0.35 | | | | |
| W | 23.7 | 24.3 | | | | |

Table 14. DPAK tape and reel mechanical data

| Tape | | | Reel | | |
|------|------|------|-----------|------|------|
| Dim. | mm | | Dim. | mm | |
| | Min. | Max. | | Min. | Max. |
| A0 | 6.8 | 7 | A | | 330 |
| B0 | 10.4 | 10.6 | B | 1.5 | |
| B1 | | 12.1 | C | 12.8 | 13.2 |
| D | 1.5 | 1.6 | D | 20.2 | |
| D1 | 1.5 | | G | 16.4 | 18.4 |
| E | 1.65 | 1.85 | N | 50 | |
| F | 7.4 | 7.6 | T | | 22.4 |
| K0 | 2.55 | 2.75 | | | |
| P0 | 3.9 | 4.1 | Base qty. | | 2500 |
| P1 | 7.9 | 8.1 | Bulk qty. | | 2500 |
| P2 | 1.9 | 2.1 | | | |
| R | 40 | | | | |
| T | 0.25 | 0.35 | | | |
| W | 15.7 | 16.3 | | | |

5.6 TO-220FP package information


Figure 29. TO-220FP package outline



7012510_Rev_12_B

Table 15. TO-220FP package mechanical data

| Dim. | mm | | |
|------|------|------|------|
| | Min. | Typ. | Max. |
| A | 4.4 | | 4.6 |
| B | 2.5 | | 2.7 |
| D | 2.5 | | 2.75 |
| E | 0.45 | | 0.7 |
| F | 0.75 | | 1 |
| F1 | 1.15 | | 1.70 |
| F2 | 1.15 | | 1.70 |
| G | 4.95 | | 5.2 |
| G1 | 2.4 | | 2.7 |
| H | 10 | | 10.4 |
| L2 | | 16 | |
| L3 | 28.6 | | 30.6 |
| L4 | 9.8 | | 10.6 |
| L5 | 2.9 | | 3.6 |
| L6 | 15.9 | | 16.4 |
| L7 | 9 | | 9.3 |
| Dia | 3 | | 3.2 |

5.7 TO-220 type A package information
Figure 30. TO-220 type A package outline


0015988_typeA_Rev_21

Table 16. TO-220 type A package mechanical data

| Dim. | mm | | |
|------|-------|-------|-------|
| | Min. | Typ. | Max. |
| A | 4.40 | | 4.60 |
| b | 0.61 | | 0.88 |
| b1 | 1.14 | | 1.55 |
| c | 0.48 | | 0.70 |
| D | 15.25 | | 15.75 |
| D1 | | 1.27 | |
| E | 10.00 | | 10.40 |
| e | 2.40 | | 2.70 |
| e1 | 4.95 | | 5.15 |
| F | 1.23 | | 1.32 |
| H1 | 6.20 | | 6.60 |
| J1 | 2.40 | | 2.72 |
| L | 13.00 | | 14.00 |
| L1 | 3.50 | | 3.93 |
| L20 | | 16.40 | |
| L30 | | 28.90 | |
| øP | 3.75 | | 3.85 |
| Q | 2.65 | | 2.95 |

Revision history

Table 17. Document revision history

| Date | Version | Changes |
|-------------|---------|--|
| 13-Oct-2006 | 1 | First release. |
| 17-Nov-2006 | 2 | Part number has been modified. |
| 02-Feb-2007 | 3 | Preliminary version. |
| 16-Feb-2007 | 4 | TO-220FP package has been added. |
| 15-Oct-2012 | 5 | Updated <i>Section 4: Package information</i> and <i>Section 4: Package information</i> . Minor text changes. |
| 16-Apr-2015 | 6 | Throughout document: – added DPAK package information – text and formatting updates Updated <i>Figure 1: Internal schematic diagram</i> Updated <i>Table 2: Absolute maximum ratings</i> Updated <i>Table 3: Thermal data</i> Updated and renamed <i>Table 5: Static</i> (was On/off states) |
| 09-Aug-2018 | 7 | Removed maturity status indication from cover page. The document status is production data. Updated Table 5. Dynamic . Updated Section 5 Package information . Minor text changes |

Contents

| | | |
|------------|--|-----------|
| 1 | Electrical ratings | 2 |
| 2 | Electrical characteristics | 3 |
| 2.1 | Electrical characteristics (curves) | 5 |
| 3 | Test circuits | 8 |
| 4 | Ordering information | 9 |
| 5 | Package information | 10 |
| 5.1 | D ² PAK (TO-263) type A package information | 10 |
| 5.2 | D ² PAK (TO-263) type B package information | 12 |
| 5.3 | DPAK (TO-252) type A2 package information | 15 |
| 5.4 | DPAK (TO-252) type C2 package information | 17 |
| 5.5 | D ² PAK and DPAK packing information | 20 |
| 5.6 | TO-220FP package information | 23 |
| 5.7 | TO-220 type A package information | 25 |
| | Revision history | 28 |

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics – All rights reserved



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.