

SOM Modules


VIA
Edge AI
Developer Kit

Ultra-compact solution for
graphics-intensive edge
computing applications

Features

- Qualcomm Snapdragon 820E quad-core SoC
- Enhanced video decoding supporting 4K@60fps, 8 x 1080p@30fps
- Built-in Wi-Fi 802.11 a/b/g/n/ac, Bluetooth 4.1, and GPS
- 13MP CMOS camera module (1/3.06" 4224 x 3136 pixel)
- Android & Linux BSPs available


Board Placement




Specifications

Model Name	SOM-9X20
Processor	Qualcomm Snapdragon 820E quad-core SoC - Two high-performance Kryo cores up to 2.15GHz - Two low power Kryo cores up to 1.593GHz
System Memory	4GB POP LPDDR4 RAM
Storage	64GB eMMC 5.1/UFS 2.0 Flash Memory
Graphics	Qualcomm Adreno 530 GPU 3D graphics accelerator with 64-bit addressing 624 MHz Graphics engine supporting OpenGL ES 3.1/GEP, GL4.4, DX11.3/4, OpenCL 2.0, Renderscript-Next Supports H.264, VP8, HEVC 8/10-bit, VP9 video decoding up to: 4K@60fps, 1080p@240fps, 8 x 1080p@30fps
Trusted Platform Module	TPM1.2 : ST33TPM12I2C
Wireless Connectivity	NFA324A-12H32 QCA6174A-1 Wi-Fi 802.11 a/b/g/n/ac + BT 4.1 combo LGA module with 2 antenna connectors Qualcomm WGR7640 GPS/GNSS RF receiver with antenna connector
HDMI	Integrated HDMI 2.0 Transmitter
Supported I/O through MXM 3.0 connector	1 HDMI port 2 MIPI DSI 4-Lane connectors 3 MIPI CSI 4-Lane connectors 1 USB 3.0 OTG 1 USB 2.0 host 1 SDIO 2 PCM/MI2S Multi-function pins for UART, I ² C, SPI, GPIO 1 JTAG 2 PCIe 2.0 1-Lane
Operating System	Android 8.0, Linux Kernel 3.18.44
Operating Temperature	-20°C ~ 70°C
Operating Humidity	0% ~ 95% (non-condensing)
Form Factor	8.2cm x 4.5cm (3.23" x 1.77")

Carrier Board Back Panel I/O



Carrier Board (SOMDB2)



Specifications

Model Name	SOMDB2
Audio	Qualcomm WCD 9335 Audio Codec
LAN	RealTek RTL8111G Ethernet Controller RealTek RTL8365MB LAN Hub
Onboard I/O	1 MIPI DSI LCD panel connector 1 MIPI CSI Interface for camera module 1 P-Cap Touch connector 2 USB 2.0 ports 1 USB 2.0 OTG switch (for Host mode/Device mode) 1 COM connector (TX/RX only for debugging) 1 GPIO connector (8 GPIO) 2 I ² C connectors (for light & proximity sensor and NFC module) 1 Front panel connector 1 JTAG connector 1 Mic-in connector 2 2W speaker connectors 2 Audio module connectors (for VT6093 audio module) 2 Volume buttons 1 Boot switch 1 RTC battery connector 1 Micro SD card slot 1 miniPCle slot 1 MXM 3.0 slot
Back Panel I/O	1 HDMI port 2 USB 3.0 ports 1 Micro USB 2.0 OTG port (for debugging) 2 Gigabit Ethernet ports 1 Power button 1 12V DC-in jack
Operating Temperature	-20°C ~ 70°C
Operating Humidity	0% ~ 95% (non-condensing)
Form Factor	17cm x 8.6cm (6.69" x 3.89")
Compliance	RoHS


Ordering Information

Part Number	SoC Frequency	Description
STK-VT6093-01A1	Qualcomm Snapdragon 820E quad-core SoC @ 2.15GHz/1.593GHz	SOM-9X20 module + SOMDB2 carrier board + 13MP CMOS camera module
STK-VT6093-00A1	Qualcomm Snapdragon 820E quad-core SoC @ 2.15GHz/1.593GHz	SOM-9X20 module + SOMDB2 carrier board

Optional Accessories

Touch Panel	
Part Number	Description
99G47-01025F	10.1" MIPI 16:10 (WUXGA 1920 x 1200, 16.7M) LCD Touch panel with USB FPC touch cable and MIPI FPC cable

Block Diagram



Packing List

Items for STK-VT6093-01A1
SOM-9X20 module
SOMDB2 carrier board
VT6093 audio module
COM cable
AC adapter
Power cord US type
2 Antennas for Wi-Fi & Bluetooth
VT6093-CAM-T Camera-CSI converter board
13MP CMOS camera module
1 FPC cable for CSI connector
Items for STK-VT6093-00A1
SOM-9X20 module
SOMDB2 carrier board
VT6093 audio module
COM cable
AC adapter
Power cord US type
2 Antennas for Wi-Fi & Bluetooth



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.