

## 3079A Multi-Conductor - DataBus® ISA/SP-50 PROFIBUS Cable



For more Information  
please call

1-800-Belden1



### General Description:

22 AWG solid bare copper conductors, FRFPE insulation, Beldfoil® (100% coverage) plus a tinned copper braid shield (65% coverage), sunlight resistant PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	22	Solid	BC - Bare Copper	.026

Total Number of Conductors: 2

#### Insulation

Insulation Material:

Insulation Material
FRFPE - Flame Retardant Foam Polyethylene

#### Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	65

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

Overall Nominal Diameter: 0.315 in.

#### Pair

Pair Color Code Chart:

Number	Color
1	Red & Green

Pair Lay Length & Direction:

Lay Length (in.)
2.750

### Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +75°C

UL Temperature Rating: 60°C

Bulk Cable Weight: 52 lbs/1000 ft.

Max. Recommended Pulling Tension: 50 lbs.

Min. Bend Radius/Minor Axis: 3.200 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMG, PLTC
CEC/C(UL) Specification:	CMG
AWM Specification:	UL Style 20201 (600 V 75°C)
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes

## 3079A Multi-Conductor - DataBus® ISA/SP-50 PROFIBUS Cable

EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

### Flame Test

UL Flame Test:	UL1685 FT4 Loading
CSA Flame Test:	FT4
IEEE Flame Test:	1202

### Suitability

Sunlight Resistance:	Yes
----------------------	-----

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Electrical Characteristics (Overall)

### Nom. Inductance:

Inductance (µH/ft)
.282

### Nom. Mutual Capacitance:

Capacitance (pF/ft)
8.5

### Nominal Velocity of Propagation:

VP (%)
78

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
16.0

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 3.900 Ohm/1000 ft

### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
0.200	0.270
4.000	0.670
16.000	1.370

### Max. Attenuation:

Freq. (MHz)	Attenuation (dB/100 m)
0.200	1.100
4.000	2.650
16.000	5.400

### Max. Operating Voltage - UL:

Voltage
300 V RMS (NEC Type CMG)
600 V RMS (UL AWM Style 20201)
300V RMS (NEC Type PLTC)

### Max. Recommended Current:

Description	Current
Per Conductor	2.3 Amps

Other Electrical Characteristic 1: Capacitance Unbalance @ 1 kHz: Less than 1000 pF/km

Other Electrical Characteristic 2: Input Impedance/Unfitted Impedance 3 - 20 MHZ, 150 +/-15 Ohms

## Notes (Overall)

Notes: Siemens Sinec L2 Cable. For CPE jacketed version order Part No. YR45047. For LS0H (FRNC) jacketed version, order Part No. YR44731.

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
3079A 0071000	1,000 FT	56.000 LB	VIOLET	C	1 PR #22 FRFPE FRPE SH PVC
3079A 0072000	2,000 FT	112.000 LB	VIOLET	C	1 PR #22 FRFPE FRPE SH PVC
3079A 0073600	3,600 FT	201.600 LB	VIOLET	C	1 PR #22 FRFPE FRPE SH PVC
3079A 0075000	5,000 FT	285.000 LB	VIOLET		1 PR #22 FRFPE FRPE SH PVC
3079A 0601000	1,000 FT	56.000 LB	CHROME	C	1 PR #22 FRFPE FRPE SH PVC

## ENGLISH MEASUREMENT VERSION

### 3079A Multi-Conductor - DataBus® ISA/SP-50 PROFIBUS Cable

3079A 0602000	2,000 FT	112.000 LB	CHROME	C	1 PR #22 FRFPE FRPE SH PVC
3079A 0603600	3,600 FT	201.600 LB	CHROME	C	1 PR #22 FRFPE FRPE SH PVC

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 4    Revision Date: 12-18-2013

© 2016 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.