

## Mini ground terminal block - MPT 2,5-PE - 3248130

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Mini ground terminal block, Connection method: Push-in connection, Cross section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 26 - 12, Width: 5.2 mm, Height: 32.1 mm, Color: green-yellow, Mounting type: NS 15

### Product Features

- ✓ Space saving thanks to compact design and mounting option on a 15 mm DIN rail
- ✓ Clear arrangement thanks to marking of all terminal points
- ✓ Tested for railway applications
- ✓ Easy potential distribution thanks to standardized plug-in bridges



### Key commercial data

|                        |          |
|------------------------|----------|
| Packing unit           | 1 pc     |
| Minimum order quantity | 50 pc    |
| Custom tariff number   | 85369010 |
| Country of origin      | Poland   |

### Technical data

#### General

|                                         |                        |
|-----------------------------------------|------------------------|
| Number of levels                        | 1                      |
| Number of connections                   | 2                      |
| Color                                   | green-yellow           |
| Insulating material                     | PA                     |
| Inflammability class according to UL 94 | V0                     |
| Area of application                     | Railway industry       |
|                                         | Mechanical engineering |
|                                         | Plant engineering      |
| Rated surge voltage                     | 6 kV                   |
| Pollution degree                        | 3                      |
| Surge voltage category                  | III                    |

# Mini ground terminal block - MPT 2,5-PE - 3248130

## Technical data

### General

|                                                                       |                                                |
|-----------------------------------------------------------------------|------------------------------------------------|
| Insulating material group                                             | I                                              |
| Connection in acc. with standard                                      | IEC 60947-7-2                                  |
| Open side panel                                                       | ja                                             |
| Shock protection test specification                                   | DIN EN 50274 (VDE 0660-514):2002-11            |
| Back of the hand protection                                           | guaranteed                                     |
| Finger protection                                                     | guaranteed                                     |
| Test specification, oscillation, broadband noise                      | DIN EN 50155 (VDE 0115-200):2008-03            |
| Test spectrum                                                         | Service life test category 2, bogie mounted    |
| Test frequency                                                        | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level                                                             | $6.12 \text{ (m/s}^2\text{)}^2/\text{Hz}$      |
| Acceleration                                                          | 3.12 g                                         |
| Test duration per axis                                                | 5 h                                            |
| Test directions                                                       | X-, Y- and Z-axis                              |
| Oscillation, broadband noise test result                              | Test passed                                    |
| Test specification, shock test                                        | DIN EN 50155 (VDE 0115-200):2008-03            |
| Shock form                                                            | Half-sine                                      |
| Acceleration                                                          | 30 g                                           |
| Shock duration                                                        | 18 ms                                          |
| Number of shocks per direction                                        | 3                                              |
| Test directions                                                       | X-, Y- and Z-axis (pos. and neg.)              |
| Shock test result                                                     | Test passed                                    |
| Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C                                         |
| Static insulating material application in cold                        | -60 °C                                         |

### Dimensions

|              |         |
|--------------|---------|
| Width        | 5.2 mm  |
| Length       | 36 mm   |
| Height       | 32.1 mm |
| Height NS 15 | 34.8 mm |

### Connection data

|                                        |                      |
|----------------------------------------|----------------------|
| Connection in acc. with standard       | IEC 60947-7-2        |
| Connection method                      | Push-in connection   |
| Conductor cross section solid min.     | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.     | 4 mm <sup>2</sup>    |
| Conductor cross section AWG/kcmil min. | 26                   |
| Conductor cross section AWG/kcmil max  | 12                   |
| Conductor cross section stranded min.  | 0.14 mm <sup>2</sup> |

## Mini ground terminal block - MPT 2,5-PE - 3248130

### Technical data

#### Connection data

|                                                                                         |                      |
|-----------------------------------------------------------------------------------------|----------------------|
| Conductor cross section stranded max.                                                   | 2.5 mm <sup>2</sup>  |
| Min. AWG conductor cross section, stranded                                              | 26                   |
| Max. AWG conductor cross section, stranded                                              | 14                   |
| Conductor cross section stranded, with ferrule without plastic sleeve min.              | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule without plastic sleeve max.              | 2.5 mm <sup>2</sup>  |
| Conductor cross section stranded, with ferrule with plastic sleeve min.                 | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule with plastic sleeve max.                 | 2.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 0.5 mm <sup>2</sup>  |
| Stripping length                                                                        | 10 mm                |
| Internal cylindrical gage                                                               | A3                   |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141121 |
| eCl@ss 4.1 | 27141121 |
| eCl@ss 5.0 | 27141141 |
| eCl@ss 5.1 | 27141141 |
| eCl@ss 6.0 | 27141141 |
| eCl@ss 7.0 | 27141141 |
| eCl@ss 8.0 | 27141141 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001329 |
| ETIM 4.0 | EC000901 |
| ETIM 5.0 | EC000901 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Approvals

#### Approvals

## Mini ground terminal block - MPT 2,5-PE - 3248130

### Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

### Approval details


| UL Recognized  |       |       |       |
|-------------------------------------------------------------------------------------------------|-------|-------|-------|
|                                                                                                 | B     | C     | D     |
| mm²/AWG/kcmil                                                                                   | 26-12 | 26-12 | 26-12 |

| cUL Recognized  |       |       |       |
|----------------------------------------------------------------------------------------------------|-------|-------|-------|
|                                                                                                    | B     | C     | D     |
| mm²/AWG/kcmil                                                                                      | 26-12 | 26-12 | 26-12 |

|                                                                                                      |  |  |  |
|------------------------------------------------------------------------------------------------------|--|--|--|
| cULus Recognized  |  |  |  |
|------------------------------------------------------------------------------------------------------|--|--|--|

### Drawings

Circuit diagram





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.